

AFRILANG Stdlib

std/stopwatch

Français. Bibliothèque AFRILANG 'std/stopwatch' (niveau simple, catégorie utilities). Elle expose 2 fonction(s) : nowMs, elapsedMs.

'import "std/stopwatch"' · 'use stopwatch'

- 'nowMs(ignored number) → number' - 'elapsedMs(start number) → number'

English. AFRILANG library 'std/stopwatch' (tier simple, category utilities). Exports 2 function(s): nowMs, elapsedMs.

'import "std/stopwatch"' · 'use stopwatch'

- 'nowMs(ignored number) → number' - 'elapsedMs(start number) → number'

Contents

Français

1. Vue d'ensemble

Bibliothèque AFRILANG 'std/stopwatch' (niveau simple, catégorie utilities). Elle expose 2 fonction(s) : nowMs, elapsedMs.

'import "std/stopwatch"' · 'use stopwatch'

```
- `nowMs(ignored number) → number`
- `elapsedMs(start number) → number`
```

2. Installation & import

Ajoutez le module à votre programme :

```
import "std/stopwatch"
use stopwatch
```

Niveau : simple · Catégorie : Utilitaires
Helpers simples et fonctions ponctuelles.

3. Référence API

- nowMs(ignored number) → number
elapsedMs(start number) → number

4. Exemples d'utilisation

```
import "std/stopwatch"
use stopwatch
```

```
create result = nowMs(/* args */)
say result
```

```
create result = elapsedMs(/* args */)
say result
```

5. Bonnes pratiques

- Préférez `import "std/stopwatch"` en tête de fichier.
Lancez `afrilang check` avant de livrer.
Combinez avec les modules stdlib de la même catégorie.
Voir /stdlib/ pour le source live et les démos playground.
Signalez les problèmes sur GitHub si une export manque.

6. Annexe — source

module stopwatch

```
function nowMs(ignored number) returns number
end
```

```
function elapsedMs(start number) returns number
end
end
```

English

1. Overview

AFRILANG library 'std/stopwatch' (tier simple, category utilities). Exports 2 function(s): nowMs, elapsedMs.

'import "std/stopwatch"' · 'use stopwatch'

```
- `nowMs(ignored number) → number`
- `elapsedMs(start number) → number`
```

2. Installation & import

Add the module to your program:

```
import "std/stopwatch"
use stopwatch
```

Tier: simple · Category: Utilities
Simple helpers and single-purpose functions.

3. API reference

- nowMs(ignored number) → number•
elapsedMs(start number) → number

4. Usage examples

```
import "std/stopwatch"
use stopwatch
```

```
create result = nowMs(/* args */)
say result
```

```
create result = elapsedMs(/* args */)
say result
```

5. Best practices

- Prefer `import "std/stopwatch"` at the top of your file. •
Run `afri-lang check` before shipping. •
Combine with related stdlib modules from the same category. •
See /stdlib/ for the live source and playground demos. •
Report issues on GitHub if an export is missing or undocumented.

6. Appendix — source

module stopwatch

```
function nowMs(ignored number) returns number
end
```

```
function elapsedMs(start number) returns number
end
end
```

Référence rapide / Quick reference

- Import : `import "std/stopwatch"`
- Vérification : `afrilang check`
- Documentation : <https://afrilang.dev/stdlib/std/stopwatch/>

Source (extrait)

```
module stopwatch

function nowMs(ignored number) returns number
end

function elapsedMs(start number) returns number
end
end
```