Confidence Maps - False Discovery Rate Control of cryo-EM maps

Maximilian Beckers EMBL Heidelberg

2018

1 Introduction

Confidence maps are complementary maps generated from cryo-EM maps by means of statistical hypothesis testing and subsequent FDR control. They allow thresholding of EM maps based on the expected amount of background noise visible at the respective threshold and thus allow rigorous error assessment of visible features in the density. Additional post-processing like local filtering or local amplitude scaling (LocScale) can be incorporated in the framework in order to increase the statistical power.

2 Getting Started

2.1 Prerequisites

The software is written in Python and only dependent on NumPy libraries.

2.2 Installing

The folder that contains the whole software has only to be copied to your computer and can then be run from the folder by

python FDRcontrol.py -em yourMap.mrc -p thePixelSize

2.2.1 Installation using Git

Alternatively, you can just clone the repository to your local machine with:

git clone https://git.embl.de/mbeckers/FDRthresholding.git

2.3 Input and Output

2.3.1 Input

Confidence maps can in general be generated from any unmasked EM map, as long as background noise can be estimated. It will work on sharpened/unsharpened and/or filtered/unfiltered maps. The most informative case might be on sharpened and filtered maps. Locally filtered maps can not be used as input, as local noise levels have to be taken into account. How to incorporate local resolution information and local filtering is explained in the next section.

2.3.2 Output

The confidence map will have the name your_input_map_confidenceMap.mrc. It contains values between 0 and 1 and can be visualized in any dedicated visualization software (e.g. Chimera, Coot, ...). E.g., thresholding a FDR-controlled confidence map at 0.99 means a false discovery rate of 1 %, i.e. that less than 1 % of all pixels seen at this threshold are expected to be background noise.

3 How to generate a confidence Map

In order to do the tutorial, please download all maps from

https://oc.embl.de/index.php/s/5GTptSDNFskvYuF

3.1 Confidence map generation without additional information

The simplest, and probably most important case, is the generation of a confidence map from a simple cryoEM density without incorporation of local resolution or atomic model information.

python FDRcontrol.py -em yourMap.mrc -p thePixelSize

The output will be the corresponding confidence map and a diagnostic image, that shows three slices through the map together with the regions used for noise estimation. In order to get good estimates of the background noise distribution, you should make sure that the region contains just noise and no signal of the particle.

Size of the noise estimation region can be adjusted with -w sizeOfRegion. If the default regions for noise estimation fall into noise, you can specify the center of region of your choice with -noiseBox x y z. For example:

python FDRcontrol.py -em yourMap.mrc -p 5.6 -w 20 -noiseBox 50 50 120

Boxes for noise estimation should be made as big possible in order to get precise and reliable background noise estimates.

3.1.1 Demonstration with TRPV1 EMD5778

We will now demonstrate the procedure using the 3.4 Angstrom structure of TRPV1 (EMD5778, Liao et al. 2013).

If you didn't download the map so far, then download it from

https://oc.embl.de/index.php/s/5GTptSDNFskvYuF

We are already ready to generate the confidence map by

python FDRcontrol.py -em /path/to/TRPV1_sharpened_-100_3.4A.map -p 1.2156

If we have a look in the diagnostic image, we see that we can increase the box sizes for background noise estimation, which should make the estimates more precise. Let's choose 50 and generate a new confidence map with

python FDRcontrol.py -em /path/to/TRPV1_sharpened_-100_3.4A.map -p 1.2156
-w 50

Don't forget to set the right path! The expected run time on normal desktop computer should be around 1-2 minutes for this example. We can have look at the confidence map with Chimera:

chimera TRPV1_sharpened_-100_3.4A_confidenceMap.mrc

3.2 Incorporation of local resolution information

A corresponding local resolution map can be supplied to the program by locResMap yourLocalResolutionMap.mrc. The ouput will be a locally filtered map together with the diagnostic image and the confidence map. Adjustment of the noise estimation region can be done accordingly. Example usage:

python FDRcontrol.py -em yourMap.mrc -p thePixelSize
-locResMap yourLocalResolutionMap.mrc

3.2.1 Turorial with beta-Galactosidase EMD2984

As above, maps are available from the same link as for the example given above. Let's generate a first confidence map by

python FDRcontrol.py -em /path/to/EMD-2984.map -p 0.637
-locResMap /path/to/betaGal_resmap.mrc

This calculation might take a few minutes, (ca 10 - 20 minutes, depending on the size of your map). So now lets have a look in diag_image.pdf.




Figure 1: diag_image.pdf. The third image on the right clearly shows that noise boxes fall into the molecule.

We see that the noise estimation regions clearly falls into molecule density, so we have to set a new noise estimation region. From the coordinate systems given in diag_image.pdf, we can see that the box center x=50, y=150, z=150 and a box size of 50 should give a reasonable region. So we run it again:

python FDRcontrol.py -em /path/to/EMD-2984.map -p 0.637
-locResMap /path/to/betaGal_resmap.mrc -noiseBox 50 50 150 -w 50

Again we check diag_image.pdf. It shows that the noise region was set to a reasonable region and 50 is quite a large sidelength of the box, which allows precise background noise estimation.




Figure 2: diag_image.pdf with new box coordinates. Box has reasonable size and is outside of the molecular density.

Again, we can have look at the confidence map with Chimera:

chimera betaGal_confidenceMap.mrc

The additional map generated is the locally filtered version and will have the name betaGal_locFilt.mrc.

3.3 Incorporation of local amplitude scaling

LocScale inside FDRcontrol.py can be used by supplying a model map with -mm youModelMap.mrc, where the model map is generated in the LocScale workflow. For usage of parallelisation, -mpi can be specified. The window size of the rolling window for local sharpening can be specified with -w_locscale windowSize. Size of the box for background noise estimation with -w boxSize and its location again with -noiseBox x y z. The ouput will be the locally scaled map together with the diagnostic image and the confidence map.

Example usage:

python FDRcontrol.py -em yourMap.mrc -p thePixelSize -mm yourModelMap.mrc

3.3.1 Turorial with beta-Galactosidase EMD2984

Using the same parameters (boxsize and box location) as before, we can run LocScale together with a respective confidence map by

python FDRcontrol.py -em /path/to/betaGal.mrc-p 0.637 -w 50
-mm /path/to/pdb5a1a_rsref_NCS_4locscale.mrc -noiseBox 50 50 150

Please note that instead of the sharpened map betaGal.mrc we input here the unsharpened and unfiltered raw map betaGal.mrc. This will take a few hours to calculate. You can use the MPI accelerated version with the flag -mpi, i.e.:

python FDRcontrol.py -em /path/to/betaGal.mrc -p 0.637 -w 50 -mpi -mm /path/to/pdb5a1a_rsref_NCS_4locscale.mrc -noiseBox 50 50 150

4 Instructions for use and important tips

The programs require an unmasked map as input. Masking will make the noise estimation impossible.

It is critical that the regions used for noise estimation do not fall into the particle of interest. While in single particle analysis (SPA), the data generating process makes choice of the regions straightforward, sub-tomogram-averaged structures usually require specification of this region from the user.

The region can be identified by means of the slice-views in the diagnostic image of a first run with default parameters, and then adjust center and width of the noise region for a subsequent run. The axes in the diagnostic image are labelled with the voxel indices.

Always have a look in the diagnostic image. After a first run you should use the information from the diagnostic image to increase the box size for noise estimation.

If your map contains large background areas, i.e. small particle compared to the box size, you should increase the sizes of the noise estimation regions in order to get more accurate estimates of the background noise distribution. The box size can be supplied with -w yourBoxSize.

Recommended workflow:

- 1. Run the FDR control on your map
- 2. Have a look in the diagnostic image and check the noise estimation. Make sure the marked regions do not fall into your molecule and identify maximum size possible for correct background noise estimaion and/or identify new box coordinates.
- 3. Rerun the FDR control with the optimised noise estimation regions. Make the regions as big as possible. Size can be set with -w and the box, if it has to be adjusted, with -noiseBox xCoord yCoord zCoord

Be aware, inclusion of either local resolution and/or atomic model information depend on the correctness of this prior information. Make sure orientations of model maps and/or local resolution maps with respect to the input EM-map are correct.

As confidence maps are almost binary and have huge contrast, they might look quite sharp and edged. For visualization the representation can be easily improved, for example in Chimera by turning on surface smoothing in the Volume Viewer in Features --> Sufrace and Mesh options.

5 FAQ

- 1. My confidence map doesn't show expected high resolution details Confidence maps are not invariant to B-factor sharpening and filtering. Oversharpening will lead to increased background noise levels; confidence maps take care of that and oversharpened regions will be simply calssified as noise. Undersharpening will be visible in confidence maps though the absence of high resolution details. So you can simply try to increase the sharpening and generate upadted confidence maps, which will help avoiding typical oversharpening issues (e.g. interpretation of noise as signal).
- 2. My confidence map shows unspecific, noise-like signal at low FDR First of all make sure, your background noise estimation did work properly by checking the diagnostic image. If your noise estimation region is to small or when you estimate noise from masked regions, your background noise estimates might be inaccurate. However, highly flexible or completely disordered regions can appear noise-like in confidence maps; especially when using masked refinement this effect might occur. These densities are indeed significant and truly there, however, care has to be taken not to interpret them as ions or water. Incorporation of local resolution information with -locResMap yourLocalResolutionMap.mrc might help in this case.
- **3.** Parts of the molecule seem to be missing in the confidence map If parts of your molecule (loops, ligands, etc.) are missing in the confidence map at low FDR, these might be due to oversharpening. An easy solution that almost always helps in this situation is incorporation of local resolution information with -locResMap yourLocalResolutionMap.mrc.
- 4. Incorporation of local resolution information seem to introduce artifacts in the confidence map

If the local resolution map contains low resolution artifacts (e.g. when estimated from masked half maps), these might introduce smeared out densities. In this case it can help to cut the lowest resolutions in your local resolution map to the lowest expected value (e.g. 10 Angstroms).

6 List of options

6.1 Required paramters

- -em EM map Example: -em yourEMmap.mrc
- -p pixel size Example: -p 1.06

6.2 Optional parameters

- -locResMap local resolution map for local filtering Example: -locResMap yourLocalResolutions.mrc
- -mm model map for LocScale Example: -mm yourModelMap.mrc
- -w window size for background noise estimation Example: -w 50
- \bullet -noise Box box coordinates for background noise estimation Example: -noise Box 50 150 150
- -method: method for error control, 'BH' for Benjamini-Hochberg FDR-control, 'BY' for Benjamini-Yekutieli FDR-control (default) or 'Holm' for Holm FWER-control
- -w_locscale window size for LocScale Example: -w_locscale 15
- -stepSize step size for LocScale Example: -stepSize 5 (default)
- -ecdf use ECDF instead of Gaussian CDF for p-value calculation Example:
 -ecdf
- -o filename for output Example: -o out.mrc
- -testProc use right-, left- or two-sided testing i.e. 'rightSided', 'leftSided'or 'twoSided' Example: -testProc 'rightSided'
- \bullet -fdr threshold confidence map at the desired FDR Example: -fdr 0.01
- -mpi MPI parallelisation for LocScale Example: -mpi
- -lowPassFilter resolution in Angstrom to low-pass filter the map before multiple testing Example: -lowPassFilter 5