



LYNX®

PRODUCT SPEC BOOK 2025
VEHICLE SPECIFICATIONS – ACCESSORIES – APPAREL



A BRP BRAND

LYNX® PRODUCT SPEC BOOK 2025

VEHICLE SPECIFICATIONS

- 7 Rave GLS
- 8 Rave RE
- 9 Rave RE with Enduro Package
- 10 Adventure
- 11 Adventure Limited
- 12 Adventure LX
- 13 Adventure Electric
- 14 Xterrain
- 15 Xterrain RE
- 16 Brutal RE
- 17 Brutal RE (500 mm)
- 18 Commander
- 19 Commander RE
- 20 Commander Limited
- 21 Shredder
- 22 Shredder RE
- 23 Shredder DS
- 24 49 Ranger
- 25 49 Ranger PRO
- 26 59 Ranger
- 27 59 Ranger PRO
- 28 59 Ranger Alpine
- 29 69 Ranger Alpine
- 30 69 Ranger PRO
- 31 Models and platforms
- 32 Comparison table

ACCESSORIES

- 37 LinQ accessories
- 38 Accessory bundles
- 40 Storage
- 49 Seats & Accessories
- 52 Wind protection & Mirrors
- 57 Bumpers
- 60 Towing
- 61 Skid plates, Protectors & Reinforcement
- 64 Ergonomics
- 66 Lights
- 67 Electrical
- 70 Rave 120 & 200 Accessories
- 71 59 Ranger & 69 Ranger Alpine Accessories
- 72 Suspension
- 74 Covers
- 76 Skis
- 77 Universal
- 79 Cooling
- 80 Trailing & Covers
- 82 Parts & Performance
- 82 PDrive Pulley Service Kits
- 83 XPS Oils and Maintenance Products
- 85 Tracks and Drive Belts

APPAREL

- 88 Shell layer comparison chart
- 90 Stamina
- 95 Technology guide: Exo Float Assist
- 96 Technology guide: Sympatex
- 97 Technology guide: Primaloft
- 98 Apparel technologies
- 99 Technology guide: Deep Snow apparel comparison
- 100 Quantum
- 104 Squadron
- 108 How to layer right
- 110 Tec Layer
- 112 Lynx x Svala
- 116 Racing
- 118 Active Wear
- 120 Advex Helmets
- 123 Oxygen Helmets
- 124 Vibe Communication System
- 126 Pyra Helmets
- 127 Exome Helmets
- 128 Radien Helmets
- 129 M-Forge, eLinQ and Fidlock technologies
- 130 Goggles
- 132 Handwear
- 133 Bags
- 134 Headwear
- 136 Sportswear: RE Collection
- 138 Sportswear: Signature Collection
- 140 Sportswear: Premium Collection
- 141 Footwear
- 142 How to measure



LYNX 2025

AT HOME IN THE HARSHEST CONDITIONS

When you come from northern Finland,
one thing you have to be is tough.

You can see it in our 2025 lineup, from the
trail-hungry Rave GLS to the fierce Brutal RE.

In fact, all of our snowmobiles take the most
inhospitable conditions in their stride.

So choose the toughest sleds on the snow,
choose Finnish.



2025 WHAT'S NEW

THE RACING LEGEND RETURNS

SPRING ONLY



RAVE GLS 40TH ANNIVERSARY EDITION

40 years of trail dominance: Retro meets Turbo in a legendary design inspired by the legendary GLS 3300 model. Unleash power with the most advanced 2-stroke turbo engine ever.

ELEVATE YOUR TRAIL TALES



ADVENTURE LIMITED TRAIL SNOWMOBILE

Irresistible comfort, top-notch performance and cutting-edge design for demanding trail adventurers. The newborn Adventure Limited takes the adventure to a new level.

UNLEASH THE TRAIL BEAST



ROTAX 850 E-TEC TURBO R ENGINE WITH WATER INJECTION

The most powerful factory-built snowmobile engine, available with Rave GLS 40th Anniversary Edition and Xterrain RE. Instant acceleration with ferocious, yet seamless power.

ALL TERRAIN ADVENTURER



BRUTAL RE EXTREME CROSSOVER SNOWMOBILE

With its turbo power and a monster track, the new Brutal RE can go places no other crossovers dare.

THE POWER TO EXPLORE FURTHER



XTERRAIN RE CROSSOVER SNOWMOBILE

For turbo-charged trail adventures. The Xterrain RE is the extreme trail crossover that thrills with its unparalleled riding dynamics, boosted with Rotax® turbo power. Kilometer after kilometer.

UNLOCK NEW ADVENTURES



10.25" TOUCHSCREEN DISPLAY WITH BUILT-IN GPS

The 10.25 inch full color touchscreen display has enhanced features like built-in GPS with trail and topographic maps, allowing you to navigate without phone connection. Connect your phone with the BRP Go! app and unlock a world of new winter adventures with extended features.

NEW NYLON REINFORCED MERINO MATERIAL!

Merino properties with Cordura durability!

CORDURA
Advanced Fabrics

Polyamide
Cordura Filament

Wool Fibre

By using a special spinning technique, where Cordura filament is twisted around Merino yarn, the result is a groundbreaking durable and lightweight natural Merino base layers.

Warm, Comfortable (no itch), Extremely Durable, Odour-resistant.

Unisex, Slim-fit, Flat seams, Round neckline, Longer hem at the back, UV blocking Merino/Cordura knit



**LYNX X SVALA
CORDURA MERINO
BASE LAYER**



LED SIGNAL LIGHTS

Add extra safety on trails: signal to other drivers about the sleds behind you or potential danger spots with distinctive colored lights. Available for windscreen or handguards.



QUANTUM LITE OPS

Experience the no-compromise attitude of the Quantum line in the new Quantum Lite OPS. The flexible shell with 2-ply Sympatex membrane keeps you warm and protected without restricting your movements.



STAMINA RE JACKET

The original Lynx Stamina provides ultimate protection even in the harshest riding conditions. The 2025 novelty Stamina Trail RE combines the collection's ultra high performance with a cool racing look.

ROTAX® ENGINES



ROTAX 2-STROKE ENGINES

Heart-thumping power, lightweight design, proven reliability – E-TEC direct-injection engine technology delivers the most sought-after attributes in the snowmobile industry.

Our lineup of 2-stroke engines now includes the brand-new 600 EFI (Electronic Fuel Injection) engine. Reliable, affordable and easy to use, it's an entry-level engine that far exceeds what you thought an entry-level engine had to be.

With E-TEC engine lineup you also get:

- Industry-leading fuel economy²
- Excellent oil economy
- Virtually no smoke or smell
- Light, linear throttle pull
- Automatic summerization process

850 E-TEC TURBO R

- 180 hp up to 2400 meters¹
- World's first factory-built 2-stroke turbo

850 E-TEC

- 165 horsepower¹
- Down to 12.3 L/100 km²

600R E-TEC

- 125 horsepower¹
- Down to 11.3 L/100 km²

600 EFI

- 85 horsepower¹
- Down to 13.3 L/100 km²

E-TEC engines are the best-selling 2-stroke engines in snowmobiling.⁴

ROTAX ACE™ 4-STROKE ENGINES

With the Advanced Combustion Efficiency (ACE) family of engines, BRP engineers optimized the combustion system, reduced mechanical friction, and freed intake and exhaust breathing. The result is the most efficient engines in snowmobiling. Not only are they efficient, they're a pleasure to operate and own. Very little maintenance is required; they run smoothly and produce a nice, solid – yet quiet – sound.

900 ACE TURBO R

- Rotax-designed turbocharger
- 180 horsepower¹
- Cable-activated throttle with reconfigured iTC

900 ACE TURBO – 130 WITH iTC

- 130 horsepower¹
- Down to 12.1 L/100 km³

900 ACE WITH iTC

- 3 cylinders
- 95 horsepower¹
- Down to 10.8 L/100 km³

600 ACE WITH iTC

- 2 cylinders
- 62 horsepower¹
- Down to 8 L/100 km – the most fuel-efficient in the entire industry³

ACE engines are the best-selling 4-stroke engines in snowmobiling.⁴

INTELLIGENT THROTTLE CONTROL

Standard on the ACE engines, the iTC™ system delivers a whole different snowmobiling experience.

- **Driving Modes:** A button on the console enables you to select one of three driving modes. Standard mode ensures a smooth start and linear acceleration; Sport enables full performance and quicker acceleration; ECO® limits top speed and acceleration rates for a more relaxed, fuel-conserving ride.
- **Finger Throttle** (only on 600 ACE and 900 ACE engines without Turbo): The throttle block can be rotate forward for use as a finger throttle, if preferred. Great for changing hand positions on a long ride and for more control through bumps.

¹ Observed metric horsepower based on internal dyno test performed in optimal conditions.

² Data based on internal engineering trail testing.

³ Data based on internal engineering trail testing in ECO mode.

⁴ Based on retail sale results as of December 31, 2019.



Experience the advantage of XPS. Oil and care products engineered to extend the life of your ride, tested in the world's harshest conditions, and designed to optimize your vehicle's performance. Learn more at XPSlubricants.com

RAVE GLS



SPRING
ONLY



Race Orange / Black

ROTAX® ENGINE

850 E-TEC Turbo R

Engine details

Liquid-cooled, two-stroke,
turbocharged, water injection
system, 3-D R.A.V.E.™

Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight	241 kg
------------	--------

COLOUR

DIMENSIONS

Vehicle overall length*	3040 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	38 mm Ice Ripper XT studded

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS ³
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

FEATURES

Frame	Radien ²	Heated throttle lever	Standard
Skis	Blade XC+	Heated grips	Standard
Seating	Sport, 1-up	Gauge	10.25" Touchscreen Display
Handlebar	U-type aluminium with hooks	Windshield	Low
Riser block height	90 mm	USB power outlet	Yes, in front compartment
Starter	Manual with SHOT	LinQ attachment	2 pairs
Reverse	RER		

* Vehicle overall length without snowflap.

RAVE RE



ROTAX® ENGINE

600R E-TEC

850 E-TEC

Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	
Displacement	599.4 cc	849 cc
Bore	72.3 mm	82 mm
Stroke	73 mm	80.4 mm
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight	220 kg	231 kg
------------	--------	--------

FEATURES

Frame	Radien ²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual Electric (spring only)
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display / 10.25" Touchscreen Display (spring only)
Windshield	Low
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs

COLOUR

Viper Red/Black

DIMENSIONS

Vehicle overall length*	3040 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	41 mm Cobra 38 mm Ice Ripper XT studded (spring only)

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS ³
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

* Vehicle overall length without snowflap.

RAVE RE WITH ENDURO PACKAGE



ROTAX® ENGINE

600R E-TEC

Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight	219 kg
------------	--------

FEATURES

Frame	Radien ²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display
Windshield	Low
USB power outlet	Yes, in front compartment
LinQ attachment	1 pair

COLOUR



Viper Red/Black

DIMENSIONS

Vehicle overall length*	2920 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3269 mm
Track profile height	41 mm Cobra

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS ³
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

* Vehicle overall length without snowflap.

ADVENTURE



Trail
+ Family Fun



ROTAX® ENGINE

600 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

COLOUR

Viper Red / Black

DIMENSIONS

Vehicle overall length*	3160 mm
Vehicle overall width	1280 mm
Vehicle overall height	1280 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3705 mm
Track profile height	41 mm Cobra

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS+
Front shock	KYB 36
Rear suspension	PPS ³
Center shock	KYB 36
Rear shock	KYB 36

DRY WEIGHT

Dry weight	227 kg
------------	--------

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	4.5" digital display
Seating	Sport, 1-up	Windshield	Medium with side deflectors
Handlebar	U-type steel with hooks	Visor Plug front / rear	Front
Riser block height	120 mm	USB power outlet	Yes, in front compartment
Starter	Electric	Air radiator with fan	
Reverse	Mechanical	LinQ attachment	2 pairs
Heated throttle lever	Standard		

* Vehicle overall length without snowflap.

ADVENTURE LIMITED



Trail
+ Family Fun



ROTAX® ENGINE

	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3	
Displacement	899.0 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM	7750 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	

POWERTRAIN

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT

Dry weight	247 kg (1 up) 258 kg (2 up)	252 kg (1 up) 263 kg (2 up)
------------	--------------------------------	--------------------------------

FEATURES

Frame	Radien ²
Skis	Blade DS+
Seating	Sport, 1-up or 2-up heated
Handlebar	U-type steel with hooks
Riser block height	120 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard

COLOUR

Noble Bronze / Black

DIMENSIONS

Vehicle overall length*	3180 mm
Vehicle overall width	1280 mm
Vehicle overall height	1320 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3705 mm
Track profile height	41 mm Cobra

SUSPENSION

Front suspension	LFS+
Front shock	KYB 36 Plus R
Rear suspension	PPS ³
Center shock	KYB 36 Plus Kashima
Rear shock	KYB 46 Plus Kashima

* Vehicle overall length without snowflap.

ADVENTURE LX



Family Fun
+ Trail



Viper Red / Black

ROTAX® ENGINE

600 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

COLOUR

DIMENSIONS

Vehicle overall length*	3060 mm
Vehicle overall width	1280 mm
Vehicle overall height	1470 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	32 mm Ripsaw

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS+
Front shock	KYB 36
Rear suspension	PPS ³
Center shock	KYB 36
Rear shock	KYB 36

DRY WEIGHT

Dry weight	240 kg
------------	--------

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	2-up
Handlebar	U-type steel with hooks
Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5" digital display
Windshield	Extra high with side deflectors
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	1 pair

* Vehicle overall length without snowflap.

ADVENTURE ELECTRIC



Family Fun
+ Trail



PACKAGE HIGHLIGHTS

- The Adventure Electric is the first in a line of electric snowmobiles to be powered by the proprietary ROTAX E-POWER technology on Radien² platform.
- Specifically designed for guided snowmobile safari operators and commercial usage.
- Offers a zero-emission snowmobiling experience.
- Provides a unique, user-friendly riding experience. Rediscover the spectacular winter landscape and enjoy the outdoors like never before!
- Range is optimized for short guided tour circuits, with fast automotive standard level 2 charging for quick return to operations.
- Longer track option, equipped with a 32 mm track profile, provides additional traction needed e.g. for usage in ski resorts.
- Recharge time with level 2 standard is 90 minutes to recharge the battery from 10% to 80%.
- Features a 10.25" in touchscreen digital display with simple easy-to-read instructions.
- Tour operators will have access to speed limitation options for inexperienced riders.
- Features 585 mm tall windshield and LED lighting.
- Up to 50 km (3050) / 30 km (3500) range**

MOTOR

ROTAX E-POWER

BATTERY

Battery	Integrated lithium-ion
Charger type	On-board charger, level 2
Connector	J1772 type 2
Charging time	1.5 h for 10%–80%. Less than 3 h for 0–100%
Range	Up to 50 km (3050)** Up to 30 km (3500)**

**Estimated total range when the snowmobile is fully charged and operated under ideal driving conditions. The actual range may decrease significantly (50% or more) depending on multiple factors. Based on a maximum speed of 25km/h (15.5 mph).

POWERTRAIN

Transmission	Clutchless direct drive with chaincase
Drive sprocket pitch	73 mm

DRY WEIGHT

Dry weight	245 kg (3050) 251 kg (3500)
------------	--------------------------------

FEATURES

Frame	Radien ²
Skis	Pilot 5.7 SLT
Seating	2-up
Handlebar	Standard with J-hooks
Riser block height	120 mm
Starter	Electric

COLOUR

Viper Red / Bright White

DIMENSIONS

Vehicle overall length*	2940 mm (3050) 3060 mm (3500)
Vehicle overall width	1250 mm
Vehicle overall height	1470 mm
Ski stance	1097 mm
Track nominal width	356 mm (3050) 381 mm (3500)
Track nominal length	3048 mm (3050) 3487 mm (3500)
Track profile height	19 mm High-Efficiency (3050) 32 mm Ripsaw (3500)

SUSPENSION

Front suspension	LFS+
Front shock	Motion Control
Rear suspension	Revised SC-5 (3050) SC-5M (3500)
Center shock	Motion Control
Rear shock	KYB 36

Reverse	Yes
Heated throttle lever	Standard
Heated grips	Standard
Gauge	10.25" Touchscreen Display
Windshield	Ultra-high
LinQ attachment	1 pair (3050) 2 pairs (3500)

* Vehicle overall length without snowflap.

XTERRAIN



On & Off Trail

+ Trail

+ Family Fun



ROTAX® ENGINE

600R E-TEC

600 EFI

Engine details

Liquid-cooled,
two-stroke, 3-D R.A.V.E.™Liquid-cooled,
two-stroke

Cylinders

2

Displacement

599.4 cc

Bore

72.3 mm

Stroke

73 mm

Maximum engine speed

8100 RPM

7500 RPM

Carburation

Electronic Direct
Injection

EFI

Recommended fuel type

Unleaded

Minimum octane

95

Fuel tank

37 liters

Oil tank capacity (2-stroke)

3.4 liters

POWERTRAIN

Drive clutch type

pDrive with clickers

pDrive

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
aluminium master cylinder

DRY WEIGHT

Dry weight

220 kg

221 kg

FEATURES

Frame

Radien² (600R)
Radien (600 EFI)

Skis

Blade XC+

Seating

Sport, 1-up

Handlebar

U-type aluminium with hooks,
low grab handle

Riser block height

120 mm

Starter

Electric and manual

Reverse

RER

Heated throttle lever

Standard

Heated grips

Standard

Gauge

4.5" digital display

Windshield

Low

Visor Plug front / rear

Front

USB power outlet

Yes, in front compartment

LinQ attachment

2 pairs

COLOUR

Race Orange / Black

DIMENSIONS

Vehicle overall length*

3180 mm

Vehicle overall width

1270 mm

Vehicle overall height

1280 mm

Ski stance

1097 mm

Track nominal width

406 mm

Track nominal length

3705 mm

Track profile height

51 mm PowderMax

SUSPENSION

Front suspension

LFS+

Front shock

KYB 36

Rear suspension

PPS³

Center shock

KYB 36

Rear shock

KYB 36

* Vehicle overall length without snowflap.

XTERRAIN RE



Trail
+ On & Off Trail



Viper Red / Black
Black (spring only on
Turbo models)

ROTAX® ENGINE

	850 E-TEC	850 E-TEC Turbo R	900 ACE Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbo-charged, water injection system, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2		3
Displacement	849 cc		899.0 cc
Bore	82 mm		74 mm
Stroke	80.4 mm		69.7 mm
Maximum engine speed	7900 RPM		
Carburation	Electronic Direct Injection with additional booster injectors		EFI
Recommended fuel type	Unleaded		
Minimum octane	95		
Fuel tank	37 liters		
Oil tank capacity (2-stroke)	3.4 liters		

POWERTRAIN

Drive clutch type	pDrive with clickers	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

DRY WEIGHT

Dry weight	244 kg	253 kg	260 kg
-------------------	--------	--------	--------

FEATURES

Frame	Radien ²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Electric and manual (850) SHOT (850 Turbo) Electric (900 Turbo)
Reverse	RER Electromechanical (900 Turbo)

COLOUR

DIMENSIONS

Vehicle overall length*	3150 mm
Vehicle overall width	1270 mm
Vehicle overall height	1260 mm
Ski stance	1097 mm
Track nominal width	406 mm 381 mm (studded)
Track nominal length	3705 mm
Track profile height	51 mm PowderMax 41 mm Ice Cobra studded (spring only)

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS ³
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display / 10.25" Touchscreen Display (spring only)
Windshield	Low
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs

* Vehicle overall length without snowflap.

BRUTAL RE



Deep Snow
+ Steep and deep
+ On & Off Trail



Viper Red / Black
Black (spring only on
Turbo model)

ROTAX® ENGINE

	850 E-TEC	900 ACE Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2	3
Displacement	849 cc	899.0 cc
Bore	82 mm	74 mm
Stroke	80.4 mm	69.7 mm
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	EFI
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN

Drive clutch type	pDrive with clickers	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

DRY WEIGHT

Dry weight	252 kg	264 kg
------------	--------	--------

FEATURES

Frame	Radien ²
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Electric and manual (850) Electric (900 Turbo)
Reverse	RER (850) Electromechanical (900 Turbo)

COLOUR

DIMENSIONS

Vehicle overall length*	3250 mm
Vehicle overall width	1200 mm
Vehicle overall height	1240 mm
Ski stance	996 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	64 mm PowderMax

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	PPS ² -DS+
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 EA-3 R Kashima

* Vehicle overall length without snowflap.

BRUTAL RE (500 mm)



Deep Snow
+ Steep and deep
+ On & Off Trail



Viper Red / Black
Black (spring only on
Turbo model)

ROTAX® ENGINE	850 E-TEC	900 ACE Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	2	3
Displacement	849 cc	899.0 cc
Bore	82 mm	74 mm
Stroke	80.4 mm	69.7 mm
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	EFI
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN

Drive clutch type	pDrive with clickers	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

DRY WEIGHT

Dry weight	259 kg	283 kg
------------	--------	--------

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Brutal, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Electric and manual (850) Electric (900 Turbo)
Reverse	RER (850) Electromechanical (900 Turbo)

COLOUR

DIMENSIONS

Vehicle overall length*	3300 mm
Vehicle overall width	1200 mm
Vehicle overall height	1230 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	60 mm PowderMax

SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	EasyRide+
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 EA-3 R Kashima

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display / 7.8" panorama display (spring only)
Windshield	Low
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

COMMANDER



On & Off Trail

+ Utility

+ Mountain / Deep Snow

+ Family Fun



ROTAX® ENGINE	600R E-TEC	900 ACE	900 ACE Turbo	COLOUR	Scandie Blue / Black
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged	DIMENSIONS	
Cylinders	2	3		Vehicle overall length*	3240 mm
Displacement	599.4 cc	899.0 cc		Vehicle overall width	1200 mm
Bore	72.3 mm	74 mm		Vehicle overall height	1500 mm
Stroke	73 mm	69.7 mm		Ski stance	996 mm
Maximum engine speed	8100 RPM	7250 RPM	7750 RPM	Track nominal width	500 mm
Carburation	Electronic Direct Injection	EFI		Track nominal length	3923 mm
Recommended fuel type	Unleaded	Unleaded		Track profile height	44 mm PowderMax
Minimum octane	95	95		DRY WEIGHT	
Fuel tank		42 liters		Dry weight	265 kg (600R E-TEC) 277 kg (900 ACE) 289 kg (900 ACE Turbo)
Oil tank capacity (2-stroke)	3.4 liters			SUSPENSION	
POWERTRAIN				Front suspension	LFS+ with curved lower A-Arms
Gearbox	2F/N/R with push-button reverse			Front shock	KYB 36
Drive clutch type	pDrive with clickers	pDrive with slider shoes	pDrive	Rear suspension	Articulated EasyRide+ with adjustment
Driven clutch type	QRS			Center shock	KYB 36
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder			Rear shock	KYB 36
FEATURES				Heated throttle lever	Standard
Frame	Radien-X			Heated grips	Standard
Skis	Blade DS+			Gauge	4.5" digital display
Seating	Modular, 1-up			Windshield	Extra high with side deflectors
Handlebar	U-type steel with hooks, low grab handle			Hitch	Standard
Riser block height	145 mm			Visor Plug front / rear	Front
Starter	Electric and manual (E-TEC) Electric (ACE)			USB power outlet	Front
Reverse	RER (E-TEC) Electromechanical (ACE)			Air radiator with fan	Yes
				LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

COMMANDER RE



On & Off Trail

+ Mountain / Deep Snow

+ Utility

+ Family Fun



ROTAX® ENGINE

900 ACE Turbo R

Engine details	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7900 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT

Dry weight	295 kg
------------	--------

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	7.2" wide digital display / 7.8" panorama display (spring only)
Windshield	Low
Hitch	Standard
Visor Plug front / rear	Front
USB power outlet	Front
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate

COLOUR

Clazier Cyan / Black

DIMENSIONS

Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1250 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)

SUSPENSION

Front suspension	LFS+ with curved lower A-Arms
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	EasyRide+ with adjustment
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 EA-3 R Kashima

* Vehicle overall length without snowflap.

COMMANDER LIMITED



On & Off Trail
+ Utility
+ Mountain / Deep Snow
+ Family Fun



ROTAX® ENGINE	900 ACE	900 ACE Turbo	COLOUR	Noble Bronze / Black
Engine details	Liquid-cooled, four-stroke D.O.H.C.		DIMENSIONS	
Cylinders	3		Vehicle overall length*	3240 mm
Displacement	899.0 cc		Vehicle overall width	1200 mm 1280 mm (w. 2up seat)
Bore	74 mm		Vehicle overall height	1500 mm
Stroke	69.7 mm		Ski stance	996 mm 1097 mm (w. 2up seat)
Maximum engine speed	7250 RPM	7750 RPM	Track nominal width	500 mm
Carburation	EFI		Track nominal length	3923 mm
Recommended fuel type	Unleaded		Track profile height	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)
Minimum octane	95		SUSPENSION	
Fuel tank	42 liters		Front suspension	LFS+ with curved lower A-Arms (1-up) LFS+ (2-up)
POWERTRAIN	2F/N/R with push-button reverse		Front shock	KYB 36 Plus (1-up) KYB 36 Plus R (2-up)
Gearbox	2F/N/R with push-button reverse		Rear suspension	Articulated EasyRide+ with adjustment
Drive clutch type	pDrive with slider shoes	pDrive	Center shock	KYB 46 Plus Kashima
Driven clutch type	QRS		Rear shock	KYB 46 Plus Kashima
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder		DRY WEIGHT	
DRY WEIGHT			Dry weight	287 kg (1 up) 298 kg (2 up)
				298 kg (1 up) 309 kg (2 up)
FEATURES	Radien-X		Heated throttle lever	Standard
Frame	Blade DS+		Heated grips	Standard
Skis	Modular, 1-up or 2-up heated		Gauge	7.2" wide digital display
Seating	U-type steel with hooks, low grab handle		Windshield	Extra high with side deflectors
Handlebar	145 mm		Hitch	Standard
Riser block height	Electric		Visor Plug front / rear	Front and rear (2-up)
Starter	Electromechanical		USB power outlet	Front
Reverse			Air radiator with fan	Yes
			LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

SHREDDER



Steep and deep
+ Mountain / Deep Snow



ROTAX® ENGINE

600R E-TEC

Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT

Dry weight	3700: 194 kg 3900: 198 kg
------------	------------------------------

FEATURES

Frame	Radien ²
Skis	Blade DS+
Seating	Mountain Light, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Manual Electric (spring only)

COLOUR

Viper Red / Black

DIMENSIONS

Vehicle overall length*	3060 mm (3700) 3190 mm (3900)
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	381 mm
Track nominal length	3705 mm 3923 mm
Track profile height	64 mm PowderMax

SUSPENSION

Front suspension	LFS
Front shock	KYB 36
Rear suspension	PPS ² -DS+
Center shock	KYB 36
Rear shock	KYB 36

* Vehicle overall length without snowflap.

SHREDDER RE



Steep and deep
+ Mountain / Deep Snow



Viper Red / Black
Black (only on Turbo
model)

ROTAX® ENGINE

600R E-TEC

850 E-TEC

850 E-TEC Turbo R

Engine details

Liquid-cooled,
two-stroke,
3-D R.A.V.E.™

Liquid-cooled,
two-stroke,
turbocharged,
3-D R.A.V.E.™

Cylinders

2

Displacement

599.4 cc

849 cc

Bore

72.3 mm

82 mm

Stroke

73 mm

80.4 mm

Maximum engine speed

8100 RPM

7900 RPM

Carburation

Electronic
Direct Injection

Electronic Direct Injection with
additional booster injectors

Recommended fuel type

Unleaded

Minimum octane

95

Fuel tank

37 liters

Oil tank capacity (2-stroke)

3.4 liters

POWERTRAIN

Drive clutch type

pDrive with clickers

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight

3700: 208 kg

3700: 215 kg
3900: 219 kg

3700: 222 kg
3900: 226 kg

FEATURES

Frame

Radien²

Skis

Blade DS+

Seating

Mountain Light, 1-up

Handlebar

U-type aluminium with hooks,
low grab handle

Riser block height

120 mm

Starter

Manual with SHOT
Electric (only on 3700)

Reverse

RER

Heated throttle lever

Standard

Heated grips

Standard

Gauge

4.5" digital display /
10.25" Touchscreen Display

USB power outlet

Yes, in front compartment

LinQ attachment

2 pairs

COLOUR

DIMENSIONS

Vehicle overall length* 3060 mm (3700)
3190 mm (3900)

Vehicle overall width 1120 mm

Vehicle overall height 1280 mm

Ski stance 921 mm

Track nominal width 381 mm

Track nominal length 3705 mm
3923 mm (64mm)
3912 mm (76mm)

Track profile height 64 mm PowderMax
76 mm PowderMax X-Light
(only on 3900)

SUSPENSION

Front suspension LFS

Front shock KYB PRO 40 EA-3 Kashima

Rear suspension PPS²-DS+

Center shock KYB 46 Plus Kashima

Rear shock KYB PRO 46 EA-3 R Kashima

* Vehicle overall length without snowflap.

SHREDDER DS



Steep and deep
+ Mountain / Deep Snow



Hot Chili Metallic / Black
Black (only on Turbo
model)

ROTAX® ENGINE

	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	
Displacement	849 cc	
Bore	82 mm	
Stroke	80.4 mm	
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder

DRY WEIGHT

Dry weight	3900: 204 kg	3900: 211 kg 4100: 216 kg
------------	--------------	------------------------------

FEATURES

Frame	Radien ²
Skis	Blade DS+
Seating	Mountain Light, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Manual with SHOT Electric (only on 3900)

COLOUR

DIMENSIONS

Vehicle overall length*	3190 mm (3900) 3335 mm (4100)
Vehicle overall width	1055 mm
Vehicle overall height	1280 mm
Ski stance	863 mm
Track nominal width	381 mm
Track nominal length	3912 mm 4178 mm
Track profile height	76 mm PowderMax X-Light

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 Plus Kashima
Rear suspension	PPS ² -DS+
Center shock	KYB 36 Plus Kashima
Rear shock	KYB 36 Plus Kashima

* Vehicle overall length without snowflap.

49 RANGER



Mountain / Deep Snow

+ On & Off Trail

+ Utility



ROTAX® ENGINE

	600 ACE	600 EFI
Engine details	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, two-stroke
Cylinders	2	
Displacement	600 cc	599.4 cc
Bore	74 mm	72.3 mm
Stroke	69.7 mm	73 mm
Maximum engine speed	7250 RPM	7500 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	

POWERTRAIN

Drive clutch type	eDrive II	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

DRY WEIGHT

Dry weight	238 kg	229 kg
------------	--------	--------

FEATURES

Frame	Radien (EFI) Radien-X (ACE)	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Sport, 1-up	Gauge	4.5" digital display
Handlebar	U-type steel with hooks	Windshield	Medium with side deflectors
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric and manual (EFI) Electric (ACE)	USB power outlet	Yes, in front compartment
Reverse	RER (EFI) Mechanical (ACE)	Air radiator with fan	Yes
		LinQ attachment	Multi-LinQ plate

COLOUR



Viper Red / Black

DIMENSIONS

Vehicle overall length*	3330 mm (ACE) 3270 mm (EFI)
Vehicle overall width	1200 mm
Vehicle overall height	1340 mm
Ski stance	996 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	38 mm DSG

SUSPENSION

Front suspension	LFS+
Front shock	KYB 36
Rear suspension	PPS ² -DS+
Center shock	KYB 36
Rear shock	KYB 36

* Vehicle overall length without snowflap.

49 RANGER PRO



Mountain / Deep Snow

- + Steep and deep
- + On & Off Trail
- + Utility



Orange/Full Moon
Silver/Black

ROTAX® ENGINE	600R E-TEC	850 E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	
Displacement	599.4 cc	849 cc
Bore	72.3 mm	82 mm
Stroke	73 mm	80.4 mm
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT

Dry weight	240 kg	249 kg
-------------------	--------	--------

FEATURES

Frame	Radien ²
Skis	Blade DS+
Seating	Sport, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric and manual
Reverse	RER
Heated throttle lever	Standard

COLOUR

DIMENSIONS

Vehicle overall length*	3385 mm
Vehicle overall width	1120 mm
Vehicle overall height	1320 mm
Ski stance	921 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	64 mm PowderMax

SUSPENSION

Front suspension	LFS with curved lower A-Arms
Front shock	KYB 36
Rear suspension	PPS ² -DS+
Center shock	KYB 36
Rear shock	KYB 36

Heated grips	Standard
Gauge	7.2" wide digital display
Windshield	Medium with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

59 RANGER



Utility

- + On & Off Trail
- + Deep Snow
- + Family Fun



Viper Red / Black

ROTAX® ENGINE

600 ACE

600 EFI

Engine details	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, two-stroke
Cylinders	2	
Displacement	600 cc	599.4 cc
Bore	74 mm	72.3 mm
Stroke	69.7 mm	73 mm
Maximum engine speed	7250 RPM	7500 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	
Oil tank capacity (2-stroke)		3.4 liters

POWERTRAIN

Drive clutch type	eDrive II	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

DRY WEIGHT

Dry weight	247 kg	241 kg
------------	--------	--------

FEATURES

Frame	Radien-X	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Modular, 1-up	Gauge	4.5" digital display
Handlebar	U-type steel with hooks	Windshield	Extra high with side deflectors
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric and manual (EFI) Electric (ACE)	USB power outlet	Yes, in front compartment
Reverse	RER (EFI) Electromechanical (ACE)	Air radiator with fan	Yes
		LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

59 RANGER PRO



Utility

- + On & Off Trail
- + Deep Snow
- + Family Fun



Orange/
Full Moon Silver/Black

ROTAX® ENGINE

600 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

COLOUR

DIMENSIONS

Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1500 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS+ with curved lower A-Arms
Front shock	KYB 36
Rear suspension	Articulated EasyRide+ with adjustment
Center shock	KYB 36
Rear shock	KYB 36

DRY WEIGHT

Dry weight	263 kg
------------	--------

FEATURES

Frame	Radien-X	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Modular, 1-up heated	Gauge	7.2" wide digital display
Handlebar	U-type steel with hooks, low grab handle	Windshield	Extra high with side deflectors
Riser block height	145 mm	Hitch	Standard
Starter	Electric	Visor Plug front / rear	Front
Reverse	Electromechanical	USB power outlet	Yes, in front compartment
		Air radiator with fan	Yes
		LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

59 RANGER ALPINE



Heavy Duty Work

- + Utility
- + On & Off Trail
- + Mountain / Deep Snow



ROTAX® ENGINE

900 ACE

Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

COLOUR

White/Orange/Black

DIMENSIONS

Vehicle overall length*	3240 mm
Vehicle overall width	1280 mm
Vehicle overall height	1470 mm
Ski stance	1080 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	38 mm Ice Cobra silent (studded)

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive with slider shoes
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36
Rear suspension	Articulated EasyRide+ with adjustment & extension lock
Center shock	KYB 36
Rear shock	KYB 36

DRY WEIGHT

Dry weight	291 kg
------------	--------

FEATURES

Frame	Radien-X	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Modular, 1-up heated	Gauge	7.2" wide digital display
Handlebar	U-type steel with hooks, low grab handle	Windshield	Extra high with side deflectors
Riser block height	145 mm	Hitch	Standard
Starter	Electric	Visor Plug front / rear	Front and rear
Reverse	Electromechanical	USB power outlet	Yes, in front compartment
		Air radiator with fan	Yes

* Vehicle overall length without snowflap.

69 RANGER ALPINE



Heavy Duty Work

- + Utility
- + Mountain / Deep Snow
- + On & Off Trail



ROTAX® ENGINE

900 ACE Turbo

Engine details	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7750 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

COLOUR

White/Orange/Black

DIMENSIONS

Vehicle overall length*	3240 mm
Vehicle overall width	1280 mm
Vehicle overall height	1500 mm
Ski stance	1080 mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	38 mm Ice Cobra silent (studded)

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36
Rear suspension	EasyRide Alpine
Center shock	KYB 36
Rear shock	2 x KYB 36

DRY WEIGHT

Dry weight	316 kg
------------	--------

FEATURES

Frame	Radien-X	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Modular, 1-up heated	Gauge	7.2" wide digital display
Handlebar	U-type steel with hooks, low grab handle	Mirrors	Standard
Riser block height	145 mm	Windshield	Extra high with side deflectors
Starter	Electric	Hitch	Standard
Reverse	Electromechanical	Visor Plug front / rear	Front and rear
		USB power outlet	Yes, in front compartment
		Air radiator with fan	Yes

* Vehicle overall length without snowflap.

69 RANGER PRO



Heavy Duty Work

- + Utility
- + Mountain / Deep Snow
- + On & Off Trail



Orange/
Full Moon Silver/Black

ROTAX® ENGINE

900 ACE

900 ACE Turbo

Engine details	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3	
Displacement	899.0 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM	7750 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive with slider shoes
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT

Dry weight	304 kg	309 kg
------------	--------	--------

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard
Heated grips	Standard

COLOUR

DIMENSIONS

Vehicle overall length*	3250 mm
Vehicle overall width	1200 mm
Vehicle overall height	1450 mm
Ski stance	996 mm
Track nominal width	600 mm
Track nominal length	3923 mm
Track profile height	38 mm

SUSPENSION

Front suspension	LFS+ with curved lower A-Arms
Front shock	KYB 36
Rear suspension	Articulated EasyRide+ with adjustment
Center shock	KYB 36
Rear shock	KYB 36

Gauge	7.2" wide digital display
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

MODELS & PLATFORMS

2025

Radien²

RAVE GLS 850 E-TEC Turbo R
 RAVE RE 850 ETEC
 RAVE RE 600R E-TEC
 RAVE RE 600R E-TEC with Enduro package
 Xterrain RE 850 E-TEC Turbo R
 Xterrain RE 850 E-TEC
 Xterrain RE 900 ACE Turbo R
 Xterrain 600R E-TEC
 49 Ranger PRO 600R E-TEC
 49 Ranger PRO 850 E-TEC
 Adventure Electric
 Adventure Limited 900 ACE
 Adventure Limited 900 ACE Turbo
 Brutal RE 850 E-TEC, 400 mm
 Brutal RE 900 ACE Turbo R, 400 mm

Radien² Deep Snow

Shredder 3700 600R ETEC
 Shredder 3900 600R ETEC
 Shredder RE 3700 600R ETEC
 Shredder RE 3700 850 ETEC
 Shredder RE 3700 850 ETEC Turbo R
 Shredder RE 3900 850 ETEC
 Shredder RE 3900 850 ETEC Turbo R
 Shredder DS 3900 850 ETEC
 Shredder DS 3900 850 ETEC Turbo R
 Shredder DS 4100 850 ETEC Turbo R

Radien

Xterrain 600 EFI
 49 Ranger 600 EFI

Radien-X 400 mm

Adventure 600 ACE
 Adventure LX 600 ACE
 49 Ranger 600 ACE

Radien-X 500 mm

Brutal RE 850 E-TEC, 500 mm
 Brutal RE 900 ACE Turbo R, 500 mm
 Commander RE 900 ACE Turbo R
 Commander 600R ETEC
 Commander 900 ACE
 Commander 900 ACE Turbo
 Commander Limited 900 ACE
 Commander Limited 900 ACE Turbo
 59 Ranger 600 ACE
 59 Ranger 600 EFI
 59 Ranger PRO 600 ACE
 59 Ranger Alpine 900 ACE

Radien-X 600 mm

69 Ranger PRO 900 ACE
 69 Ranger PRO 900 ACE Turbo
 69 Ranger Alpine 900 ACE Turbo

2024

Radien²

Xterrain RE 3700 850 E-TEC
 Xterrain 3700 600R E-TEC
 Shredder RE 3700 600R E-TEC
 Shredder RE 3700 850 E-TEC
 Shredder RE 3700 850 E-TEC Turbo R
 Shredder RE 3900 850 E-TEC
 Shredder RE 3900 850 E-TEC Turbo R
 Shredder 3900 600R E-TEC
 Shredder DS 3900 850 E-TEC
 Shredder DS 3900 850 E-TEC Turbo R
 Shredder DS 4100 850 E-TEC Turbo R
 Rave RE 850 E-TEC
 Rave RE 600R E-TEC
 Rave Enduro 600R E-TEC
 49 Ranger PRO 600R E-TEC
 49 Ranger PRO 850 E-TEC

Radien

Xterrain 3700 600 EFI

Radien-X (400 mm)

Xterrain RE 3700 900 ACE Turbo R
 Adventure 600 ACE
 Adventure SC 900 ACE
 Adventure SC 900 ACE Turbo
 Adventure LX 600 ACE
 49 Ranger 600 ACE
 49 Ranger ST 900 ACE
 49 Ranger ST 900 ACE Turbo

Radien-X (500 mm)

Xterrain Brutal 3900 850 E-TEC
 Commander RE 900 ACE Turbo R
 Commander 600R E-TEC
 Commander 900 ACE
 Commander 900 ACE Turbo
 Commander Limited 900 ACE
 Commander Limited 900 ACE Turbo
 Commander Grand Tourer 900 ACE Turbo
 Commander Grand Tourer 900 ACE Turbo R
 59 Ranger 600 ACE 600 ACE
 59 Ranger 600 EFI 600 EFI
 59 Ranger Alpine 900 ACE

Radien-X (600 mm)

69 Ranger 900 ACE
 69 Ranger Limited 900 ACE Turbo
 69 Ranger SnowCruiser 900 ACE Turbo R
 69 Ranger Alpine 900 ACE Turbo

2023

Radien²

Shredder RE 3700 850 E-TEC
 Shredder RE 3700 850 E-TEC Turbo R
 Shredder RE 3900 850 E-TEC
 Shredder RE 3900 850 E-TEC Turbo R
 Shredder DS 3900 850 E-TEC
 Shredder DS 3900 850 E-TEC Turbo R
 Shredder DS 4100 850 E-TEC Turbo R

Radien

Xterrain 3700 600 EFI
 Xterrain 3700 600R E-TEC
 Xterrain 3900 600 EFI
 Xterrain 3900 600R E-TEC
 Xterrain PRO 3900 600R E-TEC
 Xterrain PRO 3900 850 E-TEC
 Xterrain RE 3700 850 E-TEC
 Shredder 3900 600R E-TEC
 Rave RE 600R E-TEC
 Rave RE 850 E-TEC
 Rave Enduro 600R E-TEC
 49 Ranger PRO 600R E-TEC

Radien-X (400 mm)

49 Ranger 600 ACE
 49 Ranger ST 900 ACE
 49 Ranger ST 900 ACE Turbo
 Xterrain RE 3700 900 ACE Turbo R
 Adventure 600 ACE
 Adventure LX 600 ACE
 Adventure SC 900 ACE
 Adventure SC 900 ACE Turbo



Radien-X (500 mm)

Commander 600R E-TEC
 Commander 900 ACE
 Commander 900 ACE Turbo
 Commander Limited 900 ACE
 Commander Limited 900 ACE Turbo
 Commander GLX 900 ACE Turbo R
 Commander Grand Tourer 900 ACE Turbo
 Commander Grand Tourer 900 ACE Turbo R
 Xterrain Brutal 850 E-TEC
 59 Ranger 600 ACE
 59 Ranger 600 EFI
 59 Ranger Alpine 900 ACE

Radien-X (600 mm)

69 Ranger 900 ACE
 69 Ranger Limited 900 ACE Turbo
 69 Ranger Limited 900 ACE Turbo R
 69 Ranger SnowCruiser 900 ACE Turbo R
 69 Ranger Alpine 900 ACE Turbo

LYNX 2025
SPECIFICATIONS

		Rave			Adventure			
								
		RE	RE with Enduro package	GLS	LX	Limited	Electric	
COLOUR		Viper Red / Black	Viper Red / Black	Race Orange / Black	Viper Red / Black	Viper Red / Black	Noble Bronze / Black	Viper Red / Bright White
FEATURES	Frame	Radien ²	Radien ²	Radien ²	Radien-X	Radien-X	Radien ²	Radien ²
	Skis	Blade XC+	Blade XC+	Blade XC+	Blade DS+	Blade DS+	Blade DS+	Pilot 5.7 SLT
	Seating	Sport, 1-up	Sport, 1-up	Sport, 1-up	Sport, 1-up	2-up	Sport, 1-up or 2-up heated	2-up
	Handlebar	U-type aluminium with hooks	U-type aluminium with hooks	U-type aluminium with hooks	U-type steel with hooks	U-type steel with hooks	U-type steel with hooks	Standard with J-hooks
	Starter	Manual Electric (spring only)	Manual	Manual with SHOT	Electric	Electric	Electric	Electric
	Reverse	RER	RER	RER	Mechanical	Mechanical	Electro-mechanical	Yes
	Windshield	Low	Low	Low	Medium with side deflectors	Extra high with side deflectors	Medium with side deflectors	Ultra-high
	Air radiator with fan				Yes			
GAUGE		7.2" wide digital display / 10.25" Touchscreen Display (spring only)	7.2" wide digital display	10.25" Touchscreen Display	4.5" digital display	4.5" digital display	7.2" wide digital display / 10.25" Touchscreen Display (spring only on Turbo)	10.25" Touchscreen Display
SUSPENSION	Front suspension	LFS+	LFS+	LFS+	LFS+	LFS+	LFS+	LFS+
	Front shock	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB 36	KYB 36	KYB 36 Plus R	Motion Control
	Rear suspension	PPS ³	PPS ³	PPS ³	PPS ³	PPS ³	PPS ³	Revised SC-5
	Center shock	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB 36	KYB 36	KYB 36 Plus Kashima	Motion Control
	Rear shock	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB PRO 46 HLCR Kashima	KYB 36	KYB 36	KYB 46 Plus Kashima	KYB 36
ROTAX® ENGINE		600R E-TEC 850 E-TEC	600R E-TEC	850 E-TEC Turbo R	600 ACE	600 ACE	900 ACE 900 ACE Turbo	ROTAX E-POWER
Fuel tank		37 liters	37 liters	37 liters	37 liters	37 liters	37 liters	
TRACK	Track nominal length	3487 mm	3269 mm	3487 mm	3705 mm	3487 mm	3705 mm	3048 mm
	Track nominal width	381 mm	381 mm	381 mm	381 mm	381 mm	381 mm	356 mm (3050) 381 mm (3500)
	Track profile height	41 mm Cobra 38 mm Ice Ripper XT studded (spring only)	41 mm Cobra	38 mm Ice Ripper XT studded	41 mm Cobra	32 mm Ripsaw	41 mm Cobra	19 mm High-Efficiency
DIMENSIONS	Ski stance	1097 mm	1097 mm	1097 mm	1097 mm	1097 mm	1097 mm	1097 mm
	Vehicle overall length*	3040 mm	2920 mm	3040 mm	3160 mm	3060 mm	3180 mm	2940 mm (3050) 3060 mm (3500)
	Vehicle overall width	1270 mm	1270 mm	1270 mm	1280 mm	1280 mm	1280 mm	1250 mm
	Vehicle overall height	1140 mm	1140 mm	1140 mm	1280 mm	1470 mm	1320 mm	1470 mm
	(Dry) Weight	220 kg 231 kg	219 kg	241 kg	227 kg	240 kg	900 ACE: 247 kg (1 up) 258 kg (2 up) 900 ACE Turbo: 252 kg (1 up) 263 kg (2 up)	245 kg

Xterrain		Brutal		Commander		
						
RE		RE	RE (500mm)	Limited		RE
Race Orange / Black	Viper Red / Black Black (spring only on Turbo models)	Viper Red / Black Black (spring only on Turbo model)	Viper Red / Black Black (spring only on Turbo model)	Scandie Blue / Black	Noble Bronze / Black	Clazier Cyan / Black
Radien ² (600R) Radien (600 EFI)	Radien ²	Radien ²	Radien-X	Radien-X	Radien-X	Radien-X
Blade XC+	Blade XC+	Blade DS+	Blade DS+	Blade DS+	Blade DS+	Blade DS+
Sport, 1-up	Sport, 1-up	Sport, 1-up	Brutal, 1-up	Modular, 1-up	Modular, 1-up or 2-up heated	Modular, 1-up heated
U-type aluminium with hooks, low grab handle	U-type aluminium with hooks, low grab handle	U-type aluminium with hooks, low grab handle	U-type aluminium with hooks, low grab handle	U-type steel with hooks, low grab handle	U-type steel with hooks, low grab handle	U-type steel with hooks, low grab handle
Electric and manual	Electric and manual (850) SHOT (850 Turbo) Electric (900 Turbo)	Electric and manual (850) Electric (900 Turbo)	Electric and manual (850) Electric (900 Turbo)	Electric and manual (600R) Electric (900, 900 Turbo)	Electric	Electric
RER	RER Electromechanical (900 Turbo)	RER (850) Electromechanical (900 Turbo)	RER (850) Electromechanical (900 Turbo)	RER (600R E-TEC) Electromechanical (ACE)	Electromechanical	Electromechanical
Low	Low	Low	Low	Extra high with side deflectors	Extra high with side deflectors	Low
		Yes	Yes	Yes	Yes	Yes
4.5" digital display	7.2" wide digital display / 10.25" Touchscreen Display (spring only)	7.2" wide digital display / 10.25" Touchscreen Display (spring only)	7.2" wide digital display / 7.8" panorama display (spring only)	4.5" digital display	7.2" wide digital display	7.2" wide digital display / 7.8" panorama display (spring only)
LFS+	LFS+	LFS+	LFS+	LFS+ with curved lower A-Arms	LFS+ with curved lower A-Arms (1-up) LFS+ (2-up)	LFS+ with curved lower A-Arms
KYB 36	KYB PRO 46 HLCR Kashima	KYB PRO 36 EA-3 R Kashima	KYB PRO 36 EA-3 R Kashima	KYB 36	KYB 36 Plus (1-up) KYB 36 Plus R (2-up)	KYB PRO 36 EA-3 R Kashima
PPS ³	PPS ³	PPS ² -DS+	EasyRide+	Articulated EasyRide+ with adjustment	Articulated EasyRide+ with adjustment	EasyRide+ with adjustment
KYB 36	KYB PRO 46 HLCR Kashima	KYB 46 Plus Kashima	KYB 46 Plus Kashima	KYB 36	KYB 46 Plus Kashima	KYB 46 Plus Kashima
KYB 36	KYB PRO 46 HLCR Kashima	KYB PRO 46 EA-3 R Kashima	KYB PRO 46 EA-3 R Kashima	KYB 36	KYB 46 Plus Kashima	KYB PRO 46 EA-3 R Kashima
600R E-TEC 600 EFI	850 E-TEC 850 E-TEC Turbo R 900 ACE Turbo R	850 E-TEC 900 ACE Turbo R	850 E-TEC 900 ACE Turbo R	600R E-TEC 900 ACE 900 ACE Turbo	900 ACE 900 ACE Turbo	900 ACE Turbo R
37 liters	37 liters	37 liters	42 liters	42 liters	42 liters	42 liters
3705 mm	3705 mm	3923 mm	3923 mm	3923 mm	3923 mm	3923 mm
406 mm	406 mm 381 mm (studded)	406 mm	500 mm	500 mm	500 mm	500 mm
51 mm PowderMax	51 mm PowderMax 41 mm Ice Cobra studded (spring only)	64 mm PowderMax	60 mm PowderMax	44 mm PowderMax	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)
1097 mm	1097 mm	996 mm	996 mm	996 mm	996 mm 1097 mm (w. 2up seat)	996 mm
3180 mm	3150 mm	3250 mm	3300 mm	3240 mm	3240 mm	3240 mm
1270 mm	1270 mm	1200 mm	1200 mm	1200 mm	1200 mm 1280 mm (w. 2up seat)	1200 mm
1280 mm	1260 mm	1240 mm	1230 mm	1500 mm	1500 mm	1250 mm
600R E-TEC: 220 kg 600 EFI: 221 kg	850 E-TEC: 244 kg 850 E-TEC Turbo R: 253 kg 900 ACE Turbo R: 260 kg	850 E-TEC: 252 kg 900 ACE Turbo R: 264 kg	850 E-TEC: 259 kg 900 ACE Turbo R: 283 kg	600R E-TEC: 265 kg 900 ACE: 277 kg 900 ACE Turbo: 289 kg	900 ACE: 287 kg (1 up) 298 kg (2 up) 900 ACE Turbo: 298 kg (1 up) 309 kg (2 up)	295 kg

LYNX 2025 SPECIFICATIONS

Shredder



DS

RE

COLOUR		Viper Red / Black	Hot Chili Metallic / Black Black (only on Turbo model)	Viper Red / Black Black (only on Turbo model)
FEATURES	Frame	Radien ²	Radien ²	Radien ²
	Skis	Blade DS+	Blade DS+	Blade DS+
	Seating	Mountain Light, 1-up	Mountain Light, 1-up	Mountain Light, 1-up
	Handlebar	U-type aluminium with hooks, low grab handle	U-type aluminium with hooks, low grab handle	U-type aluminium with hooks, low grab handle
	Starter	Manual Electric (spring only)	Manual with SHOT Electric (only on 3900)	Manual with SHOT Electric (only on 3700)
	Reverse	RER	RER	RER
	Windshield			
	Air radiator with fan			
GAUGE		4.5" digital display	4.5" digital display / 10.25" Touchscreen Display	4.5" digital display / 10.25" Touchscreen Display
SUSPENSION	Front suspension	LFS	LFS	LFS
	Front shock	KYB 36	KYB 36 Plus Kashima	KYB PRO 40 EA-3 Kashima
	Rear suspension	PPS ² -DS+	PPS ² -DS+	PPS ² -DS+
	Center shock	KYB 36	KYB 36 Plus Kashima	KYB 46 Plus Kashima
	Rear shock	KYB 36	KYB 36 Plus Kashima	KYB PRO 46 EA-3 R Kashima
ROTAX® ENGINE		600R E-TEC	850 E-TEC 850 E-TEC Turbo R	600R E-TEC 850 E-TEC 850 E-TEC Turbo R
Fuel tank		37 liters	37 liters	37 liters
TRACK	Track nominal length	3705 mm 3923 mm	3912 mm 4178 mm	3705 mm 3923 mm (64mm) 3912 mm (76mm)
	Track nominal width	381 mm	381 mm	381 mm
	Track profile height	64 mm PowderMax	76 mm PowderMax X-Light	64 mm PowderMax 76 mm PowderMax X-Light (only on 3900)
DIMENSIONS	Ski stance	921 mm	863 mm	921 mm
	Vehicle overall length*	3060 mm (3700) 3190 mm (3900)	3190 mm (3900) 3335 mm (4100)	3060 mm (3700) 3190 mm (3900)
	Vehicle overall width	1120 mm	1055 mm	1120 mm
	Vehicle overall height	1280 mm	1280 mm	1280 mm
	(Dry) Weight	3700: 194 kg 3900: 198 kg	3900: 204 kg 3900: 211 kg 4100: 216 kg	3700: 208 kg 3700: 215 kg 3700: 222 kg 3900: 219 kg 3900: 226 kg

49 Ranger

59 Ranger

69 Ranger



PRO



PRO

Alpine



PRO

Alpine

Viper Red / Black

Orange/Full Moon
Silver/Black

Viper Red / Black

Orange/Full Moon
Silver/BlackWhite/Orange/
BlackOrange/Full Moon
Silver/BlackWhite/Orange/
BlackRadien (EFI)
Radien-X (ACE)Radien²

Radien-X

Radien-X

Radien-X

Radien-X

Radien-X

Blade DS+

Blade DS+

Blade DS+

Blade DS+

Blade DS+

Blade DS+

Blade DS+

Sport, 1-up

Sport, 1-up heated

Modular, 1-up

Modular, 1-up
heatedModular, 1-up
heatedModular, 1-up
heatedModular, 1-up
heatedU-type steel with
hooksU-type steel with
hooks, low grab
handleU-type steel
with hooksU-type steel
with hooks, low
grab handleU-type steel
with hooks, low
grab handleU-type steel
with hooks, low
grab handleU-type steel
with hooks, low
grab handleElectric and manual
(EFI)
Electric (ACE)

Electric and manual

Electric and manual
(EFI)
Electric (ACE)

Electric

Electric

Electric

Electric

RER (EFI)
Mechanical (ACE)

RER

RER (EFI)
Electromechanical
(ACE)

Electromechanical

Electromechanical

Electromechanical

Electromechanical

Medium with side
deflectorsMedium with side
deflectorsExtra high with
side deflectorsExtra high with
side deflectorsExtra high with
side deflectorsExtra high with
side deflectorsExtra high with
side deflectors

Yes

Yes

Yes

Yes

Yes

Yes

Yes

4.5" digital
display7.2" wide digital
display4.5" digital
display7.2" wide digital
display7.2" wide digital
display7.2" wide digital
display7.2" wide digital
display

LFS+

LFS
with curved lower
A-Arms

LFS+

LFS+
with curved lower
A-Arms

LFS

LFS+
with curved lower
A-Arms

LFS

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

PPS²-DS+PPS²-DS+

EasyRide+

Articulated
EasyRide+ with
adjustmentArticulated
EasyRide+ with
adjustment &
extension lockArticulated
EasyRide+ with
adjustment

EasyRide Alpine

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

KYB 36

2 x KYB 36

600 ACE
600 EFI600R E-TEC
850 E-TEC600 ACE
600 EFI

600 ACE

900 ACE

900 ACE
900 ACE Turbo

900 ACE Turbo

37 liters

37 liters

42 liters

42 liters

42 liters

42 liters

42 liters

3923 mm

3923 mm

3923 mm

3923 mm

3923 mm

3923 mm

3968 mm

406 mm

406 mm

500 mm

500 mm

500 mm

600 mm

600 mm

38 mm DSG

64 mm PowderMax

38 mm

44 mm

38 mm Ice Cobra
silent (studded)

38 mm

38 mm Ice Cobra
silent (studded)

996 mm

921 mm

996 mm

996 mm

1080 mm

996 mm

1080 mm

3330 mm (ACE)
3270 mm (EFI)

3385 mm

3240 mm

3240 mm

3240 mm

3250 mm

3240 mm

1200 mm

1120 mm

1200 mm

1200 mm

1280 mm

1200 mm

1280 mm

1340 mm

1320 mm

1500 mm

1500 mm

1470 mm

1450 mm

1500 mm

238 kg (ACE)
229 kg (EFI)240 kg (600R)
249 kg (850)247 kg (ACE)
241 kg (EFI)

263 kg

291 kg

304 kg (900 ACE)
309 kg (900 ACE
Turbo)

316 kg