

# 1 RAM Model

## 1.1 Memory

Infinite sequence of cells, contains  $w$  bits. Every cell has an address starting at 1

## 1.2 CPU

32 registers of width  $w$  bits.

### 1.2.1 Operations

Set value to register (constant or from other register). Take two integers from other registers and store the result of;  $a+b, a-b, a \cdot b, a/b$ . Take two registers and compare them;  $a < b, a = b, a > b$ . Read and write from memory.

## 1.3 Definitions

An algorithm is a set of atomic operations. Its cost is the number of atomic operations. A word is a sequence of  $w$  bits

## 2 Worst-case

Worst-case cost of an algorithm is the longest possible running time of input size  $n$

## 3 Dictionary search

let  $n$  be register 1, and  $v$  be register 2  
register  $left \rightarrow 1, right \rightarrow 1$   
while  $left \leq right$   
    register  $mid \rightarrow (left + right)/2$   
    if the memory cell at address

```
mid = v then
    return yes
else if memory cell at address
mid > v then
    right = mid - 1
else
    left = mid + 1
return no
```

Worst-case time:  $f_2(n) = 2 + 6 \log_2 n$

## 4 Big-O

We say that  $f(n)$  grows asymptotically no faster than  $g(n)$  if there is a constant  $c_1 > 0$  such that  $f(n) \leq c_1 \cdot g(n)$  and holds for all  $n$  at least a constant  $c_2$ . This is denoted by  $f(n) = O(g(n))$ .

### 4.1 Example

$1000 \log_2 n = O(n), n \neq O(10000 \log_2 n)$   
 $\log_{b_1} n = O(\log_{b_2} n)$  for any constants  $b_1 > 1$  and  $b_2 > 1$ . Therefore  $f(n) = 2 + 6 \log_2 n$  can be represented;  $f(n) = O(\log n)$

## 5 Big-Ω

If  $g(n) = O(f(n))$ , then  $f(n) = \Omega(g(n))$  to indicate that  $f(n)$  grows asymptotically no slower than  $g(n)$ . We say that  $f(n)$  grows asymptotically no slower than  $g(n)$  if  $c_1 > 0$  such  $f(n) \geq c_1 \cdot g(n)$  for  $n > c_2$ ; denoted by  $f(n) = \Omega(g(n))$

## 6 Big-Θ

If  $f(n) = O(g(n))$  and  $f(n) = \Omega(g(n))$ , then  $f(n) = \Theta(g(n))$  to indicate that  $f(n)$  grows asymptotically as fast as  $g(n)$

## 7 Sort

### 7.1 Merge Sort

Divide the array into two parts, sort the individual arrays then combine the arrays together.  $f(n) = O(n \log n)$ .

This is the fastest sorting time possible (apart from  $O(n \log \log n)$ )

### 7.2 Counting Sort

A set  $S$  of  $n$  integers and every integer is in the range  $[1, U]$ . (all integers are distinct)

**Step 1:** Let  $A$  be the array storing  $S$ . Create array  $B$  of length  $U$ . Set  $B$  to zero.

**Step 2:** For  $i \in [1, n]$ ; Set  $x$  to  $A[i]$ , Set  $B[x] = 1$

**Step 3:** Clear  $A$ , For  $x \in [1, U]$ ; If  $B[x] = 0$  continue, otherwise append  $x$  to  $A$

#### 7.2.1 Analysis

Step 1 and 3 take  $O(U)$  time, while Step 2  $O(n)$  time. Therefore running time is  $O(n + U) = O(U)$ .

## 8 Random

RANDOM( $x, y$ ) returns an integer between  $x$  and  $y$  chosen uniformly at random