

INFS3202  
Individual Proposal

Maxwell Bo

March 19, 2017

# Chapter 1

## Requirements Engineering

### 1.1 Rationale

The service is designed to solve a very specific problem, borne of my own experience at university.

I noticed that immediately after leaving classes, I was sending similar message to many group chats across Slack and Facebook, asking if any people wanted to get lunch with me.

Thus, I required a service that would:

- Be aware of when I was leaving classes
- Be aware of my friends timetables, and when they were likely on breaks between classes
- Inform me, immediately on leaving a class, who was free and how long they are free for

My friends also expressed frustration that it was difficult to find times where all members of a certain group had breaks between classes, to coordinate meetups.

They required a service that would:

- Allow them to create groups of people of whom they wished to see shared break timetables
- Be aware of the group timetables, and when they were likely on breaks between classes
- Create a list of free times that the group can meet together

I realised that both of these problems could be addressed by very similar services.

### 1.2 Business Function

A client wishing to use the service (henceforth referred to as *SyncUQ* or ‘the app’) would face the following workflow.

- If the client is using a
  - desktop, upon navigating to [syncuq.com.au](https://syncuq.com.au), the client is presented a landing page, advertising the features of *SyncUQ*. A button allows the client to use [Facebook Login](#), so that they may use the service.
  - mobile, using the *SyncUQ* app, the client is asked whether they would like to permit the app to send them push notifications. The client is then presented the landing page.

- After completing the *Facebook Login*, the primary app interface is presented.
- The client is presented a choice of different tabs, corresponding to different features. Each tab, presents a different workflow.
  - **Import**
    - \* The client is presented with instructions on how to acquire a calendar link from [timetableplanner.app.uq.edu.au](http://timetableplanner.app.uq.edu.au) (henceforth referred to as *UQ Timetable Planner*).
    - \* The client may enter this calendar link into a field. Clicking the corresponding **Submit** button will cause the service to subscribe to the specified calendar.
  - **Friends**
    - \* The client is presented with an **Add Friends** button. Clicking this button presents a list of *SyncUQ* users, who are also Facebook friends of the client. Clicking a friend's corresponding **Follow** button, sends a *follow request*.
    - \* The client is presented with a list of friends that they have *followed*. These entries have two forms:
      - *Pending follow*, where the the friend has not approved their *follow request*
      - *Pending follow request*, where a friend has requested to *follow* the client, but the client has yet to approve the *follow request*. Two buttons, a  $\checkmark$  button, and a  $\times$  button, allow the client to confirm *follow requests*.
      - *Confirmed*, with a date and time, indicating the instant that both the client and that friend share a break, a *Time until*, indicating the duration in time and minutes until that instant begins, and a *Duration*, indicating the duration of the shared break. The entry doubles as a progress bar, depicting the progress into the break that friend has made. Clicking the entry presents a timetable of *breaks* that are shared.
  - **Settings**
    - \* The client is presented with a list of settings, that may include:
      - A toggle for *Incognito Mode*, which, when enabled, prevents a clients friends from seeing their breaks
      - A toggle for *Notifications at end of classes*, which, when enabled, whenever a client's scheduled classes are ending, the client will be notified of which of their friends are currently are on, or are starting, breaks. 'Opening' this notification will present the client the **Friends** tab of the app. Enabling this option would prompt the client to enable push notifications on their mobile device, if the app has not already done so.

# Chapter 2

## Architecture

TODO

### 2.1 Development Language and Environment

#### 2.1.1 Backend

Six requirements on the backend language and environment were identified.

1. Could not be Perl, PHP, or Java
2. Should support a mature, stable and frequently used microframework
3. Should support an industry-grade date and time library
4. Should support a stable *iCalendar* (.ics) file parser
5. Should be syntactically and semantically familiar to *all* members of the group
6. Should have first-class support or documentation for deployment to [Amazon EC2](#) or [Heroku](#) cloud services

A number of considered languages and environments failed to meet these requirements.

- Haskell, using [Scotty](#) failed requirements 3, 5, and 6
- Rust, using [Rocket](#), failed requirements 2 (on the grounds that Rocket was immature), 3, 4, 5 and 6
- Clojure, using [Compojure](#), failed requirement 5

Python and Scala met all requirements.

If Python were to be used, it would use

- The [Flask](#) microframework
- The [Flask-SQLAlchemy](#) database abstraction layer
- The [icalendar](#) *iCalendar* parser
- The [mypy](#) static type checker

- [Heroku](#), with the [Python buildpack](#)

If Scala were to be used, it would use

- [Play](#) framework, or [http4s](#) interface with [circe](#) JSON library
- The [doobie](#) database abstraction layer
- The [iCal4j](#) *iCalendar* parser
- The [cats](#) library for useful functional programming abstractions
- [Heroku](#), with the [Scala buildpack](#)

With further investigation of the Python and Scala stacks, both were deemed sufficient for use on the project. Ultimately, three, rather insignificant issues, broke the tie.

1. While all members of the group are familiar with the basics of Python, I have intimate knowledge of Scala and the stack described above. Ultimately, the group decided to ensure that all group members would use a language that they were at least moderately familiar with, rather than a sole individual having a large amount of experience, and the rest having none.
2. Scala requires [tooling support](#) to be ergonomic. The group decided that they would rather not burden their laptops limited CPU, memory and battery life with heavyweight IDEs.
3. The group decided that they would prefer to prioritise development speed by using a dynamic, interpreted language, with optional [mypy](#) static type checking, rather than deal with Scala's cripplingly slow compilation and typechecking processes.

Thus, the Python stack was chosen.

### 2.1.2 Frontend

Four requirements on the frontend language and environment were identified

1. Should support a framework that uses a virtual DOM
2. Should be easy to learn for group members who have no former frontend development experience
3. Should support an ergonomic Foreign Function Interface (*FFI*) to Javascript
4. Should support the ergonomic use of [React](#) components and libraries

A number of considered languages and environments failed to meet these requirements.

- [Elm](#) failed requirements 3 and 4
- [TypeScript](#) with [React](#) failed requirement 2.

Thus, [PureScript](#) with [Pux](#) was chosen.

Furthermore, the [Sass](#) framework to be used is [Bulma](#), chosen on aesthetic and usability grounds.

To ensure that the service appeals to UQ students, the site's design draws from elements defined in the [UQ Base theme: Style Guide](#). This includes the liberal use of colours [#49075e](#) and [#FFFFFF](#) - UQ purple and white respectively.

## Chapter 3

# Design

### 3.1 Web Standards

Compliance with web standards ensure accessibility, robustness, interoperability and usability of all webpages and websites. Significant efforts have been made to ensure that the backend exposes an idiomatic, [standards compliant RESTful API](#). Ajax with JSON will mediate client-server communications, with server responses adhering to the [Google JSON Style Guide](#).

#### 3.1.1 Endpoints

REST endpoints that may need to be implemented include

- GET /friends -> Ok[List[UserID]]
- GET /friends/:userid -> Ok[FriendDetails]
- GET /friend\_breaks -> Ok[Map[FriendID, List[Break]]]
- POST /upload\_calendar -> Created[CalendarDetails]
- ...

### 3.2 Advanced Features

Advanced dynamic functionality, powered by PuresScript, includes

- A reactive, *Single Page App*, which permits the following actions to be performed without page reloads:
  - Sending friend *follow requests*
  - Confirm/deny/cancel of *pending follow requests*
- Advanced visual effects and information display features, including:
  - In-app alerts
  - Dynamic progress bars
  - Dynamic timers
  - Friend searching and filtering

### 3.3 Environment

The app is to be auto-deployed to a [Heroku](#) staging environment, triggered by a [GitHub push hook](#). Manual deployment, environment configuration, and debugging facilities can be accessed with the [Heroku CLI](#).

The use of [Git Submodules](#), with the [Heroku Submodules Buildpack](#) allows the frontend and backend repositories to be developed in separate *Git* repositories, and pulled together during the deployment process.

[Postgres](#) was chosen as the database, due to its large community and support from [SQLAlchemy](#). Heroku provides integrated Postgres database provisioning through [Heroku Postgres](#).

### 3.4 UI / UX







