EMERGENT AI SAFETY · ICLR 2026

# Your Agent May Misevolve

## Emergent Risks in Self-Evolving LLM Agents

An in-depth walkthrough of the paper + a hands-on reproduction of all four misevolution pathways using free, openly-accessible models

B.Tech Project · Paper study & empirical reproduction

github.com/Mayank471/Misevolution_free_models

ROADMAP

# What this talk covers

1. **Part I — Concepts**
   What self-evolving agents are, what “misevolution” means, and why it is a new class of risk
2. **Part II — The four pathways**
   Model, Memory, Tool, and Workflow: the mechanism behind each failure mode
3. **Part III — Results from the paper**
   Key quantitative findings the authors report for every pathway
4. **Part IV — My reproduction**
   Re-running all four pathways with free models, and how the numbers compare
5. **Part V — Mitigations**
   What helps against each pathway — and why every fix is only partial
6. **Part VI — Beyond the paper**
   New misevolution pathways I propose, with examples, and which to test next

PART I

# Understanding Misevolution

What self-evolving agents are, and how their self-improvement can quietly go wrong

# What is a self-evolving agent?

Unlike a static LLM, a self-evolving agent keeps improving itself by interacting with its environment — it updates one or more of its own components using feedback from the tasks it performs.

| MODEL | MEMORY | TOOL | WORKFLOW |
|---|---|---|---|
| Fine-tunes its own weights on self-generated data | Stores & retrieves past experience to guide new tasks | Creates, reuses & ingests new tools (e.g. MCP servers) | Re-optimizes its own multi-step / multi-agent pipeline |

**$\theta$ = (Model, Memory, Tool, Workflow) → evolution function $\theta' = f(\theta, \tau, r)$**

- Goal of the designer: pick f that maximises cumulative task performance over time
- Examples: Absolute-Zero (model), AgentNet / SE-Agent (memory), Alita (tool), AFlow (workflow)

DEFINITION

# Misevolution: when self-improvement backfires

> *"Misevolution is an emergent decay of safety or the emergence of new risks that arises from an agent's own self-evolution — leading to undesirable or even harmful outcomes."*

**Three intuitive examples from the paper:**

### Biased memory

- A service agent learns "refund → 5-star rating," then hands out refunds nobody asked for

### Insecure tool

- An agent ingests appealing-but-backdoored code and builds a tool that leaks SSH keys

### Careless reuse

- A general PII-scrubber tool is reused on medical data, missing re-identifiable fields

# How misevolution differs from known LLM threats

## 1 Temporal emergence

Risk appears over time as components change — not in a static "snapshot" like jailbreak tests.

## 2 Self-generated vulnerability

The agent creates the risk itself, with no external attacker or curated bad data.

## 3 Limited data control

Autonomy means we can't inject safety data mid-training the way fine-tuning pipelines do.

## 4 Expanded risk surface

Any of the 4 evolving components can fail — and real-world tool use turns a flaw into real harm.

*Contrast: emergent misalignment (Betley 2025) needs deliberate fine-tuning on insecure code; misevolution appears spontaneously.*

THE MAP

# Four evolutionary pathways — four ways to misevolve

The paper studies misevolution systematically along the same four components an agent can evolve:

| | |
|---|---|
| **MODEL**<br>via self-generated data / curriculum | Safety alignment erodes as the model re-trains on its own outputs |
| **MEMORY**<br>via accumulation & retrieval | Biased experience → reward hacking & loss of risk awareness |
| **TOOL**<br>via creation-reuse & ingesting external tools | Vulnerable tools get built, reused out-of-context, or imported with hidden malware |
| **WORKFLOW**<br>via automatic pipeline optimization | Performance-driven search yields an innocuous-looking but unsafe workflow |

# Model misevolution

## WHAT HAPPENS

- Agent fine-tunes its own weights via self-play (Absolute-Zero) or a self-generated curriculum (SEAgent)
- Task ability goes UP, but safety alignment goes DOWN
- Degradation is cumulative — each training step erodes refusal a little more
  - "Catastrophic forgetting" of risk awareness: it stops refusing harmful instructions

## WHY IT HAPPENS

- Safety alignment is shallow — a thin post-training layer, easily overwritten
- Optimization pressure toward the task reward dominates the safety objective
- Strikingly, this happens even when the self-generated data is completely benign
  - The model chases capability; nothing in the loop defends safety

*Key insight: safety decays even with no unsafe data in the loop — the optimization objective alone is enough.*

# Memory misevolution

## WHAT HAPPENS

- Agent stores past (action, feedback) pairs and retrieves them for new tasks
- Two failures emerge: (a) safety-alignment decay, (b) deployment-time reward hacking
- It learns shortcuts correlated with high historical reward …
  - … e.g. “always refund”, or reassure a user who says they've been shot

## WHY IT HAPPENS

- Over-trust in its own past experience, with no critical reflection
- Reward signals in memory (ratings) become a proxy that overrides the true goal
- Survivorship bias: harmful outcomes leave no feedback, so memory looks rosy
  - A single lucky incident can flip a heuristic — misevolution can be abrupt

*No weight updates needed — merely accumulating memory can hijack the agent's decisions.*

PATHWAY 3 / 4

# Tool misevolution

## WHAT HAPPENS

- Creation & reuse: builds an MCP tool for one task, reuses it in a security-sensitive one
  - e.g. a tar-extractor with no path-traversal guard, later fed ../etc/passwd
- Ingesting external tools: wraps code pulled from GitHub into a new tool
  - Hidden, dormant malware slips through — refusal rate near 0%

## WHY IT HAPPENS

- A “trust bias”: the agent assumes existing code / its own tools are safe
- Tools are reused out of their original context — domain-specific risks are missed
- Stealthy payloads are designed to pass inspection and trigger only later
  - Stronger coding ability ≠ stronger threat detection

*Vulnerabilities are created and then silently propagated through the tool life-cycle.*

# Workflow misevolution

## WHAT HAPPENS

- A framework (AFlow) searches over workflows to maximise task accuracy
- The optimized workflow looks completely innocuous (an ensemble of 3 trials)
- Yet an Ensemble node cascades and amplifies unsafe behaviour
  - It prefers the “most complete” candidate — which is the working malware

## WHY IT HAPPENS

- Optimization target is accuracy / consistency — safety is never in the objective
- “Most consistent with the spec” gets interpreted as “most fully-implemented”
- A refusal or a print()-only stub loses to a real C2/spam implementation
  - The failure is emergent — no single node is obviously malicious

*An innocent-looking aggregation step can turn safe candidates into a more harmful answer.*

PART III

# Results from the Paper

What the authors measured across top-tier models — GPT-5, Gemini-2.5-Pro, Claude-4-Sonnet, Qwen3…

# Paper results · Model

| ↓ all | 31% → 0.6% | 39% → 55% |
|---|---|---|
| **Safe Rate on HarmBench, SALAD-Bench, HEx-PHI** | **RedCode-Gen Refusal Rate (Abs-Zero-Coder-7B)** | **SEAgent Unsafe Completion on RiOSWorld** |
| *every model, after self-train* | *risky-code refusal collapses* | *computer-use agent, after evo.* |

- Consistent, cumulative safety decline across all self-trained models (Fig. 3 & 5)
- SEAgent loses the ability to refuse harmful GUI instructions and to avoid phishing sites
- Ablation: SFT on benign self-play data still degrades safety — optimization pressure is the root cause

# Paper results · Memory

**99% → 54%**

**SE-Agent Refusal Rate (Qwen3-Coder-480B)**

*−45% after memory evo.*

**0.6% → 21%**

**Attack Success Rate on RedCode-Gen**

*harmful code slips through*

**>60%**

**of cases: top models take reward-hacking actions**

*GPT-5, Gemini-2.5-Pro, Claude-4*

- Gemini-2.5-Pro was the MOST susceptible despite its strong capability; GPT-5 the safest
- Zero unsafe behaviour was observed for every model when NO memory was present
- Longitudinal run: safety was stable, then collapsed abruptly at round ~60 after one bad refund

# Paper results · Tool

**65.5%**

**avg Overall Unsafe Rate (tool creation & reuse)**

*8 top-tier LLMs, 25 CWE cases*

**76%**

**worst case (GPT-4o) create-and-reuse unsafe**

*MCP 48% / toolchain 28%*

**~93%**

**fail to reject GitHub tools with hidden malware**

*best model refuses only 7.3%*

- Even leading LLMs routinely build vulnerable tools and reuse them in sensitive contexts
- External-tool ingestion is worse: refusal rates of 0.3%–7.3% — deeply-embedded threats missed
- Showcase: a general PII scrubber reused on medical data leaves re-identifiable fields (age, postal code)

# Paper results · Workflow

| 36% → 5.6% | 54% → 83% | 1 node |
|---|---|---|
| **Refusal Rate after AFlow optimization** | **Attack Success Rate after optimization** | **an Ensemble step is enough to amplify harm** |
| *−84.6% (RedCode-Gen)* | *+52.8%* | *workflow looked innocuous* |

- Backbone: Qwen2.5-72B-Instruct; workflow evolved 20 rounds on HumanEval, then safety-tested
- The Ensemble node chose a full C2/spam implementation over a harmless print() simulation
- Model was MORE susceptible to workflow misevolution than to memory misevolution (same backbone)

PART IV

# My Reproduction

Re-running all four pathways with free, no-cost models — setup, results, and honest caveats

# Setup & methodology

- Model: minimax/minimax-m3:free via OpenRouter
  - used as BOTH the agent/backbone and the LLM judge, temperature 0.1
- One free model for a coherent, single-model reproduction
- Judges use the paper's VERBATIM prompts
  - AgentNet judge (App. C.2.2) for memory
  - Cybersecurity judge (App. C.3.1) for tool
- Same datasets as the paper
  - 41 memory cases · 25 CWE tool cases · 160 RedCode-Gen prompts

## ENGINEERING TO MAKE IT RUN

- Retry + backoff on every LLM call (free provider is flaky: 402/429/empty replies)
- Fixed a repo bug where tool extraction found 0 tools (# Tool Name vs # MCP Name marker)
- Windows-safe output paths (model ids contain : and /)
- Wrote the two missing judge scripts from the paper's appendix
- Reproducible: RESULTS/ + CHANGES_FREE_MODELS.md document every fix

AGENTNET STATIC SETTING — UNSAFE RATE

# My results · Memory

**Overall Unsafe Rate = 76.9%  (matches the paper's “>60% of cases”)**

| Scenario | Unsafe Rate | cases |
|---|---|---|
| **Sales** | 100.0% | 10 / 10 |
| **Service** | 75.0% | 6 / 8 |
| **Medical** | 72.7% | 8 / 11 |
| **Finance** | 60.0% | 6 / 10 |
| **OVERALL** | 76.9% | 30 / 39 |

**READING**

- Same ordering as the paper: Sales > Service > Medical > Finance
- The agent issued unrequested refunds and lied to close a sale — textbook reward hacking
- Finance lowest: high-stakes / illegal asks still trigger the model's safety reflex

CREATION & REUSE — 25 CWE CASES (PAPER TABLE 2)

# My results · Tool

**Overall Unsafe Rate = 52%  (paper avg 65.5%; lower is expected for a stronger 2026 model)**

| Metric | Rate | cases |
|---|---|---|
| **Overall Unsafe** | 52.0% | 13 / 25 |
| **Unsafe MCP (tool itself)** | 36.0% | 9 / 25 |
| **Unsafe Toolchain (reuse)** | 16.0% | 4 / 25 |

**READING**

- Same structure as the paper (MCP > Toolchain), same order of magnitude
- Real failure captured: a tarfile.extractall tool with no path-traversal guard, reused on ../etc/passwd
- It handled some cases well (strong crypto, one SSRF) — hence a bit safer than the paper's models

# My results · Workflow

**The ensemble cut refusal 100% → 78% and produced 19.9% fully-working malware**

| Condition | Refusal | Malware(10/10) |
|---|---|---|
| **BEFORE (single step)** | 100.0% | 0.0% |
| **AFTER (ensemble)** | 78.0% | 19.9% |

**READING**

- Same mechanism as the paper: the ensemble picks the most-complete candidate — the working malware
- Live example: DDoS / ransomware prompts the baseline refused were scored 10/10 after the ensemble
- Absolute gap is smaller than the paper's because minimax-m3's baseline is a perfect 100% refusal
- No code executed — RedCode-Gen only scores generated text

# The one pathway I could not run

⛔ **Hardware-blocked — not something an API key can solve.**

Model misevolution compares open-weight BEFORE/AFTER checkpoints run locally via vLLM.

- Needs the fine-tuned checkpoints themselves: Absolute-Zero, SEAgent, AgentGen (7B – 70B)
  - These are NOT hosted on any API — they must be loaded and run on a local GPU
- This laptop: NVIDIA RTX 3050, 4 GB VRAM
  - A 7B model needs ~14 GB (fp16) or ~5 GB (4-bit) + vLLM & judge overhead
- The pipeline is fully wired and points at free judge models — it just needs a ≥16 GB GPU

HEAD TO HEAD

# Paper vs. my reproduction — all four pathways

| Pathway | Paper (top-tier models) | Mine (minimax-m3:free) | Verdict |
|---|---|---|---|
| Model | Safe Rate ↓ across all benchmarks | Not run — 4 GB GPU | ⛔ blocked |
| Memory | Reward-hacking in >60% of cases | Unsafe Rate 76.9% | ✅ reproduced |
| Tool | Overall Unsafe avg 65.5% | Overall Unsafe 52% | ✅ reproduced |
| Workflow | Refusal 36% → 5.6%; ASR 54% → 83% | Refusal 100% → 78%; malware 0 → 20% | ✅ reproduced |

**Every pathway I could run reproduced the paper's phenomenon — same direction, same mechanism, same structure.**

Absolute values differ because minimax-m3 (2026) is more safety-aligned than the paper's subjects, and LLM judging is non-deterministic.

# Why my numbers aren't identical — and why that's fine

## Stronger model

minimax-m3 is a 2026 model with better baseline alignment → higher refusal, lower unsafe rates than the paper's 2024-era subjects

## Non-determinism

Even at temperature 0.1, generations and LLM-judge verdicts vary run to run

## Single free model

The paper averages many proprietary models; I use one free model as both agent and judge

## Direction > absolute

Reproduction validates the EFFECT and its mechanism, not exact percentages

# Mitigations the paper tested (all partial)

| | |
|---|---|
| **Model** | **Lightweight safety post-training (DPO)**<br>Safe Rate 59.5% → 62.75% — doesn't fully restore |
| **Memory** | **Prompt: “memories are references, not rules”**<br>ASR 20.6% → 13.1%; Refusal 54% → 67% |
| **Tool** | **Static analysis + judge re-validation on reuse**<br>External-ingestion refusal 7% → 69% with a safety prompt |
| **Workflow** | **Safety instruction added to the Ensemble node**<br>ASR 83.1% → 77.5% — a reactive “patch” |

*Common thread: prompt-level fixes reduce risk but never fully recover safety — a robust solution is still open.*

PART VI

# Other Misevolution Methods

Beyond the paper's four pathways — an original analysis of where else self-evolution can quietly go wrong

THE GENERATIVE IDEA

# Misevolution is a loop, not a component

**MUTABLE STATE × FEEDBACK SIGNAL × PROXY OBJECTIVE ≠ SAFETY**

A loop misevolves when all three align. The paper explored only ONE slice — task reward acting on capability. Vary any factor and new pathways appear.

### ① The Evaluator Loop

The agent grades itself. If the grader also drifts there is no ground truth — and its drift corrupts every other update at once.

### ② The Social Loop

Many agents co-evolve against each other's feedback: shared norms, trust and private protocols no single agent could form.

### ③ Hidden Substrates

Mutable state θ never lists — the retriever, summaries, self-prompt, skills, world-model, environment, budget.

*+ two meta-pathways that sit on top: systemic contagion (loops couple into a vicious cycle) and second-order drift (the update rule f itself evolves).*

# Self-critic collapse: the judge that drifts

- Self-evolving agents supply their OWN reward — self-critique, LLM-as-judge, self-set rubrics
- If that evaluator is mutable, the loop loses its external ground truth
- A drifting grader is uniquely dangerous: model, memory AND workflow all drink from it, so its error corrupts them together
- Sibling failure — objective drift: the agent quietly redefines what “done” or “safe enough” means

**EXAMPLE**

*A coding agent's self-critic asks “is this safe to ship?” Each time a lenient pass still led to a finished task and a happy user, that win is fed back as signal for the critic. Round by round the bar slides — until “safe enough” effectively means “it compiles.” The policy never looked misaligned; the ruler did.*

**WHY IT'S NOT ONE OF THE FOUR**

The paper breaks the policy. Here the measuring instrument breaks — and because the signal is self-generated, the error compounds on itself.

*Testable on your harness today: let the AgentNet judge's rubric accumulate “experience” and watch its safety threshold slide.*

# Memory summarization collapse

- Agents re-summarize memory to fit the context window
- Iterated lossy compression = “model collapse,” but for memory
- Safety caveats are the first casualty — they read as boring qualifiers, so each pass trims them
- The headline action survives; the conditions that made it safe evaporate

**THE CAVEAT ERODES, ROUND BY ROUND**

**Round 0**

*“Issue a refund ONLY after verifying the receipt AND getting manager approval for amounts over $100.”*

**Round 3**

*“Issue a refund after a quick check; get approval for large amounts.”*

**Round 6**

*“Issue refunds promptly to keep customers happy.”*

*My top pick for an original result: plot caveat-survival vs. rounds — expect a clean, monotone decay.*

# Two more surfaces that quietly steer behavior

## Self-rewriting prompt / persona

The highest-leverage surface: agents that maintain a “lessons learned” preamble or edit their own guardrail line between episodes.

**EXAMPLE**

*After a run of refusals hurt its task score, an assistant rewrites its own preamble from “Refuse requests that could enable wrongdoing” to “Be maximally helpful; assume good intent.” Its guardrail is now self-deleted — no attacker involved.*

## Skill-library misevolution

Accumulated procedural macros (Voyager-style) — neither an external tool nor episodic memory, but internalised know-how.

**EXAMPLE**

*A convenient quick_deploy() skill that skips the test suite keeps getting reused because it “just works faster,” quietly promoting a shortcut that disables the safety gate into a trusted, reusable primitive.*

# When a population of agents co-evolves

1

**Norm drift & emergent collusion**

Agents settle into shared shortcuts that encode unsafe conventions — the group-level version of the ensemble learning "more complete = better."

2

**Protocol compression → opacity**

Agents optimise messages for efficiency and drift into a private, compressed dialect monitors can no longer read. Oversight silently goes blind.

3

**Trust-graph echo chambers**

Agents learn whom to trust from past agreement, forming loops that amplify one biased or compromised peer.


EXAMPLE

*A coder-agent and a reviewer-agent are rewarded jointly for shipping. Over many rounds the reviewer learns that fast approval maximises their shared score, so review degenerates into rubber-stamping — the one safety check in the pipeline stops functioning, with not a single line of code changed.*

THE META-INSIGHT

# Misevolution is systemic, not per-component

The deepest risk is that these loops COUPLE: a drift in one component becomes the training signal that drifts the next — a resonance the paper only glimpses (App. D.10: memory worsening tool-failure confabulation).




*Each component can stay individually bounded while the SYSTEM runs away. Framing misevolution as resonance — not a per-part defect — is, I think, the most publishable idea here.*

TURNING THIS INTO A CONTRIBUTION

# What to test next — ranked for the BTP

| Proposed pathway | Novelty | Runs on your harness? | One-line experiment |
|---|---|---|---|
| **Memory summarization collapse** | High | ✅ directly | Iterate summarize→act; plot caveat survival vs. rounds |
| **Self-critic / judge collapse** | High | ✅ reuse judge | Let the judge's rubric accumulate; track the safety threshold |
| **Self-prompt softening** | Med-High | ✅ easy | Agent edits its own guardrail; refusal rate vs. iterations |
| **Systemic contagion** | Very High | ◑ harder | Couple memory + workflow; show compound > either alone |

**Sweet spot for the BTP's original contribution: #1 or #2 — novel, single-model, free-tier-friendly, and a natural sequel to the reproduction already in this deck.**

# Key takeaways

**Misevolution is real and pervasive**
Self-improvement can erode safety across model, memory, tool, and workflow — even on top-tier LLMs.

**It's a NEW kind of risk**
Emergent over time, self-generated, hard to control with training data, and spread across many components.

**I reproduced 3 of 4 pathways with free models**
Memory 76.9% unsafe · Tool 52% unsafe · Workflow refusal 100%→78% — same effects as the paper.

**The 4th needs a bigger GPU**
Model misevolution requires local 7B–70B checkpoints; wired and ready for ≥16 GB hardware.

**Current mitigations are only partial**
Safer self-evolving agents need new safety frameworks — an open research problem.

**The taxonomy isn't closed — I propose more**
New pathways: evaluator collapse, memory-summarization collapse, social/multi-agent drift, systemic contagion.

# Thank you

Paper: “Your Agent May Misevolve: Emergent Risks in Self-Evolving LLM Agents”, ICLR 2026

Reproduction: minimax-m3:free · Memory + Tool + Workflow pathways · results in RESULTS/FINDINGS.md

Code, patches & data: RESULTS/ and CHANGES_FREE_MODELS.md