

QUALITY CERTIFICATE BS EN 10204:2004 3. 1

TO: ACME SOLAR HOLDINGS LIMITED PLOT NO: 152, SECTOR 44, GURGAON 122002, INDIA

CDECIFICATION EN 1009E 9.9010

DESCRIPTION OF GOODS: HOT ROLLED PLATE

CONTRACT NO: XPIND24010CSL INVOICE NO: XPIND24010CSL-2C

JIANGYIN XINGCHENG SPECIAL STEEL WORKS CO., LTD.

NO.297, BINJIANG (E) ROAD, JIANGYIN CITY, JIANGSU PROVINCE, CHINA PC:214429

CEDITIFICATE NO



7 909509100000779

DELIVERY CONDITION Normalizing rolling EDGE All-the-sides cutting								FICATION EN 10025-2:2019 RADE S35510+N/IS2062 E350B0									U.T Test BS EN 10160:1999 S2E3								CERTIFICATE NO. Z 202502190000773 LICENSE NO.						
	EDGE HII	the brace	Cuttin				- 01	(IDE	• •									CAL COM	CAL COMPOSITION (Weight%)												
NO.	PLATE NO.	HEAT NO.		SIZE AND WEIGHT														OIII.III			I										
NO.	PLATE NO.	HEAT NO.	THICK	WIDTH	LENGTH	PIECES		С	Si	Mn	P	S	A1	Nb	V	Ti	Cr	Ni	Cu	Мо	CEV	В	N								
-	TE11 41 40000	050000	15	mm	10010	,	t	0.101	0.100	4 050	0.0100	0.0004	0.0045		0.004	0.000	0.00=	0.01	0.015	0.010	0 1101	0.000#						ļ			
7	T5114142020 T5114142030	S500088 S500088	15 15	2588 2588	10610 10610	1	3. 233 3. 233	0. 164 0. 164	0. 169			0.0021			0.001	0.002	0. 085	0.04	0.017	0.018		0.0005						ļ	1		
0	T5114142040	S500088	15	2588	10610	1	3. 233	0. 164	0. 169			0.0021					0. 085	0. 04	0.017			0.0005					-		1		
10	T5114142050	S500088	15	2588	10610	1	3. 233	0. 164	0. 169			0. 0021			0.001	0.002	0. 085	0. 04	0.017	0.018		0.0005									
10	13114142000	5500000	10	2000	10010	1	0. 200	0.101	0.103	1.013	0.0102	0.0021	0.0341	0.002	0.001	0.002	0.000	0.01	0.011	0.010	0. 1101	0.0005	0.0020								
				1																											
		MENICII D. ME	om m	TENCTIE TECT		TENSILE TEST		I D MDCM	TMDACT TECT		IMPACT TEST		IMPACT TEST		THEAC	IMDACT TECT		U.T Test		l											
		TENSILE TEST		TENSILE TEST		TENSILE TEST		TENSILE TEST		IMPACT TEST		IMPACI IESI		IMPACI IESI		IMPACT TEST		U.I lest				l									
	PLATE NO.																														
									a.		C)		CI.			1															
NO.		ReH(Y, S)		Rm (T. S) A (E. L)		A (E. L.)	ReH/Rm(Y,R)		Charpy- V_absorbed_energ y-1		Charpy- g V_absorbed_energ y-2		Charpy- V_absorbed_energ y-3		A ³	AVG		U.T inspection:													
							(/																								
		MPa		MPa		%	%		J		J		J J			J		_													
		TC t		TC t		TC t	TC t		TL t*2mm		TL t*2mm 0°C		TL t*2mm 0°C			TL t*2mm 0°C		\vdash													
-	TE114140000	0.07		501	-	0.0			0							73		. 1			ļ										
7	T5114142020	397 397		531 531	-	32		75 75	17			65	18					pted			ļ										
9	T5114142030 T5114142040	397		531		32 32			170 170		165 165		184 184		173 173		Accepted Accepted				-										
10	T5114142040	397		531		32		75		170		165		184		173		Accepted													
10	15114142050	391		991		32		19	11	10	1	00	10	94	1	13	Acce	pteu													
•	PAGE TOTAL		Accont	abla Via	sual and		WE HERED	V OPDATEV	THAT THE	MATERIAL	HACNE TO A	NIV THOUDS	(TOOTHI P	DEPENTS I	WIEN THED	E TO ANN	COMPLATA	n wou and	ZINDIV	DEOUECAEL	TO MADE	THE OTER	T ODADE I	IDATE NO D	I ATT NO C	TAL PLIT	UPDV DATE	D CAUGEG	AND MATER	DIAL IN TH	ID COMPLETION
PIE	CES WEIGHT	(t)	Ассери	size	suai aiiu	REMARKS		AMPLE SIZE															L GRADE,	HEAT NO, P	TAIE NO, S	IZE, DELI	VERY DAIL	E, CAUSES	AND MAILE	KIAL IN II	HE CONDITION
4	12. 9	32		3120																			Jia p								
												_	_					_				18	Ind	132							
	SAM	IPLE LOCATI	ON AND	ORIENTA	TION: T=TC)P; B=B01	ITOM; L=L	ONGL; C=	TRANS;	t =full	thickn	ess;t*2	mm =2mm	from r	olled s	urface	to spec	imen su	rface;			(3)	/ ,,,	C/2							
	NOTES CEV	=C+Mn/6+(Cr+	Mo+V)/5	+ (Ni+Cu)	15. Tolera	ance S355	J0+N/IS20	62 E350B0	、S355N/I	S2062 E	350C : B	S EN 100	29:2010	Class C.	Flatness	s:BS EN10	0029: 20	10 class	N type	L.	١.	اقا	OAIO	131							
																					$\overline{}$	100	35	157							
																							330 C								
						1															\rightarrow	-						1			
	ISSUED DATE		2025/1/21				PRINTED	RY			CHE	NYOU	VOIT		ΟΠΔΙ Τ		TY MANAGER		tan	5	zhang	2Ming	STA	MP OF D							
1990ED DATE				2020/1/21				I KINILD .	D1				21100			WONLI	II MANAGEN		- 1			2144) (QUALITY	ASSURAN	NCE				
															<u> </u>																

H T T--+ DC EN 10160, 1000 C9E9