

QUALITY CERTIFICATE BS EN 10204:2004 3. 1

TO: ACME SOLAR HOLDINGS LIMITED PLOT NO: 152, SECTOR 44, GURGAON 122002, INDIA

DESCRIPTION OF GOODS: HOT ROLLED PLATE

CONTRACT NO: XPIND24010CSL INVOICE NO: XPIND24010CSL-2C

JIANGYIN XINGCHENG SPECIAL STEEL WORKS CO., LTD.

NO.297, BINJIANG (E) ROAD, JIANGYIN CITY, JIANGSU PROVINCE, CHINA PC:214429





NO. PLATE NO. HEAT NO. HEAT NO. PLATE NO. PLATE NO. PLATE NO. HEAT NO. PLATE	DELIVERY CONDITION Normalizing rolling										10025-2:2019 U.T Test BS EN 10160:1999 S2E3 CERTIFICATE																					
NO. PLATE NO. HEAT NO. THICK WIDTH LENGTH PIECES C Si Mn P S Al Nb V Ti Cr Ni Cu Mo CEV B N		EDGE A1	l-the-sides	cuttin	ıg			GRA	ADE	S355J0	355J0+N/IS2062 E350B0 LICENSE NO.																					
Tile				SIZE AND WEIGHT				F				I							CHEMI	CAL COM	IP051110	JN (Weig	ght%)					1		1		
Table Tabl		PLATE NO.	HEAT NO.	THICK	WIDTH	LENGTH	DIECES		С	Si	Mn	P	S	Al	Nb	V	Ti	Cr	Ni	Cu	Мо	CEV	В	N								
T5116127020					mm		PIECES	+																					'			
T5116127020 S500109 28.5 2833 13771 1 8.112 0.165 0.187 1.402 0.0148 0.0022 0.0273 0.003 0.002 0.0017 0.101 0.032 0.025 0.013 0.4257 0.0004 0.0026		T5116127010	S500109	28. 5		13771	1		0. 165	0. 187	1. 402	0. 0148	0. 0022	0. 0273	0.003	0. 002	0.0017	0. 101	0. 032	0. 025	0.013	0. 4257	0. 0004	0. 0026					+			-
TS116129010 S500108 28.5 2633 13771 1 8.112 0.16 0.203 1.37 0.017 0.0037 0.0239 0.0022 0.002 0.0018 0.116 0.031 0.019 0.0267 0.4206 0.0004 0.0032 0.0033							1																						+ + +			
Title Stock Stoc	-						1		0. 165	0. 187	1.402	0.0148	0. 0022	0.0273					0.032			0. 4257	0.0004	0.0026								
T5116129030 S500108 28.5 2633 13771 1 8.112 0.16 0.203 1.37 0.017 0.0037 0.0239 0.0022 0.002 0.0018 0.116 0.031 0.019 0.0267 0.4208 0.0004 0.0032 0.0032 0.0038 0.0032 0.0038 0.0032 0.0038 0.016 0.031 0.019 0.0267 0.4208 0.0004 0.0032 0.0038 0.0032 0.0038 0.0032 0.0038 0.0038 0.016 0.031 0.019 0.0267 0.4208 0.0004 0.0032 0.0038 0.0032 0.0038 0.0032 0.0038 0.00		T5116129010	S500108	28. 5	2633	13771	1	8. 112	0. 16	0. 203	1. 37	0.017	0.0037	0.0239	0.0022	0.002	0.0018	0.116	0.031	0.019	0.0267	0. 4206	0.0004	0.0032					1			
NO. PLATE NO. Rel(Y,S) Ra(T,S) A(E,L) Rel/Ra(Y,R) Charpy Char		T5116129020	S500108	28. 5	2633	13771	1	8. 112	0.16	0. 203	1. 37	0.017	0.0037	0.0239	0.0022	0.002	0.0018	0.116	0.031	0.019	0.0267	0.4206	0.0004	0.0032								
NO. PLATE NO. Relift No.		T5116129030	S500108	28. 5	2633	13771	1	8. 112	0.16	0. 203	1. 37	0.017	0.0037	0.0239	0.0022	0.002	0.0018	0.116	0.031	0.019	0.0267	0.4206	0.0004	0.0032								
Reh(Y, S) Reh(Y, S) Reh(Y, S) Reh(Y, S) Reh(Y, S) Reh(Y, S) Reh(Y, R) V_absorbed_energ V_a	NO.		TENSILE TE	EST T	TENSILE TEST		SILE TEST	TENSIL	ILE TEST IMP		CT TEST I		T TEST	IMPACT TEST		IMPACT TEST		U.T Test														
TC t		PLATE NO.)	, ,		, ,		Rm(Y.R) V_absor		ed_energ V_absorbed_ene		ed_energ	g V_absorbed_energ		AVG		U.T inspection:														
1 T5116127010 394 539 27.5 73 195 197 201 198 Accepted							70			J		,	J		J		J															
1 T5116127010 394 539 27.5 73 195 197 201 198 Accepted 2 T5116127020 394 539 27.5 73 195 197 201 198 Accepted 3 T5116127030 394 539 27.5 73 195 197 201 198 Accepted 4 T5116129010 408 539 29 76 216 201 235 217 Accepted 5 T5116129020 408 539 29 76 216 201 235 217 Accepted 6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) PAGE TOTAL PIECES WEIGHT (t) Size Acceptable Visual and size REMARKS ME HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE COMPLAINT AND COMPLAINT, SAMPLE SIZE, RESPECTIVELY: 10×5×55\10×7.5×55\10×10×55\text{smm.} SAMPLE LOCATION AND ORIENTATION: T=TOP; B=BOTTOM; L=LONGL; C=TRANS; t =full thickness; t*2mm =2mm from rolled surface to specimen surface;			TC t		TC t		TC t	TC	C t																				 			
2 T5116127020 394 539 27.5 73 195 197 201 198 Accepted 3 T5116127030 394 539 27.5 73 195 197 201 198 Accepted 4 T5116129010 408 539 29 76 216 201 235 217 Accepted 5 T5116129020 408 539 29 76 216 201 235 217 Accepted 6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) 6 48.672 Acceptable Visual and size REMARKS WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE CAMPLE SIZE: PLATE THICKNESS, RESPECTIVELY: t ≥ 6-8mm\8 < t < 12mm\t ≥ 12mm, SAMPLE SIZE, RESPECTIVELY: 10 × 5 × 55\10 × 7.5 × 55\10 × 10 × 55mm. SAMPLE LOCATION AND ORIENTATION: T=TOP; B=BOTTOM; L=LONGL; C=TRANS; t =full thickness; t*2mm =2mm from rolled surface to specimen surface; NOTES CEV=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15. Tolerance S355J0+N/IS2062 E350B0. S355N/IS2062 E350C : BS EN 10029: 2010 Class C. Flatness: BS EN10029: 2010 class N type L .		WE11010E010	00.4	204 520		-	27 5		72										Assented		 						_		4			
3 T5116127030 394 539 27.5 73 195 197 201 198 Accepted 4 T5116129010 408 539 29 76 216 201 235 217 Accepted 5 T5116129020 408 539 29 76 216 201 235 217 Accepted 6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) 6 48.672 Acceptable Visual and size REMARKS WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE THE MATERIAL HASN'T ANY IMPERMISSIBLE DE																		•				-					_		+			
4 T5116129010 408 539 29 76 216 201 235 217 Accepted 5 T5116129020 408 539 29 76 216 201 235 217 Accepted 6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) 6 48.672 Acceptable Visual and size REMARKS REMARKS WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLAT IMPACT SAMPLE SIZE: PLATE THICKNESS, RESPECTIVELY: t≥6-8mm\8 <t-12mm\t≥12mm\t< td=""><td>-</td><td></td><td>_</td><td></td><td colspan="2"></td><td></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td><td></td><td>-</td><td></td><td></td><td></td><td></td><td></td><td></td><td>+</td><td></td><td></td><td></td></t-12mm\t≥12mm\t<>	-		_																			-							+			
5 T5116129020 408 539 29 76 216 201 235 217 Accepted 6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) 6 48.672 Acceptable Visual and size WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLAT IMPACT SAMPLE SIZE: PLATE THICKNESS, RESPECTIVELY: t ≥ 6-8mm\8 < t < 12mm\t ≥ 12mm, SAMPLE SIZE, RESPECTIVELY: 10 × 5 × 55\10 × 7.5 × 55\10 × 10 × 55mm. NOTES CEV=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15. Tolerance S355J0+N/IS2062 E350B0, S355N/IS2062 E350B0; S355N/IS2062 E350C: BS EN 10029: 2010 Class C. Flatness: BS EN10029: 2010 class N type L.	-																												+			-
6 T5116129030 408 539 29 76 216 201 235 217 Accepted PAGE TOTAL PIECES WEIGHT (t) 6 48.672 Acceptable Visual and size REMARKS WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLAT IMPACT SAMPLE SIZE: PLATE THICKNESS, RESPECTIVELY: t ≥ 6-8mm\8 < t < 12mm\t ≥ 12mm, SAMPLE SIZE, RESPECTIVELY: 10×5×55\10×7.5×55\10×10×55mm. SAMPLE LOCATION AND ORIENTATION: T=TOP; B=BOTTOM; L=LONGL; C=TRANS; t =full thickness; t*2mm =2mm from rolled surface to specimen surface; CEV=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15. Tolerance S355J0+N/IS2062 E350B0. S355N/IS2062 E350C: BS EN 10029: 2010 Class C. Flatness: BS EN10029: 2010 class N type L.			408			29	76		216		20	01					Accepted											+				
PIECES WEIGHT (t) Acceptable Visual and size REMARKS		T5116129030	408		539		29	7	76	21	6	20	01	23	35	2	17	Ассе	pted										1			
NOTES CEV=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15. Tolerance S355J0+N/IS2062 E350B0, S355N/IS2062 E350C : BS EN 10029:2010 Class C. Flatness:BS EN10029: 2010 class N type L .	PAGE TOTAL PIECES WEIGHT (t) Acceptable Visual and size REMARKS WE HEREBY CERTIFY THAT THE MATERIAL HASN'T ANY IMPERMISSIBLE DEFECTS. WHEN THERE IS ANY COMPLAINT, YOU ARE KINDLY REQUESTED TO MARK THE STEEL GRADE, HEAT NO, PLATE NO, SIZE, DELIVERY DATE, CAUSES AND MATERIAL IN THE CONDITION SIZE. REMARKS IMPACT SAMPLE SIZE: PLATE THICKNESS, RESPECTIVELY: 1>6-8mm\8 <t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t< td=""><td>Ñ.</td></t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<12mm\8<t<>														Ñ.																	
	SAMPLE LOCATION AND ORIENTATION: T=TOP; B=BOTTOM; L=LONGL; C=TRANS; t =full thickness;t*2mm =2mm from rolled surface to specimen surface; NOTES CEV=C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15. Tolerance S355J0+N/IS2062 E350B0, S355N/IS2062 E350C : BS EN 10029:2010 Class C. Flatness: BS EN10029: 2010 class N type L .																															
	ISSUED DATE				2025/1/21			F	PRINTED	ВҮ				CHENYOU			QUALITY MANAGER			+	Han's zhang			gMing		IP OF DEPARTMENT OF JIANGYIN XINGCI UALITY ASSURANCE SPECIAL STEEL WORL				2		