

QUALITY CERTIFICATE
BS EN 10204:2004 3. 1

TO: ACME SOLAR HOLDINGS LIMITED PLOT NO: 152, SECTOR 44, GURGAON 122002, INDIA

DESCRIPTION OF GOODS: HOT ROLLED PLATE

CONTRACT NO: XPIND24010CSL INVOICE NO: XPIND24010CSL-2C

JIANGYIN XINGCHENG SPECIAL STEEL WORKS CO., LTD.

NO.297, BINJIANG (E) ROAD, JIANGYIN CITY, JIANGSU PROVINCE, CHINA PC:214429



PLATE NO. T5115013050	HEAT NO. \$500091	THICK 17. 7		ZE AND WE LENGTH 11183	PIECES	t	С	Si									CHEMI	CAL COM	(POSITIO	N (Weig	ght%)					1	1		-	
			mm		PIECES	t.	С	Si												ON (Weig	sht%)	_								
T5115013050	S500091	17. 7		11183	1	t.			Mn	P	S	A1	Nb	V	Ti	Cr	Ni	Cu	Мо	CEV	В	N								
13113013030	3300091	11.1	2000	11100		4. 037	0. 172	0.104	1 206	0.0105	0.0011	0. 0344	0.002	0.001	0.0022	0.086	0.031	0.015	0.011	0.4972	0.0004	0. 0028								
			 		1	1.001	0.112	0.131	1. 550	0.0155	0.0011	0.0011	0.002	0.001	0.0022	0.000	0.001	0.015	0.011	0. 1213	0.0001	0.0020								
	j				1																									
	TENSILE TES	er TE	ENSILE TES	ST TENS	SILE TEST	TENST	LE TEST	IMPACT	r TEST	IMPACT	TEST	TMDACT	r TEST	TMDACT	T TEST	U. T	Toct													
	TENSILE IE	TENSIEE TEST		51 IEW	TENO:		LE IESI	ISSI ISSI ISSI		IMINOI ILGI		IMPACT TEST		IMPACT TEST		0.1	rest													
). PLATE NO.		eH (Y. S) Rm (T. S)			.(0.1)					Charpy-		Charpy-																		
	ReH(Y.S)			I	A (E. L)	ReH/I								AVG		U.T inspection:														
																	<u> </u>													
				-			70	J TI +*2mm		J TI +*2mm		J TI +*2mm		TI +	J TI +*2mm		+													
	IC t	t IC t			IC t	10 t		0°C		0°C		0°C			0°C															
T5115013050	398	398 545			28. 5		73			147		134		137		Accepted														
		-		-																										
PAGE TOTAL		Accepta	able Vis	ual and		WE HERER	V CERTIEV 1	THAT THE	MATERIAL.	HASN'T A	NY IMPERI	MISSIBLE I	DEFECTS W	HEN THER	E IS ANY	COMPLATN	T VOII ARI	KINDLY	REQUESTE	TO MARK	THE STEI	EL GRADE	HEAT NO P	PLATE NO S	SIZE DELI	VERY DATI	CAUSES	AND MATER	TAL IN TH	E CONDITION
	(t)	•	size		REMARKS																				,		,			
4.03	1					l .																India t	Tiva							
SAM	PLE LOCATIO	ON AND O	ORIENTAT	TION: T=TO	P; B=B0T	ΓΤΟM; L=L	ONGL; C=	TRANS;	t =full	thickne	ess;t*2	mm =2mm	from r	olled s	urface	to spec	imen su	rface;			. (8		10							
OTES CEV	-C+Mn/6+(Cr+)	Mo+V)/5+	·(Ni+Cu)/	15. Tolera	ance S355,	J0+N/IS20	62 E350B0、	S355N/I	S2062 E3	50C : BS	S EN 100	29:2010	Class C.	Flatness	s:BS EN10	0029: 20	10 class	N type	L.	١.	Prie	(QAIC	E							
																					7/2	330	187							
ISSUED DATE 2025/1/21						PRINTED I	ЗҮ		CHENYOU					QUALITY MANAGER HAND Zhang Ming								STA								
T	PAGE TOTAL WEIGHT 4. 03 SAM OTES CEV=	PAGE TOTAL WEIGHT (t) 4.037 SAMPLE LOCATIC CEV=C+Mn/6+ (Cr+)	PAGE TOTAL WEIGHT (t) 4.037 SAMPLE LOCATION AND CEV=C+Mn/6+(Cr+Mo+V)/5+	MPa	MPa	MPa	MPa	MPa	ReH(Y,S) Rm(T,S) A(E,L) ReH/Rm(Y,R) V_absorb y	MPa	ReH(Y, S) Rm(T, S) A(E, L) ReH/Rm(Y, R) V_absorbed_energy V_absorbed_energ	ReH(Y, S)	ReH(Y. S)	ReH(Y, S)	ReH(Y,S) Rm(T,S) A(E,L) ReH/Rm(Y,R) V_absorbed_energ V_ab	ReH(Y, S)	ReH(Y, S) Rm(T, S) A(E, L) ReH/Rm(Y, R) V_absorbed_energ V	ReH(Y, S) Rm(T, S) A(E, L) ReH/Rm(Y, R) V_absorbed_energ V	ReH(Y, S) Rm(T, S) A(E, L) ReH/Rm(Y, R) V_absorbed_energ V	ReH(Y. S) Rm(T. S) A(E. L) ReH/Rm(Y. R) V_absorbed_energ V_absorbed_energ	Relf(Y,S) Rm(T,S) A(E,L) Relf/Rm(Y,R) V_absorbed_energ V_a	ReH(Y, S) Rm(T, S) A(E, L) ReH/Rm(Y, R) V_absorbed_energ V_absorbed_energ	Relf(X, S) Rm(T, S) A(E, L) Relf(Nm(Y, R) V_absorbed_energ V_absorbed_energ	ReH(T,S) Ru(T,S) A(E,L) ReH/Ru(T,R) V_absorbed_energ V_ab	ReH(Y.S) Rm(T.S) A(E.L) Rell/Rm(Y.R) V_absorbed_energ V_ab	Relify R	Relf(Y, S) Relf(Y, S) Relf(Rm(Y, R) Y_absorbed_energ Y_absor	Relf(Y, S) Raf(T, S) A(E, L) Relf/Raf(Y, R) Y_absorbed_energ Y_absorbed_energ	ReH(Y,S) Ru(T,S) A(E,L) ReH(Ru(Y,R) V_absorbed_energ V_ab	ReH(Y, S)