

QUALITY CERTIFICATE
BS EN 10204:2004 3. 1

TO: ACME SOLAR HOLDINGS LIMITED PLOT NO: 152, SECTOR 44, GURGAON 122002, INDIA

DESCRIPTION OF GOODS: HOT ROLLED STEEL PLATE

CONTRACT NO: XPIND24010CSL INVOICE NO: XPIND24010CSL-1C

JIANGYIN XINGCHENG SPECIAL STEEL WORKS CO., LTD.

NO.297, BINJIANG (E) ROAD, JIANGYIN CITY, JIANGSU PROVINCE, CHINA PC:214429



	EDGE A1	rmalizing r l-the-sides		ng				FICATION RADE				50B0				U. T Te	st	BS EN 1	10100.13	333 34E)			C	ERTIFICA LICENS				Z 20250	219000084	16
\top	EDGE MI	T the staes	Cuttii				01	MDE	S355J0+N/IS2062 E350B0 LICENSE NO. CHEMICAL COMPOSITION (Weight%)																						
	PLATE NO.	HEAT NO.		SIZE AND WEIGHT					T	1						 		CHEMIC	JAL COM	1 031110	WC18	,110,0)									
Э.			THICK	WIDTH	LENGTH	PIECES	ES	С	Si	Mn	P	S	A1	Nb	V	Ti	Cr	Ni	Cu	Мо	CEV	В	N								
_	m=111011010	2500000		mm	10010		t																								
1	T5114011010	S500086	14. 7	2587	10340	1	3. 087	0. 168	0.194			0. 0026 0. 0026				0.0021		0. 026		0.0143											
2	T5114011020 T5114011030	S500086 S500086	14. 7 14. 7	2587 2587	10340 10340	1	3. 087	0. 168 0. 168	0. 194		0.0178		0. 0283			0.0021	0.06	0. 026 0. 026						ļ							
,	15114011030	5500086	14. /	2581	10340	1	3.087	0. 108	0. 194	1. 403	0.0178	0.0026	0. 0283	0.0021	0.002	0.0021	0.06	0.026	0.02	0.0143	0. 4202	0.0005	0.0036								
+																															
+					-																										
+				1	1	1 1		l				ı				l				1		1		ı				l	ı		
				TENSILE TEST																											
		TENSILE TE	ST I			TENSILE TEST		LE TEST	IMPACT TEST		IMPACT TEST		IMPACT TEST		IMPACT TEST		U.T Test														
Э.	PLATE NO.	D H(V C)		Rm (T. S) A (E. L)		A/E I)		(V D)	Charpy-		Charpy-		Charpy-		4770																
		ReH(Y.S)				A (E. L)	KeH/I	Rm (Y. R)	v_absorbed_energ y-1		V_absorbed_energ y-2		V_absorbed_energ y-3		AVG		U.T inspection:														
									'- !		, -		, -		I		<u> </u>														
		MPa		MPa		%		%	J	Г		J		J		J															
		TC t		TC t		TC t	TC t		TL t*2mm		TL t*2mm		TL t*2mm		TL t*2mm																
									0°			$^{\circ}$	0		0																
L	T5114011010	411				31. 5		76		134		189		185		169		Accepted													
2	T5114011020	_	411 538			31. 5			134		189		185 185		169		Accepted														
3	T5114011030	411		538		31. 5		76	13	34	1	89	18	35	1	69	Acce	pted													
_																															
\rightarrow																															
—⊢	DACE TOTAL	<u> </u>							ļ		ļ										ļ				ļ		ļ				
PIEC	PAGE TOTAL CES WEIGH	T (+)	Accept	able Vis	sual and	REMARKS	WE HEREB	Y CERTIFY	THAT THE	MATERIAL	HASN' T A	NY IMPERN	IISSIBLE :	DEFECTS. W	HEN THER	E IS ANY	COMPLAIN	, YOU ARE	KINDLY I	REQUESTEI	TO MARK	THE STE	EL GRADE,	HEAT NO, F	LATE NO, S	SIZE, DELI	VERY DATE	E, CAUSES A	AND MATER	IAL IN THE	CONDITION.
		. ,		size		KEMAKKS	IMPACT S	AMPLE SIZE	:PLATE TH	ICKNESS, I	RESPECTIV	ELY:t≥6-	8mm\8 <t< td=""><td><12mm\t≥</td><td>≥12mm, SA</td><td>MPLE SIZE</td><td>, RESPECT</td><td>VELY: 10 ></td><td><5×55\10</td><td>$0 \times 7.5 \times 5$</td><td>5\10×10</td><td>\times55mm.</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	<12mm\t≥	≥12mm, SA	MPLE SIZE	, RESPECT	VELY: 10 >	<5×55\10	$0 \times 7.5 \times 5$	5\10×10	\times 55mm.									
3	9.2	261				l .	l .																Maja t	1/L							
	SA	MPLE LOCATI	ON AND	ORIENTA	TION · T=TO	∩P · R=R∩1	TOM· I =I	ONGI · C=	TRANS.	=full	thickn	acc.+*9	mm =9mm	from r	allad e	urface	to spac	iman en	rface:			15		13%							
																						1 1.2	OAIC	1C (E.)							
	NOTES CE	V=C+Mn/6+(Cr+	Mo+V)/5	+ (Ni+Cu)/	/15. Toler	ance S355	J0+N/IS20	62 E350B0	、S355N/I	S2062 E3	350C : B	S EN 100	29:2010	Class C.	Flatness	s:BS EN10	0029: 20	0 class	N type	L.	λ	1 12	UM	<i>−/≅.</i> /						_	
											1								₹												
																					\leftarrow	<u> </u>	DEF						MADD AA	ITY DEDIC	ATED
						I																٠								IN XINGCH	
	ISSUED DATE			2025/1/21				PRINTED	BY			CHE	NYOU			QUALIT		TY MANAGER		12m	2	zhan	gMing	₹ STA		EPARTME		enr		EEL WORK	
										1					1				1 '			/	1 () (JUAL LTY	ASSURAN	NCE	I SPE	CIALSIE		O UU.,LID.