

QUALITY CERTIFICATE
BS EN 10204:2004 3. 1

TO: ACME SOLAR HOLDINGS LIMITED PLOT NO: 152, SECTOR 44, GURGAON 122002, INDIA

CDECIFICATION EN 1009E 9.9010

DESCRIPTION OF GOODS: HOT ROLLED PLATE

DELIVERY CONDITION N 1: -: -- -- 11: --

CONTRACT NO: XPIND24010CSL INVOICE NO: XPIND24010CSL-2C

JIANGYIN XINGCHENG SPECIAL STEEL WORKS CO., LTD.

NO.297, BINJIANG (E) ROAD, JIANGYIN CITY, JIANGSU PROVINCE, CHINA PC 214429

CERTIFICATE NO



7 909509100000699



DELIVERY CONDITION Normalizing rolling S EDGE All-the-sides cutting								ICATION EN 10025-2:2019 U.T Test BS EN 10160:1999 S2E3 CERTIFICATE ADE S355J0+N/IS2062 E350B0 LICENSE NO													Z 202502190000628											
				SI	ZE AND W			CHEMICAL COMPOSITION (Weight%)																								
ÑO.	PLATE NO.	HEAT NO.	THICK	1		PIECES	+	С	Si	Mn	Р	S	A1	Nb	V	Ti	Cr	Ni	Cu	Мо	CEV	В	N									
1	T5115005010	S500100	21. 3		12122	1	5. 276	0. 163	0. 184	1. 389	0. 0157	0. 0012	0.0311	0.0037	0.002	0.0024	0. 095	0. 038	0. 02	0.0083	0. 4194	0. 0005	0.0024									
-																																
			<u> </u>	•										,		1		1														
	PLATE NO.	TENSILE TE	ST T	TENSILE TEST		TENSILE TEST TENS		LE TEST	IMPAC	IMPACT TEST		IMPACT TEST		IMPACT TEST I		IMPACT TEST		U.T Test														
																					l											
																	+															
.0v		ReH(Y, S)		Rm (T. S) A (E. L)		A(E I)	ReH/Rm(Y, R)		Charpy-		Charpy- g V absorbed energ		Charpy- rg V_absorbed_energ y-3		Λ	VG	U.T inspection:															
		Kell(1.5)				Ken/	1_00		y-1 y-2			n			nro		e. i inspection.															
		MPa		MPa		%	%		T		т		т			т Т		 														
		TC t				TC t	TC t		TL t*2mm		TL t*2mm		TL t*2mm		TL :	TL t*2mm		+														
										0℃		0℃		0℃		0℃																
1	T5115005010	377		532		30		71	2	04	1	.90	2	235	2	10	Acce	pted														
									-		-		-																			
PIE	PAGE TOTAL CES WEIGH	T (+)	Accepta	able Vis	sual and	REMARKS																	EL GRADE,	HEAT NO,	PLATE NO,	SIZE, DELI	VERY DAT	E, CAUSES	AND MATER	IAL IN TH	E CONDITION.	
111	1 5.2			size		KEMAKK	IMPACT S	AMPLE SIZE	E:PLATE TH	HICKNESS,	RESPECTIV	VELY:t≥6	5-8mm\8<1	t<12mm∖t	≥12mm, SA	MPLE SIZE	, RESPECT	IVELY:10	×5×55\10	0×7.5×5	5\10×10	×55mm.	No. 1									
		•					· ·																Tugla	That								
	SA	MPLE LOCATI	ON AND	ORIENTA	TION: T=TO	OP; B=B07	TTOM; L=L	ONGL; C=	TRANS;	t =full	thickn	ness;t*2	2mm =2mn	n from 1	olled s	surface	to spec	imen su	ırface;			(3)	1	C/6								
	NOTES CE	V=C+Mn/6+(Cr+	Mo+V)/5	+(Ni+Cu),	/15. Toler	ance S355	J0+N/IS20	62 E350B0	、S355N/	IS2062 E	350C : E	BS EN 100	029:2010	Class C	Flatnes	s:BS EN1	0029: 20	10 class	N type	L.	λ	1 1 1 2	OAIC	_/3/								
																					A	140	330	187								
																							40							NTY DEDI		
			0005 (1 /- 1																1.	1-te/u/	m/		~ AAino	st/	AMP OF D	DEPARTME	ENT OF			'IN XINGC		
	ISSUED DATE			2025/1/21				PRINTED BY			CHENYOU					QUAL 1	TY MANA	GER	Han's zhang Min					STAMP OF DEPARTMENT OF QUALITY ASSURANCE				SP	SPECIAL STEEL WORKS CO.,LTD.			
_		1																	I									1	IN	SPECTION		

H T T--+ DC EN 10160, 1000 C9E9