

Relational Model

Introduction

- Relational model introduced by Codd in 1970.
- It uses the concept of mathematical relation – concept of set theory and predicate logic
- It represents the database as a collection of relations.

Relational Model Concepts

- Relation or table
- Attribute or field or column name
- Tuples or record
- Schema
- Instance
- Domains
- Keys
- **Degree:** The total number of attributes which in the relation is called the degree of the relation.
- **Cardinality:** Total number of rows present in the Table.

Student Relation

NAME	<u>ROLL_NO</u>	PHONE_NO	ADDRESS	AGE
Ram	14795	7305758992	Noida	24
Shyam	12839	9026288936	Delhi	35
Laxman	33289	8583287182	Gurugram	20
Mahesh	27857	7086819134	Ghaziabad	27
Ganesh	17282	9028293988	Delhi	40

- NAME, ROLL_NO, PHONE_NO, ADDRESS, and AGE are the attributes.
- The instance of schema STUDENT has 5 tuples.
- $t_3 = \langle \text{Laxman}, 33289, 8583287182, \text{Gurugram}, 20 \rangle$ is the third tuple in the student table
- ROLL_NO is primary key in the table
- Degree = 5 (No of Columns)
- Cardinality = 5 (No of Rows)

Relational Model Concepts Cont....

Domain

- It contains a set of permitted atomic values for an attribute in the table.
- We specify domain of attribute while creating a table.
- E.g.,
 - Month of an year can accept all the month name or numbering from 01 to 12.
 - Domain of date can accept of possible dates.

Relational Model Concepts Cont....

Domain

String shorter than 30 chars

yyyy-mm-dd

*Character
M or F*

*Integer
 $400 < x < 80000$*

EMPLOYEE	FNAME	M	LNAME	<u>SSN</u>	BDATE	ADDRESS	S	SALARY	SUPERSSN	DNO
	Ramesh	K	Narayan	666884444	1962-09-15	...	M	38000	888665555	5
	Joyce	Null	English	453453453	1972-07-31	...	F	38000	888665555	5
	Ahmad	V	Jabbar	987987987	1969-03-29	...	M	25000	888665555	4
	James	Null	Borg	888665555	1937-11-10	...	M	55000	Null	1

Relational Model Concepts Cont....

Keys

- An attribute or set of attributes which can identify the row (tuple or record) in the relation uniquely.
- It is used to access the stored data quickly and smoothly
- It is used to create relationship between different tables.

Relational Model Concepts Cont....

Types of Keys:

- Primary Key
- Candidate Key
- Alternate Key
- Super Key
- Composite Key
- Foreign Key
- Unique Key

Relational Model Concepts Cont....

Primary Key (PK)

- It is unique and can not have NULL value
- It is chosen by designer to maintain uniqueness at row level.
- In the Employee table, EID or SSN can be a PK.
- EID is preferable because SSN is PII value and secure.

Employee

EID

Name

SSN

DeptId

DOB

Relational Model Concepts Cont....

Candidate Key (CK)

- All the columns that qualifies for uniqueness of each row.
- It is also called as minimal super keys.
- In the Employee table, EID and SSN are CK.
- We pick one of the CKs as PK.

Employee

EID

Name

SSN

DeptId

DOB

Relational Model Concepts Cont....

Alternate Key

- Candidate column other than primary column is called Alternate key.
- In the Employee table, SSN is alternate key.

Employee
<u>EID</u>
Name
SSN
DeptId
DOB

Relational Model Concepts Cont....

Super Key

- If we add any other column with candidate key, then it becomes super key.
- One or more attributes are taken collectively to identify all other attributes uniquely.
- In the Employee table, EID+Name, SSN+DeptId are super keys.

Employee
<u>EID</u>
Name
SSN
DeptId
DOB

Relational Model Concepts Cont....

Composite Key

- If a table does not have CKs, then we select two or more columns to uniquely identify each row in a table.
- In the Employee table, Name+DOB can be used as a composite primary key

Employee

EID

Name

SSN


DeptId

DOB

Relational Model Concepts Cont....

Foreign Key (FK)

- It is an attribute or set of attributes that references to PK of same table or another table.
- DeptId is FK in Employee Table.



Relational Model Concepts Cont....

Unique Key

- It is same as the PK, but the difference is with the existence of NULL value.
- It allows one value as NULL value.

Employee
<u>EID</u>
Name
SSN
DeptId
DOB

Relational Model Constraints

- Relational constraints are the restrictions imposed on the database contents and operations.
- They ensure the correctness of data in the database.

Constraint Types:

- Domain Constraints
- Key Constraints
- Entity Integrity Constraints
- Referential Integrity Constraints

Relational Model Constraints Cont. ...

Domain Constraints:

- Domain constraint defines the domain or set of values for an attribute.
- It specifies that the value taken by the attribute must be the atomic value from its domain.
- In the Student table, value '**A**' is not allowed since only integer values can be taken by the age attribute.

STU_ID	Name	Age
S001	Akshay	20
S002	Abhishek	21
S003	Shashank	20
S004	Rahul	A

Relational Model Constraints Cont. ...

Key Constraints:

- All the values of primary key must be unique.
- This student relation does not satisfy the key constraint as here all the values of primary key are not unique.

STU_ID	Name	Age
S001	Akshay	20
S001	Abhishek	21
S003	Shashank	20
S004	Rahul	21

Relational Model Constraints Cont. ...

Entity Integrity Constraints:

- It specifies that no attribute of primary key must contain a null value in any relation.
- This is because the presence of null value in the primary key violates the uniqueness property.
- This student relation does not satisfy the entity integrity constraint as here the primary key contains a NULL value.

STU_ID	Name	Age
S001	Akshay	20
S002	Abhishek	21
S003	Shashank	20
	Rahul	21

Relational Model Constraints Cont. ...

Referential Integrity Constraints:

- This constraint is enforced when an FK references the PK of a relation.
- It specifies that all the values taken by the FK must either be available in the relation of the PK or be null.
- We can not insert a record into a referencing relation if the corresponding record does not exist in the referenced relation.
- We can not delete or update a record of the referenced relation if the corresponding record exists in the referencing relation.


Referential Integrity Constraint Violation

- Cause-01: Insertion in a referencing relation
- Cause-02: Deletion from a referenced relation
- Cause-03: Updating in a referenced relation

Relational Model Constraints Cont.

Referential Integrity Constraints:

- It is specified between two tables.
- If an FK in Table 1 refers to the PK of Table 2, then every value of the FK in Table 1 must be null or be available in Table 2.



Guess under which A is not allowed ??

ID	NAME	SEMENSTER	AGE
1000	Tom	1 st	17
1001	Johnson	2 nd	24
1002	Leonardo	5 th	21
1003	Kate	3 rd	19
1004	Morgan	8 th	A

Not allowed. Because AGE is an integer attribute

Guess under which constraint A is not allowed
??

ID	NAME	SEMENSTER	AGE
1000	Tom	1 st	17
1001	Johnson	2 nd	24
1002	Leonardo	5 th	21
1003	Kate	3 rd	19
1004	Morgan	8 th	A

Not allowed. Because AGE is an integer attribute

Persons Table

PersonID	LastName	FirstName	Age
1	Hansen	Ola	30
2	Svendson	Tove	23
3	Pettersen	Kari	20

Orders Table

OrderID	OrderNumber	PersonID
1	77895	3
2	44678	3
3	22456	2
4	24562	1

The following table has two attributes A and C where A is the primary key and C is the foreign key referencing A with on-delete cascade.

A	C
---	---

2	4
---	---

3	4
---	---

4	3
---	---

5	2
---	---

7	2
---	---

9	5
---	---

6	4
---	---

The set of all tuples that must be additionally deleted to preserve referential integrity when the tuple (2,4) is deleted is:

(A) (3,4) and (6,4)

(B) (5,2) and (7,2)

(C) (5,2), (7,2) and (9,5)

(D) (3,4), (4,3) and (6,4)

The following table has two attributes A and C where A is the primary key and C is the foreign key referencing A with on-delete cascade.

A	C
---	---

2	4
---	---

3	4
---	---

4	3
---	---

5	2
---	---

7	2
---	---

9	5
---	---

6	4
---	---

The set of all tuples that must be additionally deleted to preserve referential integrity when the tuple (2,4) is deleted is:

(A) (3,4) and (6,4)

(B) (5,2) and (7,2)

(C) (5,2), (7,2) and (9,5)

(D) (3,4), (4,3) and (6,4)

References

- <https://www.javatpoint.com/dbms-integrity-constraints>
- <https://www.guru99.com/relational-data-model-dbms.html>
- <https://www.gatevidyalay.com/constraints-in-dbms-types-of-constraints-in-dbms/>
- <https://beginnersbook.com/2015/04/rdbms-concepts/>