

## Aspect Oriented Programming

Q.1) Write a program to demonstrate Spring AOP – before advice.

Beforeaop.java

```
package bvimit.edu;

import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Before;
import org.aspectj.lang.annotation.Pointcut;

@Aspect
public class beforeaop {
    @Pointcut("execution(int beforeoperation.*(..))")
    public void p() {
    }

    @Before("p()")
    public void myadvice(JoinPoint jp) {
        System.out.println("before advice");
    }
}
```

Beforeoperation.java

```
package bvimit.edu;

public class beforeoperation {
    public void msg() {
        System.out.println("method 1");
    }

    public int m() {
        System.out.println("method 2 with return");
        return 2;
    }

    public int k() {
        System.out.println("method 3 with return");
        return 3;
    }
}
```

Beforetest.java

```
package bvimit.edu;
```


```

import org.springframework.context.ApplicationContext;
import
org.springframework.context.support.ClassPathXmlApplicationContext;

public class beforetest {
    public static void main(String[] args) {
        ApplicationContext context = new
ClassPathXmlApplicationContext("aopctx1.xml");
        beforeoperation e = (beforeoperation)
context.getBean("opBean");
        System.out.println("calling m1.....");
        e.msg();
        System.out.println("calling m2.....");
        e.m();
        System.out.println("calling m3.....");
        e.k();
    }
}

```

**Output :**



```

<terminated> beforetest (7) [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 1:20:53 pm)
calling m1.....
method 1
calling m2.....
before advice
method 2 with return
calling m3.....
before advice
method 3 with return

```

**Q.2)** Write a program to demonstrate Spring AOP – after advice.

**Afteraop.java**

```
package bvimit.edu;

import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.annotation.After;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Pointcut;

@Aspect
public class afteraopdata {

    @Pointcut("execution(int afteroperation.*(..))")
    public void p() {
    }

    @After("p()")
    public void myadvice(JoinPoint jp) {
        System.out.println("after advice");
    }
}
```

**Afteroperation.java**

```
package bvimit.edu;

public class afteroperation {
    public void msg() {
        System.out.println("method 1");
    }

    public int m() {
        System.out.println("method 2 with return");
        return 2;
    }

    public int k() {
        System.out.println("method 3 with return");
    }
}
```

```

        return 3;
    }
}

```

### Aftertest.java

```

package bvimit.edu;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class aftertest {

    public static void main(String[] args) {

        ApplicationContext context = new
ClassPathXmlApplicationContext("aopctx1.xml");

        afteroperation e = (afteroperation) context.getBean("opBean");

        System.out.println("calling m1.....");

        e.msg();

        System.out.println("calling m2.....");

        e.m();

        System.out.println("calling m3.....");

        e.k();

    }

}

```

### Aopctx1.xml


```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="opBean" class="bvimit.edu.afteroperation"> </bean>
    <bean id="trackMyBean" class="bvimit.edu.afteraopdata"></bean>
    <bean
class="org.springframework.aop.aspectj.annotation.AnnotationAwareAspectJAutoProxyCreator"></bean>

```

</beans>

**Output :**



```
<terminated> aftertest (4) [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 1:49:39 pm)
calling m1.....
method 1
calling m2.....
method 2 with return
after advice
calling m3.....
method 3 with return
after advice
```

Q.3) Write a program to demonstrate Spring AOP – around advice.

Bankaopdata.java

```
package bvimit.edu;
import org.aspectj.lang.ProceedingJoinPoint;
import org.aspectj.lang.annotation.Around;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Pointcut;

@Aspect
public class Bankaopdata {
    @Pointcut("execution(* Bank.*(..))")
    public void a() {
    }

    @Around("a()")
    public Object myadvice(ProceedingJoinPoint p) throws Throwable
    {
        System.out.println("Around concern Before calling actual
method");
        Object obj = p.proceed();
        System.out.println("Around Concern After calling actual
method");
        return obj;
    }
}
```

Bank.java

```
package bvimit.edu;

public class Bank {
    public void welcome() {
        System.out.println("welcome to bank");
    }

    public int icici() {
        System.out.println("icici bank interest rate");
        return 7;
    }

    public int pnb() {
        System.out.println("pnb bank interest rate");
        return 6;
    }
}
```

## Banktest.java

```
package bvimit.edu;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;


public class Banktest {
    private static ApplicationContext context;

    public static void main(String[] args) {
        context = new
ClassPathXmlApplicationContext("Bankaopdata.xml");
        Bank e = (Bank) context.getBean("opBean");
        System.out.println("Calling welcome method...");
        e.welcome();
        System.out.println("Calling icici method...");
        e.icici();
        System.out.println("Calling pnb method...");
        e.pnb();
    }
}
```

## Bankaopdata.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="opBean" class="bvimit.edu.Bank"> </bean>
    <bean id="trackMyBean" class="bvimit.edu.Bankaopdata"></bean>
    <bean
class="org.springframework.aop.aspectj.annotation.AnnotationAwareAspectJAutoProxyCreator"></bean>
</beans>
```

## Output :



```
<terminated> Banktest (9) [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 1:59:26 pm)
Calling welcome method...
Around concern Before calling actual method
welcome to bank
Around Concern After calling actual method
Calling icici method...
Around concern Before calling actual method
icici bank interest rate
Around Concern After calling actual method
Calling pnb method...
Around concern Before calling actual method
pnb bank interest rate
Around Concern After calling actual method
```

**Q.4) Write a program to demonstrate Spring AOP – after returning advice.**

**Bankaopdata.java**

```
package bvimit.edu;

import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.ProceedingJoinPoint;
import org.aspectj.lang.annotation.AfterReturning;
import org.aspectj.lang.annotation.Around;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Pointcut;

@Aspect
public class Bankaopdata {
    @AfterReturning(pointcut = "execution(* Bank.*(..))",
returning = "result")
    public void myadvice(JoinPoint jp, Object result) {
        System.out.println("AfterReturning concern");
        System.out.println("Result in advice" + result);
    }
}
```

**Bank.java**

```
package bvimit.edu;

public class Bank {
    public void welcome() {
        System.out.println("welcome to bank");
    }

    public int icici() {
        System.out.println("icici bank interest rate");
        return 7;
    }

    public int pnb() {
        System.out.println("pnb bank interest rate");
        return 6;
    }
}
```

**Banktest.java**

```
package bvimit.edu;

import org.springframework.context.ApplicationContext;
```



```

import
org.springframework.context.support.ClassPathXmlApplicationContext;

public class Banktest {
    private static ApplicationContext context;

    public static void main(String[] args) {
        context = new
ClassPathXmlApplicationContext("Bankaopdata.xml");
        Bank e = (Bank) context.getBean("opBean");
        e.welcome();
        e.icici();
        e.pnb();
    }
}

```


### Bankaopdata.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="opBean" class="bvimit.edu.Bank"> </bean>
    <bean id="trackMyBean" class="bvimit.edu.Bankaopdata"></bean>
    <bean
class="org.springframework.aop.aspectj.annotation.AnnotationAwareAspectJAutoProxyCreator"></bean>
</beans>

```

### Output :



```

<terminated> Banktest (10) [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 2:06:43 pm)
welcome to bank
AfterReturning concern
Result in advicenull
icici bank interest rate
AfterReturning concern
Result in advice7
pnb bank interest rate
AfterReturning concern
Result in advice6

```

Q.5) Write a program to demonstrate Spring AOP – after throwing advice.

Operation\_at.java

```
package bvimit.edu;

public class Operation_at {
    public void validate(int att) throws Exception {
        if (att < 75) {
            throw new ArithmeticException("Not eligible for exam");
        } else {
            System.out.println("Eligible for exam");
        }
    }
}
```

Operationaop\_at.java

```
package bvimit.edu;
import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.annotation.AfterThrowing;
import org.aspectj.lang.annotation.Aspect;

@Aspect
public class Operationaop_at {
    @AfterThrowing(pointcut = "execution(* Operation_at.*(..))",
        throwing = "error")
    public void myadvice(JoinPoint jp, Throwable error) {
        System.out.println("AfterThrowing concern");
        System.out.println("Exception is: " + error);
        System.out.println("end of after throwing advice....");
    }
}
```

OperationTest\_at.java

```
package bvimit.edu;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class OperationTest_at {
    private static ApplicationContext context;

    public static void main(String[] args) {
```

```

        ApplicationContext context = new
ClassPathXmlApplicationContext("validctx.xml");
        Operation_at op = (Operation_at)
context.getBean("opBean");
        System.out.println("calling validate....");
        try {
            op.validate(85);
        } catch (Exception e) {
            System.out.println(e);
        }
        System.out.println("calling validate again....");
        try {
            op.validate(25);
        } catch (Exception e) {
            System.out.println(e);
        }
    }
}

```


#### Validctx.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="opBean" class="bvimit.edu.Operation_at"></bean>
    <bean id="trackMyBean" class="bvimit.edu.Operationaop_at"></bean>
    <bean
class="org.springframework.aop.aspectj.annotation.AnnotationAwareAspectJAutoProxyCreator"></bean>
</beans>

```

#### Output :



```

<terminated> OperationTest_at [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 2:15:02 pm)
calling validate....
Eligible for exam
calling validate again....
AfterThrowing concern
Exception is: java.lang.ArithmeticException: Not eligible for exam
end of after throwing advice....
java.lang.ArithmeticException: Not eligible for exam

```

**Q.6) Write a program to demonstrate Spring AOP –pointcuts.**

**Aopdata\_pc.java**

```
package bvimit.edu;

import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.annotation.After;
import org.aspectj.lang.annotation.Pointcut;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Before;

@Aspect
public class Aopdata_pc {
    @Pointcut("execution(int Operation.*(..))")
    public void p() {
    }

    @After("p()")
    public void myadvice(JoinPoint jp) {
        System.out.println("After advice");
    }

    @Pointcut("execution(* Operation.*(..))")
    public void i() {
    }

    @Before("i()")
    public void myadvice1(JoinPoint jp) {
        System.out.println("Before advice");
    }
}
```

**Operation\_pc.java**

```
package bvimit.edu;

public class Operation_pc {
    public void msg() {
        System.out.println("method 1");
    }

    public int m() {
        System.out.println("method 2 with return");
        return 2;
    }

    public int k() {
        System.out.println("method 3 with return");
    }
}
```

```

        return 3;
    }
}

```

## Test\_pc.java

```

package bvimit.edu;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class Test_pc {
    public static void main(String[] args) {
        ApplicationContext context = new
ClassPathXmlApplicationContext("aopctx_pc.xml");
        Operation_pc e = (Operation_pc)
context.getBean("opBean");
        System.out.println("calling m1...");
        e.msg();
        System.out.println("calling m2...");
        e.m();
        System.out.println("calling m3...");
        e.k();
    }
}

```


## Aopctx.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="opBean" class="bvimit.edu.Operation_pc"></bean>
    <bean id="trackMyBean" class="bvimit.edu.Aopdata_pc"></bean>
    <bean
class="org.springframework.aop.aspectj.annotation.AnnotationAwareAspectJAutoProxyCreator"></bean>
</beans>

```

## Output :



The screenshot shows the Eclipse IDE's Console window. The top bar contains tabs for 'Source', 'Namespaces', 'Overview', 'beans', and 'Beans Graph'. Below this is a toolbar with icons for 'Markers', 'Properties', 'Servers', 'Data Source Explorer', 'Snippets', and 'Console'. The console text area displays the following output:

```
<terminated> Test_pc (1) [AspectJ/Java Application] C:\Program Files\Java\jdk-11\bin\javaw.exe (12-Dec-2024, 2:20:48 pm)
calling m1...
method 1
calling m2...
method 2 with return
calling m3...
method 3 with return
```