

1.Install OpenVAS or Nessus Essentials.

- Download Tenable Nessus | Tenable

tenable.com/downloads/nessus?highlighted=true

Now Tab

Tenable | Downloads

Log in

Tenable Nessus

Tenable Nessus Agent

Tenable Nessus Scanner

Tenable Security Center

Tenable Cloud Security

Integration

Service Proxy

Tenable Core

Tenable OT Security

Tenable Identity Exposure

PrivilegeGuard

Compliance & Audit Files

Tenable Patch Management

Downloads / Tenable Nessus

Tenable Nessus

1 Download and Install Nessus

Choose Download

Version

Nessus - 10.9.1

Platform

Windows - x86_64

Download

Download

Download by curl >

Docker >

Virtual Machines >

2 Start and Setup Nessus

Open Nessus and follow setup wizard to finish setting up Nessus

3 Getting Started

Check out our [documentation](#) for Nessus

Summary

Release Date: Oct 26, 2025

Release Notes

[Tenable Nessus 10.9.1](#) / [Release Notes](#)

Signing Keys

[SHA-256 \(SHA256SUMS\)](#) / [SHA-256 \(SHA256SUMS\)](#)



[SHA-512 \(SHA512SUMS\)](#) / [SHA-512 \(SHA512SUMS\)](#)

-
- The screenshot shows the Tenable Nessus Essentials web interface. The browser address bar indicates the URL is `https://localhost:8834/#/scans/folders/my-scans`. The interface has a dark theme. On the left, there is a sidebar with sections: 'COLLAPSE' (with a minus icon), 'My Scans' (with a plus icon), 'All Scans' (with a plus icon), 'Health' (with a plus icon), 'RESOURCES' (with a plus icon), 'Policies' (with a plus icon), and 'Project Room' (with a plus icon). Below the sidebar, there is a 'Tenable News' section with the headline 'How Rapid AI Adaptation is Creating an Exposure Gap' and a 'Read More' link. The main content area is titled 'My Scans' and contains a message: 'This folder is empty. Create a new scan.' There are buttons for 'Import', 'New Policy', and 'New Scan' in the top right of the main area.

2. Set up scan target as your local machine IP or localhost.

Basic Network Scan Setup


1. Go to: <https://localhost:8834/>
2. Left sidebar → **Scans**
3. Click **New Scan**
4. Select **Basic Network Scan**
5. Fill fields:
 - **Name:** Localhost Full Scan
 - **Targets:** 127.0.0.1
(or your IP: 192.168.x.x)
6. Click **Save**.



3. Start a full vulnerability scan.

1. Open **Scans** → **My Scans**
2. Hover over your scan → click **Launch**
3. Nessus begins scanning:
 - ports
 - services
 - SSL
 - SMB
 - Windows settings
 - outdated software
 - misconfigurations

Scan takes **10–25 minutes**.




4.Wait for scan to complete (may take 30-60 mins).

While the scan runs, Nessus shows:

- Count of vulnerabilities
- Breakdown by severity
- Progress percentage
- Hosts discovered

You can leave it running.

Once done, the scan status changes to **Completed**.



5. Review the report for vulnerabilities and severity.

1. Open the completed scan result.
2. Go to **Vulnerabilities** tab.
3. Nessus groups issues by severity:
 - **Critical** (red)
 - **High** (orange)
 - **Medium** (yellow)
 - **Low** (blue)
 - **Info** (grey)
4. Click each vulnerability to see:
 - Description
 - Risk
 - CVEs
 - Affected ports/services
 - Output from scan
 - Solution steps

The screenshot shows the Nessus Essentials interface. The main panel displays the 'Vulnerabilities' tab for a scan titled 'My Basic Network Scan / 192.168.1.7'. The interface includes a sidebar with 'FOLDERS' (My Scans, All Scans, Trash) and 'RESOURCES' (Policies, Plugin Rules). The main table lists 23 vulnerabilities, grouped by severity. The table has columns for Severity, CVSS, VPR, EPSS, Name, Family, and Count. The vulnerabilities are categorized as follows:

Sev	CVSS	VPR	EPSS	Name	Family	Count
MEDIUM	5.3			SMB Signing not required	Misc.	1
MEDIUM				SSL (Multiple Issues)	General	4
INFO				SMB (Multiple Issues)	Windows	6
INFO				HTTP (Multiple Issues)	Web Servers	2
INFO				TLS (Multiple Issues)	Service detection	2
INFO				Nessus Port Scanner (SSH)	Port scanners	27
INFO				DCE Services Enumeration	Windows	8
INFO				Service Detection	Service detection	2
INFO				Additional DNS Hostnames	General	1
INFO				Common Platform Enumeration (CPE)	General	1
INFO				Device Type	General	1
INFO				Host Fully Qualified Domain Name (FQDN) Resolution	General	1
INFO				Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure	Windows	1
INFO				Nessus Scan Information	Settings	1
INFO				Nessus Server Detection	Service detection	1

On the right side, the 'Host Details' panel shows the following information:

- IP: 192.168.1.7
- OS: Windows 11
- Start: Today at 7:57 PM
- End: Today at 8:04 PM
- Elapsed: 7 minutes
- KB: Download
- Auth: Fail

Below the host details is a 'Vulnerabilities' donut chart showing the distribution of severity levels: Critical (red), High (orange), Medium (yellow), Low (blue), and Info (grey). The chart shows a high proportion of Low and Info vulnerabilities.

Install and scan guide

Nessus Essentials / Folders / Vulnerabilities

Not securehttps://localhost:8834/#/scans/reports/0/vulnerabilities/57608

New Tab

TenableNessus EssentialsScansSettings

SLAYER

FOLDERS

My Scans

All Scans

Trash

RESOURCES

Policies

Plugin Rules

Tenable News

WordPress - Ultimate Dashboard exposed API Key

Read More

My Basic Network Scan / Plugin #57608

Back to Vulnerabilities

Configure

Hosts1Vulnerabilities19History2

MEDIUMSMB Signing not required

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

See Also

<http://www.nessus.org/u/8f998b63>
<https://technet.microsoft.com/en-us/library/cc731957.aspx>
<http://www.nessus.org/u/74b0d723>
<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>
<http://www.nessus.org/u/7a3cac4a>

Output

No output recorded.

To see debug logs, please visit individual host

Port	Hosts
445/http/cifs	192.168.1.7

Plugin Details

Severity: Medium
ID: 57608
Version: 1.20
Type: remote
Family: Misc.
Published: January 19, 2012
Modified: October 5, 2022

Risk Information

Risk Factor: Medium
CVSS v3.0 Base Score: 5.3
CVSS v3.0 Vector: CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/CN:R/L:N
CVSS v3.0 Temporal Vector: CVSS:3.0/E:U/R/L:O/M:C
CVSS v3.0 Temporal Score: 4.6
CVSS v2.0 Base Score: 5.0
CVSS v2.0 Temporal Score: 3.7
CVSS v2.0 Vector: CVSS2#AV:N/AC:L/Au:N/CN:R/P:N
CVSS v2.0 Temporal Vector: CVSS2#E:U/R/L:O/M:C

Vulnerability Information

Exploit Available: true
Exploit Ease: Exploits are available
Vulnerability Pub Date: January 17, 2012

Install and scan guide

Nessus Essentials / Folders / Vulnerabilities

Not securehttps://localhost:8834/#/scans/reports/0/vulnerabilities/group/51192

New Tab

TenableNessus EssentialsScansSettings

SLAYER

FOLDERS

My Scans

All Scans

Trash

RESOURCES

Policies

Plugin Rules

Tenable News

Dell Storage Manager Multiple Vulnerabilities

Read More

My Basic Network Scan / SSL (Multiple Issues)

Back to Vulnerabilities

Configure

Hosts1Vulnerabilities19History2

Search Vulnerabilities4 Vulnerabilities

Sev	CVSS	VPR	EPSS	Name	Family	Count
MEDIUM	6.5			SSL Certificate Cannot Be Trusted	General	1
INFO				SSL Certificate Information	General	1
INFO				SSL Cipher Suites Supported	General	1
INFO				SSL Perfect Forward Secrecy Cipher Suites Supported	General	1

Scan Details

Policy: Basic Network Scan
Status: Running
Severity Base: CVSS v3.0
Scanner: Local Scanner
Start: Today at 8:16 PM

Vulnerabilities

Critical

High

Medium

Low

Info

The screenshot shows the Nessus Essentials web interface. The top navigation bar includes links for "Install and scan guide", "Nessus Essentials / Folders / Vulnerabilities", and "New Tab". The main header displays "Otenable | Nessus Essentials | Scans | Settings". On the left sidebar, there are sections for "FOLDERS" (My Scans, All Scans, Trash) and "RESOURCES" (Policies, Plugin Rules). The central area shows a scan titled "My Basic Network Scan / Plugin #51192" with a status of "Not secure" and a URL "https://localhost:8034/#/scans/reports/L/vulnerabilities/group/51192/51192". Below this, a tabbed interface shows "Hosts 1", "Vulnerabilities 19", and "History 2". A specific vulnerability is highlighted: "MEDIUM SSL Certificate Cannot Be Trusted".

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below:

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's "notbefore" dates, or after one of the certificate's "notAfter" dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

Solution

Purchase or generate a proper SSL certificate for this service.

See Also

<https://www.kitintrent.co.uk/TREC-X-509/en>
<https://en.wikipedia.org/wiki/X.509>

Output

```
The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

|-Subject : O=Measus Ueess United/OO=Measus Server/L=New York/C=US/ST=NY/CN=Tarun Anilraj
|-Issuer : O=Measus Ueess United/OO=Measus Certification Authority/L=New York/C=US/ST=NY/CN=Measus Certification Authority

To see debug logs, please visit individual host
```

On the right side, the "Plugin Details" section lists: Severity: Medium, ID: 51192, Version: 1.20, Type: remote, Family: General, Published: December 15, 2010, Modified: June 16, 2025. The "Risk Information" section shows Risk Factor: Medium, CVSS v3.0 Base Score: 6.5, CVSS v3.0 Vector: CVSS:3.0/AV=N/AC=L/P=NONE/N=S/LUC/LA=JA/N, CVSS v2.0 Base Score: 6.4, CVSS v2.0 Vector: CVSS2#AV=N/AC=L/Ac=N/CIP=P/AN.

6. Research simple fixes or mitigations for found vulnerabilities.

1. SMB Signing Not Required (Medium)

Cause: Windows allows SMB traffic without mandatory signing → risk of MITM.

Fix (Windows Home):

Run in **PowerShell (Admin)**:

```
Set-ItemProperty -Path  
"HKLM:\SYSTEM\CurrentControlSet\Services\LanmanWorkstation\Parameters" -  
Name RequireSecuritySignature -Value 1
```

```
Set-ItemProperty -Path  
"HKLM:\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters" -Name  
RequireSecuritySignature -Value 1
```

2. SSL Certificate Cannot Be Trusted (Medium)

- **Cause:** Nessus UI uses a **self-signed SSL certificate**.
Browsers don't trust it — this is normal.
- **Fix:**
 - Not needed for local usage.
 - (Optional) Import the certificate into **Trusted Root Certificate Authorities** to suppress warnings