Columns in FOP

Block 0: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf. XML has associated with it a great number of other standards, most of them under W3C (World-Wide Web Consortium) auspices. Among these are XML Namespaces, XML Pointer, XPath, XSLT, XHTML, SVG, RELAX, SOAP, and any number of others. This file has been prepared using formatting objects, an XML vocabulary described in the XSL specification of October 18, 2000. Formatting objects are used to specify pagination and composition, and are intended for high-quality, precision layout-driven formatting.

Block 1: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf. XML has associated with it a great number of other standards, most of them under W3C (World-Wide Web Consortium) auspices. Among these are XML Namespaces, XML Pointer, XPath, XSLT, XHTML, SVG, RELAX, SOAP, and any number of others. This file has been prepared using formatting objects, an XML vocabulary described in the XSL specification of October 18, 2000. Formatting objects are used to specify pagination and composition, and are intended for high-quality, precision layout-driven formatting.

Block 2: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf.

Block 3: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf.

Block 4: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed

for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf.

Block 5: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf.

Block 6: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf. XML has associated with it a great number of other standards, most of them under W3C (World-Wide Web Consortium) auspices. Among these are XML Namespaces, XML Pointer, XPath, XSLT, XHTML, SVG, RELAX, SOAP, and any number of others. This file has been prepared using formatting objects, an XML vocabulary described in the XSL specification of October 18, 2000. Formatting objects are used to specify pagination and composition, and are intended for high-quality, precision layout-driven formatting.

Block 7: The Extensible Markup Language (XML) is a subset of SGML that is completely described in this document. Its goal is to enable generic SGML to be served, received, and processed on the Web in the way that is now possible with HTML. XML has been designed for ease of implementation and for interoperability with both SGML and HTML. For further information read normal.pdf. XML has associated with it a great number of other standards, most of them under W3C (World-Wide Web Consortium) auspices. Among these are XML Namespaces, XML Pointer, XPath, XSLT, XHTML, SVG, RELAX, SOAP, and any number of others. This file has been prepared using formatting objects, an XML vocabulary described in the XSL specification of October 18, 2000. Formatting objects are used to specify pagination and composition, and are intended for high-quality, precision layout-driven formatting.