

DocuSign Integration with OpenText Content Server

The information required to integrate DocuSign is in your DocuSign Admin account. Before you integrate into Content Server, ensure that you create a DocuSign account and have a valid license.

To integrate DocuSign:

1. In your DocuSign administrator account, add the following redirect URL to the integration key for Content Server: **<Content Server Base URL>/docusignoauthcallback**. For more information, see DocuSign administrator documentation about API and keys.
2. In the **Signature Providers** section of the **Content Server Administration** page, click the **DocuSign Settings** link.
3. On the **DocuSign Administration Settings** page, in the **DocuSign Account Details** area, enter the following DocuSign administrator account information:
 - DocuSign administrative username
 - DocuSign administrative password
 - DocuSign administrative user account ID
 - DocuSign login URL. For demo environments this value is `https://demo.docusign.net`. For production environments, this value may vary depending on the user account. For more information, see DocuSign documentation about post go live.
 - DocuSign integrator key
 - DocuSign authorization endpoint URL. This is either `https://account.docusign.com/oauth/auth` for production environments, or `https://account-d.docusign.com/oauth/auth` for demo environments. This is required as part of the DocuSign Authorization Code Grant flow, which is an OAuth 2.0 flow that grants an access token to server-hosted applications. Each request to the DocuSign APIs must include a valid access token. To acquire an access token, the flow exchanges an authorization code for an access token. The authorization code is acquired using the provided authorization endpoint URL. For more information, see DocuSign developer documentation about the Authorization Code Grant flow.
 - DocuSign client secret. This is a secret key used for integrations that is found in your DocuSign administrator account. For more information, see DocuSign administrator documentation about secret keys.
4. Optional To confirm that your entered information is correct, click **Test Settings**.

1. Login to DocuSign as Admin, Click on 'Admin' then 'Apps and Keys'

← → ↻ apps-d.docusign.com/admin/apps-and-keys

docusign Home Agreements Templates Reports **Admin**

Legal Disclosure Sign up for the Developer Newsletter for the latest product

Reminders and Expiration

Comments

Document Custom Fields

Envelope Custom Fields

INTEGRATIONS

Connect

Apps and Keys

API Usage Center

CORS

Payments

AGREEMENT ACTIONS

Rules

Wa

★ ★

Tell us more...

2. Note Account ID.

docusign Home Agreements Templates Reports Admin

Apps and Keys > Content Server

Opentext
Account ID: 32166465

Overview

ACCOUNT

Plan and Billing

Account Profile

Security Settings

Regional Settings

Content Server

Edit your application name, choose an authentication method

General Info

App Name *

Content Server

Integration Key

a6a54624-5cbc-4d67-b3be-40163282f248



3. Click on 'Add App and Integration Key'

The screenshot shows the Docusign Admin console. The left sidebar contains the 'Opentext' account information and a list of settings. The main content area is titled 'Apps and Keys' and includes a section for 'My Account Information' with fields for User ID, API Account ID, and Account Base URI. A yellow button labeled 'Add App and Integration Key' is highlighted in the top right corner of the main content area.

4. Enter Name and Click 'Create App'

The screenshot shows a modal dialog titled 'Add Integration Key'. It has a close button (X) in the top right corner. The 'App Name' field is required (indicated by a red asterisk) and contains the text 'Content Server'. Below the field are two buttons: 'Create App' (highlighted in blue) and 'Cancel'.

5. Note the Integration Key

General Info

App Name *

Content Server

Integration Key

a6a54624-5cbc-4d67-b3be-40163282f248



6. Click on 'Add Secret Key'; it will generate a secret key. Make sure to note it down.

Authentication Method for your App

Authorization Code Grant

Used for integrations where each user logs in individually and requires a one-time consent for the app to use their account.

☐ Require Proof Key for Code Exchange (PKCE) **RECOMMENDED**

Requires all requests to include a code verifier and code challenge, which protects your app against malicious attacks.

Secret Keys

+ Add Secret Key

7. Click 'Add URI,' enter <port>://<hostname>/otcs/cs.exe/docusignoauthcallback, and click 'Save'.

apps-d.docusign.com/admin/apps-and-keys/a6486adb-fc74-40ca-83b4-5a63726681ec

docusign

Home

Agreements

Templates

Reports

Admin

Email Preferences

Custody Transfer

Document Retention

Legal Disclosure

Reminders and Expiration

Comments

Document Custom Fields

Envelope Custom Fields

INTEGRATIONS

Connect

Apps and Keys



Service Integration

DocuSign can generate a keypair for you or you can upload your own public key.

RSA Keypairs (ID)

+ Generate RSA

+ Upload RSA

Additional settings

Redirect URIs

+ Add URI

Link to Privacy Policy

http://www.example.com/privacy

Link to Terms of Use

- Go to the DocuSign Administration settings in Content Server and enter all the details noted while creating the app in DocuSign and save changes.

One or more Admin Servers are using the default password. Admin user has the default password. Change Admin pa:

Enterprise ▾ Personal ▾ Tools ▾ Admin ▾ My Account ▾ ? ▾

DocuSign Administration Settings

DocuSign Account Details	
Account Id	Account Id of DocuSign Admin 30454857
Login URL	Base URL for DocuSign tenant https://demo.docusign.net
Integrator Key	Enter Integrator Key cb224b15-b9d1-4315-8f82-d89c56a216f3 Generated from DocuSign Admin account
Connection Status	Test Settings
Authorization Endpoint URL	Base URL for Authorization https://account-d.docusign.com/oauth/auth
Client Secret	Enter Client Secret of DocuSign Admin

DocuSign Tabs