PTC - Avenida D. Manuel I
Zona Industrial de Ovar
3880-109 OVAR

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
2504E019

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71151873 * SEQUENCE Nº 9

Validation Terminal Nº	Accessory	Applicator Type	Purchasing Order Nº	Project / Model
7115-1873-02	*	MXK	4514204126	DAIMLER TRUCK - BEV







Applicable Terminals for this Tool:

7115-1873-02	7115-1873-04		

Anvil			Wire Crimper			Insulation Crimper		
7115-1873XA		(A1)	7115-1873XW		(1)	7115-1873XI		(A1)
CW (c)	1.92	CW (i) 2.3	CW	1.9		CW	2.3	

1 - VISUAL / MEASURED CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable

			Spec. (*)	Value (**)			
	The two sides of the insulation grips are in the correct position.	O	0 - 0.3 mm 0.13 - 0.76 mm	0.24 0.52		The Bell Mouth is within the spec.	O
	Not found any Bell Mouth in the insulation area.	O	0 - 0.25 mm	0.19		The dimension of the cutting carrier is within the spec.	O
	The lance height and shape are not deformed.	O	0 - 5 ° 0 - 5 °	0.7		Bend up and Bend down are within the criteria.	O
	Not found any burr in the cutting carrier.	O	0 - 0.8 mm	0.76		The exposed conductor is within the spec.	O
	Not found any crack in the terminal.	O	0 - 5 °	0.7		The terminal is not bent sideways while looking from the top.	O
	The wire barrel is free from burrs.	O	0 - 5 °	0.3		The body of the terminal is not twisted.	O


(*) - Specified on Crimping Spec.

(**) - Measured Value(From Lower Wire Kind&Size Sample)

LOWER WIRE KIND & SIZE

UPPER WIRE KIND & SIZE

2 - MICRO CUT SAMPLES



3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1.35	1.35	6.64
	+/- **0.05**		

	NOMINAL	AVERAGE	Cmk
mm			
	+/-		

REMARKS:

Applicable wire range 0.50mm²~1.00mm²
The wire size-0.50/0.75mm² is not recommended due to the micro-cut conditions

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) nº3485	CHECKED (Operator) nº44	PREPARED (Operator) nº18388
		HELDER ROCHA
Date: 28/05/2025	Date: 26/05/2025	Date: 26/05/2025

YAZAKI

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial N°

2504E019

LOWER WIRE KIND & SIZE

C/W(I): 2.35 mm

Wire kind: FLRYB

Wire size: 1 mm²

Nominal Cr. Height:	1.35	2.3	mm
+/-	0.05	0.1	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1.350	2.302
2	1.350	2.309
3	1.348	2.302
4	1.355	2.306
5	1.348	2.299
6	1.355	2.302
7	1.349	2.301
8	1.350	2.303
9	1.350	2.306
10	1.350	2.309
11	1.349	2.320
12	1.350	2.302
13	1.352	2.299
14	1.355	2.302
15	1.350	2.309
16	1.349	2.302
17	1.350	2.300
18	1.350	2.303
19	1.349	2.301
20	1.347	2.309
21	1.350	2.300
22	1.348	2.302
23	1.355	2.298
24	1.350	2.303
25	1.355	2.301
26	1.350	2.302
27	1.349	2.309
28	1.352	2.300
29	1.348	2.302
30	1.350	2.303
31	1.349	2.302
32	1.355	2.300
33	1.349	2.309
34	1.350	2.302
35	1.347	2.302
36	1.350	2.300
37	1.348	2.303
38	1.355	2.302
39	1.350	2.300
40	1.348	2.309
41	1.349	2.302
42	1.350	2.300
43	1.355	2.302
44	1.352	2.303
45	1.349	2.309
46	1.355	2.300
47	1.350	2.307
48	1.355	2.309
49	1.347	2.301
50	1.350	2.303
Average	1.35	2.30
Cmk	6.64	8.06

UPPER WIRE KIND & SIZE

C/W(I): mm

Wire kind: NA + NA

Wire size: NA + NA mm²

Nominal Cr. Height:	NA	NA	mm
+/-	NA	NA	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
Average		
Cmk		


Acceptance criteria: Cmk >= 2

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1193	TERMINAL No. 端子品番	7115-1873
共通品番	- / -	- / -	- / -

Rev.1



②Oiling unit standard equipment.
塗油ユニット標準装備

No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称
1	7115-1873XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ
2	7115-1873XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ
3	7115-1873XA		ANVIL ｱﾝﾋﾞﾙ
4	7115-1873XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ
5	7115-1873XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ
6	7115-1873XYB		BASE ﾍﾞｰｽ
7	7115-1873XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB
8	48A47016	001	WIRE HOLDER 電線押さえ
9	48A47017	003	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ
10	48A47020	A03	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ
12	48A47024	001	SHEARBLADE ｼｬｰﾌﾞﾚｰﾄﾞ
13	48A47025	001	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ
14	48A19007	028 ①	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ
15	48A19019	020	BUSH ﾌﾞｯｼｭ
16	48A47014	001	FEEDING CAM 送りｶﾑ
17	48A47013	001	FEEDING CLAW 送り爪
18	48A19100	005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
19	48A19047	001 ①	TERMINAL SCRAPER 端子掻き落とし
20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
21	48A47032	001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
22	48A19017	003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
23	48A19023	002	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾞﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
	7115-1873XKP		BRACKET ﾌﾞﾗｹｯﾄ
27			~~STABILIZER CRIMPER~~ ~~ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
〈OPTIONｵﾌﾟｼｮﾝ〉			
13	48A47025	101	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ
14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検
②	11/17/2023	Oiling unit standard equipment	C23K032	H.KAMIYA
①	9/27/2007	027→028, 002→001	QX7	T,Suzuki

APPRICATION POST 申請部署	
HIB	
DESIGNED DATE 設計日	
8/27/2007	
APPROVED 承認	DESIGNED 設計
T,Maki	T,Suzuki
8/27/2007	8/27/2007

REVISED
ISSUE
11/22/2023
YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.

ISSUED 発行