PTC - Avenida D. Manuel I
Zona Industrial de Ovar
3880-109 OVAR

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1903E081







TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71164156 SEQUENCE Nº 9





Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7116-4156-02	*	**04 SIDE FEED**	**YSD 3500116811**	*

Anvil			Wire Crimper			Insulation Crimper		
7116-4156XA		(A)	7116-4156XW		(A)	7116-4156XI		(A)
CW (c)	2,52	*CW (i)* 3,60	*CW*	2,50		*CW*	3,60	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	**O**
	Not found any Bell Mouth in the insulation area.	**O**
	The lance height and shape are not deformed.	**O**
	Not found any burr in the cutting carrier.	**O**
	Not found any crack in the terminal.	**O**
	The wire barrel is free from major burrs.	**O**


	The Bell Mouth is within the spec.**(*)**	**O**
	The dimension of the cutting carrier is within the spec.**(*)**	**O**
	Bend up and Bend down are within the criteria**(*)**	**O**
	The exposed conductor is within the spec.(*)	**O**
	The terminal is not bent sideway, look-king from the top**(*)**	**O**
	The body of the terminal is not twisted**(*)**	**O**

LOWER WIRE KIND & SIZE

UPPER WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1,55	1,55	4,89
	+/-0.05		

	NOMINAL	AVERAGE	Cmk
mm	1,85	1,85	4,60
	+/-0.05		

REMARKS:

Aplicable wire range 1.50mm²~2.50mm²
Wire 1.50mm² C/W(I)-3.61mm
Wire 2.50mm² C/W(I)-3.64mm

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 18388
Date: 2019-abr-08	Date: 2019-abr-08	Date: 2019-abr-08

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1903E081

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Wire size: 1,5 mm²

Nominal Cr. Height:	1,55	2,75	mm
+/-	0,05	0,1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1,550	2,753
2	1,550	2,755
3	1,551	2,751
4	1,548	2,751
5	1,548	2,756
6	1,550	2,757
7	1,549	2,751
8	1,549	2,755
9	1,550	2,750
10	1,551	2,756
11	1,549	2,755
12	1,549	2,756
13	1,544	2,753
14	1,540	2,751
15	1,554	2,757
16	1,550	2,750
17	1,555	2,757
18	1,549	2,758
19	1,546	2,758
20	1,551	2,754
21	1,555	2,753
22	1,548	2,756
23	1,549	2,753
24	1,551	2,752
25	1,554	2,750
26	1,548	2,753
27	1,550	2,753
28	1,551	2,762
29	1,549	2,749
30	1,549	2,749
31	1,550	2,752
32	1,549	2,747
33	1,549	2,751
34	1,549	2,749
35	1,548	2,746
36	1,547	2,750
37	1,547	2,746
38	1,544	2,747
39	1,546	2,742
40	1,549	2,747
41	1,550	2,747
42	1,551	2,747
43	1,557	2,747
44	1,556	2,744
45	1,547	2,750
46	1,555	2,749
47	1,547	2,747
48	1,548	2,747
49	1,545	2,753
50	1,541	2,749
Average	1,55	2,75
Cmk	4,89	7,95

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Wire size: 2,5 mm²

Nominal Cr. Height:	1,85	3,2	mm
+/-	0,05	0,1	mm


Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1,850	3,202
2	1,850	3,202
3	1,849	3,203
4	1,850	3,202
5	1,849	3,206
6	1,847	3,200
7	1,845	3,200
8	1,852	3,203
9	1,843	3,203
10	1,850	3,201
11	1,846	3,198
12	1,850	3,202
13	1,850	3,199
14	1,849	3,197
15	1,851	3,202
16	1,855	3,199
17	1,846	3,201
18	1,852	3,196
19	1,848	3,196
20	1,849	3,193
21	1,851	3,203
22	1,855	3,202
23	1,850	3,198
24	1,848	3,202
25	1,853	3,199
26	1,854	3,199
27	1,855	3,198
28	1,849	3,201
29	1,851	3,201
30	1,847	3,197
31	1,848	3,197
32	1,854	3,195
33	1,848	3,203
34	1,849	3,193
35	1,854	3,204
36	1,853	3,200
37	1,846	3,200
38	1,848	3,198
39	1,853	3,196
40	1,852	3,201
41	1,858	3,201
42	1,852	3,197
43	1,853	3,194
44	1,864	3,193
45	1,850	3,192
46	1,849	3,191
47	1,847	3,197
48	1,851	3,191
49	1,849	3,191
50	1,845	3,201
Average	1,85	3,20
Cmk	4,60	8,79

Acceptance criteria: Cmk>= 2,0

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1499	TERMINAL No. 端子品番	7116-4156



No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称	No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称
1	7116-4156XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	16	48A47014	005②	FEEDING CAM 送りｶﾑ
2	7116-4156XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	17	48A47013		FEEDING CLAW 送り爪
3	7116-4156XA		ANVIL ｱﾝﾋﾞﾙ	18	48A19100	-005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
4	7116-4156XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
5	7116-4156XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
6	7116-4156XYB		BASE ﾍﾞｰｽ	21	48A47032	-001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
7	7116-4156XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	22	48A19017	-003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
8	48A47016	001	WIRE HOLDER 電線押さえ	23	48A19023	001	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾞﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
12	48A47024	002 ①	SHEARBLADE ｼｬｰﾌﾞﾚｰﾄﾞ		7116-4156XKP		BRACKET ﾌﾞﾗｹｯﾄ
13	48A47025	002/101 ①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ	27	-		~~STABILIZER CRIMPER~~ ~~ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
14	48A19007	023①③④⑤	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	〈ｵﾌﾟｼｮﾝ OPTION〉			
15	48A19019	019	BUSH ﾌﾞｯｼｭ	14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検
⑤	2009/9/22	022→023	09J-016	C,Abe
④	2009/9/1	023→022	09I-015	C,Abe
③	2008/12/11	024→023	QX7	C,Abe
②	2008/6/23	001→005	QX7	C,Sato
①	2007/6/27	001→002、022→024	QX7	T,Suzuki

APPRICATION POST 申請部署	
接続技術部	
DESIGNED DATE 設計日	
2007/3/5	
APPROVED 承認	DESIGNED 設計
K,Hiraguchi	T,Suzuki
2007/3/5	2007/3/5

ISSUED 発行

ISSUE
2013 / 09 / 16
YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.