QUALITY AND TECHNICAL DATA CERTIFICATE FOR APPLICATOR

CLIENT	MODEL		S/N	MAP
YAZAKI SALTANO DE OVAR, P.E. LDA	RSY2275-JGF1_M		L 76518	
	Cod. KIT	K K006869		
ORDER	TERMINAL TO BE CRIMPED			A#
5010993	7116-1909-02			

APPLICATOR SETUP


SETUP L.D.P. (mm.)=	190,00	STROKE	40 (mm)		MECAL	S.C.	S.T.M.	Note
Load Cal. (Kg.) =	850			Specification		X		
		Setup	Fixing. Ref.▼	Terminal Samples		X		
POSITIVE CAM (Terminal present)		X	C	Wire Samples		X		
NEGATIVE CAM (Terminal absent)				Housing Samples				
			Fixing. Ref.▲	Seal Samples		X		7158-3213-90
				Applicounter			No	
				Mobile Ejector			Yes	
				Carrier strip to be cut			No	
				Conform to Mecal norms			Yes	
				Automatic machine				

FEEDING POINT OF THE TERMINAL				
Hole	Slot	Wire wing	Insulation wing	Other
X				

	Crimp Height	Pull Force	Section	Photo
C			1,00	X
M				
K			0,50	X

Setup on		
	Mod.	S/N
Press	P107C	42877
Stripper		

Strip length = 4,50 (mm)



CRIMPING

WIRE	INSULATION	BARREL
 F	 C	
Profile dimension Wire C. Profile Width (mm.) 1,93 (toll. +) 0,02	Profile dimension Insulation C. Profile Width (mm.) 3,96 (toll. +) 0,02	Profile dimension Barrel C. Profile Width (mm.) (toll. +)

WIRE CHARACTERISTICS


CRIMPING DIMENSIONS (mm.)

SECTION	COMPOSITION		Insulation	CONDUCTOR				INSULATION				BARREL			Pull Force	Crimp Force
					Required HEIGHT ±	Required WIDTH ±	Measured WIDTH		Required HEIGHT ±	Required WIDTH ±	Measured WIDTH	Required HEIGHT ±	Required WIDTH ±	Measured WIDTH		
mm²	Nb	Ø	Ø	Index Wire	0,05	0,10		Index Insulation	0,10	0,10					Min. (N.)	C.F.A. (KN.)
0,93 Sez. reale																
1,00	19	0,25	1,90	2,34	1,35	2,05	2,01	1,50	4,20	4,05	4,06				175	3,15
0,48 Sez. reale																
0,50	19	0,18	1,40	2,55	1,18	2,05	1,99	1,44	4,00	4,05	4,00				80	3,64

CHECK



Description		Rif.	Test
Bent left or right (max)	3°	A	OK
Bent up or down (max)	3°	B	OK
Torsion (max)	3°	C	OK



Description		Rif.	Test
Bellmouth	(0.2-0.6)	D	OK
Cut-off (max)	0,3	E	OK
Wire overlay(min.)	0,1	F	OK


DATE	OPERATOR SIGNATURE	CONTROLLER SIGNATURE	QUALITY RESPONSIBLE
10/12/2015	*Amarotto*	*Toniato*	*Zatti*

N.B.: MECAL affirms that the MECAL tool is in accordance with the above mentioned characteristics

QUALITY AND TECHNICAL DATA CERTIFICATE FOR APPLICATOR

YAZAKI SALTANO DE OVAR, P.E. LDA | **WIRE** | **RSY2275-JGF1_M** | **76518**

	Terminal
	7116-1909-02
Wire Section.	1,00
CH. (mm.)	
C.W. (mm.)	
Material Compression (%)	
Wire Compression	
Terminal Compression	



	Terminal
	7116-1909-02
Wire Section.	1,00
CH. (mm.)	1,35
C.W. (mm.)	2,01
Material Compression (%)	21,2
Wire Compression	
Terminal Compression	


	Terminal
	7116-1909-02
Wire Section.	1,00
CH. (mm.)	
C.W. (mm.)	
Material Compression (%)	
Wire Compression	
Terminal Compression	

DATE	OPERATOR SIGNATURE	CONTROLLER SIGNATURE	QUALITY RESPONSIBLE
10/12/2015	*Amarotto*	*Toniato*	*Zatti*

QUALITY AND TECHNICAL DATA CERTIFICATE FOR APPLICATOR

YAZAKI SALTANO DE OVAR, P.E. LDA | **WIRE** | **RSY2275-JGF1_M** | **76518**

	Terminal
	7116-1909-02
Wire Section.	0,50
CH. (mm.)	
C.W. (mm.)	
Material Compression (%)	
Wire Compression	
Terminal Compression	



	Terminal
	7116-1909-02
Wire Section.	0,50
CH. (mm.)	1,18
C.W. (mm.)	1,99
Material Compression (%)	20,5
Wire Compression	
Terminal Compression	

	Terminal
	7116-1909-02
Wire Section.	0,50
CH. (mm.)	
C.W. (mm.)	
Material Compression (%)	
Wire Compression	
Terminal Compression	

DATE	OPERATOR SIGNATURE	CONTROLLER SIGNATURE	QUALITY RESPONSIBLE
10/12/2015	*Amarotto*	*Toniato*	*Zatti*

MECAL	DISTINTA COMPONENTI - PARTS LIST - BESTANDTEILELIST

DATA 10/12/2015

MODELLO
MODEL **RSY2275-JGF1_M**
TYPE
MODELE

TERMINALE
TERMINAL **7116-1909-02**
KONTAKT
COSSE

MATRICOLA
SERIAL NU **L 76518**
REGISTRIERNUMMER
MATRICULE

CODICE	Qt.	Rif
870550004	1	110
601051006	2	130
600052010	1	150
911190000	1	160
911070012	1	170
650231018	1	180
630104106	1	190
990270004	1	200
991320002	1	210
600041106	1	220
991280007	1	230
991320001	1	240
610111308	1	250
911110013	1	260
991300008	1	280
870620001	1	295
880480008	1	300
871980007	1	310
990400003	1	315
600061016	2	360
601058012	1	370
600050010	1	380
640060020	2	390
991290010	1	400
991290016	1	405
600050014	4	410
640050020	1	420
600041008	1	450
650242004	2	460
991350000	1	480
600050016	2	490
600050010	1	500
991590000	1	510
911010006	1	520
991340002	1	530
991330003	1	540
991310000	1	560
640050020	1	570
600052010	1	580
911090007	1	590

CODICE	Qt.	Rif
95127 0207	1	001
60006 0040	1	005
91112 0035	1	100
99101 0039	1	120
95127 0046	1	140
91103 0045	1	290
91117 0053	1	320
91118 0184	1	330
60005 0035	1	340
99017 0019	1	343
91125 0074	1	350
88146 0018	1	355
88146 0019	1	362
60004 0008	4	365
91106 0000	1	430
91105 0018	1	440
99017 0000	1	470
91102 0001	1	550
91108 0050	1	600
91011 0000	2	610
91124 0228	1	620
91119 0003	1	621
99126 0028	1	622
91116 0025	1	623
91122 0008	1	630
60003 0006	2	640
91148 0361	1	650
91148 0382	1	655
91148 0383	1	655
63010 4104	2	665
60004 1012	2	660
Personal. **L_H06-Y**		
98146 1129	**1**	**1000**
98145 1044	**1**	**1010**
99951 0460	1	1030
91130 0293	1	1040
60008 1025	1	1055
98127 1449	**1**	**1060**
60004 0010	1	1062
91134 0177	**1**	**1070**
91133 0174	**1**	**1075**
91035 0002	1	1080
20108 0061	1	1082
60003 0008	1	1085
60004 0016	4	1090
60003 0006	1	1093
91145 0025	1	1095
91141 0329	1	1096
60004 0010	1	1097
62104 0010	1	1098
91143 0039	1	1105
64002 0008	1	1110
91042 0000	1	1115
91145 0000	1	1120
91146 0000	1	1125
60004 0016	1	1130