PTC - Avenida D. Manuel I
Zona Industrial de Ovar
3880-109 OVAR

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1704E300

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71164156 SEQUENCE Nº 9

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7116-4156-02	*	**04 SIDE FEED**	**YSD-PO 25ENG/2017**	*







Anvil		
7116-4156XA		(A)
CW (c) 2.52	*CW (i)* 3.60	






Wire Crimper	
7116-4156XW	(A)
CW 2.50	

Insulation Crimper	
7116-4156XI	(A)
CW 3.60	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	O
	Not found any Bell Mouth in the insulation area.	O
	The lance height and shape are not deformed.	O
	Not found any burr in the cutting carrier.	O
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O


	The Bell Mouth is within the spec.**(*)**	O
	The dimension of the cutting carrier is within the spec.**(*)**	O
	Bend up is within the criteria**(*)**	O
	Bend down is within the criteria**(*)**	O
	The terminal is not bent sideway, looking from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1.47	1.47	4.46
	+/-0,05		

	NOMINAL	AVERAGE	Cmk
mm	1.76	1.76	4.29
	+/-0,05		

REMARKS:

Aplicable wire 1.50mm²~2.50mm²
Wire 1.50mm² C/W(I)-361mm
Wire 2.50mm² C/W(I)-363mm

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 18388
Date: 2017-mai-17	Date: 2017-mai-17	Date: 2017-mai-17

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1704E300

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 1,5 mm^2

Nominal Cr. Height:	1.47	2.8	mm
+/-	0.05	0.1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.471	2.803
2	1.472	2.803
3	1.470	2.801
4	1.474	2.799
5	1.474	2.799
6	1.474	2.796
7	1.470	2.796
8	1.469	2.803
9	1.474	2.804
10	1.474	2.812
11	1.471	2.798
12	1.472	2.805
13	1.473	2.808
14	1.472	2.798
15	1.470	2.796
16	1.475	2.800
17	1.473	2.798
18	1.471	2.801
19	1.471	2.802
20	1.470	2.799
21	1.475	2.798
22	1.469	2.805
23	1.477	2.804
24	1.474	2.805
25	1.469	2.798
26	1.471	2.800
27	1.473	2.801
28	1.468	2.797
29	1.466	2.802
30	1.473	2.801
31	1.473	2.801
32	1.473	2.799
33	1.474	2.803
34	1.465	2.796
35	1.472	2.800
36	1.464	2.799
37	1.464	2.801
38	1.467	2.800
39	1.466	2.800
40	1.462	2.795
41	1.467	2.798
42	1.467	2.799
43	1.466	2.798
44	1.468	2.792
45	1.466	2.796
46	1.465	2.797
47	1.465	2.794
48	1.463	2.789
49	1.467	2.788
50	1.465	2.796
Average	1.47	2.80
Cmk	4.46	7.79

UPPER WIRE KIND & SIZE

Wire kind: FLRYB

Total wire size: 2,5 mm^2

Nominal Cr. Height:	1.76	3.2	mm
+/-	0.05	0.1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.758	3.202
2	1.762	3.206
3	1.762	3.205
4	1.760	3.208
5	1.762	3.207
6	1.762	3.206
7	1.764	3.206
8	1.758	3.204
9	1.762	3.208
10	1.762	3.205
11	1.761	3.208
12	1.759	3.209
13	1.760	3.205
14	1.764	3.207
15	1.766	3.206
16	1.759	3.203
17	1.760	3.200
18	1.757	3.203
19	1.760	3.200
20	1.760	3.200
21	1.759	3.201
22	1.764	3.201
23	1.766	3.203
24	1.764	3.199
25	1.763	3.204
26	1.757	3.200
27	1.762	3.207
28	1.756	3.201
29	1.754	3.202
30	1.760	3.212
31	1.751	3.202
32	1.749	3.199
33	1.761	3.211
34	1.750	3.211
35	1.763	3.207
36	1.762	3.207
37	1.761	3.202
38	1.767	3.208
39	1.765	3.208
40	1.764	3.208
41	1.762	3.207
42	1.759	3.201
43	1.756	3.201
44	1.757	3.207
45	1.757	3.205
46	1.764	3.200
47	1.762	3.210
48	1.762	3.209
49	1.761	3.206
50	1.763	3.210
Average	1.76	3.20
Cmk	4.29	8.93


Acceptance criteria: Cmk>= 2

Cmk= {maximum of (AVERAGE-LOWER LIMIT) and (UPPER LIMIT-AVERAGE)} / 3 STD DEVIATION

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1499	TERMINAL No. 端子品番	7116-4156



No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称	No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称
1	7116-4156XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	16	48A47014	005②	FEEDING CAM 送りｶﾑ
2	7116-4156XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	17	48A47013		FEEDING CLAW 送り爪
3	7116-4156XA		ANVIL ｱﾝﾋﾞﾙ	18	48A19100	-005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
4	7116-4156XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
5	7116-4156XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
6	7116-4156XYB		BASE ﾍﾞｰｽ	21	48A47032	-001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
7	7116-4156XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	22	48A19017	-003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
8	48A47016	001	WIRE HOLDER 電線押さえ	23	48A19023	001	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾞﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
12	48A47024	002 ①	SHEARBLADE ｼｬｰﾌﾞﾚｰﾄﾞ		7116-4156XKP		BRACKET ﾌﾞﾗｹｯﾄ
13	48A47025	002/101 ①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ	27	-		~~STABILIZER CRIMPER~~ ~~ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
14	48A19007	023①③④⑤	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	〈ｵﾌﾟｼｮﾝ OPTION〉			
15	48A19019	019	BUSH ﾌﾞｯｼｭ	14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検
⑤	2009/9/22	022→023	09J-016	C,Abe
④	2009/9/1	023→022	09I-015	C,Abe
③	2008/12/11	024→023	QX7	C,Abe
②	2008/6/23	001→005	QX7	C,Sato
①	2007/6/27	001→002、022→024	QX7	T,Suzuki

APPRICATION POST 申請部署	
接続技術部	
DESIGNED DATE 設計日	
2007/3/5	
APPROVED 承認	DESIGNED 設計
K,Hiraguchi	T,Suzuki
2007/3/5	2007/3/5

ISSUED 発行

ISSUE
2013 / 09 / 16
YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.