PTC - Avenida D. Manuel I
Zona Industrial de Ovar
3880-109 OVAR

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1704E318

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71151637 SEQUENCE Nº 9

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7115-1637-02	**7158-3213-90**	**04 SIDE FEED**	**YSD-PO 25ENG/2017**	*







Anvil		
7115-1637DDXA		(N)
CW (c) 1.97	*CW (i)* 4.00	




Wire Crimper	
7115-1637DDXW	(1)
CW 1.95	

Insulation Crimper	
7115-1637DDXI	(A1)
CW 4.00	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	**O**
	Not found any Bell Mouth in the insulation area.	**O**
	The lance height and shape are not deformed.	**O**
	Not found any burr in the cutting carrier.	**O**
	Not found any crack in the terminal.	**O**
	The wire barrel is free from major burrs.	**O**


	The Bell Mouth is within the spec.**(*)**	**O**
	The dimension of the cutting carrier is within the spec.**(*)**	**O**
	Bend up is within the criteria**(*)**	**O**
	Bend down is within the criteria**(*)**	**O**
	The terminal is not bent sideway, looking from the top**(*)**	**O**
	The body of the terminal is not twisted**(*)**	**O**

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1.27	1.27	4.78
	+/-0.05		

	NOMINAL	AVERAGE	Cmk
mm	1.45	1.45	3.26
	+/-0.05		

REMARKS:

Aplicable wire range-0.50~1.00mm²
Size 0.50mm² C/W(I)-4.06mm
Size 1.00mm² C/W(I)-4.11mm

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 2624
Date: 2017-mai-09	Date: 2017-mai-08	Date: 2017-mai-08

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1704E318

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 0.5 mm^2

Nominal Cr. Height:	1.27	3.9	mm
+/-	0.05	0.1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.278	3.899
2	1.275	3.906
3	1.272	3.908
4	1.274	3.907
5	1.274	3.902
6	1.278	3.901
7	1.277	3.904
8	1.275	3.906
9	1.272	3.909
10	1.269	3.904
11	1.270	3.899
12	1.270	3.894
13	1.272	3.894
14	1.274	3.898
15	1.273	3.902
16	1.272	3.903
17	1.268	3.901
18	1.269	3.897
19	1.270	3.894
20	1.274	3.892
21	1.274	3.897
22	1.277	3.898
23	1.275	3.900
24	1.271	3.898
25	1.269	3.894
26	1.270	3.891
27	1.271	3.895
28	1.275	3.900
29	1.276	3.904
30	1.275	3.900
31	1.272	3.892
32	1.273	3.890
33	1.274	3.890
34	1.281	3.894
35	1.280	3.895
36	1.277	3.897
37	1.275	3.901
38	1.271	3.895
39	1.272	3.891
40	1.272	3.895
41	1.276	3.897
42	1.278	3.897
43	1.280	3.888
44	1.277	3.888
45	1.273	3.893
46	1.274	3.894
47	1.277	3.897
48	1.279	3.893
49	1.278	3.888
50	1.275	3.891
Average	1.27	3.90
Cmk	4.78	5.97

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 1 mm^2

Nominal Cr. Height:	1.45	4.2	mm
+/-	0.05	0.1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.458	4.192
2	1.463	4.196
3	1.457	4.199
4	1.454	4.201
5	1.451	4.194
6	1.448	4.189
7	1.449	4.185
8	1.455	4.189
9	1.458	4.192
10	1.460	4.194
11	1.455	4.196
12	1.450	4.192
13	1.447	4.191
14	1.443	4.186
15	1.445	4.190
16	1.448	4.192
17	1.451	4.194
18	1.456	4.196
19	1.460	4.191
20	1.454	4.186
21	1.451	4.185
22	1.448	4.189
23	1.450	4.189
24	1.453	4.192
25	1.458	4.194
26	1.461	4.188
27	1.456	4.186
28	1.453	4.184
29	1.450	4.187
30	1.448	4.189
31	1.444	4.192
32	1.445	4.192
33	1.448	4.187
34	1.452	4.184
35	1.455	4.189
36	1.451	4.189
37	1.448	4.191
38	1.446	4.194
39	1.444	4.189
40	1.450	4.186
41	1.450	4.183
42	1.454	4.187
43	1.450	4.190
44	1.447	4.192
45	1.444	4.193
46	1.445	4.194
47	1.447	4.189
48	1.453	4.186
49	1.448	4.183
50	1.445	4.189
Average	1.45	4.19
Cmk	3.26	7.48

Acceptance criteria: Cmk>= 2


Cmk= {maximum of (AVERAGE-LOWER LIMIT) and (UPPER LIMIT-AVERAGE)} / 3 STD DEVIATION

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1160	TERMINAL No. 端子品番	7115-1637DD

Common PN 共通品番	7FB9-9098	–	–	–
	–	–		



No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称	No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称
1	7115-1637XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	17	48A47013	001	FEEDING CLAW 送り爪
2	7115-1637XID		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	18	48A19100	005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
3	7115-1637XAD		ANVIL ｱﾝﾋﾞﾙ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
4	7115-1637XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
5	7115-1637XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	21	48A47032	001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
6	7115-1637XYB		BASE ﾍﾞｰｽ	22	48A19017	003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
7	7115-1637XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	23	48A19023	002	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
8	48A47016	002	WIRE HOLDER 電線押さえ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	003	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾞﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ		7115-1637XKP		BRACKET ﾌﾞﾗｹｯﾄ
12	48A19049	002 ①	SHEARBLADE ｼｬｰﾌﾞﾚｰﾄﾞ	27			~~STABILIZER CRIMPER ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
13	48A47025	003 ①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ	〈OPTION ｵﾌﾟｼｮﾝ〉			
14	48A19007	017	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	13	48A47025	101	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ
15	48A19019	027②	BUSH ﾌﾞｯｼｭ	14	48A47042	-002	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)
16	48A47014	005 ①	FEEDING CAM 送りｶﾑ				

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検	APPRICATION POST 申請部署	
					HIB	
					DESIGNED DATE 設計日	
					2007/8/27	
②	2010/12/15	030→027	10G-024	K.Muramatsu	APPROVED 承認	DESIGNED 設計
①	2007/10/3	CHANGED No.	QX7	T,Suzuki	T,Maki	T,Suzuki
					2007/8/27	2007/8/27

ISSUED 発行

ISSUE
2014/05/12
YAZAKI PARTS CO.,LTD HAIBARA OFFICE