APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1709E123

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71164156 SEQUENCE Nº 9

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7116-4156-02	*	**04 SIDE FEED**	**SD-DAIMLER SFTP XVK**	*







Anvil		
7116-4156XA		(A)
CW (c) 2,52	*CW (i)* 3,60	





Wire Crimper		
7116-4156XW		(A)
CW 2,50		

Insulation Crimper		
7116-4156XI		(A)
CW 3,60		

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	O
	Not found any Bell Mouth in the insulation area.	O
	The lance height and shape are not deformed.	O
	Not found any burr in the cutting carrier.	O
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O


	The Bell Mouth is within the spec.**(*)**	O
	The dimension of the cutting carrier is within the spec.**(*)**	O
	Bend up is within the criteria**(*)**	O
	Bend down is within the criteria**(*)**	O
	The terminal is not bent sideway, looking from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1.55	1.55	3.37
	+/-0.05		


	NOMINAL	AVERAGE	Cmk
mm	1.85	1.85	2.97
	+/-0.05		

REMARKS:

Aplicable wire range 1.50mm² ~ 2.50mm²
Wire 1.50mm² C/W(I)-3.60mm
Wire 2.50mm² C/W(I)-365mm

EVALUATION DECISION

SUITABLE [X] FOR USE IN PRODUCTION
NOT SUITABLE [ ]

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 18597
		
Date: 2017/Oct/16	Date: 2017/Oct/13	Date: 2017/Oct/13

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1709E123

LOWER WIRE KIND & SIZE

Wire kind: FLRYB

Total wire size: 1.5 mm^2

Nominal Cr. Height:	1.55	2.75	mm
+/-	0.05	0.1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.551	2.751
2	1.549	2.751
3	1.556	2.753
4	1.555	2.750
5	1.557	2.741
6	1.558	2.755
7	1.552	2.757
8	1.551	2.749
9	1.545	2.747
10	1.545	2.750
11	1.541	2.755
12	1.551	2.760
13	1.551	2.751
14	1.538	2.745
15	1.534	2.740
16	1.536	2.757
17	1.552	2.747
18	1.553	2.758
19	1.553	2.749
20	1.553	2.747
21	1.546	2.759
22	1.552	2.767
23	1.547	2.757
24	1.544	2.749
25	1.554	2.746
26	1.550	2.751
27	1.549	2.751
28	1.552	2.746
29	1.549	2.750
30	1.547	2.748
31	1.552	2.750
32	1.549	2.749
33	1.554	2.749
34	1.550	2.754
35	1.554	2.748
36	1.554	2.751
37	1.555	2.757
38	1.553	2.749
39	1.551	2.748
40	1.550	2.751
41	1.546	2.756
42	1.553	2.758
43	1.551	2.755
44	1.547	2.749
45	1.552	2.751
46	1.551	2.751
47	1.555	2.755
48	1.552	2.755
49	1.551	2.755
50	1.549	2.755
Average	1.55	2.75
Cmk	3.37	6.67

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 2.5 mm^2

Nominal Cr. Height:	1.85	3.2	mm
+/-	0.05	0.1	mm


Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1.850	3.202
2	1.846	3.199
3	1.848	3.198
4	1.852	3.190
5	1.849	3.199
6	1.852	3.195
7	1.855	3.201
8	1.850	3.197
9	1.851	3.203
10	1.858	3.204
11	1.856	3.199
12	1.854	3.205
13	1.858	3.189
14	1.850	3.210
15	1.847	3.201
16	1.849	3.208
17	1.858	3.193
18	1.860	3.201
19	1.860	3.185
20	1.857	3.196
21	1.859	3.194
22	1.861	3.198
23	1.858	3.202
24	1.852	3.200
25	1.858	3.197
26	1.856	3.199
27	1.854	3.198
28	1.851	3.198
29	1.855	3.201
30	1.851	3.198
31	1.851	3.198
32	1.854	3.200
33	1.854	3.203
34	1.848	3.205
35	1.851	3.196
36	1.849	3.200
37	1.848	3.197
38	1.852	3.202
39	1.845	3.206
40	1.852	3.203
41	1.856	3.203
42	1.861	3.201
43	1.858	3.209
44	1.855	3.204
45	1.861	3.213
46	1.858	3.204
47	1.857	3.200
48	1.866	3.196
49	1.864	3.196
50	1.867	3.202
Average	1.85	3.20
Cmk	2.97	6.52

Acceptance criteria: Cmk>= 2.0

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1499	TERMINAL No. 端子品番	7116-4156



No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称	No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称
1	7116-4156XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	16	48A47014	005②	FEEDING CAM 送りｶﾑ
2	7116-4156XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	17	48A47013		FEEDING CLAW 送り爪
3	7116-4156XA		ANVIL ｱﾝﾋﾞﾙ	18	48A19100	-005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
4	7116-4156XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
5	7116-4156XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
6	7116-4156XYB		BASE ﾍﾞｰｽ	21	48A47032	-001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
7	7116-4156XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	22	48A19017	-003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
8	48A47016	001	WIRE HOLDER 電線押さえ	23	48A19023	001	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾞﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
12	48A47024	002 ①	SHEARBLADE ｼｬｰﾌﾞﾚｰﾄﾞ		7116-4156XKP		BRACKET ﾌﾞﾗｹｯﾄ
13	48A47025	002/101 ①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾞﾚｰﾄﾞ	27	-		~~STABILIZER CRIMPER~~ ~~ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
14	48A19007	023①③④⑤	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	〈ｵﾌﾟｼｮﾝ OPTION〉			
15	48A19019	019	BUSH ﾌﾞｯｼｭ	14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検
⑤	2009/9/22	022→023	09J-016	C,Abe
④	2009/9/1	023→022	09I-015	C,Abe
③	2008/12/11	024→023	QX7	C,Abe
②	2008/6/23	001→005	QX7	C,Sato
①	2007/6/27	001→002、022→024	QX7	T,Suzuki

APPRICATION POST 申請部署	
接続技術部	
DESIGNED DATE 設計日	
2007/3/5	
APPROVED 承認	DESIGNED 設計
K,Hiraguchi	T,Suzuki
2007/3/5	2007/3/5

ISSUED 発行

ISSUE
2013 / 09 / 16
YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.