APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1709E127

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71164157 SEQUENCE Nº 1

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7116-4157-02	*	**04 SIDE FEED**	**SD-DAIMLER SFTP XVK**	*







Anvil		
7116-4157XA		(A)
CW (c) 2,02	*CW (i)* 2,50	





Wire Crimper		
7116-4157XW		(N)
CW 2,00		

Insulation Crimper		
7116-4157XI		(A)
CW 2,50		

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable

	The two sides of the insulation grips are in the correct position.	O
	Not found any Bell Mouth in the insulation area.	O
	The lance height and shape are not deformed.	O
	Not found any burr in the cutting carrier.	O
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O


	The Bell Mouth is within the spec.**(*)**	O
	The dimension of the cutting carrier is within the spec.**(*)**	O
	Bend up is within the criteria**(*)**	O
	Bend down is within the criteria**(*)**	O
	The terminal is not bent sideway, looking from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1,2	1,20	4,37
	+/-0.05		



	NOMINAL	AVERAGE	Cmk
mm	1,35	1,35	4,87
	+/-0.05		

REMARKS:

Aplicable wire range 0.50mm²~1.00mm²
Wire 0.50mm² C/W(I)-2.54mm
Wire 1.00mm² C/W(I)-2.56mm

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 18388
		
Date: 2017-out-19	Date: 2017-out-19	Date: 2017-out-17

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1709E127

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 0,5 mm^2

Nominal Cr. Height:	1,2	2,15	mm
+/-	0,05	0,1	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1,202	2,148
2	1,207	2,154
3	1,204	2,149
4	1,205	2,149
5	1,205	2,150
6	1,203	2,149
7	1,206	2,148
8	1,204	2,148
9	1,202	2,148
10	1,201	2,142
11	1,198	2,143
12	1,201	2,142
13	1,205	2,141
14	1,198	2,140
15	1,201	2,137
16	1,205	2,142
17	1,205	2,142
18	1,201	2,144
19	1,203	2,143
20	1,200	2,143
21	1,200	2,141
22	1,198	2,144
23	1,196	2,140
24	1,196	2,141
25	1,200	2,136
26	1,196	2,139
27	1,201	2,135
28	1,194	2,140
29	1,194	2,141
30	1,197	2,144
31	1,197	2,145
32	1,197	2,139
33	1,199	2,144
34	1,202	2,144
35	1,198	2,145
36	1,203	2,145
37	1,203	2,142
38	1,206	2,143
39	1,197	2,141
40	1,201	2,145
41	1,198	2,144
42	1,195	2,145
43	1,199	2,144
44	1,196	2,141
45	1,202	2,143
46	1,194	2,136
47	1,194	2,141
48	1,207	2,138
49	1,196	2,142
50	1,204	2,138
Average	1,20	2,14
Cmk	4,37	7,94

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 1 mm^2

Nominal Cr. Height:	1,35	2,75	mm
+/-	0,05	0,1	mm


Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1,353	2,751
2	1,352	2,753
3	1,352	2,757
4	1,353	2,752
5	1,352	2,748
6	1,350	2,749
7	1,352	2,754
8	1,349	2,751
9	1,353	2,751
10	1,349	2,748
11	1,350	2,748
12	1,351	2,750
13	1,349	2,746
14	1,349	2,748
15	1,353	2,745
16	1,351	2,749
17	1,349	2,747
18	1,349	2,751
19	1,349	2,747
20	1,349	2,746
21	1,349	2,750
22	1,348	2,748
23	1,348	2,751
24	1,346	2,746
25	1,346	2,749
26	1,340	2,740
27	1,348	2,742
28	1,349	2,755
29	1,349	2,746
30	1,344	2,752
31	1,346	2,751
32	1,343	2,747
33	1,348	2,742
34	1,344	2,753
35	1,344	2,748
36	1,346	2,757
37	1,342	2,754
38	1,343	2,747
39	1,348	2,750
40	1,349	2,750
41	1,349	2,748
42	1,346	2,754
43	1,346	2,745
44	1,344	2,749
45	1,345	2,747
46	1,344	2,749
47	1,349	2,757
48	1,342	2,749
49	1,351	2,743
50	1,344	2,755
Average	1,35	2,75
Cmk	4,87	8,62

Acceptance criteria: Cmk>= 2.0

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1500	TERMINAL No. 端子品番	7116-4157
Common PN 共通品番	-	-	-
	-	-	



No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称	No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称
1	7116-4157XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	17	48A47013	001	FEEDING CLAW 送り爪
2	7116-4157XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	18	48A19100	005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
3	7116-4157XA		ANVIL ｱﾝﾋﾞﾙ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
4	7116-4157XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
5	7116-4157XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	21	48A47032	001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
6	7116-4157XYB		BASE ﾍﾞｰｽ	22	48A19017	003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
7	7116-4157XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	23	48A19023	002	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
8	48A47016	001	WIRE HOLDER 電線押さえ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾟﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ		7116-4157XKP		BRACKET ﾌﾞﾗｹｯﾄ
12	48A47024	002①	SHEARBLADE ｼｬｰﾌﾟﾚｰﾄﾞ	27			
13	48A47025	002①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾟﾚｰﾄﾞ	<OPTION ｵﾌﾟｼｮﾝ>			
14	48A19007	024	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	13	48A47025	101	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾟﾚｰﾄﾞ
15	48A19019	020	BUSH ﾌﾞｯｼｭ	14	48A47042	001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)
16	48A47014	001	FEEDING CAM 送りｶﾑ				

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検	APPRICATION POST 申請部署	
					HIB	
					DESIGNED DATE 設計日	
					2007/6/20	
	2013/06/14	PTC			APPROVED 承認	DESIGNED 設計
①	2007/7/9	001→002,021→025	QX7	T.Suzuki	K.Hiraguchi	T.Suzuki
					2007/6/20	2007/6/20

ISSUED '10.05.31 YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.

ISSUED 発行