APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
S3071

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 70041286 SEQUENCE Nº 9

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7004-1286-02	*	**MSES868-XA**	**YSD-3500095361**	*







Anvil		
7004-1286MBA		(A)
CW (c)	*CW (i)*	




Wire Crimper		
7004-1286MBW		(A)
CW		

Insulation Crimper	
NA	
CW	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable

	The two sides of the insulation grips are in the correct position.	NA
	Not found any Bell Mouth in the insulation area.	NA
	The lance height and shape are not deformed.	NA
	Not found any burr in the cutting carrier.	NA
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O

	The Bell Mouth is within the spec.**(*)**	NA
	The dimension of the cutting carrier is within the spec.**(*)**	NA
	Bend up and Bend down are within the criteria**(*)**	O
	The exposed conductor is within the spec.(*)	O
	The terminal is not bent sideway, look-king from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES



3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	3,4	3,43	3,97
	+/-0,1		

	NOMINAL	AVERAGE	Cmk
mm	NA		
	+/-NA		

REMARKS:

Aplicable wire range-16.0mm²~16.0mm².

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 5061
Date: 2018-dez-12	Date: 2018-dez-06	Date: 2018-dez-06

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
S3071

LOWER WIRE KIND & SIZE

Wire kind: KABFLYW

Wire size: 25 mm²

Nominal Cr. Height:	3,4	NA	mm
+/-	0,1	NA	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	3,423	
2	3,427	
3	3,424	
4	3,421	
5	3,427	
6	3,432	
7	3,431	
8	3,424	
9	3,426	
10	3,430	
11	3,429	
12	3,422	
13	3,429	
14	3,420	
15	3,424	
16	3,421	
17	3,429	
18	3,424	
19	3,417	
20	3,413	
21	3,413	
22	3,421	
23	3,426	
24	3,434	
25	3,426	
26	3,425	
27	3,429	
28	3,425	
29	3,437	
30	3,427	
31	3,425	
32	3,433	
33	3,422	
34	3,437	
35	3,439	
36	3,443	
37	3,433	
38	3,425	
39	3,436	
40	3,426	
41	3,433	
42	3,423	
43	3,421	
44	3,432	
45	3,431	
46	3,425	
47	3,426	
48	3,422	
49	3,433	
50	3,429	
Average	3,43	
Cmk	3,97	

UPPER WIRE KIND & SIZE

Wire kind: NA + NA

Wire size: NA + NA mm²

Nominal Cr. Height:	NA	NA	mm
+/-	NA	NA	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
Average		
Cmk		

Acceptance criteria: Cmk>= 2,0

END