APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1710E172

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 71164156 SEQUENCE Nº 9

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7116-4156-02	*	**04 SIDE FEED**	**YSD-XVK81**	*







Anvil		
7116-4156XA		(A)
CW (c) 2,52	*CW (i)* 3,60	





Wire Crimper		
7116-4156XW		(A)
CW 2,50		

Insulation Crimper		
7116-4156XI		(A)
CW 3,60		

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	O
	Not found any Bell Mouth in the insulation area.	O
	The lance height and shape are not deformed.	O
	Not found any burr in the cutting carrier.	O
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O


	The Bell Mouth is within the spec.**(*)**	O
	The dimension of the cutting carrier is within the spec.**(*)**	O
	Bend up is within the criteria**(*)**	O
	Bend down is within the criteria**(*)**	O
	The terminal is not bent sideway, looking from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1,47	1,47	4,78
	+/-0,05		



	NOMINAL	AVERAGE	Cmk
mm	1,76	1,76	3,72
	+/-0,05		

REMARKS:

Aplicable Wire Range 1.50mm²~2.50mm²
Wire 1.50mm² C/W(I)-3.58mm
Wire 2.50mm² C/W(I)-3.62mm

EVALUATION DECISION

SUITABLE [X]
NOT SUITABLE [ ]
FOR USE IN PRODUCTION

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 678
		
Date: 2017-dez-13	Date: 2017-dez-11	Date: 2017-dez-11

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1710E172

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 1,5 mm^2

Nominal Cr. Height:	1,47	2,8	mm
+/-	0,05	0,1	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1,475	2,807
2	1,469	2,799
3	1,472	2,805
4	1,475	2,808
5	1,481	2,814
6	1,475	2,808
7	1,473	2,800
8	1,472	2,799
9	1,479	2,792
10	1,476	2,797
11	1,473	2,802
12	1,470	2,808
13	1,475	2,802
14	1,475	2,799
15	1,473	2,801
16	1,472	2,808
17	1,469	2,811
18	1,472	2,805
19	1,477	2,798
20	1,482	2,803
21	1,476	2,807
22	1,472	2,807
23	1,471	2,801
24	1,469	2,798
25	1,471	2,801
26	1,474	2,805
27	1,471	2,810
28	1,473	2,810
29	1,477	2,799
30	1,474	2,799
31	1,473	2,803
32	1,474	2,807
33	1,476	2,797
34	1,478	2,794
35	1,473	2,803
36	1,476	2,806
37	1,478	2,810
38	1,480	2,809
39	1,476	2,800
40	1,469	2,798
41	1,468	2,807
42	1,473	2,812
43	1,474	2,800
44	1,472	2,798
45	1,470	2,796
46	1,473	2,793
47	1,477	2,801
48	1,475	2,810
49	1,471	2,800
50	1,470	2,797
Average	1,47	2,80
Cmk	4,78	6,08

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 2,5 mm^2

Nominal Cr. Height:	1,76	3,2	mm
+/-	0,05	0,1	mm


Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1,761	3,207
2	1,769	3,197
3	1,765	3,205
4	1,758	3,213
5	1,762	3,197
6	1,765	3,210
7	1,767	3,209
8	1,761	3,218
9	1,759	3,221
10	1,763	3,212
11	1,771	3,206
12	1,767	3,211
13	1,761	3,206
14	1,760	3,197
15	1,760	3,203
16	1,766	3,203
17	1,763	3,195
18	1,763	3,196
19	1,760	3,205
20	1,764	3,208
21	1,767	3,210
22	1,767	3,203
23	1,761	3,202
24	1,760	3,206
25	1,758	3,210
26	1,756	3,208
27	1,767	3,201
28	1,766	3,201
29	1,764	3,207
30	1,763	3,210
31	1,770	3,197
32	1,774	3,203
33	1,760	3,200
34	1,758	3,214
35	1,757	3,203
36	1,755	3,196
37	1,760	3,205
38	1,765	3,207
39	1,758	3,203
40	1,757	3,202
41	1,761	3,208
42	1,765	3,213
43	1,768	3,200
44	1,769	3,204
45	1,761	3,202
46	1,761	3,200
47	1,763	3,198
48	1,767	3,205
49	1,758	3,206
50	1,764	3,202
Average	1,76	3,20
Cmk	3,72	5,53

Acceptance criteria: Cmk>= 2

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-1499	TERMINAL No. 端子品番	7116-4156



No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称	No.	PARTS No. 部品番号	DRW. No. 図番	PARTS NAME 部品名称
1	7116-4156XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	16	48A47014	005②	FEEDING CAM 送りｶﾑ
2	7116-4156XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	17	48A47013		FEEDING CLAW 送り爪
3	7116-4156XA		ANVIL ｱﾝﾋﾞﾙ	18	48A19100	-005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
4	7116-4156XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	19	48A19047	001	TERMINAL SCRAPER 端子掻き落とし
5	7116-4156XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
6	7116-4156XYB		BASE ﾍﾞｰｽ	21	48A47032	-001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
7	7116-4156XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	22	48A19017	-003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
8	48A47016	001	WIRE HOLDER 電線押さえ	23	48A19023	001	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
10	48A47020	A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾟﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
11	48A47022	001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
12	48A47024	002 ①	SHEARBLADE ｼｬｰﾌﾟﾚｰﾄﾞ		7116-4156XKP		BRACKET ﾌﾞﾗｹｯﾄ
13	48A47025	002/101 ①	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾟﾚｰﾄﾞ	27	-		~~STABILIZER CRIMPER~~ ~~ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
14	48A19007	023①③④⑤	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	〈オプション OPTION〉			
15	48A19019	019	BUSH ﾌﾞｯｼｭ	14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検
⑤	2009/9/22	022→023	09J-016	C,Abe
④	2009/9/1	023→022	09I-015	C,Abe
③	2008/12/11	024→023	QX7	C,Abe
②	2008/6/23	001→005	QX7	C,Sato
①	2007/6/27	001→002、022→024	QX7	T,Suzuki

APPRICATION POST 申請部署	
接続技術部	
DESIGNED DATE 設計日	
2007/3/5	
APPROVED 承認	DESIGNED 設計
K,Hiraguchi	T,Suzuki
2007/3/5	2007/3/5

ISSUED 発行

ISSUE
2013 / 09 / 16
YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.