APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
1801E024

TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 72115181 SEQUENCE Nº 1

Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7211-5181-02	*	**04 SIDE FEED**	**YWTC-4510728895**	*







Anvil		
7211-5181XA		(N)
CW (c) 1,42	*CW (i)* 2,03	




Wire Crimper	
7211-5181XW	(N)
CW 1,40	

Insulation Crimper	
7211-5181XI	(N)
CW 2,03	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable


	The two sides of the insulation grips are in the correct position.	O
	Not found any Bell Mouth in the insulation area.	O
	The lance height and shape are not deformed.	O
	Not found any burr in the cutting carrier.	O
	Not found any crack in the terminal.	O
	The wire barrel is free from major burrs.	O

	The Bell Mouth is within the spec.**(*)**	O
	The dimension of the cutting carrier is within the spec.**(*)**	O
	Bend up is within the criteria**(*)**	O
	Bend down is within the criteria**(*)**	O
	The terminal is not bent sideway, looking from the top**(*)**	O
	The body of the terminal is not twisted**(*)**	O

(*) - Specified on Crimping Std.

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES





3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	0,95	0,96	4,00
	+/-0,05		



	NOMINAL	AVERAGE	Cmk
mm	1,05	1,06	4,70
	+/-0,05		

REMARKS:

Aplicable wire range-0.50~0.75mm2
Size 0.50mm2 C/W(I)-2.01mm
Size 0.75mm2 C/W(I)-2.05mm

EVALUATION DECISION

SUITABLE [X] FOR USE IN PRODUCTION
NOT SUITABLE [ ]

APPROVED (Section Chief) 3485	CHECKED (Operator) 44	PREPARED (Operator) nº 2624
		
Date: 2018-jan-29	Date: 2018-jan-29	Date: 2018-jan-29

PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
1801E024

LOWER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 0,5 mm^2

Nominal Cr. Height:	0,95	1,7	mm
+/-	0,05	0,1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	0,958	1,708
2	0,960	1,712
3	0,963	1,716
4	0,966	1,712
5	0,962	1,708
6	0,959	1,704
7	0,957	1,706
8	0,957	1,709
9	0,959	1,714
10	0,962	1,710
11	0,960	1,705
12	0,958	1,702
13	0,956	1,705
14	0,957	1,707
15	0,960	1,712
16	0,963	1,709
17	0,966	1,707
18	0,964	1,703
19	0,961	1,705
20	0,960	1,708
21	0,957	1,711
22	0,957	1,713
23	0,958	1,709
24	0,960	1,707
25	0,963	1,703
26	0,967	1,699
27	0,965	1,704
28	0,962	1,705
29	0,960	1,709
30	0,958	1,708
31	0,956	1,705
32	0,958	1,700
33	0,961	1,703
34	0,966	1,705
35	0,962	1,707
36	0,959	1,710
37	0,956	1,708
38	0,954	1,705
39	0,956	1,702
40	0,957	1,699
41	0,961	1,702
42	0,964	1,705
43	0,961	1,707
44	0,958	1,710
45	0,955	1,710
46	0,953	1,707
47	0,955	1,703
48	0,956	1,706
49	0,961	1,707
50	0,958	1,703
Average	0,96	1,71
Cmk	4,00	8,27

UPPER WIRE KIND & SIZE

Wire kind: FLRYA

Total wire size: 0,75 mm^2

Nominal Cr. Height:	1,05	2,05	mm
+/-	0,05	0,1	mm

Sample number	Crimp height WIRE (mm)	Crimp height INSULATION (mm)
1	1,056	2,055
2	1,058	2,057
3	1,057	2,059
4	1,055	2,054
5	1,052	2,049
6	1,054	2,053
7	1,055	2,056
8	1,059	2,058
9	1,057	2,056
10	1,054	2,052
11	1,050	2,049
12	1,052	2,053
13	1,055	2,057
14	1,058	2,060
15	1,061	2,060
16	1,064	2,056
17	1,059	2,053
18	1,057	2,049
19	1,054	2,052
20	1,056	2,054
21	1,061	2,057
22	1,063	2,060
23	1,060	2,056
24	1,058	2,053
25	1,056	2,049
26	1,058	2,053
27	1,058	2,055
28	1,061	2,058
29	1,062	2,061
30	1,060	2,059
31	1,058	2,056
32	1,056	2,052
33	1,058	2,056
34	1,060	2,058
35	1,063	2,062
36	1,060	2,060
37	1,057	2,057
38	1,055	2,057
39	1,057	2,064
40	1,059	2,067
41	1,061	2,060
42	1,059	2,057
43	1,056	2,056
44	1,054	2,063
45	1,056	2,065
46	1,058	2,058
47	1,059	2,054
48	1,062	2,060
49	1,060	2,064
50	1,057	2,059
Average	1,06	2,06
Cmk	4,70	7,42


Acceptance criteria: Cmk>= 2

END

04 APPLICATOR CONSUMABLE PARTS LIST ／ 04 ｱﾌﾟﾘｹｰﾀｰ 消耗部品表

PRODUCT No. 製品番号	C0100-5632	TERMINAL No. 端子品番	7211-5181

共通品番	–	–	–	–
	–	–		



No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称	No,	PARTS No, 部品番号	DRW No, 図番	PARTS NAME 部品名称
1	7211-5181XW		WIRE CRIMPER ﾜｲﾔｰｸﾘﾝﾊﾟｰ	17	48A47013	-001	FEEDING CLAW 送り爪
2	7211-5181XI		INSULATION CRIMPER ｲﾝｼｭﾚｰｼｮﾝｸﾘﾝﾊﾟｰ	18	48A19100	-005	WIRE STOPPER Assy 電線ｽﾄｯﾊﾟｰ ｱｯｼｰ
3	7211-5181XA		ANVIL ｱﾝﾋﾞﾙ	19	48A19047	-002	TERMINAL SCRAPER 端子掻き落とし
4	7211-5181XJE		ANVIL HOLDER ｱﾝﾋﾞﾙﾎﾙﾀﾞｰ	20	48A47031		RETURN SPRING 戻しｽﾌﾟﾘﾝｸﾞ
5	7211-5181XYY		SUPPORTING STOPPER ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰ	21	48A47032	-001	SUPPORTING STOPPER SPRING ｻﾎﾟｰﾃｨﾝｸﾞｽﾄｯﾊﾟｰｽﾌﾟﾘﾝｸﾞ
6	7211-5181XYB		BASE ﾍﾞｰｽ	22	48A19017	-003	FEEDING CLAW SPRING 送り爪ｽﾌﾟﾘﾝｸﾞ
7	7211-5181XYH		TERMINAL GUIDE PLATE B ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄB	23	48A19023	-002	WIRE HOLDER SPRING 電線押さえｽﾌﾟﾘﾝｸﾞ
8	48A47016	-001	WIRE HOLDER 電線押さえ	24	48A19074		TERMINAL HOLDER SPRING ﾀｰﾐﾅﾙ押さえｽﾌﾟﾘﾝｸﾞ
9	48A47017	-002	CUTTING PUNCH & WIRE HOLDER 切断ﾎﾟﾝﾁ兼電線押さえﾎﾙﾀﾞｰ	25	48A19050		SHEARBLADE SPRING ｼｬｰﾌﾟﾚｰﾄﾞｽﾌﾟﾘﾝｸﾞ
10	48A47020	-A04	TERMINAL GUIDE PLATE A ﾀｰﾐﾅﾙｶﾞｲﾄﾞﾌﾟﾚｰﾄA	26	48A19999		TERMINAL OIL UNIT ﾀｰﾐﾅﾙ塗油ﾕﾆｯﾄ
11	48A47022	-001	TERMINAL HOLDER ﾀｰﾐﾅﾙ押さえ		7211-5181XKP		BRACKET ﾌﾞﾗｹｯﾄ
12	48A47024	-001	SHEARBLADE ｼｬｰﾌﾟﾚｰﾄﾞ	27	~~7211-5181XQ~~		~~STABILIZER CRIMPER ｽﾀﾋﾞﾗｲｻﾞｰｸﾘﾝﾊﾟｰ~~
13	48A47025	-001	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾟﾚｰﾄﾞ	〈OPTION ｵﾌﾟｼｮﾝ〉			
14	48A19007	-026	INSULATION ADJUSTING PIECE ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ	13	48A47025	-101	OUTER SHEARBLADE ｱｳﾀｰｼｬｰﾌﾟﾚｰﾄﾞ
15	48A19019	-016	BUSH ﾌﾞｯｼｭ	14	48A47042	-001	INSULATION ADJUSTING PIECE(MECAL) ｲﾝｼｭﾚｰｼｮﾝ調整ｺﾏ(ﾒｶﾙ)
16	48A47014	-003	FEEDING CAM 送りｶﾑ				

MARK 記号	DATE 日付	REVISION RECORD 改訂記録	No. 番号	CHECKED 点検

APPRICATION POST 申請部署	
YUL	
DESIGNED DATE 設計日	
15-02-2013	
APPROVED 承認	DESIGNED 設計
T,Maki	C.Almeida
15-02-2013	15-02-2013

ISSUED 発行