PTC - Avenida D. Manuel I
Zona Industrial de Ovar
3880-109 OVAR

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

(Spec. YEL-RP-02-0004)

Applicator Serial Nº
912B128






TOOLS MANAGEMENT INFORMATION ---> TOOL Nº 70171181 SEQUENCE Nº 9



Terminal Nº	Rubber Seal	Applicator Type	Purchasing Order Nº	Project / Model
7017-1181-02	*	**ASE**	**YSD-3500159601**	*

Anvil		Wire Crimper		Insulation Crimper	
7017-1181SA	(N)	7017-1181SWW	(2)	NA	
CW (c) 3.12	*CW (i)*	*CW* 3.10		*CW*	

1 - VISUAL CHECK ITEMS

O - ok **X** - ng **NA** - not aplicable

	The two sides of the insulation grips are in the correct position.	**NA**
	Not found any Bell Mouth in the insulation area.	**NA**
	The lance height and shape are not deformed.	**NA**
	Not found any burr in the cutting carrier.	**O**
	Not found any crack in the terminal.	**O**
	The wire barrel is free from major burrs.	**O**

	The Bell Mouth is within the spec.**(*)**	**O**
	The dimension of the cutting carrier is within the spec.**(*)**	**O**
	Bend up and Bend down are within the criteria**(*)**	**NA**
	The exposed conductor is within the spec.(*)	**O**
	The terminal is not bent sideway, look-king from the top**(*)**	**NA**
	The body of the terminal is not twisted**(*)**	**NA**

LOWER WIRE KIND & SIZE	**UPPER** WIRE KIND & SIZE

2 - MICRO CUT SAMPLES



3 - CRIMPING HEIGHT STABILITY

	NOMINAL	AVERAGE	Cmk
mm	1.6	1.60	3.65
	+/-0.05		

	NOMINAL	AVERAGE	Cmk
mm	NA		
	+/-NA		

REMARKS:

Aplicable wire range 0.90mm²~1.40mm².
The wire size 0.30mm²+0.85mm² is not recommended due to crimping microcut conditions.

EVALUATION DECISION

SUITABLE [X] FOR USE IN PRODUCTION
NOT SUITABLE [ ]

APPROVED (Section Chief) 3485	CHECKED (Operator) 5061	PREPARED (Operator) nº 18597
	Luis Dias	Rui Domingues
Date: 2020/May/18	Date: 2020/May/14	Date: 2020/May/14

YAZAKI
PORTO TECHNICAL CENTRE

APPLICATOR VALIDATION REPORT

Applicator Serial Nº
912B128

LOWER WIRE KIND & SIZE

Wire kind:	CAVS	+	CAVS	
Wire size:	0.5	+	0.85	mm^2
Nominal Cr. Height:	1.6		NA	mm
+/-	0.05		NA	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1	1.600	
2	1.600	
3	1.601	
4	1.586	
5	1.602	
6	1.600	
7	1.600	
8	1.599	
9	1.597	
10	1.601	
11	1.599	
12	1.587	
13	1.607	
14	1.603	
15	1.606	
16	1.599	
17	1.605	
18	1.608	
19	1.598	
20	1.604	
21	1.599	
22	1.598	
23	1.601	
24	1.603	
25	1.598	
26	1.604	
27	1.597	
28	1.603	
29	1.598	
30	1.605	
31	1.605	
32	1.605	
33	1.598	
34	1.598	
35	1.602	
36	1.597	
37	1.601	
38	1.601	
39	1.594	
40	1.599	
41	1.603	
42	1.587	
43	1.603	
44	1.599	
45	1.601	
46	1.604	
47	1.602	
48	1.602	
49	1.604	
50	1.603	
Average	1.60	
Cmk	3.65	

UPPER WIRE KIND & SIZE

Wire kind:	NA	+	NA	
Wire size:	NA	+	NA	mm^2
Nominal Cr. Height:	NA		NA	mm
+/-	NA		NA	mm

Sample number	Crimp height **WIRE** (mm)	Crimp height **INSULATION** (mm)
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
Average		
Cmk		

Acceptance criteria: Cmk>= 2.0

END

製品名称 Product name	KAM JOINT APPLICATOR	製品品番 Terminal No.	7017-1181
製品番号 Product No.	C0345－000		

共通品番 Common No.			
	—	—	—
	—	—	—
	—	—	—

No.	部品番号 Part No.	図番 Drawing No.	部品名称 Part name	数量 QTY	材料 Material	備考 Notes
			＜Spesific Part 専用部品＞			
1	70171181SA		アンビル ANVIL	1	S7	
2	70171181SWW		ﾜｲﾔｰｸﾘﾝﾊﾟｰ WIRE CRIMPER	1	S7	
3	70171180SYS		払い落としBI SCRAPPER BI	1	SS400	
4	70171180ZS ①		シャーブレード SHAER BLADE	1	SKD11	
5	70171180SYB		ベース BASE	1	SKS3	
6	70171180SYF		送り爪 FEEDING CLAW	1	SK	
7	70171180SYJ		ターミナル押さえ TERMINAL HOLDER	1	SK5	
8	~~70171181SYK~~		~~カラー COLOR~~	~~1~~	~~S45C~~	
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						

					申請部署 Requested		ISSUE 2020/03/27 YAZAKI PARTS CO.,LTD. HIB MACHINE PRODUCT DEP.
					作成日 Date		
					2000/2/3		
					承認 Approved	作成 Designed	
①	2006/8/25	70171180SS→ZS	QX7	鈴木		増田	発行 ISSUE
符号 Let	年月日 Date	記事 Revision recode	No.	点検 Revised			