1. For the time axis (for all figures), please don't use the GPS time. Use the time from the start of the trajectory (this is your zero, initial time). You can subtract the GPS time in each trip instant from the initial GPS time at the start of the trajectory. This way your time axis will make much sense. It will be better and make much sense to present it in minutes (or hours).

2. In presenting the latitude and the longitude error graphs, it may not look professional to present in as angles (either degrees or radians). You will not be able to recognize how significant the errors are. You got to covert these errors into North position error in meters (corresponding to the latitude error) and East position error in meters (corresponding to the longitude error).

Delta_Position_North = Delta_Latitude * (R + h)
Delta_Position_East = Delta_Longitude * (R + h) * cos(Latitude)

Note all angles in the above two equations shall be in radians.

Please make sure to adopt this way of representing the latitude and the longitude errors in project 2.

3. It is also nice to present errors (with respect to the available reference solution as the ground truth) in terms of Maximum error and RMS error. For position errors, please use Max and RMS errors in addition to the error as percentage of the distance travelled. For example, if you calculate the actual error at certain time instant as 1 meter and the distance travelled along this direction (North or East) is 100 meters, this means you have 1% error.

4. For the calculation of the distance travelled, you can use very similar equations to those mentioned in point #2 above. The only difference is instead of Delta_Latitude, you should use Latitude(i) - Latitude(0), and instead of Delta_Longitude, you should use Longitude(i) - Longitude(0); where i is the time instant where you calculate the position and 0 is the initial time instant.