Static Analysis Report:

File Identification

The file type, determined by signature, not extension, was PE32, which is a 32-bit Portable Executable (PE) file format used for executables [figure 1]. The true extension matched the claimed extension, with both being a .exe extension. However, I couldn't rely on this alone- I needed to verify that what the file presented itself as and what it was coincided. I used VirusTotal [figure 2] and Detect It Easy (DiE) [figure 1] to confirm this. The file size was 305.50 KB [figure 1]. The sample was supplied inside a password-protected ZIP file and extracted. VirusTotal associated its hash with the file name meccha-camouflageV3.exe [figure 3].

Hashing & Reputation

I hashed the file using SHA-256 [figure 4] and ran it on VirusTotal for reputation analysis. The analysis showed that 39/46 security vendors had flagged the file as malicious [figure 5]. The sample received the popular threat label trojan.msil/xworm. The associated family labels returned were msil, xworm, and asyncrat. The reported threat categories were trojan and adware [figure 5].

PE Header & Metadata Analysis

Operating system	Windows
Architecture	1386/32-bit
Subsystem	GUI
Linker	Microsoft linker (11.0)
Compiler	VB.NET
Language	VB.NET
Library	NET Framework (CLR 4.0.30319)
Timestamp UTC [figure 8]	2026-07-01, 11:49:05
Version info [figure 7]	Internal name & original filename= meccha-camouflageV3.exe

[figure 6]

Section & Packing Analysis

The section table overview can be found in [figure 8]. The entropy values, according to the graph [figure 9] were mostly in the 5–6 range, with some regions reaching 7–8. The higher values signalled signs of hacking and obfuscation. DiE assessed the sample as not packed with 78% confidence. Overall, the sample was assessed as not packed, but possibly obfuscated. The findings on DiE "(Heur) Protection: Obfuscation [Modified managed EP + Bad namings] and (Heur) Protection: Anti analysis [Anti-debug + Anti-SandBoxie + Anti-VM] [figure 6]" indicated that the sample appeared to have been deliberately modified to make analysis more difficult and may have contained techniques that were designed to avoid detection.

Import Table Analysis

I found no suspicious API imports from the import table. The observed imports: mscoree.dll and _CorExeMain, are associated with .NET execution[figure 10]. This just showed that the file was a .NET programmme, which is used to start the program.

Static Verdict

Based on the static analysis, the sample is likely malicious and appears to be a trojan. VirusTotal's family labels of the xworm and asyncrat suggest that the sample may have remote access capabilities and malicious capabilities. The sample also showed signs of obfuscation and anti-analysis techniques, which may have been used to make its behaviour more difficult to examine or detect [figure 1]. I didn't observe any API imports, but the file may execute differently with dynamic analysis.

Screenshots:

Figure 1




Figure 2




Figure 3




Figure 4



General
Emblems
Highlight
Permissions
Checksums
Hash Function
Digest
MD5
179e5c88bbd34e45830e7ee3610d5216
MD6-224
MD6-256
MD6-384
MD6-512
SHA1
SHA224
SHA256
0aac658075b7d9e81419d0beaa3db796569bc14fd57
SHA384
Check:
HMAC Key:
Hash
Help
Close

Figure 5



39
DETECTION
DETAILS
RELATIONS
BEHAVIOR
COMMUNITY

Figure 6




Figure 7




Figure 8




Figure 9




Figure 10

