
TEXT RETRIEVAL AND SEARCH ENGINES

The basic concepts, principles, and the major techniques in text retrieval,
which is the underlying science of search engines.

Course author:

ChengXiang Zhai



*University of Illinois at Urbana-Champaign
&
Coursera*

2015


Contents

1	Natural Language Content Analysis	2
1.1	An Example of NLP	2
1.2	The State of the Art	2
1.3	Recommended reading	2
2	Text Access	3
2.1	Two Modes of Text Access: Pull vs. Push	3
2.2	Pull Mode: Querying vs. Browsing	3
2.3	Recommended reading	3
3	Text Retrieval Problem	4
3.1	What Is Text Retrieval?	4
3.2	Formal Formulation of TR	4
3.3	How to Compute $R'(q)$	4
3.4	Theoretical Justification for Ranking	5
3.5	Recommended reading	5
4	Overview of Text Retrieval Methods	5
4.1	How to Design a Ranking Function	5
4.2	Retrieval Models	5
4.3	Common Ideas in State of the Art Retrieval Models	6
4.4	Which Model Works the Best?	6
4.5	Recommended reading	6
5	Vector Space Retrieval Model: Basic Idea	7
5.1	Vector Space Model (VSM): Illustration	7
5.2	VSM Is a Framework	7
5.3	What VSM Doesn't Say	7
6	Vector Space Retrieval Model: Simplest Instantiation	8
6.1	What VSM Doesn't Say	8
6.2	Simplest VSM = Bit-Vector + Dot-Product + BOW	8
7	Vector Space Retrieval Model: Improved Instantiation	9
7.1	Improved VSM with Term Frequency (TF) Weighting	9
7.2	IDF Weighting: Penalizing Popular Terms	9
7.3	Adding Inverse Document Frequency (IDF)	9
8	Vector Space Retrieval Model: TF Transformation	10
8.1	Ranking Function with TF-IDF Weighting	10
8.2	TF Transformation: BM25 Transformation	10
8.3	Summary	10
9	Vector Space Retrieval Model: Doc Length Normalization	11
9.1	Pivoted Length Normalization	11
9.2	State of the Art VSM Ranking Functions	11
9.3	Further Improvement of VSM?	11
9.4	Further Improvement of BM25	12
9.5	Summary of Vector Space Model	12
9.6	Recommended reading	13


1 Natural Language Content Analysis

NLP = Natural Language Processing

1.1 An Example of NLP



1.2 The State of the Art




1.3 Recommended reading

- Chris Manning and Hinrich Schütze, «Foundations of Statistical Natural Language Processing», MIT Press. Cambridge, MA: May 1999.

2 Text Access

2.1 Two Modes of Text Access: Pull vs. Push

- Pull Mode (search engines) – Users take initiative
 - Ad hoc information need
- Push Mode (recommender systems)
 - Systems take initiative
 - Stable information need or system has good knowledge about a user's need



2.2 Pull Mode: Querying vs. Browsing

- Querying
 - User enters a (keyword) query
 - System returns relevant documents
 - Works well when the user knows what keywords to use
- Browsing
 - User navigates into relevant information by following a path enabled by the structures on the documents
 - Works well when the user wants to explore information, doesn't know what keywords to use, or can't conveniently enter a query

2.3 Recommended reading

- N. J. Belkin and W. B. Croft. 1992. «Information filtering and information retrieval: two sides of the same coin?» Commun. ACM 35, 12 (Dec. 1992), 29-38.

3 Text Retrieval Problem

3.1 What Is Text Retrieval?

TR = Text Retrieval¹

- Collection of text documents exists
- User gives a query to express the information need
- Search engine system returns relevant documents to users
- Often called “information retrieval” (IR), but IR is actually much broader
- Known as «search technology» in industry

TR is an empirically defined problem:

- Can't mathematically prove one method is better than another
- Must rely on empirical evaluation involving users!

3.2 Formal Formulation of TR

- **Vocabulary:** $V = \{w_1, w_2, \dots, w_N\}$ of language
- **Query:** $q = q_1, \dots, q_m$, where $q_i \in V$
- **Document:** $d_i = d_{i1}, \dots, d_{im_i}$, where $d_{ij} \in V$
- **Collection:** $C = \{d_1, \dots, d_M\}$
- **Set of relevant documents:** $R(q) \subseteq C$
 - Generally unknown and user-dependent
 - Query is a «hint» on which doc is in $R(q)$
- **Task:** compute $R'(q)$, an approximation of $R(q)$

3.3 How to Compute $R'(q)$

- Strategy 1: Document selection
 - $R'(q) = \{d \in C \mid f(d, q) = 1\}$, where $f(d, q) \in \{0, 1\}$ is an indicator function or binary classifier
 - System must decide if a doc is relevant or not (absolute relevance)
- Strategy 2 (generally preferred): Document ranking
 - $R'(q) = \{d \in C \mid f(d, q) > \theta\}$, where $f(d, q) \in \mathfrak{R}$ is a relevance measure function; θ is a cutoff determined by the user
 - System only needs to decide if one doc is more likely relevant than another (relative relevance)

¹Retrieval - поиск

3.4 Theoretical Justification for Ranking

Probability Ranking Principle [Robertson 77]: Returning a ranked list of documents in descending order of probability that a document is relevant to the query is the optimal strategy under the following two assumptions:

- The utility of a document (to a user) is independent of the utility of any other document
- A user would browse the results sequentially

3.5 Recommended reading

- S.E. Robertson, «The probability ranking principle in IR». *Journal of Documentation* 33, 294-304, 1977
- C. J. van Rijsbergen, «**Information Retrieval**», **2nd Edition**, Butterworth-Heinemann, Newton, MA, USA, 1979

4 Overview of Text Retrieval Methods


4.1 How to Design a Ranking Function

- **Query:** $q = q_1, \dots, q_m$, where $q_i \in V$
- **Document:** $d = d_1, \dots, d_n$, where $d_i \in V$
- **Ranking function:** $f(q, d) \in \mathfrak{R}$
- **Key challenge:** how to measure the likelihood that document d is relevant to query q
- **Retrieval model:** formalization of relevance (give a computational definition of relevance)

4.2 Retrieval Models

- **Similarity-based models:** $f(q, d) = \text{similarity}(q, d)$
 - Vector space model
- **Probabilistic models:** $f(d, q) = p(R = 1 \mid d, q)$, where $R \in \{0, 1\}$
 - Classic probabilistic model
 - Language model
 - Divergence-from-randomness model
- **Probabilistic inference model:** $f(q, d) = p(d \rightarrow q)$
- **Axiomatic model:** $f(q, d)$ must satisfy a set of constraints

4.3 Common Ideas in State of the Art Retrieval Models



State of the art ranking functions tend to rely on:

- Bag of words representation
- Term Frequency (TF) and Document Frequency (DF) of words
- Document length

4.4 Which Model Works the Best?

When optimized, the following models tend to perform equally well [Fang et al. 11]:

- **Pivoted length normalization – BM25**
- Query likelihood
- PL2


4.5 Recommended reading

- Hui Fang, Tao Tao, and Chengxiang Zhai. 2011. «Diagnostic Evaluation of Information Retrieval Models». ACM Trans. Inf. Syst. 29, 2, Article 7 (April 2011)
- ChengXiang Zhai, «Statistical Language Models for Information Retrieval», Morgan & Claypool Publishers, 2008. (Chapter 2)

5 Vector Space Retrieval Model: Basic Idea

VSM - Vector Space Model

5.1 Vector Space Model (VSM): Illustration



5.2 VSM Is a Framework


- Represent a doc/query by a term vector
 - **Term:** basic concept, e.g., word or phrase
 - Each term defines one dimension
 - N terms define an **N-dimensional space**
 - **Query vector:** $q = (x_1, \dots, x_N)$, $x_i \in \Re$ is query term weight
 - **Doc vector:** $d = (y_1, \dots, y_N)$, $y_j \in \Re$ is doc term weight
- $relevance(q, d) \propto similarity(q, d) = f(q, d)$

5.3 What VSM Doesn't Say

- How to define/select the “basic concept” – Concepts are assumed to be orthogonal
- How to place docs and query in the space (= how to assign term weights)
 - Term weight in query indicates importance of term
 - Term weight in doc indicates how well the term characterizes the doc
- How to define the similarity measure

6 Vector Space Retrieval Model: Simplest Instantiation

6.1 What VSM Doesn't Say



6.2 Simplest VSM = Bit-Vector + Dot-Product + BOW

$$\begin{array}{ll}
 \mathbf{q}=(x_1, \dots x_N) & x_i, y_i \in \{0,1\} \\
 \mathbf{d}=(y_1, \dots y_N) & 1: \text{word } W_i \text{ is present} \\
 & 0: \text{word } W_i \text{ is absent}
 \end{array}$$

$$\text{Sim}(\mathbf{q}, \mathbf{d}) = \mathbf{q} \cdot \mathbf{d} = x_1 y_1 + \dots + x_N y_N = \sum_{i=1}^N x_i y_i$$

Simplest VSM:

- Dimension = word
- Vector = 0-1 bit vector (word presence/absence)
- Similarity = dot product
- $f(q,d)$ = number of distinct query words matched in d

7 Vector Space Retrieval Model: Improved Instantiation

Improved VSM:

- Dimension = word
- Vector = TF-IDF weight vector
- Similarity = dot product

7.1 Improved VSM with Term Frequency (TF) Weighting


$$q = (x_1, \dots, x_N) \quad \boxed{x_i = \text{count of word } W_i \text{ in query}}$$

$$d = (y_1, \dots, y_N) \quad \boxed{y_i = \text{count of word } W_i \text{ in doc}}$$


$$\text{Sim}(q, d) = q \cdot d = x_1 y_1 + \dots + x_N y_N = \sum_{i=1}^N x_i y_i$$

7.2 IDF Weighting: Penalizing Popular Terms

IDF — inverse document frequency



7.3 Adding Inverse Document Frequency (IDF)



8 Vector Space Retrieval Model: TF Transformation


8.1 Ranking Function with TF-IDF Weighting

$$f(q, d) = \sum_{i=1}^N x_i y_i = \sum_{w \in q \cap d} c(w, q) c(w, d) \log \frac{M+1}{df(w)}$$

- $w \in q \cap d$ - all matched query (q) words in document (d)
- $c(w, q)$ - count of word w in document d
- M - total number of documents in collection
- $df(w)$ - Doc Frequency (total number of documents containing word w)

8.2 TF Transformation: BM25 Transformation

BM = Best Matching



8.3 Summary


- Sublinear TF Transformation is needed to
 - capture the intuition of «diminishing return» from higher TF
 - avoid dominance by one single term over all others
- BM25 Transformation
 - has an upper bound
 - is robust and effective
- Ranking function with BM25 TF ($k \geq 0$):

$$f(q, d) = \sum_{i=1}^N x_i y_i = \sum_{w \in q \cap d} c(w, q) \frac{(k+1)c(w, d)}{c(w, d) + k} \log \frac{M+1}{df(w)}$$

9 Vector Space Retrieval Model: Doc Length Normalization

9.1 Pivoted Length Normalization

Pivoted length normalizer: use average doc length as «pivot»². Normalizer = 1 if $|d|$ = average doc length (avdl).



9.2 State of the Art VSM Ranking Functions

Pivoted Length Normalization VSM [Singhal et al 96]:

$$f(q, d) = \sum_{w \in q \cap d} c(w, q) \frac{\ln[1 + \ln(1 + c(w, d))]}{1 - b + b \frac{|d|}{avdl}} \log \frac{M + 1}{df(w)}$$

BM25/Okapi [Robertson & Walker 94]:

$$f(q, d) = \sum_{w \in q \cap d} c(w, q) \frac{(k + 1)c(w, d)}{c(w, d) + k \left(1 - b + b \frac{|d|}{avdl}\right)} \log \frac{M + 1}{df(w)}$$

9.3 Further Improvement of VSM?

- Improved instantiation of dimension?
 - stemmed words, stop word removal, phrases, latent semantic indexing (word clusters), character n-grams, ...
 - bag-of-words with phrases is often sufficient in practice
 - Language-specific and domain-specific tokenization is important to ensure “normalization of terms”
- Improved instantiation of similarity function?
 - cosine of angle between two vectors?
 - Euclidean?
 - dot product seems still the best (sufficiently general especially with appropriate term weighting)


²Pivot - стержень; точка опоры, вращения

9.4 Further Improvement of BM25


- BM25F [Robertson & Zaragoza 09]
 - Use BM25 for documents with structures («F»=fields)
 - Key idea: combine the frequency counts of terms in all fields and then apply BM25 (instead of the other way)
- BM25+ [Lv & Zhai 11]
 - Address the problem of over penalization of long documents by BM25 by adding a small constant to TF
 - Empirically and analytically shown to be better than BM25

9.5 Summary of Vector Space Model

- $\text{Relevance}(q,d) = \text{similarity}(q,d)$
- Query and documents are represented as vectors
- Heuristic³ design of ranking function
- Major term weighting heuristics
 - TF weighting and transformation
 - IDF weighting
 - Document length normalization
- BM25 and Pivoted normalization seem to be most effective



³Heuristic - эвристический



9.6 Recommended reading

- A. Singhal, C. Buckley, and M. Mitra. «Pivoted document length normalization». In Proceedings of ACM SIGIR 1996.
- S. E. Robertson and S. Walker. «Some simple effective approximations to the 2-Poisson model for probabilistic weighted retrieval», Proceedings of ACM SIGIR 1994.
- S. Robertson and H. Zaragoza. «The Probabilistic Relevance Framework: BM25 and Beyond», Found. Trends Inf. Retr. 3, 4 (April 2009).
- Y. Lv, C. Zhai, «Lower-bounding term frequency normalization». In Proceedings of ACM CIKM 2011.