



MACHINE LEARNING IN THE TIDYVERSE

Exploring coefficients across models

Dmitriy (Dima) Gorenshteyn

Lead Data Scientist,

Memorial Sloan Kettering Cancer Center

77 models

```
gap_nested <- gapminder %>%  
  group_by(country) %>%  
  nest()  
gap_models <- gap_nested %>%  
  mutate(model = map(data, ~lm(life_expectancy~year, data = .x)))
```

```
gap_models  
# A tibble: 77 x 3  
  country      data      model  
  <fct>      <list>    <list>  
1 Algeria    <tibble [52 x 6]> <S3: lm>  
2 Argentina  <tibble [52 x 6]> <S3: lm>  
3 Australia  <tibble [52 x 6]> <S3: lm>  
4 Austria    <tibble [52 x 6]> <S3: lm>  
5 Bangladesh <tibble [52 x 6]> <S3: lm>  
6 Belgium    <tibble [52 x 6]> <S3: lm>
```



Regression coefficients

$$y = \alpha + \beta x$$




Regression coefficients

$$y = \alpha + \beta x$$

Life Expectancy	=	Term: (intercept)	+	Term: year	Year
-----------------	---	-------------------	---	------------	------

```
tidy(gap_models$model[[1]])  
  term      estimate ...  
1 (Intercept) -1196.5647772 ...  
2      year      0.6348625 ...
```



Coefficients of multiple models

```
gap_models %>%  
  mutate(coef = map(model, ~tidy(.x))) %>%  
  unnest(coef)
```

```
# A tibble: 154 x 6  
  country      term      estimate std.error statistic  p.value  
  <fct>      <chr>      <dbl>      <dbl>      <dbl>      <dbl>  
1 Algeria (Intercept) -1197      39.9      -30.0 1.32e-33  
2 Algeria year         0.635    0.0201     31.6 1.11e-34  
3 Argentina (Intercept) - 372      7.91     -47.0 4.66e-43  
4 Argentina year         0.223    0.00398    56.0 8.78e-47  
5 Australia (Intercept) - 429      9.37     -45.8 1.71e-42  
6 Australia year         0.254    0.00472    53.9 5.83e-46  
7 Austria (Intercept) - 415      8.04     -51.6 5.07e-45  
8 Austria year         0.246    0.00405    60.8 1.48e-48
```



MACHINE LEARNING IN THE TIDYVERSE

Let's practice!



MACHINE LEARNING IN THE TIDYVERSE

Evaluating the fit of many models

Dmitriy (Dima) Gorenshteyn

Lead Data Scientist,

Memorial Sloan Kettering Cancer Center





The fit of our models

$$R^2 = \frac{\% \text{ variation explained by the model}}{\% \text{ total variation in the data}}$$



The fit of our models



Glance across your models

```
model_perf <- gap_models %>%  
  mutate(coef = map(model, ~glance(.x))) %>%  
  unnest(coef)
```

```
model_perf  
  
# A tibble: 77 x 14  
  country data model r.squared adj.r.squared sigma statistic ...  
  <fct>    <lis> <lis>    <dbl>         <dbl> <dbl>    <dbl>    <dbl>  
1 Algeria <tib... <S3:... 0.952         0.951    2.18     996     ...  
2 Argenti... <tib... <S3:... 0.984         0.984    0.431    3137    ...  
3 Austral... <tib... <S3:... 0.983         0.983    0.511    2905    ...  
4 Austria <tib... <S3:... 0.987         0.986    0.438    3702    ...  
5 Banglad... <tib... <S3:... 0.949         0.947    1.83     921     ...  
6 Belgium <tib... <S3:... 0.990         0.990    0.331    5094    ...  
# ... with 71 more rows
```

Best & worst fitting models

```
model_perf %>%  
  top_n(n = 2, wt = r.squared)  
  
# A tibble: 2 x 14  
  country data  model r.squared adj.r.squared sigma statistic  
  <fct>    <lis> <lis>    <dbl>         <dbl> <dbl>         <dbl>  
1 Canada  <tib... <S3:...  0.995         0.995 0.231         10117  
2 Italy   <tib... <S3:...  0.997         0.997 0.226         15665
```

```
> model_perf %>%  
  top_n(n = 2, wt = -r.squared)  
  
# A tibble: 2 x 14  
  country data  model r.squared adj.r.squared sigma statistic  
  <fct>    <lis> <lis>    <dbl>         <dbl> <dbl>         <dbl>  
1 Botswa~ <tib... <S3:...  0.0136        -0.00608  5.11          0.692  
2 Lesotho <tib... <S3:...  0.00296        -0.0170   5.32          0.148
```



MACHINE LEARNING IN THE TIDYVERSE

Let's practice!



MACHINE LEARNING IN THE TIDYVERSE

Visually inspect the fit of your models

Dmitriy (Dima) Gorenshteyn

Lead Data Scientist,

Memorial Sloan Kettering Cancer Center


Building augmented datframes

```
augmented_models <- gap_models %>%  
  mutate(augmented = map(model, ~augment(.x))) %>%  
  unnest(augmented)
```

```
> augmented_models  
# A tibble: 4,004 x 10  
  country life_expectancy year .fitted .se.fit .resid .hat .sigma ...  
  <fct>          <dbl> <int>   <dbl>   <dbl>   <dbl> <dbl> <dbl> ...  
1 Algeria         47.5  1960    47.8    0.595 -0.266 0.0747 2.20 ...  
2 Algeria         48.0  1961    48.4    0.578 -0.381 0.0705 2.20 ...  
3 Algeria         48.6  1962    49.0    0.561 -0.486 0.0664 2.20 ...  
4 Algeria         49.1  1963    49.7    0.544 -0.600 0.0625 2.20 ...  
5 Algeria         49.6  1964    50.3    0.527 -0.725 0.0587 2.20 ...  
6 Algeria         50.1  1965    50.9    0.511 -0.850 0.0551 2.20 ...
```


Model for Italy $R^2 : 0.99$

```
augmented_model %>% filter(country == "Italy") %>%  
  ggplot(aes(x = year, y = life_expectancy)) +  
  geom_point() +  
  geom_line(aes(y = .fitted), color = "red")
```






Model for Fiji $R^2 : 0.82$





Model for Kenya $R^2 : 0.42$





MACHINE LEARNING IN THE TIDYVERSE

Let's practice!



MACHINE LEARNING IN THE TIDYVERSE

Improve the fit of your models

Dmitriy (Dima) Gorenshteyn

Lead Data Scientist,

Memorial Sloan Kettering Cancer Center



Multiple Linear Regression model

$$y = \alpha + \beta_1 X_1 + \beta_2 X_2 + \dots$$

Life Expectancy	=	<table border="1"><tr><td>Term: (intercept)</td></tr></table>	Term: (intercept)	+	<table border="1"><tr><td>Term: year</td><td>Year</td></tr></table>	Term: year	Year	+	<table border="1"><tr><td>Term: population</td><td>Population</td></tr></table>	Term: population	Population	+	<table border="1"><tr><td>Term: ...</td><td>...</td></tr></table>	Term:
Term: (intercept)															
Term: year	Year														
Term: population	Population														
Term:														

Available Features: year, population, infant_mortality, fertility, gdpPercap

Using all features

Simple Linear Model: **life_expectancy ~ year**

```
gap_models <- gap_nested %>%  
  mutate(model = map(data, ~lm(formula = life_expectancy ~ year, data = .x)))
```

Multiple Linear Model: **life_expectancy ~ year + population + ...**

Multiple Linear Model: **life_expectancy ~ .**

```
gap_fullmodels <- gap_nested %>%  
  mutate(model = map(data, ~lm(formula = life_expectancy ~ ., data = .x)))
```

Using broom with Multiple Linear Regression models

```
tidy(gap_fullmodels$model[[1]])
```

	term	estimate	std.error	statistic	p.value
1	(Intercept)	-1.830195e+03	1.502271e+02	-12.182848	5.325478e-16
2	year	9.814091e-01	7.800580e-02	12.581232	1.693870e-16
3	infant_mortality	-1.603504e-01	4.021732e-03	-39.870986	2.525847e-37
4	fertility	-2.600935e-01	1.648652e-01	-1.577614	1.215074e-01
5	population	-1.611437e-06	1.704374e-07	-9.454716	2.347590e-12
6	gdpPercap	-1.797662e-03	4.878209e-04	-3.685086	6.008755e-04

```
augment(gap_fullmodels$model[[1]])
```

	life_expectancy	year	infant_mortality	fertility	populationfitted
1	47.50	1960	148.2	7.65	11124892	...	47.45394
2	48.02	1961	148.1	7.65	11404859	...	48.35078
3	48.55	1962	148.2	7.65	11690152	...	49.26449
...

```
glance(gap_fullmodels$model[[1]])
```

	r.squared	adj.r.squared	sigma	statistic	p.value	df	logLik	...
1	0.9990732	0.9989724	0.3160595	9917.133	1.562325e-68	6	-10.70225	...



Adjusted R^2

```
glance(gap_fullmodels$model[[1]])
```

	r.squared	adj.r.squared	sigma	statistic	p.value	df	logLik	...
1	0.9990732	0.9989724	0.3160595	9917.133	1.562325e-68	6	-10.70225	...



MACHINE LEARNING IN THE TIDYVERSE

Let's practice!