

Exercise 1 — Intelligent Document Processing (IDP)

Goal: replace the two placeholder IDP service tasks with real **Document Classification** and **Document Extraction** templates powered by OpenAI. Read three uploaded PDFs, classify them, extract the structured fields, and feed them into the DMN validation step.

What you will learn

- The Camunda 8.9 IDP capability split: *classification templates vs extraction templates*.
- How to wire the OpenAI Compatible provider so IDP runs against OpenAI directly.
- How to publish an IDP template as a connector and apply it to a BPMN service task.
- How to feed the structured extraction output into a downstream DMN decision (already shipped: `document-validity.dmn`).
- How extraction confidence and the fallback "unclassified-document" value give you deterministic gateway routing.

Prerequisites

1. Exercise 1 complete — workers are running.
2. A Camunda 8 SaaS cluster with cluster version $\geq$ **8.9.x** (classification requires this).
3. An OpenAI API key with chat-completions access (model used: `gpt-4.5-mini`).
4. The cluster's **Connector secrets** configured (see Step 1).

Step 1 — Register the OpenAI secrets in SaaS

1. Open the **Console** for your SaaS cluster.
2. Navigate to **Manage cluster** ▶ **Connector secrets**.
3. Add the following secrets:

Secret name	Value	Value with Camunda LLM.
<code>OPENAI_API_KEY</code>	your OpenAI key (<code>sk-...</code>)	value from secret <code>CAMUNDA_PROVIDED_LLM_API_KEY</code>
<code>IDP_OPENAI_COMPATIBLE_ENDPOINT</code>	<code>https://api.openai.com/v1</code>	value from secret <code>CAMUNDA_PROVIDED_LLM_API_ENDPOINT</code>
<code>IDP_OPENAI_COMPATIBLE_HEADERS</code>	<code>{"Authorization": "Bearer OPENAI_API_KEY"}</code>	<code>{"Authorization": "Bearer OPENAI_API_KEY"}</code>

Why a separate `IDP_OPENAI_COMPATIBLE_HEADERS` ? The IDP OpenAI Compatible provider expects authentication via headers, not a top-level API key. The connector substitutes `${OPENAI_API_KEY}`

from the secret store at runtime.

Step 2 — Create an IDP application

1. In Web Modeler, click **Create new ▶ IDP application**.
2. Name it `office-alpaca-idp` and select your cluster.
3. The IDP application becomes a folder where classification and extraction templates live.

Step 3 — Build the classification template

1. Inside the IDP application click **Create new ▶ Classification template**.
2. Fill in:
 - **Name:** `Alpaca document classifier`
 - **Description:** Classifies the 3 supporting documents for an alpaca request.
 - **Provider:** OpenAI Compatible.
3. Click **Create**.
4. Define the explicit document types (don't use auto-classification — we want predictable routing):

Type id	Display name	Classification Prompt
<code>alpaca-suitability</code>	Alpaca Suitability	Has "OFFICE ALPACA SUITABILITY FORM" in the headline.
<code>alpaca-business-justification-memo</code>	Alpaca Business Justification Memo	Contains "BUSINESS JUSTIFICATION MEMO" in the headline.

Leave the default **fallback output value** of `unclassified-document` — the DMN in `document-validity.dmn` already routes that to *Request missing information*.

5. In the **Configure model** tab choose:
 - Model: `gpt-5.4-mini` (enter the name and hit ENTER).
 - for Camunda provided LLM use `openai.gpt-oss-20b` (enter the name and hit ENTER)
6. **Test** the template with the sample files we ship in `office-alpaca-app/sample-documents/`.
7. Click **Publish => to Project** — this makes the template available as a connector element template.

Step 4 — Build the Alpaca Suitability extraction template

1. Click **Create new ▶ Extraction template** inside the same IDP application.
2. Fill in:
 - **Name:** `Alpaca Suitability Extraction`
 - **Provider:** OpenAI Compatible

- **Extraction method:** Unstructured (the documents are free-form PDFs).

3. Define the extraction fields:

Field name	Type	Description
officeLocation	string	the office location preferred for the visit.
vaccinationValidUntil	string	the vaccination valid until date
temperamentScore	number	the temperament score
alpacaName	string	the name of the Alpaca
visitDate	string	the planned visit date
vaccinationStatus	string	the vaccination status

4. **Test** the template against your sample PDFs and confirm that all fields populate.

5. **Publish to your project.**

Step 5 — Build the Business Justification Memo extraction template

1. Click **Create new » Extraction template** inside the same IDP application.

2. Fill in:

- **Name:** Business Justification Memo Extraction
- **Provider:** OpenAI Compatible
- **Extraction method:** Unstructured (the documents are free-form PDFs).

3. Define the extraction fields:

Field name	Type	Description
expectedBusinessValue	string	the expected business value.
requestedBudget	string	the estimated overall budget as number (without currency)

4. **Test** the template against your sample PDFs and confirm that all fields populate.

5. **Publish to your project.**

Step 6 — Apply the templates to the BPMN

1. Open `Extract Alpaca Data` in Web Modeler.

2. Click **Classify uploaded documents » Element template** ▶ select `Alpaca document classifier`.

3. Configure:

- **Documents input** (`documents`): `=document` — the array of uploaded file references.
- **Result variable:** `classificationResult`.

4. Repeat for **Extract Business Justification and Extract Alpaca suitability Info** with the according extraction templates:
 - **Documents input:** `=document`
 - **Result expression:** `={extractedFields: extractedFields}`.
5. Save and re-deploy from Modeler.

Acceptance criteria

- ☐ Both classification and extraction templates are published.
- ☐ The BPMN tasks display the IDP template names (not the placeholder task types) in Modeler.
- ☐ A real Tasklist upload of the sample PDFs runs end-to-end to `Check Office Readiness`.
- ☐ At least one negative scenario routes the process to *Request missing information*.

Reference links

- [IDP overview](#)
- [IDP document classification](#)
- [IDP document extraction](#)
- [IDP OpenAI Compatible provider](#)
- [IDP integrate into processes](#)
- [Document handling](#)