

Computer Science 3A

Practical 3


02 March 2023



UNIVERSITY
OF
JOHANNESBURG

Doubly Linked Lists:

The basic Doubly Linked List:



Size = 3



For Practical 3: Overview

1. Complete the Node Class
2. Complete the DList class methods



For Practical 3: Overview

1. Complete the Node Class

- Accessor methods
- Mutator methods
- toString method



For Practical 3: Overview

2. Complete the DList class methods


- `fromArray()` – construct a list from an array ; `toArray()` – convert a list to an array
- `clone()` – construct a copy of the linked list
- `addAfter()` – adds an element after a given node in the list ; `addBefore()` – adds an element before a given node in the list
- `remove()` – remove a specified node from the list ; `search()` – returns the node which contains the specified element
- `tail()` – returns the list that contains everything except the first element
- `toString()` – returns a string representation of the linked list
- Quicksort methods

NOTE: pay attention to the signature and return type of a method/function



For Practical 3:

Quicksort



For Practical 3: Quicksort

- An efficient method of sorting a list of items
- Algorithm:
 1. Choose a "pivot" element (we'll use the first element in the list)
 2. Split the list into three smaller lists
 - a. One list that only contains items that are smaller than the pivot element (`splitLess()` method)
 - b. One list that only contains items that are greater than the pivot element (`splitGreater()` method)
 - c. One list that only contains items that are equal to the pivot element (`splitEqual()` method)
 3. Call quicksort on the list of smaller elements
 4. Call quicksort on the list of greater elements
 5. Merge the smaller list, the equal lists, and the greater lists together (`merge` method)



Questions?

