

Data X

Loss vs Risk
Data, Signals, and Systems

Ikhlaq Sidhu
Chief Scientist & Founding Director,
Sutardja Center for Entrepreneurship & Technology
IEOR Emerging Area Professor Award, UC Berkeley

Remember this Classification Example




Illustration only
These numbers are not real



Classification Extended to Multiple Variables

Illustration only
These numbers are not real


Train
Data

X

1	2
2	3
5	2
4	3
7	9
10	8

$F(X, W)$

W is (2×3)




Choose best
parameter of W

Y

0	0	0
1	0	0
0	0	1
0	1	1
1	1	1
1	1	1

$$f(x_i, W) = \frac{1}{1 + e^{-(w_0 + x_{i,1}w_1 + x_{i,2}w_2 \dots)}}$$




Model for Prediction

y1 boundary
y2 boundary
y3 boundary




How Should We Decide a Classification Boundary?



One way is by likelihood that it is red vs green

$P(\text{green} | x) > P(\text{red} | x)$ for all x
(this is maximum likelihood estimation)

Suppose we are detecting Red:
For now, let's look at Red = true
And Green as (not Red), ie False



For Reference: Maximum Likelihood Estimation

To use the method of maximum likelihood,^[7] one first specifies the **joint density function** for all observations. For an **independent and identically distributed** sample, this joint density function is

$$f(x_1, x_2, \dots, x_n | \theta) = f(x_1 | \theta) \times f(x_2 | \theta) \times \dots \times f(x_n | \theta).$$

Now we look at this function from a different perspective by considering the observed values x_1, x_2, \dots, x_n to be fixed "parameters" of this function, whereas θ will be the function's variable and allowed to vary freely; this same function will be called the **likelihood**:

$$\mathcal{L}(\theta; x_1, \dots, x_n) = f(x_1, x_2, \dots, x_n | \theta) = \prod_{i=1}^n f(x_i | \theta).$$

Note that " ; " denotes a separation between the two categories of input arguments: the parameters θ and the observations x_1, \dots, x_n .

In practice it is often more convenient when working with the **natural logarithm** of the likelihood function, called the **log-likelihood**:

$$\ln \mathcal{L}(\theta; x_1, \dots, x_n) = \sum_{i=1}^n \ln f(x_i | \theta),$$

or the average log-likelihood:

$$\hat{\ell} = \frac{1}{n} \ln \mathcal{L}.$$


The **hat** over ℓ indicates that it is akin to some estimator. Indeed, $\hat{\ell}$ estimates the expected log-likelihood of a single observation in the model.

The method of maximum likelihood estimates θ_0 by finding a value of θ that maximizes $\hat{\ell}(\theta; x)$. This method of estimation defines a **maximum likelihood estimator (MLE)** of θ_0 :



How Should We Decide a Classification Boundary?

Another way would be to use a loss function to decide




$L_{\text{red}}(x)$: red loss as a function of vector X
(assume the actual outcome is red, then $L_{\text{red}}(x)$ is larger when x is not likely predict to be red.)
 $L_{\text{green}}(x)$: green loss as a function of vector X

Boundary could be where $L(\text{red})=L(\text{green})$


e.g. Cross Entropy $= -t \ln(f(\vec{x})) - (1-t) \ln(1-f(\vec{x}))$

Suppose we are detecting Red:
For now, let's look at Red = true
And Green as (not Red), ie False



How Should We Decide a Classification Boundary?

- Loss function in math notation:




In math notation:

Loss Function: $L(\theta, \delta(X))$

Expected Loss: $R(\theta, \delta) = \mathbb{E}(L(\theta, \delta(X)))$


e.g. Cross Entropy $= -t \ln(f(\vec{x})) - (1-t) \ln(1-f(\vec{x}))$

Suppose we are detecting Red:
For now, lets look at Red = true
And Green as (not Red), ie False




How Should We Decide a Classification Boundary?

- Another way would be to use a loss function to decide:



Boundary could be where $L(\text{red})=L(\text{green})$
BUT THERE IS A PROBLEM WITH THIS

Suppose we are detecting Red:
For now, let's look at Red = true
And Green as (not Red), ie False



How Should We Decide a Classification Boundary?

National Security

Consider the Application:

Red = there is a national security breach

Green = everything is OK

Reward or Risk is not same as loss

Predicted	Predicted No Breach	Predicted Breach
Actual: No Breach	Loss = 0 COST = 0	Loss = .5 COST = 10
Actual: Breach	Loss = 0.6 COST = 1000	Loss = 0 COST = 0




How Should We Decide a Classification Boundary?

	Consider the Application:	Reward or Risk is not same as loss	
National Security	<p>Red = there is a national security breach</p> <p>Green = everything is OK</p>	Predicted	Predicted No Breach
		Actual: No Breach	Loss = 0 COST = 0
		Actual: Breach	Loss = 0.6 COST = 1000

Supermarket Coupon by fingerprint	Red = fingerprint does not match for supermarket coupon	Predicted	Predicted Match	Predicted No Match
		Actual: Match	Loss = 0 COST = 0	Loss = .5 COST = 1000
		Actual: No match	Loss = 0.6 COST = 10	Loss = 0 COST = 0



A Risk Function will consider the application



Predicted	Predicted RED	Predicted GREEN
Actual: RED	#500 Risk = 0	#100 FN COST = 50
Actual: GREEN	#300 FP	#300 COST = 10 Risk = 0

We want to set the boundary where the Risk of False Positive = Risk of False Negative

$$\text{Alpha} \times \text{FPcost} = \text{Beta} \times \text{FNcost}$$

Risk (Red = actual, Green = predicted)

$$= \text{Prob (Red actual and Green predicted)} \times \text{cost of false negative}$$

$$= 100/600 \times 50 = 8.3$$

Risk (Green actual, Red predicted) = Prob (Green actual, red predicted) x cost of false positive

$$= 300/600 \times 10 = 5$$





Logistic Regression Example from Notebook

Example: 2 features/predictors, 1 output decision

Test if false positive or false negative rate per risk and cost. (in example too many false positives)

Option A: change boundary threshold from 0.5 to higher (0.66. in example)

Option B: Eliminate the most false negative data points from X until the boundary moves



End of Section

0 0 0 1 0 1 0 1 0 1 1 1 0 0 0 0 0 0 1 0 0 1 0 1 0 1 1 1 0 0
1 0 1 1 X 1 1 0 0 1 0 1 0 0 1 0 1 0 1 0 1 1 1 1 1 0 1 0 1 1 1 0 0
1 Data 0 0 1 0 1 0 1 0 1 0 0 1 0 1 0 1 0 1 1 1 1 1 0 1 0 1 1 1 0 0