10GBASE-LRM SFP+ 1310nm 220m DOM Transceiver

SFP-10GLRM-31

Features

- Hot-pluggable SFP+ footprint
- Supports 10.3Gb/s bit rate
- Power dissipation < 1W
- RoHS-6 compliant (lead-free)
- Commercial temperature range 0 to 70° C
- Single 3.3V power supply
- Maximum link length of 220m
- Uncooled directly modulated
- Fabry-Perot (FP) laser at 1310nm
- Receiver linear electrical interface
- Duplex LC connector
- Built-in digital diagnostic functions

Application

- 10GBASE-LRM 10G Ethernet
- Legacy FDDI multimode links

Datasheet

Description

10GBASE-LRM Enhanced Small Form Factor Pluggable SFP+ transceivers are designed for use in 10-Gigabit Ethernet links up to 220m over Multi Mode fiber. They are compliant with SFF-8431, SFF-8432 and IEEE 802.3 aq 10GBASE-LRM. Digital diagnostics functions are available via a 2-wire serial interface.

The transceiver is a "linear module" i.e. it employs a linear receiver. Host board designers using an EDC PHY IC should follow the IC manufacturer's recommended settings for interoperating the host board EDC PHY with a linear receiver SFP+ module. The optical transceivers are compliant per the RoHS Directive 2011/65/EU.

Product Specifications

I. General Specifications

Parameter		Symbol	Min	Type	Max	Unit	Ref.
Bit Rate		BR		10.3125		Gb/s	1
Bit Error Ratio		BER			10^{-12}		2
Maximum Supported Distances							
Fiber Type	1310nm OFL Bandwidth						
62.5μm	"FDDI" 160MHz/km	Lmax			220	m	3
	OM1 200MHz/km				220		
50μm	400MHz/km	Lmax			100		3
	OM2 500MHz/km				220		
	OM3 2000MHz/km				220	m	

Notes:
1. 10GBASE-LRM
2. Tested with a $2^{31} - 1$ PRBS
3. Operating range as defined by IEEE standards. Longer reach possible depending upon link implementation.

II. Absolute Maximum Ratings

Parameter	Symbol	Min	Type	Max	Unit	Ref.
Maximum Supply Voltage	Vcc	-0.5		4.0	V	
Storage Temperature	T_S	-40		85	°C	
Relative Humidity	RH	0		85	%	1

Note:
  1. Non-condensing.

III. Electrical Characteristics (TOP = 0 to 70 °C, V_{CC} = 3.14 to 3.46 Volts)

Parameter	Symbol	Min	Type	Max	Unit	Ref.
Supply Voltage	Vcc	3.14		3.46	V	
Supply Current	Icc		200	300	mA	
Power Dissipation	P			1.0	W	
Transmitter						
Input differential impedance	R_{in}		100		Ω	1
Differential data input swing	Vin,pp	90		350	mV	2
Transmit Disable Voltage	V_D	2		Vcc	V	3
Transmit Enable Voltage	V_{EN}	Vee		Vee+ 0.8	V	

Receiver						
Termination Mismatch at 1 MHz	ΔZ_M			5	%	
Single Ended Output Voltage Tolerance		-0.3		4.0	V	
Output AC Common Mode Voltage				7.5	mV RMS	
Output Rise and Fall time (20% to 80%)	Tr, Tf	30			Ps	4
Relative Noise LRM Links with crosstalk	RN		per SFF-8431			5
Difference Waveform Distortion Penalty	dWDP		per SFF-8431		dBo	5,6
Differential Voltage Modulation Amplitude	VMA	180		600	mV	
LOS Fault	$V_{LOS\ fault}$	2		Vcc$_{HOST}$	V	7
LOS Normal	$V_{LOS\ norm}$	Vee		Vee+0.8	V	7
Power Supply Noise Tolerance	VccT/VccR		per SFF-8431		mVpp	8

Notes:
1. Connected directly to TX data input pins. AC coupling from pins into laser driver IC.
2. Per SFF-8431 Rev 4.1.
3. Into 100 ohms differential termination.
4. Measured with Module Compliance Test Board and OMA test pattern.
5. Values shown in Table 20, SFF-8431. dWDP and RN is calculated by the following equation:
   RN $\leq$ min[(m1 $\times$ dWDP + b1), (m2 $\times$ dWDP + b2), RNmax].
6. Defined with reference receiver with 14 T/2 spaced FFE taps and 5 T spaced DFE taps.
7. LOS is an open collector output. Should be pulled up with 4.7kΩ – 10kΩ on the host board. Normal operation is logic 0; loss of signal is logic 1. Maximum pull-up voltage is 5.5V.
8. As described in Section 2.8.1, SFF-8431 Rev 4.1.

Datasheet

IV. Optical Characteristics (TOP = 0 to 70 ℃, V_{CC} = 3.14 to 3.46 Volts)

Parameter	Symbol	Min	Type	Max	Unit	Ref.
Transmitter (Tx)						
Optical Modulation Amplitude (OMA)	P_{OMA}	-4.5		+1.5	dBm	
Average Launch Power	P_{AVE}	-6.5		0.5	dBm	1
Peak Launch Power	P_{MAX}			3	dBm	
Optical Wavelength	λ	1260		1355	nm	
RMS Spectral Width	λ_{rms} @1260nm			2.4	nm	2
	λ_{rms} @ 1260nm-1300nm			See Figure as below		
	λ_{rms} @ 1300nm-1355nm			4		
Optical Extinction Ratio	ER	3.5			dB	
Optical Eye Mask Margin		0			%	3
Transmitter Waveform Dispersion Penalty	TWDP			4.7	dB	4
Average Launch power of OFF transmitter	P_{OFF}			-30	dBm	
Uncorrelated Jitter [rms]	Tx_j			0.033	UI	
Relative Intensity Noise	$RIN_{12}OMA$			-128	dB/Hz	
Encircled Flux	<5μm <11μm	30 81			%	
Transmitter Reflectance				-12	dB	
Optical Return Loss Tolerance		20			dB	

Receiver (Rx)						
Receiver Overload	POMA	+1.5			dBm	5
Comprehensive Stressed Receiver Sensitivity (OMA) @ 10.3125Gb/s	Precursor			-6.5	dBm	6
	Symmetrical			-6.0		
	Postcursor			-6.5		
Wavelength Range	λ_C	1260	1355		N_m	
Receiver Reflectance	R_{rx}			-12	dB	
LOS De-Assert	LOS_D			-11	dBm	
LOS Assert	LOS_A	-30			dBm	
LOS Hysteresis		0.5			dB	

Notes:
1. Average power figures are informative only, per IEEE802.3aq
2. Maximum RMS spectral width as specified by Figure as below
3. Optical Eye Mask requires the host board to be SFF-8431 compliant. Optical eye mask per IEEE802.3aq.
4. TWDP figure requires the host board to be SFF-8431 compliant. TWDP is calculated using the Matlab code provided in clause 68.6.6.2 of IEEE802.3aq
5. Receiver overload specified in OMA and under the worst comprehensive stressed condition.
6. Conditions of stressed receiver tests per IEEE802.3aq. CSRS testing requires the host board to be SFF-8431 compliant.

V. Digital Diagnostic Specifications

Transmitter Maximum RMS Spectral Width

Parameter	Symbol	Min	Type	Max	Units	Ref.
Accuracy						
Internally measured transceiver temperature	DD_{Temp}			3	°C	
Internally measured transceiver supply voltage	$DD_{Voltage}$			100	mV	
Measured TX bias current	DD_{Bias}			10	%	1
Measured TX output power	$DD_{Tx-Power}$			2	dB	
Measured RX received average optical power	$DD_{Rx-Power}$			2	dB	

Dynamic Range for Rated Accuracy					
Internally measured transceiver temperature	DD_{Temp}	-5		75	°C	
Internally measured transceiver supply voltage	$DD_{Voltage}$	3.1		3.5	V	
Measured TX bias current	DD_{Bias}	0		75	mA	
Measured TX output power	$DD_{Tx-Power}$	-6.5		0.5	dBm	
Measured RX received average optical power	$DD_{Rx-Power}$	-20		-10	dBm	
Max Reporting Range					
Internally measured transceiver temperature	DD_{Temp}	-40		125	°C	
Internally measured transceiver supply voltage	$DD_{Voltage}$	2.8		4.0	V	
Measured TX bias current	DD_{Bias}	0		75	mA	
Measured TX output power	$DD_{Tx-Power}$	-10		3	dBm	
Measured RX received average optical power	$DD_{Rx-Powe}$	-22		0	dBm	

Notes:
1. Accuracy of Measured Tx Bias Current is 10% of the actual Bias Current from the laser driver to the laser.

VI. Pin Description

Diagram of Host Board Connector Block Pin Numbers and Names

Pin	Symbol	Name/Description	Ref.
1	V_{EET}	Transmitter Ground	1
2	T_{FAULT}	Transmitter Fault	
3	T_{DIS}	Transmitter Disable. Laser output disabled on high or open.	2
4	SDA	2-wire Serial Interface Data Line	3
5	SCL	2-wire Serial Interface Clock Line	3
6	MOD_ABS	Module Absent. Grounded within the module	3
7	RS0	No connection required	

| 8	RX_LOS	Loss of Signal indication. Logic 0 indicates normal operation.	4
9	RS1	No connection required	
10	V_{EER}	Receiver Ground	1
11	V_{EER}	Receiver Ground	1
12	RD-	Receiver Inverted DATA out. AC Coupled.	
13	RD+	Receiver Non-inverted DATA out. AC Coupled.	
14	V_{EER}	Receiver Ground	1
15	V_{CCR}	Receiver Power Supply	
16	V_{CCT}	Transmitter Power Supply	
17	V_{EET}	Transmitter Ground	1
18	TD+	Transmitter Non-Inverted DATA in. AC Coupled.	
19	TD-	Transmitter Inverted DATA in. AC Coupled.	
20	V_{EET}	Transmitter Ground	1

Notes:
1. Circuit ground is internally isolated from chassis ground.
2. Laser output disabled on T DIS >2.0V or open, enabled on T DIS <0.8V.
3. Should be pulled up with 4.7k – 10kohms on host board to a voltage between 2.0V and 3.6V.
   MOD_ABS pulls line low to indicate module is plugged in.
4. RX_LOS is open collector output. Should be pulled up with 4.7k – 10kohms on host board to a voltage between 2.0V and 3.6V. Logic 0 indicates normal operation; logic 1 indicates loss of signal.

VII. Mechanical Specifications

## Datasheet

VIII. PCB Layout and Bezel Recommendations

NOTES:

⚠ MINIMUM PITCH OLLUSTRATED, ENGLISH DIMENSIONS
ARE FOR REFERENCE ONLY

2 NOT RECOMMENDED FOR PCI EXPANSION
CRAD APPLICATIONS

Test Center

Only when quality and 100% compatibility is verified and proved do our modules enter the market. This depends on Fiberstore test center which is supported by a variety of mainstream original brand switches and professional staff. We are proud of this test center and believe all of these devices worth the investments, because it brings the best to our customers.

The original switches could be found nowhere but at Fiberstore's test center, eg: Juniper MX960 & EX 4300 series, Cisco Nexus 9396PX & Cisco ASR 9000 Series, HP 5900 Series & HP 5406R ZL2 V3(J9996A), Arista 7050S-64, Brocade ICX7750-26Q & ICX6610-48, Avaya VSP 7000 MDA 2, etc.

Cisco ASR 9000 Series(A9K-MPA- 1X40GE)

ARISTA 7050S-64(DCS-7050S-64)

Juniper MX960

Brocade ICX 7750-26Q

Extreme Networks X670V VIM-40G4X

Mellanox M3601Q

Dell N4032F

HP 5406R ZL2 V3(J9996A)


AVAYA 7024XLS(7002QQ-MDA)

Test Assured Program

Fiberstore truly understands the value of compatibility and interoperability to each optics. Every module Fiberstore provides must run through programming and an extensive series of platform diagnostic tests to prove its performance and compatibility. In our test center, we care of every detail from staff to facilities—professionally trained staff, advanced test facilities and comprehensive original-brand switches, to ensure our customers to receive the optics with superior quality.

Our smart data system allows effective product management and quality control according to the unique serial number, properly tracing the order, shipment and every part.

Our in-house coding facility programs all of our parts to standard OEM specs for compatibility on all major vendors and systems such as Cisco, Juniper, Brocade, HP, Dell, Arista and so on.

With a comprehensive line of original-brand switches, we can recreate an environment and test each optics in practical application to ensure quality and distance.

The last test assured step to ensure our products to be shipped with perfect package.

Order Information

Part Number	Description
SFP-10GSR-85	10GBASE-SR SFP+ 850nm 300m DOM Transceiver
SFP-10GLRM-31	10GBASE-LRM SFP+ 1310nm 220m DOM Transceiver
SFP-10GLR-31	10GBASE-LR SFP+ 1310nm 10km DOM Transceiver
SFP-10GER-55	10GBASE-ER SFP+ 1550nm 40km DOM Transceiver
SFP-10GZR-55	10GBASE-ZR SFP+ 1550nm 80km DOM Transceiver
SFP-10GZRC-55	10GBASE-ZR SFP+ 1550nm 100km DOM Transceiver
SFP-10GSR-85	Dual-Rate 1000BASE-SX and 10GBASE-SR SFP+ 850nm 300m DOM Transceiver
SFP-10GLR-31	Dual-Rate 1000BASE-LX and 10GBASE-LR SFP+ 1310nm 10km DOM Transceiver

Note:
Every transceiver is individually tested on corresponding equipment, walks through the testing challenges and 100% compatible with Cisco, Arista, Juniper, Dell, Brocade and other brands.

Contact Us

Fiberstore China
Room 301, Third Floor, Weiyong
Building, No. 10 Kefa Road,
Nanshan District, Shenzhen, 518057,
China
Tel: +86 (755) 8300 3611
Fax: +86 (755) 8326 9395

Fiberstore U.S.
331 Andover Park East Ste330,
Tukwila, WA 98188,
United States
Tel: +1-425-226-2035
Fax: +1-253-246-7881

Fiberstore Hong Kong
1220 Tung Chun Commercial
Centre, 438-444 Shanghai Street,
Kowloon, HongKong
Tel: +(852) 817 636 06
Fax: +(852) 817 636 06

Fiberstore U.K.
Third Floor 207 Regent Street,
London, W1B 3HH,
United Kingdom
Tel: +44 (020) 3287 6810

Addresses, phone number and fax number also have been listed at www.fs.com. Please e-mail us at sales@fs.com or call us for assistance.

All statements, technical information, and recommendations related to the products here are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact FS for more information.