

Christian McGovern, The problem for this lab was fixing 3 operators. (), *, and a negative number (unary) in yacc and lex.

Files created by yacc: y.tab.c and t.tab.h

Files created by lex: lex.yy.c

We do not compile Lex output directly here because we put

```
#include "lex.yy.c"
```

which implicitly compiles it to our yacc program.

Yacc code:

```
%{
```

```
/*
```

```
*          **** CALC ****
```

```
*
```

```
* This routine will function like a desk calculator
```

```
* There are 26 integer registers, named 'a' thru 'z'
```

```
*
```

```
*/
```

```
/* This calculator depends on a LEX description which outputs either VARIABLE or INTEGER.
```

The return type via yylval is integer

When we need to make yylval more complicated, we need to define a pointer type for yylval and to instruct YACC to use a new type so that we can pass back better values

The registers are based on 0, so we subtract 'a' from each single letter we get.

based on context, we have YACC do the correct memory look up or the storage depending on position

Shaun Cooper

January 2015

problems fix unary minus, fix parenthesis, add multiplication

problems make it so that verbose is on and off with an input argument instead of compiled in

*/

```
/* begin specs */
```

```
#include <stdio.h>
```

```
#include <ctype.h>
```

```
#include "lex.yy.c"
```

```
int regs[26];
```

```
int base, debugsw;
```

```
void yyerror (s) /* Called by yyparse on error */
```

```
    char *s;
```

```
{
```

```
    printf ("%s\n", s);
```

```
}
```

```
%}
```

```
/* defines the start symbol, what values come back from LEX and how the operators are associated */
```

%start list

%token INTEGER

%token VARIABLE

%left '|'

%left '&'

%left '+' '-'

%left '*' '/' '%'

%left UMINUS

%% /* end specs, begin rules */

```
list      :      /* empty */
          |      list stat '\n'
          |      list error '\n'
              { yyerrok; }
          ;
```

```
stat      :      expr
              { fprintf(stderr,"the answer is %d\n", $1); }
          |      VARIABLE '=' expr
              { regs[$1] = $3; }
          ;
```

```
expr      :      '(' expr ')'
              { $$ = $2; }
```

```

|      expr '-' expr
        { $$ = $1 - $3; }

|      expr '+' expr
        { $$ = $1 + $3; }

|      expr '/' expr
        { $$ = $1 / $3; }

//added multiplication rules
|      expr '*' expr
        { $$ = $1 * $3; }

|      expr '%' expr
        { $$ = $1 % $3; }

|      expr '&' expr
        { $$ = $1 & $3; }

|      expr '|' expr
        { $$ = $1 | $3; }

|      '-' expr %prec UMINUS //removed the expr before the '-'
        { $$ = -$2; }

|      VARIABLE
        { $$ = regs[$1]; fprintf(stderr,"found a variable value = %d\n",$1); }

|      INTEGER {$$=$1; fprintf(stderr,"found an integer\n");}

;

%%      /* end of rules, start of program */


main()
{ yyparse();
}

```

Lex code:

```

/*      Small LEX routine which returns two formal tokens (INTEGER and VARIABLE)

```

along with single string elements like '+'.

This LEX definition is the companion to the docalc.y YACC routine which is a simple calculator

Shaun Cooper

January 2015

```
*/
%{
int mydebug=1;
#include "y.tab.h"
%}
%%

[a-z]          {if (mydebug) fprintf(stderr,"Letter found\n");
                yylval=*yytext-'a'; return(VARIABLE);}

[0-9][0-9]*    {if (mydebug) fprintf(stderr,"Digit found\n");
                yylval=atoi((const char *)yytext); return(INTEGER);}

[ \t]          {if (mydebug) fprintf(stderr,"Whitespace found\n");}

[=()\-+*/%&|] {if (mydebug) fprintf(stderr,"return a token %c\n",*yytext); //added () to set
                return (*yytext);}

\n            { if (mydebug) fprintf(stderr,"cariage return %c\n",*yytext);
                return (*yytext);}

%%

int yywrap(void)
{ return 1;}
```

```
mcgovern@Christian: /mnt/c/Users/Christian/Desktop/Google_Drive/Course-Work/NMSU-Compilers/lab2.2
[41] Stopped ./lab2docalc
mcgovern@Christian: /mnt/c/Users/Christian/Desktop/Google_Drive/Course-Work/NMSU-Compilers/lab2.2$ clear
mcgovern@Christian: /mnt/c/Users/Christian/Desktop/Google_Drive/Course-Work/NMSU-Compilers/lab2.2$ -(3#8)
-bash: syntax error near unexpected token `3#8'
mcgovern@Christian: /mnt/c/Users/Christian/Desktop/Google_Drive/Course-Work/NMSU-Compilers/lab2.2$ ./lab2docalc
-(3#8)
return a token -
return a token (
Digit found
found an integer
return a token *
Digit found
found an integer
return a token )
carriage return

the answer is -27
-
```