O'REILLY®



Deep Dive into Git

#oscon

Edward Thomson
ethomson

Talking about version control and trying to make it interesting... is like talking about sex and trying to make it boring.

- Eric Sink, Version Control by Example



"It's easy! It's just a directed acyclic graph!"

- Emma Jane Hogbin Westby (on Anti-Patterns for Teaching Git)





Edward Thomson @ethomson

Software Engineer, **GitHub**Maintainer, **libgit2** (www.libgit2.org)
Author, **Git for Visual Studio** (www.gitforvisualstudio.com)



Why care about how Git works?




Goals for Creating Git

Fast
Support a Distributed Workflow
Provide safeguards against accidental data corruption

Take the CVS project as an example of what not to do





If that doesn't fix it, git.txt contains the phone number of a friend of mine who understands git. Just wait through a few minutes of 'It's really pretty simple, just think of branches as...' and eventually you'll learn the commands that will fix everything.

xkcd: http://xkcd.com/1597/



Git Has Some Strange Commands

```
git rebase --onto origin/master HEAD~5 HEAD
git rerere forget foo/bar.c
git checkout branch
git checkout -b newbranch
git checkout -- foo/bar.c
git checkout origin/master changed_file.c
```



Git Has Some Strange Messages

```
foo.c: needs update
warning: LF will be replaced by CRLF
warning: CRLF will be replaced by LF
By default, updating the current branch in a non-
bare repository is denied
fatal: https://foo.com/info/refs not found: did you
run git update-server-info on the server?
You are in 'detached HEAD' state.
```



Git Has Some Strange Documentation

Forward-port local commits to the updated upstream head

Join two or more development histories together

Reveal all downstream commits below the sent upstream paths

Update remote refs along with associated objects



Git Has Some Strange Documentation

Git Man Page Generator:

http://git-man-page-generator.lokaltog.net



The Git commands are simply a leaky abstraction over the data storage.





What is a Distributed Version Control System





What is Distributed Version Control?

Not a classic "centralized" version control system

- Many operations must be performed against the server: get, revert, query history
- Even getting the status of your local working folders may talk to the server



What is Distributed Version Control?

Not a classic "centralized" version control system

- Many operations must be performed against the server: get, revert, query history
- Even getting the status of your local working folders may talk to the server

Distributed Version Control requires no central server

- Each user has an independent copy of the repository, including history
- Operations work against the local repository, including "commit"
- Users publish their changes independently of committing them
- Two independent changes must be merged to ensure logical consistency





The Git Repository




My repository








My repository









My repository









My repository








My repository










Demo How History is Modeled



Git represents history in a Directed Acyclic Graph






Git represents history in a Directed Acyclic Graph




Git represents history in a Directed Acyclic Graph






Git represents history in a Directed Acyclic Graph






Git represents history in a Directed Acyclic Graph






How are commit IDs generated?





How are commit IDs generated?


Can't be monotonically increasing (without a server to arbitrate)





How are commit IDs generated?


Can't be monotonically increasing (without a server to arbitrate)





How are commit IDs generated?


- Can't be monotonically increasing (without a server to arbitrate)
- SHA1 hash of the contents of the commit





How are commit IDs generated?

- Can't be monotonically increasing (without a server to arbitrate)
- SHA1 hash of the contents of the commit





Commits

Represent the entire repository

- Contain a pointer to the repository tree at that particular version
- To see what changed from the previous commit, you must run a diff



Commits

Represent the entire repository

- Contain a pointer to the repository tree at that particular version
- To see what changed from the previous commit, you must run a diff


Created from trees and blobs

- Trees represent a directory, blobs represent a file
- Together can represent an entire filesystem




Commits

Commits





Commits





Commits







Demo How Objects are Stored




Exist at the repository level

- A branch applies to the entire repository
- Unlike (most) centralized tools where branches exist inside the repository


Exceptionally lightweight

- Implemented as a pointer to a commit in the graph
- Exist only in the local repository until they're explicitly shared
- Encourages feature branches




















Demo

How Branches are Stored













Demo

How the Current Branch is Stored




Merging Two Commits








Merging Two Commits












Demo

Merging Two Commits




Fast-Forwards














Demo

Fast-Forward Merges




Rebase





Rebasing a Commit








Demo

Rebasing a Commit Onto a New Branch




Rebasing a Commit





Rebasing a Commit





The Git commands are simply a leaky abstraction over the data storage.





Thank you!

Edward Thomson

Twitter, GitHub: @ethomson

Author, Git for Visual Studio (www.gitforvisualstudio.com)





