



南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY



香港科技大學
THE HONG KONG
UNIVERSITY OF SCIENCE
AND TECHNOLOGY



THE HONG KONG
POLYTECHNIC UNIVERSITY
香港理工大學



東北大學
NORTHEASTERN UNIVERSITY

Understanding and Detecting Runtime Permission Issues in Android Applications

Yepang Liu


Department of Computer Science and Engineering
Southern University of Science and Technology

► Background

Permissions on Android




- Android is the most popular smartphone OS
 - 2+ billion users
 - 69.7% market share
- To protect user privacy, Android OS uses **permissions** to restrict apps to access:
 - **User data** (e.g., contacts, photos)
 - **Sensitive functionalities** (e.g., device pairing, audio recording, location sensing)



Source: <https://www.statista.com/topics/876/android/#dossierKeyfigures>


Static Permission Model

- Before Android 6.0
 - Ask users for permissions at install time
 - Cannot revoke permissions



Runtime Permission Model

- Introduced in Android 6.0 (in 2015)
- Request users for permissions at runtime
- Users can revoke granted permissions



Permission Management



- **Step 1:** Understand the required dangerous permissions

`requestLocationUpdates` Dangerous API Added in API level 3

```
public void requestLocationUpdates (String provider,
    long minTimeMs,
    float minDistanceM,
    PendingIntent pendingIntent)
```

Register for location updates using the named provider, and callbacks delivered via the provided `PendingIntent`.

The delivered pending intents will contain extras with the callback information. The keys used for the extras are `KEY_LOCATION_CHANGED` and `KEY_PROVIDER_ENABLED`. See the documentation for each respective extra key for information on the values.

To unregister for location updates, use `removeUpdates(android.app.PendingIntent)`.

See `requestLocationUpdates(java.lang.String, long, float, android.location.LocationListener)` for more detail on how this method works.

Requires `Manifest.permission.ACCESS_COARSE_LOCATION` or `Manifest.permission.ACCESS_FINE_LOCATION`

To invoke the location sensing API, the app needs to obtain either of the permissions:

- `ACCESS_COARSE_LOCATION`
- `ACCESS_FINE_LOCATION`

Permission Management



- **Step 2: Declare the required permissions** in `AndroidManifest.xml`

```
1 <manifest xmlns:android="http://schemas.android.com/apk/res/android"
2   package="com.developerplus">
3
4   <uses-permission android:name="android.permission.INTERNET" />
5   <uses-permission android:name="android.permission.CAMERA" />
6   <uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
7
8   <application
9     android:name=".MainApplication"
10    android:label="@string/app_name"
11    android:icon="@mipmap/ic_launcher"
12    android:roundIcon="@mipmap/ic_launcher_round"
13    android:allowBackup="false"
14    android:theme="@style/AppTheme">
15
16     <activity
17       android:name=".MainActivity"
18       android:label="@string/app_name"
19       android:configChanges="keyboard|keyboardHidden|orientation|screenSize"
20       android:windowSoftInputMode="adjustResize">
21       <intent-filter>
22         <action android:name="android.intent.action.MAIN" />
23         <category android:name="android.intent.category.LAUNCHER" />
24       </intent-filter>
25     </activity>
26     <activity android:name="com.facebook.react.devsupport.DevSettingsActivity" />
27   </application>
28 </manifest>
29
```

To tell the Android OS that the app might need the declared permissions at runtime

Permission Management




- Step 3: **Check permission status** before calling the dangerous API

```
if(checkSelfPermission(Manifest.permission.RECORD_AUDIO) == PackageManager.PERMISSION_GRANTED) {
```

- Step 4: **Request the permission** from users if not granted

```
String[] permissions = new String[]{Manifest.permission.RECORD_AUDIO};  
requestPermissions(permissions, 1001);
```



Permission Management



- Step 5: **Handle users' choices**
- Step 6: **Explain to users** why the permissions are necessary...

- The permission management process is quite complicated under the new model.
- Developers (especailly novices) may often make mistakes, thus inducing various **runtime permission issues**.

► Understanding Runtime Permission Issues

Research Questions

- **RQ1:** Are runtime permission issues common in real-world Android projects?
- **RQ2:** What are the common types of runtime permission issues?

For more RQs and findings, please refer to our TSE 2022 paper:

Ying Wang, Yibo Wang, Sinan Wang, Yepang Liu, Chang Xu, Shing-Chi Cheung, Hai Yu, and Zhiliang Zhu. “Runtime Permission Issues in Android Apps: Taxonomy, Practices, and Ways Forward.” *IEEE Transactions on Software Engineering*, 2022.

Empirical Findings



- We studied 415 popular open-source Android projects (hosted on GitHub), which declare at least one dangerous permission



FINDINGS

1. Runtime permission issues are common. We found **199 real issues** in the 415 projects.
2. The 199 real issues can be categorized into **11 types** according to their root cause.

Two Common Issue Types


- **Type-1 (Missing Permission Check):**
 - A dangerous API is called without a permission check on the target Android version
- **Type-2 (Incompatible Permission Usage):**
 - A dangerous API can be called on incompatible platforms, or the evolution of permission specification is not fully handled

Type-1 Issue Example

ML Manager:

- An APK manager
- 100,000+ downloads on Google Play

A **safe** scenario:




Type-1 Issue Example

ML Manager:

- An APK manager
- 100,000+ downloads on Google Play

A buggy scenario:



Type-2 Issue Example

- Type-2 issues are compatibility issues caused by the evolution of the Android framework

```
public class WiFiActivity extends Activity {  
    protected void onCreate(...) {  
        WifiManager wifiManager = getSystemService("wifi");  
        if(checkSelfPermission("ACCESS_COARSE_LOCATION") == 0) {  
            WifiInfo wifiInfo = wifiManager.getConnectionInfo();  
            Log.i(TAG, "ssid:" + wifiInfo.getSSID());  
        }  
    }  
}
```

- Before API level 29, `getSSID()` requires either COARSE or FINE location permission
- Since API level 29, `getSSID()` requires FINE location permission

The app does not work on Android 10 (API Level 29) or newer versions but works well on older versions (prior to Android 10).

► Detecting Runtime Permission Issues

Technical Challenges

- **Challenge 1:** Asynchronous permission managements and usages


- Android programs have multiple possible entry points (due to their event-driven nature)
- Permission check/request operations and permission use (at the call site of dangerous API) can be **in different callbacks**, or even **across different app components**

```
public class OptionsActivity extends Activity implements ... {  
    public void onSharedPreferenceChanged(...) {  
        // ...  
        if(checkSelfPermission("ACCESS_COARSE_LOCATION") != 0)  
            requestPermissions(  
                new String[]{"ACCESS_COARSE_LOCATION"}, 1000);  
        // ...  
    }  
  
    protected void onPause() {  
        // ...  
        // starts the LocationTrackerService  
        Basics.getOrCreateInstance(getApplicationContext())  
            .safeCheckLocationBasedTracking();  
    }  
}  
  
public class LocationTrackerService extends Service {  
    public int onStartCommand(...) {  
        // ...  
        // calls the requestLocationUpdates API  
        res = locationTracker.startTrackingByLocation(...)  
    }  
}
```

Permission check
and request

Dangerous
API call site

Possible Practices: Synchronous Management



(a) Intra-procedure

The intra-procedural case:

The permission check/request methods and the dangerous APIs are invoked in the same method

○ Normal Method



Component Lifecycle Callback




Permission Check or Request

○ Dangerous API



Method Call Relation

Possible Practices: Synchronous Management



(b) Inter-procedure

The inter-procedural case:

The permission check/request method calls are put in another wrapper method

○ Normal Method



Component Lifecycle Callback




Permission Check or Request

○ Dangerous API




Method Call Relation

Possible Practices: Asynchronous Management




The inter-callback case:

The permission check/request methods and the dangerous APIs are invoked in different callbacks of the same app component




Possible Practices: Asynchronous Management



The inter-component case:


The permission check/request methods and the dangerous APIs are invoked in different callbacks of different app components




How Common Are The Practices?

- Dataset: Google Play
 - Top-500 apps in 32 categories
 - Using at least one dangerous API and permission check/request API

apps: 13,352



How Common Are The Practices?




Technical Challenges

- **Challenge 2: Evolving API-permission mappings and mechanism**
 - API-permission mappings have been constantly changing over time
 1. Dangerous API additions and removals
 2. Same API corresponds to different permissions
 - Changes of permission mechanisms:
 1. Permission groups often change
 2. The introduction of one-time permission (Android 11)

Need to analyze app behaviors on different Android versions!

Calciati, P., Kuznetsov, K., Gorla, A., & Zeller, A. (2020, June). Automatically granted permissions in Android apps: An empirical study on their prevalence and on the potential threats for privacy. In Proceedings of the 17th International Conference on Mining Software Repositories (pp. 114-124).

The Aper Tool




Input:

- An app's APK file
- The mappings between APIs and permissions (extracted from framework code)

Output:

- Type-1 & Type-2 bugs
- Calling contexts of dangerous APIs (for debugging)


The Aper Tool



Context Extractor:

- Traverse the call graph to find the call sites of (also extract calling contexts):
 - Dangerous APIs
 - Permission check APIs


The Aper Tool



Dataflow Analyzer:

- Perform reaching-definition analysis on inter-procedural control-flow graph to infer two sets of facts:
 - Possible string values passed to the check APIs
 - Reachable runtime versions on which dangerous APIs can be called

The Aper Tool




Misuse detector:

- Leverage the API calling contexts and dataflow facts to detect Type-1 & Type-2 bugs

The Basic Idea

- Permission management should happen before dangerous API calls
(**domination requirement**)




(a) Intra-procedure


○ SHOULD happen-before ○

Domination relation between API call sites on control-flow graph.

○ Permission management (check & request) ○ Dangerous API

The Basic Idea




 Bugs may occur if we find **violations of the domination requirement** on the control-flow graph



Handling Asynchronous Cases

1. We consider the temporal order of callbacks by referring to the lifecycle model of app components




Handling Asynchronous Cases

2. We also built the inter-component communication graph following Li et al.’s work



The two steps allow us to know the execution order among callback methods, such that we can find the violations of the domination requirement even if the developers manage permissions asynchronously.



Li, L., Bartel, A., Bissyandé, T. F., Klein, J., Le Traon, Y., Arzt, S., ... & McDaniel, P. (2015, May). Iccta: Detecting inter-component privacy leaks in android apps. In 2015 IEEE/ACM 37th IEEE International Conference on Software Engineering (Vol. 1, pp. 280-291). IEEE.

Detecting Compatibility Issues

- We extend the previous domination requirement by further requiring that **the runtime version checks should dominate the call to the evolving dangerous APIs**

```
if (android.os.Build.VERSION.SDK_INT >= 16) {  
    SQLiteDatabase.disableWriteAheadLogging();  
}
```

Wei, L., Liu, Y., Cheung, S. C., Huang, H., Lu, X., & Liu, X. (2018). Understanding and detecting fragmentation-induced compatibility issues for android apps. *IEEE Transactions on Software Engineering*, 46(11), 1176-1199.

Evaluation

- **RQ3:** How effective is Aper in detecting runtime permission issues, compared with the existing tools?
- **RQ4:** Can Aper detect unknown issues in real-world apps?

The Baseline Tools

1. **ARPDroid**^[1]: For migrating pre-6.0 apps to new platforms
2. **RevDroid**^[2]: Find issues related to permission revocation
3. **Lint**^[3]: A rule-based checker in Android Studio

[1] Dilhara Malinda, Haipeng Cai, and John Jenkins. "Automated detection and repair of incompatible uses of runtime permissions in android apps." *Proceedings of the 5th International Conference on Mobile Software Engineering and Systems*. 2018.

[2] Fang, Zheran, et al. "revDroid: Code analysis of the side effects after dynamic permission revocation of android apps." *Proceedings of the 11th ACM on Asia Conference on Computer and Communications Security*. 2016.

[3] Lint. <https://developer.android.com/studio/write/lint>

The ARPfix Benchmark

- We built the benchmark from open-source Android projects:
 - ARP-related commits/PRs
 - Manually remove irrelevant code
 - Two versions for each issue: buggy/patched
 - Size:
 - Type-1: 35×2 APKs
 - Type-2: 25×2 APKs
- Available at: <https://github.com/sqlab-sustech/APER-ARPfix-benchmark>

The Metrics



- **True positives (TP):** # buggy versions on which a tool reports issues
- **True negatives (TN):** # patched versions on which a tool reports no issues
- **False positives (FP):** # patched versions on which a tool reports issues
- **False negatives (FN):** # buggy versions on which a tool reports no issues

$$Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN}$$

$$F_1 - score = \frac{2 \cdot Precision \cdot Recall}{Precision + Recall}$$

Tool Performance



Common Limitations of Existing Tools

- No explicit modeling of asynchronous permission management
 - This causes many false positives
- Does not take the API and permission evolution into consideration
 - Cannot effectively find Type-2 issues

Detecting Unknown Issues




- We used 214 open-source apps indexed by F-Droid for the experiment
 - Should use dangerous permissions
 - Should be actively maintained

	Detected	Verified	Recorded Video
Type-1	66	23	21
Type-2	18	11	3
Total	84	34	24

(unverified \neq false alarm)

All videos available at: <https://aper-project.github.io/>



Conclusion

- Runtime permission issues are common in Android apps
- We found 11 types of runtime permission issues from open-source projects
- We built a static analyzer, Aper, to detect two prominent types of issues
- Future work:
 - Study runtime permission issues caused by the interference of third-party libraries
 - Improve the Aper tool (support more issue types, reduce false positives)

Thanks for Listening!

Aper is open-sourced at: <https://github.com/sqlab-sustech/APER-tool/>

Contact us: liuyp1@sustech.edu.cn