

TEE API의 정형 명세 및 모델 검증

유근열

POSTECH

커지는 보안의 중요성



무단 도용 방지
(저작권 보호)

자산 탈취 방지
(결제 정보 보호)




SAMSUNG
pay



→ 기존보다 더 강력한 보안 요구

Secure OS

연산을 보호된 환경에서 처리하는 운영체제



Secure OS 표준 문서

TEE API

memory

storage

timer

crypto

I/O

event

session

calc

GLOBALPLATFORM[®]
THE STANDARD FOR SECURE DIGITAL SERVICES AND DEVICES

GlobalPlatform Technology
TEE Internal Core API Specification
Version 1.1.2.50 (Target v1.2)

Public Review
June 2018
Document Reference: GPD_SPE_010

Copyright © 2011-2018 GlobalPlatform, Inc. All Rights Reserved.
Recipients of this document are invited to submit, with their comments, notification of any relevant patents or other intellectual property rights (collectively, "IPR") of which they may be aware which might be necessarily infringed by the implementation of the specification or other work product set forth in this document, and to provide supporting documentation. The technology provided or described herein is subject to updates, revisions, and extensions by GlobalPlatform. This documentation is currently in draft form and is being reviewed and enhanced by the Committees and Working Groups of GlobalPlatform. Use of this information is governed by the GlobalPlatform license agreement and any use inconsistent with that agreement is strictly prohibited.

연구 동기

- 표준 명세 자체에 설계 결함이 있다면?
- 표준 명세를 따른 구현이 명세 요구 사항을 만족하는가?

→ 검증의 필요성

어려운 점


- 문서를 읽고 정형 명세하는 것 자체에 많은 노력과 시간이 필요
 - 자연어로 적힌 문서 → 모호한 표현 해석 필요
- 동시성을 어떻게 고려할 것인가?
 - Code-based testing & static analysis로는 하기 어려움
- 구현 되어있는 Real-world 프로그램을 어떻게 검증할 것인가?
 - Real-world 프로그램은 C/C++로 작성되어 있음

연구 전략

- 문서를 읽고 정형 명세하는 것 자체에 많은 노력과 시간이 필요
 - → 열심히 하자!
- 동시성을 어떻게 고려할 것인가?
 - → Maude로 명세
- 구현 되어있는 Real-world 프로그램을 어떻게 검증할 것인가?
 - → C-like language 지원

TEE 정형 명세

- 주요 컴포넌트 정의 및 명세
 - 어플리케이션, 커널, TEE 리소스



TEE 정형 명세

- TEE 표준 API 모델링

| Category | Types | # APIs |
|----------------|-----------------------|--------|
| Secure Storage | Generic | 5 |
| | Transient | 8 |
| | Persistent | 4 |
| | Persistent Enumerator | 5 |
| | Data Stream Access | 4 |

| Category | Types | # APIs |
|-------------------------|-------------------------------------|--------|
| Cryptographic Operation | Generic | 9 |
| | Symmetric Cipher & MAC | 7 |
| | Authenticated Encryption | 5 |
| | Asymmetric & Random Data Generation | 5 |
| | Key Derivation & Message Digest | 4 |

TEE 정형 명세

- Real-world 프로그램 검증 위한 언어 실행 지원
 - C-like 프로그램 syntax

```
struct Person { var age } ;  
Person john ; john.age = 0 ;  
while (john.age < 10) { john.age += 1 }
```

- C-like 프로그램 semantics
 - Memory model (x) multi-threading (x)

TEE 모델 검증 예시

- TEE API spec 검사
 - Reachable state analysis, LTL model checking

```
search run(teeApi)  $\Rightarrow^*$  RESULT such that checkSpec(RESULT) .  
red modelCheck(teeApi, [] invariant(teeApi)) .
```

- TEE 프로그램 검증
 - E.g., process2는 항상 process1 보다 나중에 끝나야 함

```
red modelCheck(init(proc1) init(proc2), [] exitAfter(proc1, proc2)) .
```

- 상태 공간 축소 기법
 - Invisible transition reduction, partial order reduction

Case study: MQT-TZ


- IoT message protocol을 사용한 real-world 프로그램
 - TEE를 사용하여 message 탈취 방지
- TEE 여부에 따른 message 탈취 가능성 검증

| # Msg | # State | Time | # Msg | Intruder | Intercept | Max Trial | # State | Time |
|-------|---------|-------|-------|----------|-----------|-----------|----------|----------|
| 1 | 15112 | < 100 | 1 | O | T | 25 | 59304 | 7.828 |
| 2 | 77784 | | | X | ⊥ | 25 | 395576 | 17.408 |
| 3 | 254632 | | 2 | O | T | 25 | 59740 | 8.352 |
| 4 | 677880 | | | X | ⊥ | 25 | 22633856 | 2543.146 |
| 5 | 1611976 | | 3 | O | T | 25 | 59740 | 8.367 |
| 6 | 3585832 | | | X | ⊥ | 25 | - | T/O |
| 7 | 7657224 | | 4 | - | - | 25 | - | T/O |



BACKGROUND

- A trusted execution environment (TEE) is an isolated code execution environment to provide high-level of trust.
- Global Platform defines standard APIs and architectures for TEE and device vendors provide their own TEE implementations.
- Maude is a language and tool for formal specification and analysis of distributed systems.



MOTIVATION


- What if there is a design flaw in the standard APIs?
- Does a TEE implementation follow the standard?
- Is a TEE application safe and bug-free?

CHALLENGE

- Specifying the standard APIs is itself challenging.
 - e.g., free all the resources (?) after TEE_FreeTransientObject.
- How to verify concurrent behaviours?
 - code-based testing (x), code-based static analysis (x).
- How to verify real-world TEE applications only with their code?

FORMAL SPECIFICATION OF TEE IN MAUDE

- Specify models for trusted & rich applications.
- Specify abstracted objects for REE & TEE kernels.
- Specify objects representing TEE resources.
 - handle objects, secure storage objects, cryptographic objects.
- Define overall relations b/w them.



- Specify the standard TEE APIs.

| Category | Types | # API | Category | Types | # API |
|----------------|--------------------|-------|------------------|-------------------------------|-------|
| Secure Storage | Generic | 5 | Crypto Operation | Generic | 9 |
| | Transient | 8 | | Symmetric Cipher & MAC | 7 |
| | Persistent | 5 | | Authenticated Encryption | 5 |
| | Enumerator | 4 | | Asymmetric & Message Digest | 7 |
| | Data Stream Access | 4 | | Key Deriv. & Rand. Generation | 4 |

PROGRAMMING LANGUAGE SEMANTICS FOR TEE

- C-like language syntax.
 - e.g., structure, if-else, loop, function call.
- ```

struct Person { var age } ;
Person john ; john.age = 0 ;
while (john.age < 10) { john.age += 1 }

```
- C-like language semantics.
    - memory model (x), multi-threading (x), executing a program (o)

## FORMAL VERIFICATION OF TEE USING MAUDE

- Verify the TEE formal specification using Maude.
    - reachable state analysis, LTL model checking
- ```


search teeApi => * STATE such that checkSpec(STATE) .
red modelCheck(teeApi, [] invariant(teeApi)) .
    
```
- Verify real-world TEE applications using Maude.
 - using C-like language semantics
 - high-level behaviour analysis (o), code-level analysis (x)
 - e.g., program2 always exits after program1
- ```

red modelCheck(init(p1 p2), [] exitAfter(p1, p2)) .

```


## STATE SPACE REDUCTION

- Invisible transition reduction
  - reduce a transition b/w equivalent states.
  - i.e., remove stuttering equivalent paths.



- Partial order reduction
  - explore only necessary paths w.r.t independent relations.
  - i.e., do not consider all interleavings.

## CASE STUDY: MQT-TZ IOT APPLICATION



- MQTT is a standard messaging protocol for the IoTs.
- MQT-TZ protects MQTT broker using TEE.
  - preventing message interception, modification
- Analyzing MQT-TZ using formal specification.
  - Model an intruder that tries to intercept messages.
  - Simulate the intruder can intercept a message w/o TEE.
  - Verify the intruder fails to intercept any message w/ TEE.

| # Msg | # State | Time  | # Msg | Intruder | Intercept | Max Trial | # State  | Time     |
|-------|---------|-------|-------|----------|-----------|-----------|----------|----------|
| 1     | 15112   | < 100 | 1     | O        | T         | 25        | 59304    | 7.828    |
| 2     | 77784   |       | 2     | X        | ⊥         | 25        | 395576   | 17.408   |
| 3     | 254632  |       | 2     | O        | T         | 25        | 59740    | 8.352    |
| 4     | 677880  |       | 2     | X        | ⊥         | 25        | 22633856 | 2543.146 |
| 5     | 1611976 |       | 3     | O        | T         | 25        | 59740    | 8.367    |
| 6     | 3585832 |       | 3     | X        | ⊥         | 25        | -        | T/O      |
| 7     | 7657224 |       | 4     | -        | -         | 25        | -        | T/O      |