

IRCBot Lua Reference



[Github Repository](#)

» [Main Lua Function](#)

» [Functions](#)

- › [Data](#)
- › [Connection](#)
- › [Messaging](#)
- › [Access Managing](#)

Main Lua Function

function main(messageData,messageComponents,ircbot)

The main function that is called when executing a .lua file

messageData is an array of message components, it contains

Objects:	raw	sender	hostmask	msgType	sentTo	message
Location:	1	2	3	4	5	6

messageComponents is a subarray of messagedata's message.

Functions

Data

ircbot:getRooms()

Returns an array of rooms the bot is connected to.
Array((roomName, roomStatus), (roomName, roomStatus), ...)

ircbot:getActions()

Returns an array containing all the actions the bot can do.
Actions are prefixed with a + if they are restricted and a - if they aren't

ircbot:getTriggers()

Returns an array containing the triggers the bot currently responds to.

ircbot:getNickname()

Returns the the bots IRC nickname as a utf8_string.

ircbot:getVersion()

Returns the current version number as a utf8_string.

Connection

ircbot:`disconnectWithMessage(message)`

Disconnects from the IRC server with the specified quit message

Note: message sometimes don't work, especially if you disconnect right after connecting

ircbot:`joinRoom(roomName)`

Joins the specified irc room.

ircbot:`partRoom(roomName)`

Parts the specified irc room.

Messaging

ircbot:`sendMessage_to_(message, recipient)`

Sends a IRC message to the recipient.

If you want more control you can always use, ircbot:`sendRawMessage(message)`.

ircbot:`sendNotice_to_(message, recipient)`

Sends a irc notice to recipient.

If you want more control you can always use, ircbot:`sendRawMessage(message)`.

ircbot:`sendActionMessage_to_(message, recipient)`

Sends a irc action message to recipient.

ircbot:`sendRawMessage(message)`

Sends a raw IRC message to the irc server.

For correct formatting see: [RFC 1459](#).

Access Managing

ircbot:`addHostmask_block_(hostmask, boolean)`

Adds the hostmask to the hostmask list with boolean to specify if it should be blocked.

ircbot:`removeHostmask(hostmask)`

Removes the specified hostmask from the hostmask list.

ircbot:`blockHostmask(hostmask)`

Blocks the specified hostmask from using any actions.

ircbot:`unblockHostmask(hostmask)`

Unblocks the specified hostmask and allows it to use the unrestricted actions.

ircbot:`checkAuthFor(hostmask)`

Checks if the specified hostmask is blocked.