

Guides and gravity in McStas

Mads Bertelsen



Works at ESS DMSC on McStas development

Overview

- Description of phase-space and propagation
- Reflectivity
- McStas coordinate system
- Gravitation in McStas
- Guide components with support for gravity
 - Guide_gravity
 - Elliptic_guide_gravity
- Ballistic guide
- Breaking line of sight
- Examples from guide_bot
- Exercise



Beam propagation in free space

“Phase-space” at source





Beam propagation in free space



Wanted “phase-space” at sample





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space





Beam propagation in free space



Beam propagation in free space





Beam propagation in free space





Beam propagation in free space

- We lost some phase-space to propagation





Beam propagation in guide



Wanted “phase-space” at sample





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide





Beam propagation in guide



Beam propagation in guide





Beam propagation in guide



Beam propagation in guide



With a guide we lost less phase-space area!



Reflectivity curves



- Reflectivity, super mirror, reflectivity curve

$$m = \frac{\theta_{mirror}}{\theta_{Ni}}$$



Reflectivity curves in McStas


$$R(q) = \begin{cases} R_0 & \text{if } q < q_c \\ R_0(1 - \tanh((q - mq_c)/W))(1 - \alpha(q - q_c))/2 & \text{otherwise} \end{cases}$$



$= 0$
 $W = 0$
 Only m matters
 Better mirrors
 available today

Guide placement in McStas

- The center is the front of the guide element
- Tip: Insert a guide at the end of the guide



Gravitation in McStas

- Enabled by adding `-g / --gravitation` on command line or by selecting “Gravity On” in mcgui

- Default ~ gravity on earth

```
#define GRAVITY 9.81 /* [m/s^2] gravitational acceleration */
```

(If on the moon, use `-DGRAVITY=1.62` ;-))

- For guides, only `Guide_gravity` and `Elliptic_guide_gravity` support parabolic propagation. (Many others propagate linearly in *v direction*.)


- As you will see in the practical, implications are greatest with long wavelengths and at long distances

- “How about e.g. elliptic mirror optic X that does not support gravity?”

- often a good workaround is to add a monitor close to the surface of object X, this takes care that propagation up to the monitor includes gravitation:


- Gravity is enabled in any call to `PROP_DT`, `PROP_Z0` etc., but not in `intersect_*` routines (most monitors use `PROP_Z0` directly, no `intersect_*` call first

- OK to propagate without gravitation e.g. within sample, through velocity selector etc. / range of ~cm’s




Popular guide components: Guide_gravity

- Typical guide component with gravity, parameter-interface similar to e.g. Guide.comp
- Many additional features, channels, fermi chopper, ... (see mcdoc pages for more info)





Popular guide components: Guide_gravity

- Typical guide component with gravity, parameter-interface similar to e.g. Guide.comp
- Many additional features, channels, fermi chopper, ... (see mcdoc pages for more info)



Popular guide components: Guide_gravity


- Typical guide component with gravity



Popular guide components: Elliptical_guide_gravity



- Useful for elliptic and parabolic guide geometries, focusing, ballistic, coating distribution, ...

xwidth and yheight at DimensionsAt = "entrance" , "mid" or "exit"




Popular guide components: Elliptical_guide_gravity

- Useful for elliptic and parabolic guide geometries, focusing, ballistic, coating distribution, ...




Comparison: Guide_gravity and Elliptic_guide_gravity



Guide_gravity




Elliptic_guide_gravity




Balistic guide



Balistic guide with gravity





With gravity




Balistic guide with and without gravity

With gravity




Breaking line of sight

- Importance of breaking line of sight, ways of doing so, ...









Breaking line of sight

- Bender / Guide_curved component or many straight sections
Mind the gaps, avoid overlap



Guide optimization

- Optimization result from MATLAB guide_bot
- Python guide_bot available



Guide optimization

- Optimization results from python guide_bot
- `pip install guide_bot --upgrade`

In [13]: `results.plot_any_monitor()`

Data source

monitor:

run_name:

moderator:

Scanned sample parameters

height:

max_wavel...:

Scanned moderator parameters

height:


Guide selection

☐ Guide_SGS

☒ Guide_EGE

☐ Guide_SCS

☐ Guide_E



In [11]: `results.plot_guide()`

Data source

moderator:

Scanned sample parameters

height:

max_wavel...:

Scanned moderator parameters

height:

Guide selection

☐ Guide_SGS



☐ Guide_EGE

☒ Guide_SCS

☐ Guide_E

Fom slider

Worst Best



Solution on github, use if you are stuck

Guide exercise

- Start with instrument file provided on github
- **Task 1)**
 - Compare output for two different guide lengths
- **Task 2)**
 - Introduce a parameter that control width of the guide
 - Compare two runs with different guide widths
- **Task 3)**
 - Check how much gravity impacts the output
- **Task 4)**
 - Exchange the last 20% of the guide with an elliptic nose.
 - See the geometry with mcdisplay
 - Identify how the resulting beam have changed