

RESEARCH

Physcraper: A Python package for continually updated phylogenetic trees using the Open Tree of Life

Luna L. Sanchez Reyes^{1*}, Martha Kandziora^{1,2} and Emily Jane McTavish^{1*}

*Correspondence:
sanchez.reyes.luna@gmail.com;
ejmctavish@ucmerced.edu

¹School of Natural Sciences,
 University of California, Merced,
 USA

Full list of author information is
 available at the end of the article

Abstract

Background: Phylogenies are a key part of research in many areas of biology. Tools that automate some parts of the process of phylogenetic reconstruction, mainly molecular character matrix assembly, have been developed for the advantage of both specialists in the field of phylogenetics and non-specialists. However, interpretation of results, comparison with previously available phylogenetic hypotheses, and selection of one phylogeny for downstream analyses and discussion still impose difficulties to one that is not a specialist either on phylogenetic methods or on a particular group of study.

Results: Physcraper is a command-line Python program that automates the update of published phylogenies by adding public DNA sequences to underlying alignments of previously published phylogenies. It also provides a framework for straightforward comparison of published phylogenies with their updated versions, by leveraging upon tools from the Open Tree of Life project to link taxonomic information across databases. The program can be used by the nonspecialist, as a tool to generate phylogenetic hypotheses based on publicly available expert phylogenetic knowledge. Phylogeneticists and taxonomic group specialists will find it useful as a tool to facilitate molecular dataset gathering and comparison of alternative phylogenetic hypotheses (topologies).

Conclusions: The Physcraper workflow showcases the benefits of doing open science for phylogenetics, encouraging researchers to strive for better sharing practices. Physcraper can be used with any OS and is released under an open-source license. Detailed instructions for installation and usage are available at <https://physcraper.readthedocs.io>.

Keywords: gene tree; interoperability; open science; reproducibility; public database; DNA alignment

Background

Phylogenies capture the shared history of organisms and provide key evolutionary context for our biological observations [1]. The Open Tree of Life project (OpenTree) constructs a comprehensive tree of life by synthesizing published phylogenies and taxonomy. OpenTree's "synthetic" tree comprises 2.3 million tips, of which around 90,000 (87,740) are supported by phylogenies - the remaining 1.4 million taxa are placed in the tree based on taxonomy. Meaning that there is still a lot of work to do to complete a full phylogenetic tree of all life.

Decades of single locus sequencing have generated massive amounts of homologous DNA datasets that have the potential to be used for phylogenetic reconstruction

at many scales [2]. More than a decade ago, GenBank release 159 (April 15, 2007) already hosted 72 million DNA sequences that were gauged to have the potential to resolve phylogenetic relationships of 98.05% of the almost 241,000 distinct taxa in the NCBI taxonomy at the time [2].

With more than XXXX million single locus sequences in GenBank today, there is a considerable amount of phylogenetically informative data in GenBank that has not been analysed and/or made publicly available with the potential to give phylogenetic light to the tree of life.

Phylogenies constructed from single locus super matrix datasets are still widely generated and relevant to the field. Notable examples include the

Notable examples of phylogenies constructed using multi-locus, database mined, super matrix approach: Magallon, Soltis, examples with fish, bats, [3] mining by hand - flowering plant families - has been cited 561 times [4] 38k clades of plants with seeds - cited 176 times [5] 6k bird species - cited [6] mining with phlawd - cited 202 times

These studies are widely cited and immensely relevant for the biological community.

Some of these multilocus phylogenetic studies have implemented pipelines such as PHLAWD, other studies have curated their matrices by hand, which is largely non-reproducible.

Make emphasis on these really great studies (and pipelines) that do not rely on genomic data, and that there is a lot of single locus data that can be analysed.

Assembling a DNA alignment from such a massive database can be done "by hand", but it is a largely time consuming and mostly non-reproducible approach. Computational pipelines that mine DNA databases fast, efficiently, and reproducibly, have been applied to infer phylogenetic relationships in a variety of organisms (e.g., [7, 8, 9]). However, fine-grained curated markers and alignments can improve phylogenetic reconstructions, even in phylogenomic analyses [10].

There are almost 8,200 publicly available, peer-reviewed alignments, covering around 100,000 distinct taxa in the TreeBASE database [11], which can be used as seeds to mine molecular databases, and as "jump-start" alignments for phylogenetic reconstructions [12] to continually enrich, update and compare existing phylogenetic knowledge.

Taxonomic idiosyncrasies across databases represent a huge challenge for automatic integration of data into phylogenies, which can be addressed with a unified taxonomy for name standardization.

To achieve this, OpenTree unifies taxonomic data from various databases [13], including the USA National Center for Biodiversity Information (NCBI) molecular database GenBank [14], among others. The OpenTree taxonomy represents a key resource for connecting data from any biological database that has been integrated to it.

Physcraper is a Python pipeline using OpenTree's taxonomy and programmatic access protocols (API's) to implement a database interoperability framework that automatically links phylogenies that have been standardized to OpenTree taxonomy, to alignments from TreeBASE, data from GenBank, and phylogenies from

OpenTree's Phylesystem. Physcraper aims to demonstrate the benefits of reproducible workflows and open science in phylogenetics, and encourage better data sharing practices in the community.

Implementation

The general Physcraper framework (Figure 1) consists of 4 steps: 1) identifying and processing a tree and its underlying alignment; 2) performing a BLAST search of DNA sequences from original alignment on GenBank, and filtering of new sequences; 3) profile-aligning new sequences to original alignment; 4) performing a phylogenetic analysis and comparing the updated tree to existing phylogenies.

The inputs: a tree and an alignment

Taxon names in the input tree must be standardized to OpenTree taxonomy [13] using OpenTree's bulk Taxonomic Name Resolution Service [TNRS](#) tool. Users can upload their own tree, or choose from among the 2,950 standardized trees stored in OpenTree's [Phylesystem](#) that also have alignments available on TreeBASE [11].

The input alignment is a single locus DNA dataset that was used in part or in whole to generate the input tree. Physcraper retrieves TreeBASE alignments automatically. Alternatively, users must provide the path to a local copy of the alignment. Only taxa that are both in the sequence alignment and in the tree are considered further for analysis; at least one taxon and its corresponding sequence are required.

DNA sequence search and filtering

The Basic Local Alignment Search Tool, BLAST [15] is used for DNA sequence search on a remote or local GenBank database. It is constrained to a "search taxon", a taxonomic group in the NCBI taxonomy that is automatically identified using the OpenTree [API](#) [13], as the most recent common ancestor of ingroup taxa that is also a named clade in the NCBI taxonomy (Figure 1).

BLAST is implemented with the 'blastn' function [16] and the BioPython [17] BLAST function from [NCBIWWW module](#) modified to accept an alternative BLAST address. Each sequence in the alignment is BLASTed once against all DNA sequences in GenBank. New sequences are excluded for analysis if they 1) are not in the search taxon; 2) have an e-value above the cutoff (default to 0.00001); 3) fall outside a min and max length threshold, defined as the proportion of the average length without gaps of all sequences in input alignment (default values of 80 respectively); 4) or if they are either identical to or shorter than an existing sequence in the input alignment and they represent the same taxon in OpenTree or NCBI taxonomy. An arbitrary maximum number of randomly chosen sequences per taxon are allowed (default to 5).

Reverse, complement, and reverse-complement sequences are identified and translated using BioPython internal functions [17]. Iterative cycles of BLAST searches can be performed, by blasting all new sequences until no new ones are found. By default only one BLAST cycle is performed.

New DNA sequence alignment

MUSCLE [18] is used to perform a profile alignment in which the original alignment is used as a template of homology criteria to align new sequences. The final alignment is not further automatically checked, and additional inspection and refinement are recommended.

Tree reconstruction and comparison

RAxML [19] is implemented to reconstruct a Maximum Likelihood (ML) gene tree for each input alignment with default settings (GTRCAT model and 100 bootstrap replicates with default algorithm), using input tree as starting tree for ML searches. Bootstrap results are summarized using DendroPy's SumTrees module [20].

Physcraper's main result is an updated phylogenetic hypothesis for the search taxon. Updated and original tree are compared with Robinson-Foulds weighted and unweighted metrics estimated with Dendropy [20], and with a node by node comparison between the synthetic OpenTree and original and updated tree individually, using OpenTree's conflict API [21].

Results

Case Study: The hollies

A user is interested in phylogenetic relationships within the genus *Ilex*. Commonly known as "hollies", the genus encompasses between 400-700 living species, and is the only extant clade within the family Aquifoliaceae, order Aquifoliales of flowering plants.

An online literature review in June 2020 (Google scholar search for "ilex phylogeny") reveals that there are several published phylogenies showing relationships within the hollies [22, 23, 24, 25], but only two have data publicly available [26, 27]. [26] made original tree and alignment available in TreeBASE study 1091. The tree sampling 41 species was also added to OpenTree's Phylesystem study pg_2827 and it has been integrated into OpenTree's synthetic tree [here](#).

The most recent *Ilex* tree [27] is available in OpenTree's Phylesystem study ot_1984 and in the DRYAD repository [28]. With 175 tips, the [27] tree is the best sampled phylogeny yet available for the hollies.

We ran Physcraper on a laptop Linux computer to update an internal transcribed spacer DNA region (ITS) alignment from [26], using a local GenBank database. BLAST and RAxML analyses ran for 19hrs 45min, with bootstrap analyses taking an additional 13hrs. The updated [26] tree (Figure 2) displays all 41 distinct taxa from the original study plus 231 new tips, contributing phylogenetic data to 84 additional *Ilex* taxa. The best RaxML tree is 99% resolved, with 25% of nodes with bootstrap support < 0.1 and 48% nodes with bootstrap support > 0.75. A large portion of internal branches are negligibly small, with 30 branches < 0.00001 substitution rate units, from which only 9 have a bootstrap support > 0.75 (Figure 2). For comparison, [27] also contains all 41 distinct taxa from the original [26] study, and contributes phylogenetic data to 134 additional *Ilex* taxa, from which 'r 135-68' are also in updated [26]. While [27] also used ITS as a marker, their GenBank data is not released yet, so Physcraper was unable to incorporate 68 additional taxa into the analysis. However, Physcraper was able to incorporate 18 taxa that were not in [27].

Discussion

Databases preserving and democratizing access to biological data have become essential resources for science. New molecular data keep accumulating and tools facilitating its integration into existent evolutionary knowledge are needed.

Phylogenetic pipelines designed to make evolutionary sense of the vast amount of public molecular data (e.g., Phylota [2], PHLAWD [7], SUPERSMART [8]) focus on generating full phylogenies *de novo*, i.e., inferring phylogenetic relationships from a newly generated homology hypothesis, as opposed to e.g., supertrees, that are generated by summarizing previous phylogenetic estimates. While Physcraper does not generate phylogenies *de novo* in a traditional sense, it successfully generates new phylogenetic knowledge, revealing the importance of open science in facilitating phylogenetic placement of public molecular data and accelerating enrichment and updating of phylogenetic relationships in any region of the tree of life. The PUMPER pipeline [9] also uses the concept of updating pre-existing alignments to incorporate public molecular data into phylogenies. Unfortunately, installation was unsuccessful following instructions from the author, and a comparison analysis between Physcraper and PUMPER is unfeasible at present.

Physcraper generates individual gene trees, failing to capture the complexity of species' evolutionary history [29]. Yet, Physcraper facilitates gathering alignments and gene trees for multiple loci from a group of interest, that can be used to reconstruct species trees with ASTRAL [30], BEAST2 [31], or SVD Quartets [32]).

Physcraper can potentially link phylogenies to data available in any of the taxonomies integrated in the OpenTree taxonomy [13], such as geographical locations from the Global Biodiversity Information Facility, or fossils from the Paleobiology Database. The Physcraper workflow can be used to rapidly (in a matter of hours) address challenges overarching both fields of ecology and evolution, such as phylogenetically placing newly discovered species [33], systematizing molecular (and other) databases, i.e., curating taxonomic assignments [34], and generating custom trees for ecological [35] and evolutionary downstream analyses [36].

Data repositories hold more information than meets the eye. Beyond the main data, they are rich sources of metadata that can be leveraged for the advantage of all areas of biology as well as the advancement of scientific policy and applications. Initial ideas about the data are constantly changed by results from new analyses. Physcraper provides a framework for reproducible phylogenetics that has the potential to consistently provide context for these ideas, highlighting the importance of data sharing and open science in the field, biology and science.

Conclusions

Text for this section...

Availability and requirements

Project name: Physcraper

Project home page: <https://physcraper.readthedocs.io/en/latest/index.html>

Operating System: Linux, Mac, Windows

Programming Language: Python

Other requirements: Dependencies

License: GNU

Any restrictions to use by non-academics: As specified by the License

Abbreviations

OpenTree: The Open Tree of Life project

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The datasets generated and analysed during the current study are available in the repositories "physcraper" containing the source code, <https://github.com/McTavishLab/physcraper>; "physcraperex" containing the examples, <https://github.com/McTavishLab/physcraperex>; and, "physcraper.ms" containing this reproducible manuscript, <https://github.com/McTavishLab/physcraper.ms>.

Competing interests

The authors declare that they have no competing interests.

Funding

This research was supported by the grant "Sustaining the Open Tree of Life", NSF ABI No. 1759838, and ABI No. 1759846. Computer time was provided by the Multi-Environment Research Computer for Exploration and Discovery (MERCED) cluster from the University of California, Merced (UCM), supported by the NSF Grant No. ACI-1429783.

Authors' contributions

LLSR wrote manuscript, alignment code, documentation, performed analyses and developed examples; MK wrote code for ncbidataparser module, filtering of sequences per OTU and using offline blast searches, wrote documentation and tests; EJM conceived study, wrote most of the code, documentation and tests. All authors contributed to the manuscript and gave final approval for publication. . . .

Acknowledgements

We thank the members of the OpenTree development team and the "short bar" Science and Engineering Building 1, UCM, joint lab paper discussion group for valuable comments on this manuscript.

Author details

¹School of Natural Sciences, University of California, Merced, USA. ²Department of Botany, Faculty of Science, Charles University, Prague, Czech Republic.

References

1. Dobzhansky, T.: Nothing in biology makes sense except in the light of evolution. *The American Biology Teacher* **35**(3), 125–129 (1973)
2. Sanderson, M.J., Boss, D., Chen, D., Cranston, K.A., Wehe, A.: The PhyLoTA Browser: Processing GenBank for Molecular Phylogenetics Research. *Systematic Biology* **57**(3), 335–346 (2008). doi:[10.1080/10635150802158688](https://doi.org/10.1080/10635150802158688). <https://academic.oup.com/sysbio/article-pdf/57/3/335/24203605/57-3-335.pdf>
3. Magallón, S., Gómez-Acevedo, S., Sánchez-Reyes, L.L., Hernández-Hernández, T.: A metacalibrated time-tree documents the early rise of flowering plant phylogenetic diversity. *New Phytologist* **207**(2), 437–453 (2015)
4. Smith, S.A., Brown, J.W.: Constructing a broadly inclusive seed plant phylogeny. *American Journal of Botany* **105**(3), 302–314 (2018). doi:[10.1002/ajb2.1019](https://doi.org/10.1002/ajb2.1019)
5. Jetz, W., Thomas, G., Joy, J.J.B., Hartmann, K., Mooers, A.: The global diversity of birds in space and time. *Nature* **491**(7424), 444–448 (2012). doi:[10.1038/nature11631](https://doi.org/10.1038/nature11631)
6. Rabosky, D.L., Chang, J., Title, P.O., Cowman, P.F., Sallan, L., Friedman, M., Kaschner, K., Garilao, C., Near, T.J., Coll, M., *et al.*: An inverse latitudinal gradient in speciation rate for marine fishes. *Nature* **559**(7714), 392–395 (2018)
7. Smith, S.A., Beaulieu, J.M., Donoghue, M.J.: Mega-phylogeny approach for comparative biology: an alternative to supertree and supermatrix approaches. *BMC Evolutionary Biology* **9**(1), 37 (2009). doi:[10.1186/1471-2148-9-37](https://doi.org/10.1186/1471-2148-9-37)
8. Antonelli, A., Hettling, H., Condamine, F.L., Vos, K., Nilsson, R.H., Sanderson, M.J., Sauquet, H., Scharn, R., Silvestro, D., Töpel, M., *et al.*: Toward a self-updating platform for estimating rates of speciation and migration, ages, and relationships of taxa. *Systematic Biology* **66**(2), 152–166 (2017). doi:[10.1093/sysbio/syw066](https://doi.org/10.1093/sysbio/syw066)
9. Izquierdo-Carrasco, F., Cazes, J., Smith, S.A., Stamatakis, A.: Pumper: phylogenies updated perpetually. *Bioinformatics* **30**(10), 1476–1477 (2014). doi:[10.1093/bioinformatics/btu053](https://doi.org/10.1093/bioinformatics/btu053)
10. Fragoso-Martínez, I., Salazar, G.A., Martínez-Gordillo, M., Magallón, S., Sánchez-Reyes, L., Lemmon, E.M., Lemmon, A.R., Sazatornil, F., Mendoza, C.G.: A pilot study applying the plant Anchored Hybrid Enrichment method to New World sages (*Salvia* subgenus *Calosphaea*; Lamiaceae). *Molecular Phylogenetics and Evolution* **117**, 124–134 (2017). doi:[10.1016/j.ympev.2017.02.006](https://doi.org/10.1016/j.ympev.2017.02.006)

11. Piel, W., Chan, L., Dominus, M., Ruan, J., Vos, R., Tannen, V.: Treebase v. 2: A database of phylogenetic knowledge. e-Biosphere. London (2009)
12. Morrison, D.A.: Multiple sequence alignment for phylogenetic purposes. Australian Systematic Botany **19**(6), 479–539 (2006). doi:[10.1071/SB06020](https://doi.org/10.1071/SB06020)
13. Rees, J.A., Cranston, K.: Automated assembly of a reference taxonomy for phylogenetic data synthesis. Biodiversity Data Journal (5) (2017). doi:[10.3897/BDJ.5.e12581](https://doi.org/10.3897/BDJ.5.e12581)
14. Benson, D.A., Karsch-Mizrachi, I., Lipman, D.J., Ostell, J., Rapp, B.A., Wheeler, D.L.: Genbank. Nucleic Acids Research **28**(1), 15–18 (2000). doi:[10.1093/nar/28.1.15](https://doi.org/10.1093/nar/28.1.15)
15. Altschul, S.F., Gish, W., Miller, W., Myers, E.W., Lipman, D.J.: Basic local alignment search tool. Journal of Molecular Biology **215**(3), 403–410 (1990). doi:[10.1016/S0022-2836\(05\)80360-2](https://doi.org/10.1016/S0022-2836(05)80360-2)
16. Camacho, C., George, C., Vahram, A., Ning, M., Jason, P., Kevin, B., Thomas, L.: BLAST+: Architecture and applications. BMC Bioinformatics **10**(1), 421 (2009). doi:[10.1186/1471-2105-10-421](https://doi.org/10.1186/1471-2105-10-421)
17. Cock, P.J., Antao, T., Chang, J.T., Chapman, B.A., Cox, C.J., Dalke, A., Friedberg, I., Hamelryck, T., Kauff, F., Wilczynski, B., et al.: Biopython: freely available Python tools for computational molecular biology and bioinformatics. Bioinformatics **25**(11), 1422–1423 (2009). doi:[10.1093/bioinformatics/btp163](https://doi.org/10.1093/bioinformatics/btp163)
18. Edgar, R.C.: Muscle: multiple sequence alignment with high accuracy and high throughput. Nucleic Acids Research **32**(5), 1792–1797 (2004). doi:[10.1093/nar/gkh340](https://doi.org/10.1093/nar/gkh340)
19. Stamatakis, A.: Raxml version 8: a tool for phylogenetic analysis and post-analysis of large phylogenies. Bioinformatics **30**(9), 1312–1313 (2014). doi:[10.1093/bioinformatics/btu033](https://doi.org/10.1093/bioinformatics/btu033)
20. Sukumaran, J., Holder, M.T.: DendroPy: a Python library for phylogenetic computing. Bioinformatics **26**(12), 1569–1571 (2010). doi:[10.1093/bioinformatics/btq228](https://doi.org/10.1093/bioinformatics/btq228)
21. Redelings, B.D., Holder, M.T.: A supertree pipeline for summarizing phylogenetic and taxonomic information for millions of species. PeerJ **5**, 3058 (2017). doi:[10.7717/peerj.3058](https://doi.org/10.7717/peerj.3058)
22. Cuénoud, P., Martinez, M.A.d.P., Loizeau, P.-A., Spichiger, R., Andrews, S., Manen, J.-F.: Molecular phylogeny and biogeography of the genus *Ilex* L.(aquifoliaceae). Annals of Botany **85**(1), 111–122 (2000). doi:[10.1006/anbo.1999.1003](https://doi.org/10.1006/anbo.1999.1003)
23. Manen, J.-F., Barriera, G., Loizeau, P.-A., Naciri, Y.: The history of extant *Ilex* species (Aquifoliaceae): evidence of hybridization within a Miocene radiation. Molecular Phylogenetics and Evolution **57**(3), 961–977 (2010). doi:[10.1016/j.ympev.2010.09.006](https://doi.org/10.1016/j.ympev.2010.09.006)
24. Setoguchi, H., Watanabe, I.: Intersectional gene flow between insular endemics of *Ilex* (Aquifoliaceae) on the Bonin Islands and the Ryukyu Islands. American Journal of Botany **87**(6), 793–810 (2000). doi:[10.2307/2656887](https://doi.org/10.2307/2656887)
25. Selbach-Schnadelbach, A., Cavalli, S.S., Manen, J.-F., Coelho, G.C., De Souza-Chies, T.T.: New information for *Ilex* phylogenetics based on the plastid psbA-trnH intergenic spacer (Aquifoliaceae). Botanical Journal of the Linnean Society **159**(1), 182–193 (2009). doi:[10.1111/j.1095-8339.2008.00898.x](https://doi.org/10.1111/j.1095-8339.2008.00898.x)
26. Gottlieb, A.M., Giberti, G.C., Poggio, L.: Molecular analyses of the genus *Ilex* (aquifoliaceae) in southern south america, evidence from afp and its sequence data. American Journal of Botany **92**(2), 352–369 (2005). doi:[10.3732/ajb.92.2.352](https://doi.org/10.3732/ajb.92.2.352)
27. Yao, X., Song, Y., Yang, J.-B., Tan, Y.-H., Corlett, R.T.: Phylogeny and biogeography of the hollies (*Ilex* L., aquifoliaceae). Journal of Systematics and Evolution **58**(5), 1–10 (2020). doi:[10.1111/jse.12567](https://doi.org/10.1111/jse.12567)
28. Yao, X., Song, Y., Yang, J.-B., Tan, Y.-H., Corlett, R.T.: Phylogeny and biogeography of the hollies (*Ilex* L., Aquifoliaceae), Dryad, Dataset. <https://datadryad.org/stash/dataset/doi:10.5061/dryad.k0p2ngf4x>. Accessed April 2020
29. Song, S., Liu, L., Edwards, S.V., Wu, S.: Resolving conflict in eutherian mammal phylogeny using phylogenomics and the multispecies coalescent model. Proceedings of the National Academy of Sciences **109**(37), 14942–14947 (2012). doi:[10.1073/pnas.1211733109](https://doi.org/10.1073/pnas.1211733109)
30. Mirarab, S., Reaz, R., Bayzid, M.S., Zimmermann, T., Swenson, M.S., Warnow, T.: ASTRAL: genome-scale coalescent-based species tree estimation. Bioinformatics **30**(17), 541–548 (2014). doi:[10.1093/bioinformatics/btu462](https://doi.org/10.1093/bioinformatics/btu462)
31. Bouckaert, R., Vaughan, T.G., Barido-Sottani, J., Duchêne, S., Fourment, M., Gavryushkina, A., Heled, J., Jones, G., Kühnert, D., Maio, N.D., Matschiner, M., Mendes, F.K., Müller, N.F., Ogilvie, H.A., Plessis, L.d., Poppinga, A., Rambaut, A., Rasmussen, D., Siveroni, I., Suchard, M.A., Wu, C.-H., Xie, D., Zhang, C., Stadler, T., Drummond, A.J.: BEAST 2.5: An advanced software platform for Bayesian evolutionary analysis. PLOS Computational Biology **15**(4), 1006650 (2019). doi:[10.1371/journal.pcbi.1006650](https://doi.org/10.1371/journal.pcbi.1006650). Publisher: Public Library of Science
32. Chifman, J., Kubatko, L.: Quartet inference from SNP data under the coalescent model. Bioinformatics **30**(23), 3317–3324 (2014). doi:[10.1093/bioinformatics/btu530](https://doi.org/10.1093/bioinformatics/btu530). Publisher: Oxford Academic
33. Webb, C.O., Slik, J.F., Triono, T.: Biodiversity inventory and informatics in Southeast Asia. Biodiversity and Conservation **19**(4), 955–972 (2010). doi:[10.1007/s10531-010-9817-x](https://doi.org/10.1007/s10531-010-9817-x)
34. San Mauro, D., Agorreta, A.: Molecular systematics: a synthesis of the common methods and the state of knowledge. Cellular & Molecular Biology Letters **15**(2), 311 (2010). doi:[10.2478/s11658-010-0010-8](https://doi.org/10.2478/s11658-010-0010-8)
35. Helmus, M.R., Ives, A.R.: Phylogenetic diversity–area curves. Ecology **93**(sp8), 31–43 (2012). doi:[10.1890/11-0435.1](https://doi.org/10.1890/11-0435.1)
36. Stoltzfus, A., Lapp, H., Matasci, N., Deus, H., Sidlauskas, B., Zmasek, C.M., Vaidya, G., Pontelli, E., Cranston, K., Vos, R., et al.: Phylotastic! making tree-of-life knowledge accessible, reusable and convenient. BMC Bioinformatics **14**(1), 158 (2013). doi:[10.1186/1471-2105-14-158](https://doi.org/10.1186/1471-2105-14-158)

Figure 1 The Physcraper framework consists of 4 general steps (see text). The software is fully described on its documentation website at <https://physcraper.readthedocs.io>, along with installation instructions, function usage descriptions, examples and tutorials.

Figure 2 A) Phylogeny updated with Physcraper from original [26] tree in B. Tips in original alignment and new tips added with Physcraper are depicted in black and red, respectively. Physcraper obtained sequences from the GenBank database via local BLAST of all sequences in the original alignment that generated tree in B), filtered them following criteria from section "DNA sequence search and filtering", aligned them to original alignment using MUSCLE and performed a phylogenetic reconstruction using RAxML with 100 bootstraps. B-D conflict analyses performed with OpenTree tools.

Table 1 Sample table title. This is where the description of the table should go

	B1	B2	B3
A1	0.1	0.2	0.3
A2
A3

Figures

Tables

Additional Files

Additional file 1 — Sample additional file title
Additional file descriptions text (including details of how to view the file, if it is in a non-standard format or the file extension). This might refer to a multi-page table or a figure.

Additional file 2 — Sample additional file title
Additional file descriptions text.