山西高科投光电科技有限公司
Shanxi High-tech Photoelectronic Technology Co., Ltd.
Add: 65. Beidong New Street, Changzhi city, Shanxi province, China.
Tel: +86 355 5807588 Fax: +86 355 5807562 Website: www.gkgd.com

Specification of PM3.91 Outdoor LED Module

Module		Module photo
Pixel pitch	3.91 mm	
Pixel Density	65,536 dots/m²	
Pixel configuration	1R1G1B	
LED type	3-in-1 SMD1921	
Module size	250*250mm	
Module weight	601.2g	
Module resolution	64*64 dots	
Module QTY/ m²	16 pcs/ m²	
Min. Viewing Distance	≥3.91m	
Brightness	≥4000 cd/m²	
Viewing Angle	H≥120° V≥120°	
Driving Mode	1/16 scan constant current	
Interface	HUB75	
Input voltage	4.8-5.5VDC	
Max. Power Consumption	608 w/m²	
Avg. Power Consumption	304 w/m²	
Max. Current	7.6 A	
Gray Level	16384	
Vedio frame rate	60 frames/s	
Refresh Rate	≥1920Hz	
Defective Dots Rate	＜0.0001 (LED industry standard: ≤ 0.0003)	
Decay Rate	≤5%/year	
Brightness Conformity	＞95%	
Colors	16384^3	
MTBF	≥10000 hours	
Lifespan	≥100000 hours	
Protective function	Over-heat/Over-load /Power-down /Power-leakage /Lightning-protection etc.	
Operating Temperature	-10℃～+40℃	
Operating Humidity	10-80% no condensation	
Storage Temperature	-20℃～+60℃	
Storage Humidity	10-85% no condensation	
Control system parameter		
Color temperature	Adjustable by software.	
Brightness level	256 levels, automatic or manual adjustment.	
Control way	Computer, real-time, off-line, wireless, internet etc.	
Communication Distance	Cat5 UTP 100 meters, max. 130 meters; or optical fiber.	
Packing		
Carton	20pcs/carton, size: 565*290*290mm, weight: 12.8kgs	

Note: The specification may subject to change without prior notice.