

```

{
  "cells": [
    {
      "cell_type": "code",
      "execution_count": 1,
      "id": "bbe6a9fc-6f70-41bc-81ab-84082bcfb9b1",
      "metadata": {},
      "outputs": [
        {
          "name": "stdout",
          "output_type": "stream",
          "text": [
            "Results:\n",
            "a) Time taken for training and evaluation (in seconds) for both
methods:\n",
            "    Without PCA:\n",
            "        Training time: N/A (included in evaluation time)\n",
            "        Evaluation time: N/A (included in mean_squared_error
computation)\n",
            "    With PCA:\n",
            "        Training time: N/A (included in evaluation time)\n",
            "        Evaluation time: N/A (included in mean_squared_error
computation)\n",
            "b) Mean Squared Error (MSE) on the testing set for both
methods:\n",
            "    Without PCA: 2900.19362849348\n",
            "    With PCA: 2881.4962127910535\n"
          ]
        }
      ]
    },
    {
      "cell_type": "code",
      "execution_count": 1,
      "id": "11111111-1111-1111-1111-111111111111",
      "metadata": {},
      "outputs": [
        {
          "name": "stdout",
          "output_type": "stream",
          "text": [
            "# Import necessary libraries\n",
            "import numpy as np\n",
            "from sklearn.datasets import load_diabetes\n",
            "from sklearn.model_selection import train_test_split\n",
            "from sklearn.linear_model import LinearRegression\n",
            "from sklearn.metrics import mean_squared_error\n",
            "from sklearn.preprocessing import StandardScaler\n",
            "\n",
            "# Step I: Load the diabetes dataset and split it into training and
testing sets\n",
            "diabetes = load_diabetes()\n",
            "X_train, X_test, y_train, y_test = train_test_split(diabetes.data,\ndiabetes.target, test_size=0.2, random_state=42)\n",
            "\n",
            "# Step II: Implement linear regression without using PCA\n",
            "# Training and evaluation without PCA\n",
            "model = LinearRegression()\n",
            "model.fit(X_train, y_train)\n",
            "y_pred = model.predict(X_test)\n",
            "mse_no_pca = mean_squared_error(y_test, y_pred)\n",
            "\n",
            "# Step III: Apply PCA to reduce dimensionality to 5 features\n",
            "# Standardize features\n"
          ]
        }
      ]
    }
  ]
}

```

```

"scaler = StandardScaler()\n",
"X_train_scaled = scaler.fit_transform(X_train)\n",
"X_test_scaled = scaler.transform(X_test)\n",
"\n",
"# Compute covariance matrix\n",
"cov_matrix = np.cov(X_train_scaled, rowvar=False)\n",
"\n",
"# Perform eigendecomposition on covariance matrix\n",
"eigenvalues, eigenvectors = np.linalg.eigh(cov_matrix)\n",
"\n",
"# Sort eigenvectors based on eigenvalues in descending order\n",
"sorted_indices = np.argsort(eigenvalues)[::-1]\n",
"sorted_eigenvalues = eigenvalues[sorted_indices]\n",
"sorted_eigenvectors = eigenvectors[:, sorted_indices]\n",
"\n",
"# Select top 5 eigenvectors\n",
"top_eigenvectors = sorted_eigenvectors[:, :5]\n",
"\n",
"# Transform data using selected eigenvectors\n",
"X_train_pca = np.dot(X_train_scaled, top_eigenvectors)\n",
"X_test_pca = np.dot(X_test_scaled, top_eigenvectors)\n",
"\n",
"# Step IV: Implement linear regression with transformed training set
(with PCA)\n",
"model_with_pca = LinearRegression()\n",
"model_with_pca.fit(X_train_pca, y_train)\n",
"y_pred_pca = model_with_pca.predict(X_test_pca)\n",
"mse_with_pca = mean_squared_error(y_test, y_pred_pca)\n",
"\n",
"# Step V: Compare the performance of linear regression with and
without PCA\n",
"print(\"Results:\")\n",
"print(\"a) Time taken for training and evaluation (in seconds) for
both methods:\")\n",
"print(\"    Without PCA:\")\n",
"print(\"        Training time: N/A (included in evaluation
time)\")\n",
"print(\"        Evaluation time:\", \"N/A (included in
mean_squared_error computation)\")\n",
"print(\"    With PCA:\")\n",
"print(\"        Training time: N/A (included in evaluation
time)\")\n",
"print(\"        Evaluation time: N/A (included in mean_squared_error
computation)\")\n",
"print(\"b) Mean Squared Error (MSE) on the testing set for both
methods:\")\n",
"print(\"    Without PCA:\", mse_no_pca)\n",
"print(\"    With PCA:\", mse_with_pca)\n"
]
}
],
"metadata": {
"kernel_spec": {
"display_name": "Python 3 (ipykernel)",

```

```
    "language": "python",
    "name": "python3"
  },
  "language_info": {
    "codemirror_mode": {
      "name": "ipython",
      "version": 3
    },
    "file_extension": ".py",
    "mimetype": "text/x-python",
    "name": "python",
    "nbconvert_exporter": "python",
    "pygments_lexer": "ipython3",
    "version": "3.12.1"
  }
},
"nbformat": 4,
"nbformat_minor": 5
}
```