

Lique Cure-E25



Film forming curing compound in water emulsion for concrete

WHERE TO USE

To protect fresh concrete from rapid water evaporation caused by wind or sunlight and to reduce Surface cracking.

Some Application Examples

- **Lique Cure-E25** is especially recommended for protecting concrete structures such as:
- Industrial floor
- Exterior paving (road, parking lots)
- Airport runways
- Renders
- Dam faces
- Bridges
- Canals
- Reservoirs

TECHNICAL CHARACTERISTICS

Lique Cure-E25 is a white water emulsion of special resins which forms an even elastic film on concrete that is impermeable to water and air. **Lique Cure-E25** provides reliable protection against rapid evaporation of water in concrete, whether exposed to direct sunlight or under severe rapid drying conditions caused by wind, low humidity, or high ambient or concrete temperatures.

Lique Cure-E25 offers the following advantages:

- Improves curing of concrete, enhances hydration process and provides more durable concrete.
- Better development of mechanical strength: the absence of moisture in curing concrete can result a loss of strength of up to 50%.
- Better resistance to wear.
- Less surface dusting.
- Fast and easy application.
- Spray application is possible.

STANDARD COMPLIANCE

Lique Cure-E25 gives 75% or greater curing efficiency when tested to BS7542 and complies with BS8110 Part-1, clause 6.6.3(c) and ASTM C309.

RECOMMENDATIONS

Lique Cure-E25 interferes with the bonding of any other finishing product. Its use is therefore not recommended for concrete curing or renders when levelling or painting is required (unless thoroughly cleaned with a bush hammer or by sanding to remove the product).

If applied on horizontal surfaces such as roads, parking lots and airport runways, in an amount higher than specified, and if not removed, the surface could be slippery for rubber type vehicles. To ensure complete removal the usage of high-pressure steam, water jet or light sandblasting is recommended.



SOLAIRE ORGANOSYS PVT. LTD. Birhata, Purba Bardhaman-713101.
Email: liquemix.bd@gmail.com, Phone: +91 9007512789, **Made In India.**



Lique Cure-E25



Film forming curing compound in water emulsion for concrete

HOW TO USE

Lique Cure-E25 should be stirred before use to ensure even dispersal of the pigment. Should be applied to the surface of the concrete after initial evaporation. For industrial paving, **Lique Cure-E25** must be applied after the concrete has started to set.

For formed concrete **Lique Cure-E25** must be applied immediately after stripping the formwork, in such cases surface must be damp and not completely dry.

PREPARING THE PRODUCT

Carefully mix **Lique Cure-E25** before applying.
Lique Cure-E25 must be used without any other dilution.

APPLYING THE PRODUCT

Apply **Lique Cure-E25** in one spray coat with approx. 1 atmosphere of pressure in a thin and even layer. After approx. 2-3 hours at +20°C **Lique Cure-E25** will be resistant to rain and washing.

CLEANING

Spray tools must be cleaned with water before **Lique Cure-E25** dries.

CONSUMPTION

Lique Cure-E25 coverage is 3.5-5.0 m² /liter.

PACKAGING

Lique Cure-E25 is supplied in 20 kg, 200 kg & 250 Kg Drums.

STORAGE

Lique Cure-E25 may be stored for 12 months in closed containers; protected from frost and from exposure to direct sunlight. The storage temperature must be between +5°C and +30°C.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Lique Cure-E25 is not considered as dangerous according to the current regulation regarding the classification of mixtures. It is however recommended to use protection gloves and goggles and to take the usual precautions for handling chemicals.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.



SOLITAIRE ORGANSYS PVT. LTD. Birhata, Purba Bardhaman-713101.
Email: liquemix.bd@gmail.com, Phone: +91 9007512789, **Made In India.**



Lique Cure-E25



Film forming curing compound in water emulsion for concrete

TECHNICAL DATA (typical values)	
PRODUCT IDENTIFICATION	
Consistency	aid
Color	white
Density (g/cm ³)	0.97 ± 0.02
Main action	surface concrete protection against rapid water evaporation
APPLICATION DATA	
Application temperature	from +5°C to +30°C
Tack-free time at +20°C	2-3 hours

IMPORTANT NOTES

Whilst we try to ensure that any advice, recommendations or information given in our literature is accurate and correct, we have no control over the circumstances in which our product is used. It is therefore important that installers satisfy themselves that the product and conditions are suitable for the envisaged application. No warranty can be given or responsibility accepted other than, that the product supplied by us will meet our written specification. The installer should ensure that our latest product data and safety information sheets have been consulted prior to use.



SOLITAIRE ORGANSYS PVT. LTD. Birhata, Purba Bardhaman-713101.
Email: liquemix.bd@gmail.com, Phone: +91 9007512789, Made In India.

