

DESCRIPTION

LIQUE- SHUTTERLUBE is an economical, chemically reactive concrete form release agent for general use in concrete forming applications. LIQUE- SHUTTERLUBE contains a proprietary ingredient that provides release capability superior to traditional, barrier-type form oils. LIQUE- SHUTTERLUBE is compliant with all VOC regulations in the U.S. and Canada. Because it is not water-based, LIQUE- SHUTTERLUBE does not require protection from freezing. Forms treated with LIQUE- SHUTTERLUBE can be put to use faster than those treated with water-based release products. Metal, plastic, wood and composition forms strip cleanly with LIQUE- SHUTTERLUBE.

PRIMARY APPLICATION

Preventing the adhesion of concrete to forms of all types in general concrete forming applications

FEATURES/BENEFITS

- Forms release easily and cleanly from concrete
- Less staining than barrier-type form oils
- Compliant with all VOC regulations in the U.S. and Canada
- Reduces the occurrence of voids and bugholes
- Tolerant to freezing conditions during storage and transportation
- Treated forms are ready for use quickly
- Not regulated for transportation - easy storage and shipping
- Very low odor

TECHNICAL INFORMATION

VOC content< 5 g/L
Weight/gal7.3 lb/gal (0.86 kg/L)
Appearance: LIQUE- SHUTTERLUBE is a pale yellow liquid

PACKAGING

LIQUE- SHUTTERLUBE is packaged in 275 gal (1041 L) totes, 55 gal (208 L) drums and 5 gal (18.9 L) pails.

SHELF LIFE

2 years in original, unopened container.

SPECIFICATIONS/COMPLIANCES

- ACI 347
- Compliant with all VOC regulations in the U.S. and Canada

COVERAGE

	ft ² /gal (m ² /L)
Plywood Forms	350 to 500 (8.59 to 12.27)
Wood Composition Forms	350 to 500 (8.59 to 12.27)
Plastic Forms	800 to 1000 (19.63 to 24.54)
Metal Forms	800 to 1000 (19.63 to 24.54)

Note: Coverage rates are approximate and for estimating purposes only. Surface temperature, porosity and texture will determine actual material requirements.

Directions for Use

Surface Preparation: The form surface must be free from dirt, cement paste, hardened concrete and other residue that could transfer to the finished concrete surface. Before coating plywood forms, apply a heavy brush coat to the plywood edges to protect laminations.

Application: In cold weather or if LIQUE- SHUTTERLUBE has been stored in a cold location, gently stir the product before using. LIQUE- SHUTTERLUBE can be applied by brush, spray or roller. Apply in a continuous film, avoiding excessive buildup, runs and puddles. Forms treated with LIQUE- SHUTTERLUBE will be ready to use within one hour on plywood and 2 to 3 hours on metal and plastic forms. Used forms can be recoated with LIQUE- SHUTTERLUBE if proper surface preparation techniques are followed.

CLEAN-UP

Clean tools and application equipment immediately after use with mineral spirits. Clean drips and overspray while still wet.

Precautions/Limitations

- Do not thin or dilute LIQUE- SHUTTERLUBE.
- The viscosity of LIQUE- SHUTTERLUBE increases at low temperatures, resulting in reduced sprayability.
- In all cases, consult the Safety Data Sheet before use.

WARRANTY: The manufacturer solely and expressly warrants that its products shall be free from defects in materials and workmanship for a period of one (1) year from the date of purchase. No other representations or statements, whether written or oral, shall modify or extend this warranty unless formally authorized in writing by a designated officer of the manufacturer. The manufacturer makes no warranties, express or implied, including but not limited to warranties of merchantability or fitness for a particular purpose, and hereby disclaims all such warranties. In the event that any product is found to be defective within the warranty period, the manufacturer shall replace the product at no cost to the buyer. This replacement shall be the sole and exclusive remedy available. The buyer shall not be entitled to any claim for incidental or consequential damages. All warranty claims must be submitted within one (1) year from the date of the alleged defect. No person or entity is authorized to make any statements or representations that alter the manufacturer's installation guidelines or instructions as provided in official product literature or packaging. Failure to follow such instructions shall void this warranty. Any product demonstrations are provided for illustrative purposes only and shall not be construed as a warranty or modification of this warranty. The buyer is solely responsible for determining the suitability of the product for its intended use.