

1) Block-level element : This element takes full line or new element

A block-level element takes up whole available width and usually starts on new line.

Ex:

<h1> Hello </h1>

<p> My name is Riya </p>

<p> I am Learning HTML </p>

o/p :

Hello

My name is Riya

I am Learning HTML

Here :

• <h1> → block-level element

Common block-level element :

<div> <p> <h1> to <h6> <section>

<article> <header> <footer>

Easy way :

Block = takes a full line / new line

2) Inline Elements :

An Inline element takes only the space it needs.

It does not normally start on new line.

Example :

<P>

→ inline element

my name is Ritesh and I am
learning HTML.

</P>

O/P :

my name is Ritesh and I am learning HTML

 and stay inside the same line

common inline elements :

<a>

<i>

<u>

<small>

<mark>

<sub>

<sup>

Easy way :

Inline = stay in same line.

3) Semantic and non-semantic : (Parent element)

Semantic Tags :

A semantic tag tells us what the content means.

Think of a building :

If u see a door labelled ,

"Main Entrance"

you immediately understand its purpose.

Exi

<header>

my website

</header>

<nav>

Home / About / Contact

</nav>

<main>

welcome to my website

</main>

• <header> → top / header area

• <nav> → navigation

• <main> → main content

Common tags:

<header>

<nav>

<main>

<section>

<article>

<aside>

<footer>

<figure>

<form>

<time>

<address>

Non-semantic tags:

<div>

see:
m

<div>

my website

</div>

<div>

home/about/contact

</div>

we see div, but we don't know whether it is:

- a header
- navigation
- main content

that's why semantic tags are often preferred when they accurately describe the content.

4) Formatting tags: used in inline elements

Formatting tags are used to change or emphasize

the appearance / meaning of text.

Imagine notebook where,

- make something bold
- make something italic
- underline something
- Highlight something

<P>

This is bold

This is <i> italic </i>

This is <u> underlined </u>

<P>

O/p:

This is bold

This is italic

This is underlined

Common element :

 <i> <u> <mark>

<small> <ins> <sub> <sup>

Ex 1

H ₂ ⁰

O/p:

H₂⁰

5) Interactive tags :

Interactive tags allow the user to interact with webpage.

<input type="text">

For Ex;

- click a link

- Press a button

- Enter your name

- Select an option

- open / close information

Ex;

`<a href = "https://example.com"> visit website </a>`

O/p :

visit website to click that link when u click it it takes you to another page.

6) Self - closing Tag :

These are tags that don't need a separate closing tag.

These are :

<code><p></code>	hello	<code></p></code>
↓	↓	↓
opening tag	content	closing tag

Ex;

`<img src = "photo.jpg" alt = "my photo" />`

There is no

`</img>`