MOHAMED RIYAS

1. JS :

*. Javascript is High-level, interpreted Programming Language used to make website interactive and dynamic.

*. It can update website content without reloading entire page

*. It Handle user actions such as click, typing, scrolling and form submission.

*. It as ES6+ features for JS code shorter, cleaner and easier to understand.

2. Diff var, let and const :

*. var, Let and const are keyword used to declare variable in JS.

*. And ES+6 feature introduced Let and const.

var :
- Function-scope
- can be redeclared
- can be reassigned

let :
- Block-scope
- cannot be redeclared in same scope
- Reassigned

const :
- Block-scope
- cannot redeclared and Reassigned

3) different Data types JS;

Data types specify what kind of value a variable can store in JS.

i) Primitive - string, Num, boolean, null, undefined
ii) Non-Primitive - Array, obj, Arr of obj

i) Primitive.

Primitive data types store a single, simple value, they are Immutable.

ii) Non-Primitive;

Non-Primitive data types are used to store collections of data or complex data.

4) Function in JS;

A function is a reusable block of code that performs a specific task, we can call a function whenever we need to executed that task.

We call a function through argument and that argument we pass value that value goes to parameter.

i) Function Declaration

It is a traditional method, It can be called before its declaration.

ii) Function Expression :

* A Function is stored Inside a variable.

iii) Arrow Function : (⇒)

*. A Shorter way to write Function

*. It is a syntax sugar .

5) D/w == and === JS ;

Both are == and === comparison operators used to compare two value .

*. == is weak sign It's only compare value Not datatypes . (Loose equality)

*. === Strong sign It's compare both value and datatype . (Strict equality)

6) React . JS ?

*. React . JS is JS library developed by Meta for building user interfaces , especially Single - page application .

1) Component - Based Architecture

2) Virtual DOM

3) Reusable Code → Reapr

4) Fast UI Development .

7) what is component :

A component is a small, independent, reusable part of a react application. Each component represents a part of user interface.

Ex: Navbar, Footer, Login, Register

*. We can use same component in different pages without writing same code.

*. These are JS function that return JSX

*. Each component can manage its own logic and UI

8) Virtual DOM :

Virtual DOM is lightweight JS representation of real DOM. React uses it to identify changes in user interface and update necessary parts of actual DOM

*. Diffing - React compares the previous and new Render O/P to Identify what was changed.

*. Reconciliation - React applies the necessary update to the real DOM instead of unnecessarily rebuilding the page.

9) what is JSX in react?

JSX stands for Javascript XML. It is a syntax Extension for JS that allows us to write HTML-like code inside JS.

*. HTML-like syntax: JSX allows us write UI elements using HTML-like syntax.

*. Compilation: Browsers do not directly understand JSX. Tools such as Babel or React build toolchain

*. Easy to understand: JSX makes react code easier to read and maintained.