

भारतीय मानक

IS 18698 : 2026

Indian Standard

डाइमेथाइल ईथर (डीएमई) मिश्रित
तरलीकृत पेट्रोलियम गैस
(एलपीजी) — विशिष्टि

(पहला पुनरीक्षण)

Dimethyl Ether (DME) Blended
Liquefied Petroleum Gas
(LPG) — Specification

(First Revision)

ICS 71.080.60; 78.160.30.

© BIS 2026

Follow us @



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002
www.bis.gov.in www.standardsbis.in

May 2026

Price Group 6

Petroleum and their Related Products of Synthetic or Biological or Natural Origin Sectional Committee, PCD 03

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Petroleum and their Related Products of Synthetic or Biological or Natural Origin Sectional Committee had been approved by the Petroleum, Coal and Related Products Division Council.

Liquefied Petroleum Gas (LPG) is being used in India to cater to the energy needs of domestic, commercial and industrial sectors apart from use as an automotive fuel. The consumption of LPG in the country is expected to rise. This necessitates the use of alternate fuels to partially substitute LPG with fuel such as synthetically produced dimethyl ether (DME).

DME is an alternative which can be blended with LPG. It is the simplest ether with oxygen connecting two methyl groups having no C-C bond. DME can be blended with LPG and the manufacturer/supplier shall comply with household cooking standards as per the following:

- a) IS 4246 : 2025 — Domestic gas stove and built in hob for use with LPG — Specification
- b) IS 8737 : 2017 — Valve fittings for use with liquefied petroleum gas (LPG) of upto 250 litre water capacity — Specification (*second revision*)
- c) IS 9573 (Part 1) : 2017 — Rubber hose for liquefied petroleum gas (LPG) — Specification: Part 1 Industrial application
- d) IS 9573 (Part 2) : 2017 — Rubber hose for liquefied petroleum gas (LPG) — Specification: Part 2 Domestic and commercial application
- e) IS 9798 : 2013 — Low pressure regulators for use with liquefied petroleum gas (LPG) — Specification

For some requirements in [Table 1](#), Indian Standards do not exist for the test methods, hence reference is provided to other internationally used standards. Once Indian Standards are formulated for these tests, the references will be modified accordingly. Also, alternate test methods are provided below for few characteristics and in case of dispute, the referee methods prescribed in [Table 1](#) shall be followed:

<i>Characteristic</i>	<i>Alternate Method of Tests</i>
Density at 15 °C, kg/m ³	ASTM D1657
Vapour pressure at 40 °C, kPa	ASTM D1267, ASTM D6897
Evaporation temperature for 95 percent by volume at 760 mm Hg pressure, °C	EN 15470, EN 15471
Copper strip corrosion at 38 °C for 1 h	ASTM D1838
Hydrogen sulphide	ASTM D2420
Free water content	ASTM D1657 (visual observation)

This standard was first published in 2024. This revision has been brought out to keep pace with the latest technological developments and international practices. In this revision, the following major modifications have been made:

- a) The composition, mass fraction of DME has been changed from 20 percent, max to 8 percent, max as an outcome of the R&D Report — 2025 on ‘Study of compatibility of elastomers used in LPG distribution chains with various Di Methyl Ether (DME)-LPG blends’ issued by LPG Equipment Research Centre, Bangalore, India;
- b) Foreword, scope and terminology of Di Methyl Ether (DME) has been modified;
- c) Terminology of LPG-DME blend has been incorporated;

([Continue on third cover](#))

Indian Standard

DIMETHYL ETHER (DME) BLENDED LIQUEFIED PETROLEUM GAS (LPG) — SPECIFICATION

(*First Revision*)

1 SCOPE

1.1 This standard prescribes the requirements and methods of sampling and test for Dimethyl Ether (DME) blended Liquefied Petroleum Gas (LPG) marked for distribution and usage in household, commercial and industrial applications excluding automotive use in the country.

1.2 This standard does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2 REFERENCES

The standards listed in [Annex A](#) contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are advised to use the latest edition of these standards.

3 TERMINOLOGY

For the purpose of this standard, the following definitions shall apply.

3.1 Liquefied Petroleum Gas (LP Gas or LPG) — See IS 4639 (Part 1).

3.1.1 LP gases mainly consist of one or more of the following hydrocarbons:

- a) Propane (C_3H_8);
- b) Propylene (C_3H_6);
- c) *n*-butane (C_4H_{10});
- d) ISO-butane (C_4H_{10}); and
- e) Butylene (C_4H_8).

3.1.2 Small quantities of one or more of the following hydrocarbons may also be present:

- a) Ethane (C_2H_6);
- b) Ethylene (C_2H_4);
- c) Pentane (C_5H_{12}); and

- d) Pentene (C_5H_{10}).

3.2 Di Methyl Ether (DME) — Colorless gas containing Oxygen, synthetically produced from gasification of biomass or coal, methanol, Syn gas or natural gas, capable of being used as alternate fuel.

3.3 DME LPG Blend — Blend of LPG and DME as per specified ratio. This blend contains Oxygen molecule.

4 REQUIREMENTS

4.1 LPG shall meet the requirements as per IS 4576.

4.2 DME shall meet the requirements as per IS 16704.

4.3 DME blended LPG shall comply with the requirements given in [Table 1](#) when tested according to appropriate methods given in col (4) of [Table 1](#).

4.4 DME blended LPG shall contain a minimum quantity of odourant, generally a mercaptan, to detect a leak. Adequate odour shall be observed, when tested as mentioned below:

5 ml doctor solution + 8 ml ISO-octane + pinch of sulphur powder to be taken in 25 ml stoppered cylinder. The solution to be shaken and 2 ml LPG (Aq.) to be added. The solution to be shaken slowly by releasing pressure. Odour is adequate if the solution turns yellowish brown.

4.5 Residue of LPG

Subject to agreement between the purchaser and the supplier, the material shall also pass the agreed limits for residue when tested according to IS 1448 (Part 70).

5 PACKING AND MARKING

5.1 Packing

The material shall be packed in suitable cylinders/containers as agreed to between the

IS 18698 : 2026

purchaser and the supplier and subject to the requirements prescribed by statutory authorities. (For cylinders, see IS 3196 (Part 1).

5.2 Marking

The cylinders/containers shall be marked as prescribed by statutory authorities from time to time. They shall bear the labels marked with the following information:

- a) Name of the material;
- b) Mass in kg of the material in the container;
- c) Maximum vapor pressure;
- d) Manufacturer's name and trade mark, if any; and
- e) Any other statutory requirements.

5.2.1 Each cylinder/container shall also be marked with the caution label 'FLAMMABLE' together

with the corresponding symbol for labeling dangerous goods [see Fig.18 of IS 1260 (Part 1)].

5.2.2 BIS Certification Marking

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the standard mark.

6 SAMPLING

6.1 Representative liquid samples of DME blended liquefied petroleum gas shall be drawn as prescribed in IS 1447 (Part 2).

6.2 Tests on vapour pressure shall be conducted on individual samples and the rest of the tests shall be conducted on composite samples.

Table 1 Requirements for DME Blended LPG

(Clause 4.3)

SI No. (1)	Characteristics (2)	Requirements (3)	Method of Test, Ref to (4)
(i)	Density ¹⁾ at 15 °C, kg/m ³	Report	IS 1448 (Part 76) ⁸⁾ IS 16074
(ii)	Vapour pressure at 40 °C, kPa, gauge, <i>Max</i>	1050 ²⁾	IS 1448 (Part 71) ⁸⁾ /ASTM D6897
(iii)	Composition, mass fraction of DME, percent, <i>m/m, Max</i>	8	IS 18887
(iv)	a) Other Hydrocarbons, liquid volume percent ³⁾ : 1) C ₂ hydrocarbon; 2) C ₃ hydrocarbon; 3) C ₄ hydrocarbon; and 4) C ₅ hydrocarbon and heavier, <i>Max</i> .	Report Report Report 2.5	IS 1448 (Part 151)
	OR		
	b) Volatility: 1) Evaporation temperature for 95 percent by volume at 760 mm Hg pressure, °C, <i>Max</i>	2.2	IS 1448 (Part 72) ⁸⁾
(v)	Total volatile sulphur ⁴⁾ , mg/kg (ppmw), <i>Max</i>	140	ASTM D6667 ⁸⁾
(vi)	Copper strip corrosion at 38 °C for 1 h	Not worse than No 1	IS 1448 (Part 152) ⁸⁾
(vii)	Hydrogen sulphide ⁵⁾	Pass	IS 1448 (Part 73) ⁸⁾
(viii)	Free water content ^{6),7)}	None	IS 1448 (Part 76) ⁸⁾ (visual observation)
(ix)	Caustic test	Pass	See Note 10

NOTES

- Density/Relative density may also be determined by analyzing the gas by gas chromatograph and using composition and density factor data as per ISO 8973/ASTM D2598/IP 432. DME density at 15 °C 675 kg/m³ need to be taken for calculation
- Each consignment of the product shall be designated by its maximum vapor pressure in kPa at 40 °C and shall not exceed 16.87 kg/sq.cm at 65 °C for transportation through road tank trucks. Further, if purchaser and the supplier agreed, the minimum vapor pressure of that mixture shall be not lower than 200 kPa gauge compared to the designated maximum vapor pressures and in any case the minimum for the mixture shall be not lower than 520 kPa at 40 °C.
- Molar composition of LPG determined by gas chromatographic analysis can be converted into Liquid-Volume using the standard Practice as per ASTM D2421.
- Total sulphur limits in these specifications do include sulphur compounds used for odorizing purposes.
- 'Pass' the test indicates Hydrogen Sulphide not more than 5 ppm. Hydrogen Sulphide can also be determined with the following procedure:
Take 5 ml of lead acetate solution (prepared in IPA) + 25 ml LPG (liquid) in measuring cylinder and shake well. If black precipitation is not seen, then H₂S test passes.
- Free water: Water promotes rust on internal surface of steel storage tanks and iron piping systems. Water can also cause odourant to fade and can block small openings. LPG shall not contain any free water at 0 °C and shall be determined by visual inspection of sample using equipment on which density is determined. Subject to agreement between purchaser and supplier, limit, temperature and method for water content determination may be changed for specific applications like shipment of refrigerated LPG, etc.
- Free water content can also be determined with the following procedure:
a) Take 100 ml of liquid in dry graduated tube and allow to vaporize the LPG. When about 2 ml to 3 ml residue is left, shake and pour the residue on whatman filter paper. Allow the residue on filter paper to evaporate; if wet spot not seen, free water is absent.
- In case of dispute, this method shall be the referee method.
- For caustic test following procedure may be adopted:
a) 2 ml LPG (liq) + 5 ml demineralised water in a weathering tube, add a drop of Alizarin Yellow R indicator (Mordant Orange-1, 5-(4-Nitrophenylazo) Salicylic acid, Dye content 70 percent, CAS no 2243-76-7). Caustic test is pass, if it doesn't turn into red from yellow.
b) Preparation of indicator: Take 0.1 gm in 100ml volumetric flask and dissolve it in demineralised water then make up to the mark with demineralised water.

IS 18698 : 2026

ANNEX A

(Clause 2)

LIST OF REFERRED STANDARDS

IS No./Other Standards	Title		for low pressure liquefiable gases: Part 1 Cylinders for liquefied petroleum gases (LPG) — Specification (<i>sixth revision</i>)
IS 1260 (Part 1) : 1973	Pictorial marking for handling and labelling of goods: Part 1 Dangerous good (<i>first revision</i>)	IS 4576 : 2021	Liquefied petroleum gases — Specification (<i>fourth revision</i>)
IS 1447 (Part 2): 2013/ISO 4257 : 2001	Methods of sampling of petroleum and its products: Part 2 Liquefied petroleum gases — Method of sampling (<i>second revision</i>)	IS 4639 (Part 1) : 2000/ISO 1998-1 : 1998	Petroleum industry — Terminology: Part 1 Raw materials and product (<i>first revision</i>)
IS 1448	Methods of test for petroleum and its products	IS 16704 : 2018/ISO 16861 : 2015	Petroleum products — Fuels (Class F) — Specifications of dimethyl ether (DME)
(Part 70) : 2018	Determination of residue in liquefied petroleum gases (<i>first revision</i>)	IS 18887 : 2024	DME blended liquified petroleum gas (LPG) fuel — Quantitative determination of dimethyl ether (DME) content by gas chromatography
(Part 71) : 2004 /ISO 4256 : 1996	Liquefied petroleum gases — Determination of gauge vapour pressure — LPG method (<i>second revision</i>)	ISO 8973 : 1997	Liquefied petroleum gases — Calculation method for density and vapour pressure
(Part 72) : 2023	Volatility test of liquefied petroleum gases (<i>first revision</i>)	ASTM D2421-21	Standard practice for interconversion of analysis of C5 and lighter hydrocarbons to gas — Volume, liquid — Volume, or mass basis
(Part 73) : 2004 /ISO 8819 : 1993	Liquified petroleum gases — Detection of hydrogen sulphide — Lead acetate method (<i>first revision</i>)	ASTM D2598-21	Standard practice for calculation of certain physical properties of liquefied petroleum (LP) gases from compositional analysis
(Part 76) : 2019 /ISO 3993 : 1984	Liquified petroleum gases and light hydrocarbons — Determination of density or relative density — Pressure hydrometer method (<i>first revision</i>)	ASTM D6667-21	Standard test method for determination of total volatile sulphur in gaseous hydrocarbons and liquefied petroleum gases by ultraviolet fluorescence
(Part 151): 2004 /ISO 7941 : 1998	Commercial propane and butane — Analysis by gas chromatography	IP 432	Liquefied petroleum gases — Calculation method for density and vapour pressure
(Part 152) : 2004/ISO 6251 : 1996	Liquefied petroleum gases — Corrosiveness to copper — Copper strips test		
IS 3196 (Part 1) : 2013	Welded low carbon steel cylinders exceeding 5 litres water capacity		

To access Indian Standards click on the link below:

<https://standards.bis.gov.in/website/know-your-standards>

ANNEX B

(Foreword)

COMMITTEE COMPOSITION

Petroleum and their Related Products of Synthetic or Biological or Natural Origin Sectional Committee, PCD 03

<i>Organization</i>	<i>Representative(s)</i>
CSIR - Indian Institute of Petroleum, Dehradun	DR HARENDER SINGH BISHT (Chairperson)
Ashok Leyland Limited, Chennai	SHRI MAHESH P. SHRI MUTHUKUMAR N. (<i>Alternate I</i>) SHRI BALAKRISHNAN D. (<i>Alternate II</i>)
Association of State Road Transport Undertakings, New Delhi	CAPT V. V. RATNAPARKHI SHRI R. R. K. KISHORE (<i>Alternate</i>)
Automotive Research Association of India, Pune	SHRI S. D. RAIRIKAR SHRI M. I. JAMADAR (<i>Alternate</i>)
Bajaj Auto Limited, Pune	SHRI RAMESH GOYKAR MS DIKSHA (<i>Alternate</i>)
Bharat Petroleum Corporation Limited, Mumbai	SHRI C. SHANMUGANATHAN SHRI RAJESH V. (<i>Alternate</i>)
Bio Diesel Association of India, Mumbai	SHRI N. S. BALAMUKUNDAN SHRI SANJEEV GUPTA (<i>Alternate</i>)
Bosch Limited, Bengaluru	DR VENKATESH R.
Centre for High Technology, New Delhi	SHRI RAJESH AGARWAL SHRI SHEKAR KULKARNI (<i>Alternate</i>)
Centre for Science and Environment, New Delhi	SHRIMATI ANUMITA ROYCHOWDHURY SHRI VIVEK CHATTOPADHYAYA (<i>Alternate</i>)
Chennai Petroleum Corporation Limited, Chennai	SHRI ABDUL KAREEM SHRI M. BALAGURU (<i>Alternate I</i>) SHRI S. ARUN PRAKASH (<i>Alternate II</i>)
Consumer Guidance Society of India, Mumbai	DR SITARAM DIXIT DR M. S. KAMATH (<i>Alternate</i>)
CSIR - Indian Institute of Petroleum, Dehradun	DR ANIL KUMAR SINHA SHRI SALEEM A. FAROOQUI (<i>Alternate</i>)
Directorate General of Aeronautical Quality Assurance, New Delhi	SHRI SANTOSH NAMDEO
Directorate General of Civil Aviation, New Delhi	SHRI RAKESH KUMAR SHRI AMIT GUPTA (<i>Alternate I</i>) SHRI DHARMENDRA SINGH YADAV (<i>Alternate II</i>)
Directorate General of Quality Assurance, Ministry of Defence, Kanpur	DR OM PRAKASH SINGH SHRI VIKIN JAIN (<i>Alternate</i>)

IS 18698 : 2026

<i>Organization</i>	<i>Representative(s)</i>
DRDO - Centre for Military Airworthiness and Certification, Bengaluru	SHRI R. SHANMUGAVEL SHRI R. KAMALAKANNAN (<i>Alternate</i>)
Federation of Indian Petroleum Industry, New Delhi	SHRI D. L. N. SASTRI SHRI P. S. RAVI (<i>Alternate I</i>) SHRI SHARIQUE HUSSAIN (<i>Alternate II</i>)
Gulf Oil Lubricants India Limited, Mumbai	SHRI K SWAMINATHAN IYER SHRI JENCEN MATHAI ARIVANNOOR (<i>ALTERNATE I</i>) SHRI M. P. SAJEEV (<i>Alternate II</i>)
Hero Motocorp Limited, New Delhi	SHRI FERAZ ALI KHAN SHRI RAKESH SHARMA (<i>Alternate</i>)
Hindustan Petroleum Corporation Limited, Mumbai	SHRI RAJA KISHOR BARIK SHRI S. N. SHESHACHALA (<i>Alternate I</i>) SHRI SHITANSHU PATI TRIPATHI (<i>Alternate II</i>)
Indian Biogas Association, Gurugram	DR A. R. SHUKLA
Indian Oil Corporation (R and D Centre), Faridabad R&D	DR AJAY KUMAR ARORA DR A. S. MATHUR (<i>Alternate</i>)
Indian Oil Corporation Limited, New Delhi	SHRI SOUMEN MONDAL SHRI MANISH MALHAN (<i>Alternate I</i>) Ms S. PRINCY RAGILA (<i>Alternate II</i>) DR Y. S. JHALA (<i>Alternate III</i>)
Lubrizol India Limited, Mumbai	SHRI ANAND REDKAR
Mahindra and Mahindra Limited, Mumbai	SHRI R. RAMAPRABHU SHRI KARUPPASAMY T. (<i>Alternate</i>)
Mangalore Refinery and Petro Chemical Limited, Mangalore	SHRI MURALIDHAR N. KALE SHRI YOGESHA (<i>Alternate</i>)
Maruti Suzuki India Limited, Gurugram	SHRI NISHANT SARNA SHRI GURURAJ RAVI (<i>Alternate</i>)
Ministry of Petroleum and Natural Gas, New Delhi	SHRI DEEPAK SRIVASTAVA
Nayara Energy Limited, Mumbai	SHRI PRATIK SHAH SHRI MILAN VASOYA (<i>Alternate I</i>) SHRI NARHAR DESHPANDE (<i>Alternate II</i>)
Oil and Natural Gas Corporation Limited, New Delhi	SHRI AMIT KUMAR MISHRA DR DEVKISHAN CHHIMPA (<i>Alternate</i>)
Reliance India Limited, Mumbai	SHRI BALASUBRAMANIAN K. SHRI PRAMOD MALL (<i>Alternate</i>)
Society of Indian Automobile Manufacturers (SIAM), Delhi	SHRI PRASHANT KUMAR BANERJEE SHRI KARTIKE KARWAL (<i>Alternate</i>)
Tata Motors Limited, Pune	SHRI SETHURAMALINGAM TYAGARAJAN SHRI SHAILENDRA DEWANGAN (<i>Alternate</i>)

<i>Organization</i>	<i>Representative(s)</i>
TVS Motor Company Limited, Hosur	SHRI MANISH GOPAL SHRI M. S. ANANDKUMAR (<i>Alternate I</i>) SHRI N. ARUN (<i>Alternate II</i>)
In Personal Capacity, (<i>Flat - 1002, Raheja Heights, D - Wing, off Gen A K Vaidya Marg, Dindoshi, Malad East Mumbai - 400097</i>)	DR Y. P. RAO
BIS General Directorate	SHRI CHINMAY DWIVEDI, SCIENTIST 'E'/DIRECTOR AND HEAD (PETROLEUM, COAL AND RELATED PRODUCTS) [REPRESENTING DIRECTOR GENERAL (<i>Ex-officio</i>)]

Member Secretary
SHRI HARI MOHAN MEENA
SCIENTIST 'D'/JOINT DIRECTOR
(PETROLEUM, COAL AND RELATED PRODUCTS), BIS

Subcommittee, Gaseous Fuels, PCD 3 : 5

<i>Organization</i>	<i>Representative(s)</i>
In Individual Capacity (<i>Tower 8, Flat 12 B, Beverly Park, Sector 14, Koparkhairane, Opposite Reliance Foundation School, Gate 4, Navi Mumbai - 400709</i>)	DR MADHUKAR GARG (<i>Convenor</i>)
Automotive Research Association of India, Pune	SHRI M. A. BAWASE SHRI M. I. JAMADAR (<i>Alternate I</i>) SHRI DEBJYOTI BANDYOPADHYAY (<i>Alternate II</i>)
Bharat Petroleum Corporation Limited, Mumbai	SHRI ADALAZHAGAN K. SHRI SIDDHARTHA MITRA (<i>Alternate</i>)
CSIR - Indian Institute of Petroleum, Dehradun	SHRI SOUMEN DASGUPTA SHRI ANKUR BORDOLOI (<i>Alternate</i>)
Centre for High Technology, New Delhi	SHRI RAJESH AGARWAL SHRI SHEKAR KULKARNI (<i>Alternate</i>)
Federation of Indian Petroleum Industry, New Delhi	SHRI D. L. N. SASTRI SHRI P. S. RAVI (<i>Alternate I</i>) SHRI SHARIQUE HUSSAIN (<i>Alternate II</i>)
GAIL (India) Limited, New Delhi	SHRI AJIT KUMAR JHA SHRI NITIN KUMAR MISHRA (<i>Alternate</i>)
Hindustan Petroleum Corporation Limited, Mumbai	SHRI S N SHESHACHALA SHRI SUDHIR ANAMANAMURI (<i>Alternate</i>)
Indian Biogas Association, Gurugram	DR A. R. SHUKLA
Indian Oil Corporation (R and D Centre), Faridabad R&D	SHRI RAJESH BADHE SHRI M. SITHANANTHAN (<i>Alternate</i>)
Indian Oil Corporation Limited - Refineries and Pipelines Division, New Delhi	SHRIMATI SOMA CHATTOPADHAYA DR Y. S. JHALA (<i>Alternate</i>)

IS 18698 : 2026

<i>Organization</i>	<i>Representative(s)</i>
Mangalore Refinery and Petro Chemical Limited, Mangalore	SHRI R. M. PRAKASH SHRI SUBRAMANAYA PRABHU (<i>Alternate</i>)
Maruti Udyog Limited, Gurugram	SHRI AJAY KUMAR SHRI NISHANT SARNA (<i>Alternate</i>)
Nayara Energy Limited, Mumbai	SHRI PRATIK SHAH SHRI MILAN VASOYA (<i>Alternate</i>)
Nutzen Engineering Solutions LLP, Pune	SHRI VIKRANT PALYEKAR
Oil India Limited, Duliajan	MS EURACIA L. WAHLANG
Oil and Natural Gas Corporation Limited, New Delhi	DR GOUR MOHAN DASS DR DEVKISHAN CHHIMPA (<i>Alternate I</i>) SHRIMATI LEENA JOHN (<i>Alternate II</i>)
Petroleum and Natural Gas Regulatory Board, New Delhi	SHRI GAGAN AGGARWAL SHRI SUMIT SARKAR (<i>Alternate</i>)
Reliance India Limited, Mumbai	SHRI BALASUBRAMANIAN K. SHRI DEBASIS SARMA (<i>Alternate I</i>) SHRI S. R. UDAYAN (<i>Alternate II</i>)
Society of Indian Automobile Manufacturers (SIAM), Delhi	SHRI PRASHANT KUMAR BANERJEE
Tata Motors Limited, Pune	SHRI SETHURAMALINGAM TYAGARAJAN SHRI SHAILENDRA DEWANGAN (<i>Alternate</i>)

PCD 3 : 5 /WG 1 - IS 18698 : 2024 - 20 Percent Dimethyl Ether DME Blended Liquefied Petroleum Gas

<i>Organization</i>	<i>Representative(s)</i>
Indian Oil Corporation Limited, New Delhi	DR Y. S. JHALA (Convenor)
Centre for High Technology, New Delhi	SHRI BALJEET SINGH SHRI GAURANG MISHRA (<i>Alternate</i>)
CSIR - Indian Institute of Petroleum, Dehradun	SHRI PANKAJ KUMAR ARYA
Indian Oil Corporation (R and D Centre), Faridabad	DR SAMIK KUMAR HAIT
LPG Equipment Research Centre, Bangalore	SHRI T. D. SABU
Oil Industry Safety Directorate, Noida	SHRI N. K. PANDEY

(Continue from second cover)

- d) Annex B 'Determination of mass fraction of dimethyl ether (DME) in DME blended LPG' has been substituted by IS 18887; and
- e) References have been updated.

The composition of the Committee responsible for the revision of this standard is given in [Annex B](#).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website- www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: PCD 03 (34076).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : 5 th Floor/MTNL CETTM, Technology Street, Hiranandani Gardens, Powai, Mumbai 400076	{ 2570 0030 2570 2715

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.