

SurakshaPay API DOCUMENT\

PayIn:

Baseurl: <https://admin.surakshapay.com/>

UPI QR Generate API:

endpoint: /api/v2/upi/UpiPay

Request:

```
{
  "client_transction_id": "{{clientOrderId}}",
  "returnUrl": "https://example.com",
  "amount": "102",
  "mobile": "xxxxxxxxxxx"
}
```

Response:

```
{
  "statuscode": "200",
  "status": "success",
  "message": "QR generated Successfully",
  "data": {
    "apiTxnId": "SUK2025012015343387053",
    "qrString":
"upi://pay?ver=01&mode=22&pa=rapidekart782314.rzp@ic
ici&pn=RAPIDEKART&tr=EZV2025012015343445128594&cu=IN
R&mc=7392&qrMedium=04&tn=PaymenttoRAPIDEKART&am=102.
00",
    "transaction_id": "SM1737367473167981"
  }
}
```

Callback Response:

Callback response will receive in query string

Sample response :

?status=success&transction_id=SM1737364684027391&txnId=SUK2025012014480423402&vpaddress=&payId=SUK2025012014480423402&amount=105&bankTxnId=&customer_virtual_address=xxxxxxxxx-2%40axl&customer_account_name=Anvi&orderAmount=105&utr=34434343434344

Payout Initiate Api:

endpoint: api/v2/settlement/transaction

Request:

```
{
  "client_transction_id": "unique transaction id",
  "amount": 105,
  "firstName": "xxxx",
  "lastName": "xxxxx",
  "email": "xxxx@gmail.com",
  "mobile": "xxxxxxxxxxx",
  "mode": "imps",
  "accountNumber": "xxxxxxxxxxx",
  "ifsc": "xxxxxxxxxxx",
  "bank": "xxxxxxxxxxx"
}
```

Response :

```
{
  "statuscode": "200",
  "status": "pending",
  "message": "Txn pending",
}
```

```
"utr": ""  
}
```

Callback Response:

Callback response will receive in query string

Sample response :

?status=success&statuscode=200&utr=502213925389&message=Transaction+Success.&amount=105&client_transaction_id=SM1737531851657425&txnid=SUK41987836

statuscode	Status Of Transaction
success	Transaction Successful
pending	Transaction Pending
failed	Transaction Failed or any validation Error

N.B: Payin and Payout callback response will get in Query String GET method as per sample.